



# AlterMundus



Alain Matthes

September 17, 2025 Documentation V.5.11c

<http://altermundus.fr>

# tkz-euclide

AlterMundus

Alain Matthes

✂ **tkz-euclide** is a set of convenient macros for drawing in a plane (fundamental two-dimensional object) with a Cartesian coordinate system. It handles the most classic situations in Euclidean Geometry. **tkz-euclide** is built on top of PGF and its associated front-end TikZ and is a (La)TeX-friendly drawing package. The aim is to provide a high-level user interface to build graphics relatively effortlessly. The goal is to guide users through constructing diagrams step by step, mirroring the natural process of manual construction as closely as possible.

Version 5 of **tkz-euclide** includes the option to utilize Lua for performing certain calculations, refer to the news and lua sections.

Please note: English is not my native language, so there may be some errors.

✂ Firstly, I would like to thank **Till Tantau** for the beautiful  $\text{\TeX}$  package, namely **TikZ**.

✂ Acknowledgements : I received much valuable advices, remarks, corrections and examples from Jean-Côme Charpentier, Josselin Noirel, Manuel Pégourié-Gonnard, Franck Pastor, David Arnold, Ulrike Fischer, Stefan Kottwitz, Christian Tellechea, Nicolas Kisselhoff, David Arnold, Wolfgang Büchel, John Kitzmiller, Dimitri Kapetas, Gaétan Marris, Mark Wibrow, Yves Combe, Paul Gaborit, Laurent Van Deik and Muzimuzhi Z.

✂ I would also like to thank Eric Weisstein, creator of MathWorld: **MathWorld**.

✂ You can find some examples on my site: [altermundus.fr](http://altermundus.fr). under construction!

Please report typos or any other comments to this documentation to: [Alain Matthes](mailto:Alain.Matthes@univ-lorraine.fr).

This file can be redistributed and/or modified under the terms of the  $\text{\TeX}$  Project Public License Distributed from [CTAN](http://CTAN) archives.

## Contents

I.	General survey : a brief but comprehensive review	15
0.1.	With 5.10 version . . . . .	16
1.	Working with lua	17
1.0.1.	Option lua . . . . .	17
1.0.2.	Option mini . . . . .	17
2.	Installation	17
3.	Presentation and Overview	18
3.1.	Why <b>tkz-euclide</b> ? . . . . .	18
3.2.	<b>TikZ</b> vs <b>tkz-euclide</b> . . . . .	18
3.2.1.	Book I, proposition I <b>_Euclid's Elements_</b> . . . . .	19
3.2.2.	Complete code with <b>tkz-euclide</b> . . . . .	20
3.2.3.	Book I, Proposition II <b>_Euclid's Elements_</b> . . . . .	20
3.3.	<b>tkz-euclide 4</b> vs <b>tkz-euclide 3</b> . . . . .	22
3.4.	<b>tkz-euclide 5</b> vs <b>tkz-euclide 4</b> . . . . .	22
3.5.	How to use the <b>tkz-euclide</b> package ? . . . . .	22
3.5.1.	Let's look at a classic example . . . . .	22
3.5.2.	Part I: golden triangle . . . . .	24
3.5.3.	Part II: two others methods with golden and euclid triangle . . . . .	25
3.5.4.	Complete but minimal example . . . . .	26
4.	The Elements of tkz code	28
4.1.	Objects and language . . . . .	28
4.2.	Notations and conventions . . . . .	29
4.3.	<b>Set</b> , <b>Calculate</b> , <b>Draw</b> , <b>Mark</b> , <b>Label</b> . . . . .	30
5.	About this documentation and the examples	31
II.	Setting	32
6.	First step: fixed points	33
7.	Definition of a point : <b>\tkzDefPoint</b> or <b>\tkzDefPoints</b>	33
7.1.	Defining a named point <b>\tkzDefPoint</b> . . . . .	34
7.1.1.	Cartesian coordinates . . . . .	34
7.1.2.	Calculations with <b>xfp</b> . . . . .	35
7.1.3.	Polar coordinates . . . . .	35
7.1.4.	Relative points . . . . .	35
7.2.	Point relative to another: <b>\tkzDefShiftPoint</b> . . . . .	35
7.2.1.	Isosceles triangle . . . . .	36
7.2.2.	Equilateral triangle . . . . .	36
7.2.3.	Parallelogram . . . . .	36
7.3.	Definition of multiple points: <b>\tkzDefPoints</b> . . . . .	37
7.4.	Create a triangle . . . . .	37
7.5.	Create a square . . . . .	37

III. Calculating	38
8. Auxiliary tools	39
8.1. Constants	39
8.2. New point by calculation	39
9. Special points	40
9.1. Middle of a segment <code>\tkzDefMidPoint</code>	40
9.1.1. Use of <code>\tkzDefMidPoint</code>	40
9.2. Golden ratio <code>\tkzDefGoldenRatio</code>	40
9.2.1. Use the golden ratio to divide a line segment	41
9.2.2. Golden arbelos	41
9.3. Barycentric coordinates with <code>\tkzDefBarycentricPoint</code>	41
9.3.1. with two points	42
9.3.2. with three points	42
9.4. Internal and external Similitude Center	42
9.4.1. Internal and external with <code>node</code>	43
9.4.2. D'Alembert Theorem	43
9.4.3. Example with <code>node</code>	44
9.5. Harmonic division with <code>\tkzDefHarmonic</code>	45
9.5.1. options <code>ext</code> and <code>int</code>	45
9.5.2. Bisector and harmonic division	45
9.5.3. option <code>both</code>	46
9.6. Equidistant points with <code>\tkzDefEquiPoints</code>	46
9.6.1. Using <code>\tkzDefEquiPoints</code> with options	46
9.7. Middle of an arc	46
10. Point on line or circle	48
10.1. Point on a line with <code>\tkzDefPointOnLine</code>	48
10.1.1. Use of option <code>pos</code>	49
10.2. Point on a circle with <code>\tkzDefPointOnCircle</code>	49
10.2.1. Altshiller's Theorem	49
10.2.2. Use of <code>\tkzDefPointOnCircle</code>	50
11. Special points relating to a triangle	51
11.1. Triangle center: <code>\tkzDefTriangleCenter</code>	51
11.1.1. Option <code>ortho</code> or <code>orthic</code>	51
11.1.2. Option <code>centroid</code>	52
11.1.3. Option <code>circum</code>	52
11.1.4. Option <code>in</code>	52
11.1.5. Option <code>ex</code>	52
11.1.6. Option <code>euler</code>	53
11.1.7. Option <code>symmedian</code>	53
11.1.8. Option <code>spieker</code>	54
11.1.9. Option <code>gergonne</code>	54
11.1.10. Option <code>nagel</code>	55
11.1.11. Option <code>mittenpunkt</code>	55
11.1.12. Relation between <code>gergonne</code> , <code>centroid</code> and <code>mittenpunkt</code>	56
12. Definition of points by transformation	56
12.1. <code>\tkzDefPointBy</code>	57
12.1.1. <code>translation</code>	57
12.1.2. <code>reflection</code> (orthogonal symmetry)	58
12.1.3. <code>homothety</code> and <code>projection</code>	58

12.1.4.	<code>projection</code>	59
12.1.5.	<code>symmetry</code>	59
12.1.6.	<code>rotation</code>	60
12.1.7.	<code>rotation in radian</code>	60
12.1.8.	<code>rotation with nodes</code>	60
12.1.9.	<code>inversion</code>	61
12.1.10.	<code>Inversion of lines ex 1</code>	62
12.1.11.	<code>inversion of lines ex 2</code>	62
12.1.12.	<code>inversion of lines ex 3</code>	62
12.1.13.	<code>inversion of circle and homothety</code>	63
12.1.14.	<code>inversion of Triangle with respect to the Incircle</code>	63
12.1.15.	<code>inversion: orthogonal circle with inversion circle</code>	63
12.1.16.	<code>inversion negative</code>	64
12.2.	<code>Transformation of multiple points; \tkzDefPointsBy</code>	65
12.2.1.	<code>translation of multiple points</code>	65
12.2.2.	<code>symmetry of multiple points: an oval</code>	66
13.	<code>Defining points using a vector</code>	66
13.1.	<code>\tkzDefPointWith</code>	66
13.1.1.	<code>Option colinear at, simple example</code>	67
13.1.2.	<code>Option colinear at, complex example</code>	67
13.1.3.	<code>Option colinear at</code>	68
13.1.4.	<code>Option colinear at</code>	68
13.1.5.	<code>Option orthogonal</code>	68
13.1.6.	<code>Option orthogonal</code>	69
13.1.7.	<code>Option orthogonal more complicated example</code>	69
13.1.8.	<code>Options colinear and orthogonal</code>	70
13.1.9.	<code>Option orthogonal normed</code>	70
13.1.10.	<code>Option orthogonal normed and K=2</code>	70
13.1.11.	<code>Option linear</code>	70
13.1.12.	<code>Option linear normed</code>	71
13.2.	<code>\tkzGetVectxy</code>	71
13.2.1.	<code>Coordinate transfer with \tkzGetVectxy</code>	71
14.	<code>Straight lines</code>	71
14.1.	<code>Definition of straight lines</code>	71
14.1.1.	<code>With mediator</code>	72
14.1.2.	<code>An envelope with option mediator</code>	72
14.1.3.	<code>A parabola with option mediator</code>	73
14.1.4.	<code>With options bisector and normed</code>	73
14.1.5.	<code>With option parallel=through</code>	73
14.1.6.	<code>With option orthogonal and parallel</code>	74
14.1.7.	<code>With option altitude</code>	74
14.1.8.	<code>With option euler</code>	74
14.1.9.	<code>Tangent passing through a point on the circle tangent at</code>	75
14.1.10.	<code>Choice of contact point with tangents passing through an external point option tangent from</code>	75
14.1.11.	<code>Example of tangents passing through an external point</code>	76
14.1.12.	<code>Example of Andrew Mertz</code>	76
14.1.13.	<code>Drawing a tangent option tangent from</code>	77

15.	Triangles	77
15.1.	Definition of triangles <code>\tkzDefTriangle</code>	77
15.1.1.	Option <code>equilateral</code>	78
15.1.2.	Option <code>two angles</code>	79
15.1.3.	Option <code>school</code>	79
15.1.4.	Option <code>pythagore</code>	79
15.1.5.	Option <code>pythagore</code> and <code>swap</code>	79
15.1.6.	Option <code>golden</code>	80
15.1.7.	Option <code>euclid</code>	80
15.1.8.	Option <code>isosceles right</code>	81
15.1.9.	Option <code>gold</code>	81
15.2.	Specific triangles with <code>\tkzDefSpcTriangle</code>	82
15.2.1.	How to name the vertices	82
15.3.	Option <code>medial</code> or <code>centroid</code>	82
15.3.1.	Option <code>in</code> or <code>incentral</code>	83
15.3.2.	Option <code>ex</code> or <code>excentral</code>	83
15.3.3.	Option <code>intouch</code> or <code>contact</code>	84
15.3.4.	Option <code>extouch</code>	84
15.3.5.	Option <code>orthic</code>	85
15.3.6.	Option <code>feuerbach</code>	86
15.3.7.	Option <code>tangential</code>	86
15.3.8.	Option <code>euler</code>	87
15.3.9.	Option <code>euler</code> and Option <code>orthic</code>	88
15.3.10.	Option <code>symmedial</code>	89
15.4.	Permutation of two points of a triangle	89
15.4.1.	Modification of the <code>school</code> triangle	90
16.	Definition of polygons	90
16.1.	Defining the points of a square	90
16.1.1.	Using <code>\tkzDefSquare</code> with two points	90
16.1.2.	Use of <code>\tkzDefSquare</code> to obtain an isosceles right-angled triangle	91
16.1.3.	Pythagorean Theorem and <code>\tkzDefSquare</code>	91
16.2.	Defining the points of a rectangle	91
16.2.1.	Example of a rectangle definition	91
16.3.	Definition of parallelogram	92
16.3.1.	Example of a parallelogram definition	92
16.4.	The golden rectangle	92
16.4.1.	Golden Rectangles	92
16.4.2.	Construction of the golden rectangle	93
16.5.	Regular polygon	93
16.5.1.	Option <code>center</code>	93
16.5.2.	Option <code>side</code>	94
17.	Circles	95
17.1.	Characteristics of a circle: <code>\tkzDefCircle</code>	95
17.1.1.	Example with option <code>R</code>	96
17.1.2.	Example with option <code>diameter</code>	96
17.1.3.	Circles inscribed and circumscribed for a given triangle	96
17.1.4.	Example with option <code>ex</code>	96
17.1.5.	Euler's circle for a given triangle with option <code>euler</code>	97
17.1.6.	Apollonius circles for a given segment option <code>apollonius</code>	98
17.1.7.	Circles exinscribed to a given triangle option <code>ex</code>	98
17.1.8.	Spieker circle with option <code>spieker</code>	98

17.2.	Projection of excenters . . . . .	99
17.2.1.	<b>Excircles</b> . . . . .	100
17.2.2.	<b>Orthogonal from</b> . . . . .	101
17.2.3.	<b>Orthogonal through</b> . . . . .	101
17.3.	Definition of circle by transformation; <code>\tkzDefCircleBy</code> . . . . .	102
17.3.1.	<b>Translation</b> . . . . .	103
17.3.2.	<b>Reflection</b> (orthogonal symmetry) . . . . .	103
17.3.3.	<b>Homothety</b> . . . . .	103
17.3.4.	<b>Symmetry</b> . . . . .	104
17.3.5.	<b>Rotation</b> . . . . .	104
17.3.6.	<b>Inversion</b> . . . . .	104
18.	<b>Intersections</b> . . . . .	104
18.1.	Intersection of two straight lines <code>\tkzInterLL</code> . . . . .	105
18.1.1.	Example of intersection between two straight lines . . . . .	105
18.2.	Intersection of a straight line and a circle <code>\tkzInterLC</code> . . . . .	105
18.2.1.	test line-circle intersection . . . . .	106
18.2.2.	Line-circle intersection . . . . .	106
18.2.3.	Line passing through the center option <b>common</b> . . . . .	106
18.2.4.	Line-circle intersection with option <b>common</b> . . . . .	107
18.2.5.	Line-circle intersection order of points . . . . .	107
18.2.6.	Example with <code>\foreach</code> . . . . .	108
18.2.7.	Line-circle intersection with option <b>near</b> . . . . .	108
18.2.8.	More complex example of a line-circle intersection . . . . .	109
18.2.9.	Circle defined by a center and a measure, and special cases . . . . .	109
18.2.10.	Calculation of radius . . . . .	110
18.2.11.	Option with <b>nodes</b> . . . . .	111
18.3.	Intersection of two circles <code>\tkzInterCC</code> . . . . .	111
18.3.1.	test circle-circle intersection . . . . .	112
18.3.2.	circle-circle intersection with <b>common</b> point. . . . .	112
18.3.3.	circle-circle intersection order of points. . . . .	112
18.3.4.	Construction of an equilateral triangle. . . . .	113
18.3.5.	Segment trisection . . . . .	113
18.3.6.	With the option with <b>nodes</b> . . . . .	114
18.3.7.	Mix of intersections . . . . .	114
18.3.8.	Altshiller-Court's theorem . . . . .	114
19.	<b>Angles</b> . . . . .	115
19.1.	Definition and usage with <b>tkz-euclide</b> . . . . .	115
19.2.	Recovering an angle <code>\tkzGetAngle</code> . . . . .	116
19.3.	Angle formed by three points . . . . .	116
19.3.1.	Verification of angle measurement . . . . .	117
19.3.2.	Determination of the three angles of a triangle . . . . .	117
19.3.3.	Angle between two circles . . . . .	117
19.4.	Angle formed by a straight line with the horizontal axis <code>\tkzFindSlopeAngle</code> . . . . .	118
19.4.1.	How to use <code>\tkzFindSlopeAngle</code> . . . . .	118
19.4.2.	Use of <code>\tkzFindSlopeAngle</code> and <code>\tkzGetAngle</code> . . . . .	118
19.4.3.	Another use of <code>\tkzFindSlopeAngle</code> . . . . .	119
20.	<b>Random point definition</b> . . . . .	119
20.1.	Obtaining random points . . . . .	119
20.1.1.	Random point in a rectangle . . . . .	120
20.1.2.	Random point on a segment or a line . . . . .	120

20.1.3. Random point on a circle or a disk . . . . .	120
<b>IV. Drawing and Filling</b>	<b>121</b>
<b>21. Drawing</b>	<b>122</b>
21.1. Draw a point or some points . . . . .	122
21.1.1. Drawing points <code>\tkzDrawPoint</code> . . . . .	122
21.1.2. Example of point drawings . . . . .	122
21.1.3. Example . . . . .	123
<b>22. Drawing the lines</b>	<b>123</b>
22.1. Draw a straight line . . . . .	123
22.1.1. Examples with <code>add</code> . . . . .	124
22.1.2. Example with <code>\tkzDrawLines</code> . . . . .	124
<b>23. Drawing a segment</b>	<b>124</b>
23.1. Draw a segment <code>\tkzDrawSegment</code> . . . . .	124
23.1.1. Example with point references . . . . .	125
23.1.2. Example of extending an segment with option <code>add</code> . . . . .	125
23.1.3. Adding dimensions with option <code>dim</code> new code from Muzimuzhi Z . . . . .	125
23.1.4. Adding dimensions with option <code>dim part I</code> . . . . .	126
23.1.5. Adding dimensions with option <code>dim part II</code> . . . . .	127
23.2. Drawing segments <code>\tkzDrawSegments</code> . . . . .	127
23.2.1. Place an arrow on segment . . . . .	127
23.3. Drawing line segment of a triangle . . . . .	128
23.3.1. How to draw <code>Altitude</code> . . . . .	128
23.4. Drawing a polygon . . . . .	128
23.4.1. <code>\tkzDrawPolygon</code> . . . . .	128
23.4.2. Option <code>two angles</code> . . . . .	129
23.4.3. Style of line . . . . .	129
23.5. Drawing a polygonal chain . . . . .	129
23.5.1. Polygonal chain . . . . .	130
23.5.2. The idea is to inscribe two squares in a semi-circle. . . . .	130
23.5.3. Polygonal chain: index notation . . . . .	130
<b>24. Draw a circle with <code>\tkzDrawCircle</code></b>	<b>130</b>
24.1. Draw one circle . . . . .	130
24.1.1. Circles and styles, draw a circle and color the disc . . . . .	131
24.2. Drawing circles . . . . .	131
24.2.1. Circles defined by a triangle. . . . .	132
24.2.2. Concentric circles. . . . .	132
24.2.3. Exinscribed circles. . . . .	133
24.2.4. Cardioid . . . . .	133
24.3. Drawing semicircle . . . . .	134
24.3.1. Use of <code>\tkzDrawSemiCircle</code> . . . . .	134
24.4. Drawing semicircles . . . . .	134
24.4.1. Use of <code>\tkzDrawSemiCircles</code> : Golden arbelos . . . . .	134
<b>25. Draw an ellipse with <code>\tkzDrawEllipse</code></b>	<b>135</b>
25.1. Draw an ellipse . . . . .	135
25.1.1. Example of drawing an ellipse . . . . .	135



26.	Drawing arcs	135
26.1.	Macro: <code>\tkzDrawArc</code>	135
26.1.1.	Option <code>towards</code>	136
26.1.2.	Option <code>towards</code>	136
26.1.3.	Option <code>rotate</code>	137
26.1.4.	Option <code>R</code>	137
26.1.5.	Option <code>R</code> with <code>nodes</code>	137
26.1.6.	Option <code>delta</code>	137
26.1.7.	Option <code>angles</code> : example 1	138
26.1.8.	Option <code>angles</code> : example 2	139
26.1.9.	Option <code>reverse</code> : inversion of the arrow	139
27.	Drawing a sector or sectors	139
27.1.	<code>\tkzDrawSector</code>	139
27.1.1.	<code>\tkzDrawSector</code> and <code>towards</code>	140
27.1.2.	<code>\tkzDrawSector</code> and <code>rotate</code>	140
27.1.3.	<code>\tkzDrawSector</code> and <code>R</code>	140
27.1.4.	<code>\tkzDrawSector</code> and <code>R</code> with <code>nodes</code>	140
27.1.5.	<code>\tkzDrawSector</code> and <code>R</code> with <code>nodes</code>	141
27.2.	Coloring a disc	141
27.2.1.	Yin and Yang	142
27.2.2.	From a sangaku	142
27.2.3.	Clipping and filling part I	143
27.2.4.	Clipping and filling part II	143
27.2.5.	Clipping and filling part III	144
27.3.	Coloring a polygon	144
27.3.1.	<code>\tkzFillPolygon</code>	144
27.4.	<code>\tkzFillSector</code>	144
27.4.1.	<code>\tkzFillSector</code> and <code>towards</code>	145
27.4.2.	<code>\tkzFillSector</code> and <code>rotate</code>	145
27.5.	Colour an angle: <code>\tkzFillAngle</code>	145
27.5.1.	Example with <code>size</code>	146
27.5.2.	Changing the order of items	146
27.5.3.	Multiples angles	147
28.	Controlling Bounding Box	147
28.1.	Utility of <code>\tkzInit</code>	147
28.2.	<code>\tkzInit</code>	148
28.3.	<code>\tkzClip</code>	148
28.4.	<code>\tkzClip</code> and the option <code>space</code>	148
28.5.	<code>tkzShowBB</code>	149
28.5.1.	Example with <code>\tkzShowBB</code>	149
28.6.	<code>tkzClipBB</code>	149
28.6.1.	Example with <code>\tkzClipBB</code> and the bisectors	150
29.	Clipping different objects	151
29.1.	Clipping a polygon	151
29.1.1.	<code>\tkzClipPolygon</code>	151
29.1.2.	<code>\tkzClipPolygon[out]</code>	151
29.1.3.	Example: use of <code>Clip</code> for Sangaku in a square	152
29.2.	Clipping a disc	152
29.2.1.	Simple clip	152
29.3.	Clip out	153

29.4.	Intersection of disks	153
29.5.	Clipping a sector	153
29.5.1.	Example 1	154
29.5.2.	Example 2	154
29.6.	Options from TikZ: trim left or right	154
29.7.	TikZ Controls <code>\pgfinterruptboundingbox</code> and <code>\endpgfinterruptboundingbox</code>	154
29.7.1.	Example about controlling the bounding box	155
29.8.	Reverse clip: <code>tkzreverseclip</code>	155
29.8.1.	Example with <code>\tkzClipPolygon[out]</code>	155
<b>V.</b>	<b>Marking</b>	<b>157</b>
29.9.	Mark a segment <code>\tkzMarkSegment</code>	158
29.9.1.	Several marks	158
29.9.2.	Use of <code>mark</code>	158
29.10.	Marking segments <code>\tkzMarkSegments</code>	158
29.10.1.	Marks for an isosceles triangle	158
29.11.	Another marking	159
29.12.	Mark an arc <code>\tkzMarkArc</code>	159
29.12.1.	Several marks	159
29.13.	Mark an angle mark: <code>\tkzMarkAngle</code>	159
29.13.1.	Example with <code>mark = x</code> and with <code>mark =</code>	160
29.14.	Problem to mark a small angle: <code>Option vecLen</code>	160
29.15.	Marking a right angle: <code>\tkzMarkRightAngle</code>	161
29.15.1.	Example of marking a right angle	161
29.15.2.	Example of marking a right angle, german style	162
29.15.3.	Mix of styles	162
29.15.4.	Full example	163
29.16.	<code>\tkzMarkRightAngles</code>	163
29.17.	Angles Library	163
29.17.1.	Angle with TikZ	164
<b>VI.</b>	<b>Labelling</b>	<b>165</b>
<b>30.</b>	<b>Labelling</b>	<b>166</b>
30.1.	Label for a point	166
30.1.1.	Example with <code>\tkzLabelPoint</code>	166
30.1.2.	Label and reference	166
30.2.	Add labels to points <code>\tkzLabelPoints</code>	166
30.2.1.	Example with <code>\tkzLabelPoints</code>	167
30.3.	Automatic position of labels <code>\tkzAutoLabelPoints</code>	167
30.3.1.	Label for points with <code>\tkzAutoLabelPoints</code>	167
31.	Label for a segment	167
31.0.1.	First example	168
31.0.2.	Example: blackboard	168
31.0.3.	Labels and option: <code>swap</code>	168
31.0.4.	Labels for an isosceles triangle	169
32.	Add labels on a straight line <code>\tkzLabelLine</code>	169
32.0.1.	Example with <code>\tkzLabelLine</code>	169
32.1.	Label at an angle: <code>\tkzLabelAngle</code>	169
32.1.1.	Example author js bibra stackexchange	170

32.1.2.	With <code>pos</code> . . . . .	170
32.1.3.	<code>pos</code> and <code>\tkzLabelAngles</code> . . . . .	171
32.2.	Giving a label to a circle . . . . .	171
32.2.1.	Example . . . . .	172
33.	Label for an arc . . . . .	172
33.0.1.	Label on arc . . . . .	172
VII.	Complements . . . . .	173
34.	Using the compass . . . . .	174
34.1.	Main macro <code>\tkzCompass</code> . . . . .	174
34.1.1.	Option <code>length</code> . . . . .	174
34.1.2.	Option <code>delta</code> . . . . .	174
34.2.	Multiple constructions <code>\tkzCompassss</code> . . . . .	174
34.2.1.	Use <code>\tkzCompassss</code> . . . . .	175
35.	The Show . . . . .	175
35.1.	Show the constructions of some lines <code>\tkzShowLine</code> . . . . .	175
35.1.1.	Example of <code>\tkzShowLine</code> and <code>parallel</code> . . . . .	175
35.1.2.	Example of <code>\tkzShowLine</code> and <code>perpendicular</code> . . . . .	176
35.1.3.	Example of <code>\tkzShowLine</code> and <code>bisector</code> . . . . .	176
35.1.4.	Example of <code>\tkzShowLine</code> and <code>mediator</code> . . . . .	176
35.2.	Constructions of certain transformations <code>\tkzShowTransformation</code> . . . . .	176
35.2.1.	Example of the use of <code>\tkzShowTransformation</code> . . . . .	177
35.2.2.	Another example of the use of <code>\tkzShowTransformation</code> . . . . .	177
36.	Protractor . . . . .	178
36.1.	The macro <code>\tkzProtractor</code> . . . . .	178
36.1.1.	The circular protractor . . . . .	178
36.1.2.	The circular protractor, transparent and returned . . . . .	179
37.	Miscellaneous tools and mathematical tools . . . . .	179
37.1.	Duplicate a segment . . . . .	179
37.1.1.	Use of <code>\tkzDuplicateSegment</code> . . . . .	179
37.1.2.	Proportion of gold with <code>\tkzDuplicateSegment</code> . . . . .	180
37.1.3.	Golden triangle or sublime triangle . . . . .	180
37.2.	Segment length <code>\tkzCalcLength</code> . . . . .	180
37.2.1.	Compass square construction . . . . .	181
37.2.2.	Example . . . . .	181
37.3.	Transformation from pt to cm or cm to pt . . . . .	181
37.4.	Change of unit . . . . .	182
37.5.	Get point coordinates . . . . .	182
37.5.1.	Coordinate transfer with <code>\tkzGetPointCoord</code> . . . . .	182
37.5.2.	Sum of vectors with <code>\tkzGetPointCoord</code> . . . . .	182
37.6.	Swap labels of points . . . . .	183
37.6.1.	Use of <code>\tkzSwapPoints</code> . . . . .	183
37.7.	Dot Product . . . . .	183
37.7.1.	Simple example . . . . .	184
37.7.2.	Cocyclic points . . . . .	184
37.8.	Power of a point with respect to a circle . . . . .	185
37.8.1.	Power from the radical axis . . . . .	185

37.9.	Radical axis . . . . .	185
37.9.1.	Two circles disjointed . . . . .	186
37.10.	Two intersecting circles . . . . .	186
37.11.	Two externally tangent circles . . . . .	186
37.12.	Two circles tangent internally . . . . .	187
37.12.1.	Three circles . . . . .	187
37.13.	<code>\tkzIsLinear</code> , <code>\tkzIsOrtho</code> . . . . .	187
37.13.1.	Use of <code>\tkzIsOrtho</code> and <code>\tkzIsLinear</code> . . . . .	188
VIII. Working with style		189
38.	Predefined styles	190
39.	Points style	190
39.1.	Use of <code>\tkzSetUpPoint</code> . . . . .	190
39.1.1.	Global style or local style . . . . .	191
39.1.2.	Local style . . . . .	191
39.1.3.	<b>Style</b> and <b>scope</b> . . . . .	191
39.1.4.	Simple example with <code>\tkzSetUpPoint</code> . . . . .	191
39.1.5.	Use of <code>\tkzSetUpPoint</code> inside a group . . . . .	192
40.	Lines style	192
40.1.	Use of <code>\tkzSetUpLine</code> . . . . .	192
40.1.1.	Change line width . . . . .	193
40.1.2.	Change style of line . . . . .	193
40.1.3.	Example 3: extend lines . . . . .	194
41.	Arc style	194
41.1.	The macro <code>\tkzSetUpArc</code> . . . . .	194
41.1.1.	Use of <code>\tkzSetUpArc</code> . . . . .	194
42.	Compass style, configuration macro <code>\tkzSetUpCompass</code>	195
42.1.	The macro <code>\tkzSetUpCompass</code> . . . . .	195
42.1.1.	Use of <code>\tkzSetUpCompass</code> . . . . .	195
42.1.2.	Use of <code>\tkzSetUpCompass</code> with <code>\tkzShowLine</code> . . . . .	195
43.	Label style	195
43.1.	The macro <code>\tkzSetUpLabel</code> . . . . .	195
43.1.1.	Use of <code>\tkzSetUpLabel</code> . . . . .	196
44.	Own style	196
44.1.	The macro <code>\tkzSetUpStyle</code> . . . . .	196
44.1.1.	Use of <code>\tkzSetUpStyle</code> . . . . .	196
45.	How to use <b>arrows</b>	196
45.1.	Arrows at endpoints on segment, ray or line . . . . .	197
45.1.1.	Scaling an arrow head . . . . .	198
45.1.2.	Using vector style . . . . .	198
45.2.	Arrows on middle point of a line segment . . . . .	198
45.2.1.	In a parallelogram . . . . .	198
45.2.2.	A line parallel to another one . . . . .	199
45.2.3.	Arrow on a circle . . . . .	199
45.3.	Arrows on all segments of a polygon . . . . .	199
45.3.1.	Arrow on each segment with <b>tkz arrows</b> . . . . .	199

45.3.2. Using <b>tkz arrows</b> with a circle . . . . .	200
<b>IX. Examples</b>	<b>201</b>
46. Different authors	202
46.1. Code from Andrew Swan . . . . .	202
46.2. Example: Dimitris Kapeta . . . . .	202
46.3. Example : John Kitzmiller . . . . .	203
46.4. Example 1: from Indonesia . . . . .	204
46.5. Example 2: from Indonesia . . . . .	205
46.6. Illustration of the Morley theorem by Nicolas François . . . . .	207
46.7. Gou gu theorem / Pythagorean Theorem by Zhao Shuang . . . . .	208
46.8. Reuleaux-Triangle . . . . .	209
47. Some interesting examples	210
47.1. Square root of the integers . . . . .	210
47.2. About right triangle . . . . .	211
47.3. Archimedes . . . . .	211
47.3.1. Square and rectangle of same area; Golden section . . . . .	213
47.3.2. Steiner Line and Simson Line . . . . .	214
47.4. Lune of Hippocrates . . . . .	215
47.5. Lunes of Hasan Ibn al-Haytham . . . . .	215
47.6. About clipping circles . . . . .	217
47.7. Similar isosceles triangles . . . . .	218
47.8. Revised version of "Tangente" . . . . .	219
47.9. "Le Monde" version . . . . .	220
47.10. Triangle altitudes . . . . .	221
47.11. Altitudes - other construction . . . . .	222
47.12. Three circles in an Equilateral Triangle . . . . .	223
47.13. Law of sines . . . . .	224
47.14. Flower of Life . . . . .	225
47.15. Pentagon in a circle . . . . .	227
47.16. Pentagon in a square . . . . .	228
47.17. Hexagon Inscribed . . . . .	229
47.17.1. Hexagon Inscribed version 1 . . . . .	229
47.17.2. Hexagon Inscribed version 2 . . . . .	229
47.18. Power of a point with respect to a circle . . . . .	230
47.19. Radical axis of two non-concentric circles . . . . .	231
47.20. External homothetic center . . . . .	232
47.21. Tangent lines to two circles . . . . .	233
47.22. Tangent lines to two circles with radical axis . . . . .	234
47.23. Middle of a segment with a compass . . . . .	236
47.24. Definition of a circle _Apollonius_ . . . . .	237
47.25. Application of Inversion : <b>Pappus chain</b> . . . . .	238
47.26. Book of lemmas proposition 1 Archimedes . . . . .	239
47.27. Book of lemmas proposition 6 Archimedes . . . . .	239
47.28. "The" Circle of APOLLONIUS . . . . .	242
<b>X. FAQ</b>	<b>245</b>
48. FAQ	246
48.1. Most common errors . . . . .	246



## Part I.

General survey : a brief but comprehensive review

## News and compatibility

### 0.1. With 5.10 version

- Added french documentation
- Added the mini option. You can use this option with the `tkz-elements` package. Only the modules required for tracing will be loaded. This option is currently only available if you are using `tkz-elements`.



## 1. Working with lua

### 1.0.1. Option lua

You can now use the `lua` option with `tkz-euclide` version 5. You just have to write in your preamble `\usepackage[lua]{tkz-euclide}`. Obviously, you'll need to compile with LuaLaTeX. Nothing changes for the syntax.

Without the option you can use `tkz-euclide` with the proposed code of version 4.25.

This version is not yet finalized although the documentation you are currently reading has been compiled with this option.

Some information about the method used and the results obtained. Concerning the method, I considered two possibilities. The first one was simply to replace everywhere I could the calculations made by `xfp` or sometimes by `lua`. This is how I went from `fp` to `xfp` and now to `lua`. The second and more ambitious possibility would have been to associate to each point a complex number and to make the calculations on the complexes with `lua`. Unfortunately for that I have to use libraries for which I don't know the license.

Otherwise the results are good. This documentation with LuaLaTeX and `xfp` compiles in 47s while with `lua` it takes only 30s for 236 pages.

Another document of 61 pages is compiled 16s with pdfLaTeX and `xfp` and 13s with LuaLaTeX and `xfp`.

This documentation compiles with `\usepackage{tkz-base}` and `\usepackage[lua]{tkz-euclide}` but I didn't test all the interactions thoroughly.

### 1.0.2. Option mini

When you use `tkz-elements` solely to determine the points in your figures, it is not necessary to load all the modules of `tkz-euclide`. In this case, by using the `mini` option `\usepackage[mini]{tkz-euclide}`, you will only load the modules necessary for the drawings.

## 2. Installation

`tkz-euclide` is on the server of the CTAN<sup>1</sup>. If you want to test a beta version, just put the following files in a `texmf` folder that your system can find. You will have to check several points:


- The `tkz-euclide` folder must be located on a path recognized by `latex`.
- The `tkz-euclide` uses `xfp`.
- You need to have PGF installed on your computer. `tkz-euclide` use several libraries of TikZ

<sup>1</sup> `tkz-euclide` is part of TeXLive and `tlmgr` allows you to install them. This package is also part of MiKTeX under Windows.

angles,  
 arrows,  
 arrows.meta,  
 calc,  
 decorations,  
 decorations.markings,  
 decorations.pathreplacing,  
 decorations.shapes,  
 decorations.text,  
 decorations.pathmorphing,  
 intersections,  
 math,  
 plotmarks,  
 positioning,  
 quotes,  
 shapes.misc,  
 through

- This documentation and all examples were obtained with `lualatex` but `pdflatex` or `xelatex` should be suitable.

### 3. Presentation and Overview



```

\begin{tikzpicture}[scale=.25]
\tkzDefPoints{0/0/A,12/0/B,6/12*sind(60)/C}
\foreach \density in {20,30,...,240}{%
\tkzDrawPolygon[fill=teal!\density](A,B,C)
\pgfnodealias{X}{A}
\tkzDefPointWith[linear,K=.15](A,B) \tkzGetPoint{A}
\tkzDefPointWith[linear,K=.15](B,C) \tkzGetPoint{B}
\tkzDefPointWith[linear,K=.15](C,X) \tkzGetPoint{C}}
\end{tikzpicture}

```

#### 3.1. Why `tkz-euclide`?

My initial goal was to provide other mathematics teachers and myself with a tool to quickly create Euclidean geometry figures without investing too much effort in learning a new programming language. Of course, `tkz-euclide` is for math teachers who use  $\text{\LaTeX}$  and makes it possible to easily create correct drawings by means of  $\text{\LaTeX}$ .

It appeared that the simplest method was to reproduce the one used to obtain construction by hand. To describe a construction, you must, of course, define the objects but also the actions that you perform. It seemed to me that syntax close to the language of mathematicians and their students would be more easily understandable; moreover, it also seemed to me that this syntax should be close to that of  $\text{\LaTeX}$ . The objects, of course, are points, segments, lines, triangles, polygons and circles. As for actions, I considered five to be sufficient, namely: define, create, draw, mark and label.

The syntax is perhaps too verbose but it is, I believe, easily accessible. As a result, the students like teachers were able to easily access this tool.

#### 3.2. `TikZ` vs `tkz-euclide`

I love programming with `TikZ`, and without `TikZ` I would never have had the idea to create `tkz-euclide` but never forget that behind it there is `TikZ` and that it is always possible to insert code from `TikZ`. `tkz-euclide` doesn't prevent you from using `TikZ`. That said, I don't think mixing syntax is a good thing.

There is no need to compare TikZ and `tkz-euclide`. The latter is not addressed to the same audience as TikZ. The first one allows you to do a lot of things, the second one only does geometry drawings. The first one can do everything the second one does, but the second one will more easily do what you want.

The main purpose is to define points to create geometrical figures. `tkz-euclide` allows you to draw the essential objects of Euclidean geometry from these points but it may be insufficient for some actions like coloring surfaces. In this case you will have to use TikZ which is always possible.

Here are some comparisons between TikZ and `tkz-euclide` 4. For this I will use the geometry examples from the PGFManual. The two most important Euclidean tools used by early Greeks to construct different geometrical shapes and angles were a compass and a straightedge. My idea is to allow you to follow step by step a construction that would be done by hand (with compass and straightedge) as naturally as possible.

### 3.2.1. Book I, proposition I \_Euclid's Elements\_

#### Book I, proposition I \_Euclid's Elements\_

*To construct an equilateral triangle on a given finite straight line.*

Explanation :

The fourth tutorial of the *PgfManual* is about geometric constructions. *T. Tantau* proposes to get the drawing with its beautiful tool TikZ. Here I propose the same construction with *tkz-elements*. The color of the TikZ code is green!50!black and that of *tkz-elements* is red.

```
\usepackage{tikz}
\usetikzlibrary{calc,intersections,through,backgrounds}

\usepackage{tkz-euclide}
```

How to get the line AB ? To get this line, we use two fixed points.

```
\coordinate [label=left:$A$] (A) at (0,0);
\coordinate [label=right:$B$] (B) at (1.25,0.25);
\draw (A) -- (B);

\tkzDefPoint(0,0){A}
\tkzDefPoint(1.25,0.25){B}
\tkzDrawSegment(A,B)
\tkzLabelPoint[left](A){$A$}
\tkzLabelPoint[right](B){$B$}
```

We want to draw a circle around the points A and B whose radius is given by the length of the line AB.

```
\draw let \p1 = ($ (B) - (A) $),
\n2 = {veclen(\x1,\y1)} in
      (A) circle (\n2)
      (B) circle (\n2);
```

```
\tkzDrawCircles(A,B B,A)
```

The intersection of the circles  $\mathcal{D}$  and  $\mathcal{E}$

```
draw [name path=A--B] (A) -- (B);
node (D) [name path=D,draw,circle through=(B),label=left:$D$] at (A) {};
node (E) [name path=E,draw,circle through=(A),label=right:$E$] at (B) {};
path [name intersections={of=D and E, by={ [label=above:$C$]C, [label=below:$C'$]C' }}];
draw [name path=C--C',red] (C) -- (C');
path [name intersections={of=A--B and C--C',by=F}];
node [fill=red,inner sep=1pt,label=-45:$F$] at (F) {};
```

```
\tkzInterCC(A,B)(B,A) \tkzGetPoints{C}{X}
```

How to draw points :


```
\foreach \point in {A,B,C}
\fill [black,opacity=.5] (\point) circle (2pt);

\tkzDrawPoints[fill=gray,opacity=.5](A,B,C)
```

### 3.2.2. Complete code with tkz-euclide

We need to define colors

```
\colorlet{input}{red!80!black}
\colorlet{output}{red!70!black}
\colorlet{triangle}{green!50!black!40}
```



```
\colorlet{input}{red!80!black}
\colorlet{output}{red!70!black}
\colorlet{triangle}{green!50!black!40}
\begin{tikzpicture}[scale=1.25,thick,help lines/.style={thin,draw=black!50}]
\tkzDefPoint(0,0){A}
\tkzDefPoint(1.25+rand(),0.25+rand()){B}
\tkzInterCC(A,B)(B,A) \tkzGetPoints{C}{X}

\tkzFillPolygon[triangle,opacity=.5](A,B,C)
\tkzDrawSegment[input](A,B)
\tkzDrawSegments[red](A,C B,C)
\tkzDrawCircles[help lines](A,B B,A)
\tkzDrawPoints[fill=gray,opacity=.5](A,B,C)

\tkzLabelPoints(A,B)
\tkzLabelCircle[below=12pt](A,B)(180){$\mathcal{D}$}
\tkzLabelCircle[above=12pt](B,A)(180){$\mathcal{E}$}
\tkzLabelPoint[above,red](C){C}

\end{tikzpicture}
```

## 3.2.3. Book I, Proposition II \_Euclid's Elements\_

## Book I, Proposition II \_Euclid's Elements\_

*To place a straight line equal to a given straight line with one end at a given point.*

## Explanation

In the first part, we need to find the midpoint of the straight line AB. With TikZ we can use the calc library

```
\coordinate [label=left:$A$] (A) at (0,0);
\coordinate [label=right:$B$] (B) at (1.25,0.25);
\draw (A) -- (B);
\node [fill=red,inner sep=1pt,label=below:$X$] (X) at ($ (A)!.5!(B) $) {};
```

With tkz-euclide we have a macro `\tkzDefMidPoint`, we get the point X with `\tkzGetPoint` but we don't need this point to get the next step.

```
\tkzDefPoints{0/0/A,0.75/0.25/B,1/1.5/C}
\tkzDefMidPoint(A,B) \tkzGetPoint{X}
```

Then we need to construct a triangle equilateral. It's easy with tkz-euclide . With TikZ you need some effort because you need to use the midpoint X to get the point D with trigonometry calculation.

```
\node [fill=red,inner sep=1pt,label=below:$X$] (X) at ($ (A)!.5!(B) $) {};
```

```
\node [fill=red,inner sep=1pt,label=above:$D$] (D) at
($ (X) ! {sin(60)*2} ! 90:(B) $) {};
```

```
\draw (A) -- (D) -- (B);
```

```
\tkzDefTriangle[equilateral](A,B) \tkzGetPoint{D}
```

We can draw the triangle at the end of the picture with

```
\tkzDrawPolygon{A,B,C}
```

We know how to draw the circle  $\mathcal{H}$  around B through C and how to place the points E and F

```
\node (H) [label=135:$H$,draw,circle through=(C)] at (B) {};
```

```
\draw (D) -- ($ (D) ! 3.5 ! (B) $) coordinate [label=below:$F$] (F);
```

```
\draw (D) -- ($ (D) ! 2.5 ! (A) $) coordinate [label=below:$E$] (E);
```

```
\tkzDrawCircle(B,C)
```

```
\tkzDrawLines[add=0 and 2](D,A D,B)
```

We can place the points E and F at the end of the picture. We don't need them now.

Intersecting a Line and a Circle : here we search the intersection of the circle around B through C and the line DB. The infinite straight line DB intercepts the circle but with TikZ we need to extend the lines DB and that can be done using partway calculations. We get the point F and BF or DF intercepts the circle

```
\node (H) [label=135:$H$,draw,circle through=(C)] at (B) {};
```

```
\path let \p1 = ($ (B) - (C) $) in
coordinate [label=left:$G$] (G) at ($ (B) ! vecLen(\x1,\y1) ! (F) $);
```

```
\fill[red,opacity=.5] (G) circle (2pt);
```


Like the intersection of two circles, it's easy to find the intersection of a line and a circle with tkz-euclide. We don't need F

```
\tkzInterLC(B,D)(B,C)\tkzGetFirstPoint{G}
```

There are no more difficulties. Here the final code with some simplifications. We draw the circle  $\mathcal{K}$  with center D and passing through G. It intersects the line AD at point L.  $AL = BC$ .

```
\tkzDrawCircle(D,G)
```

```
\tkzInterLC(D,A)(D,G)\tkzGetSecondPoint{L}
```



```
\begin{tikzpicture}[scale=1.5]
\tkzDefPoint(0,0){A}
\tkzDefPoint(0.75,0.25){B}
\tkzDefPoint(1,1.5){C}
\tkzDefTriangle[equilateral](A,B)\tkzGetPoint{D}
\tkzInterLC[near](D,B)(B,C)\tkzGetSecondPoint{G}
\tkzInterLC[near](A,D)(D,G)\tkzGetFirstPoint{L}
\tkzDrawCircles(B,C D,G)
\tkzDrawLines[add=0 and 2](D,A D,B)
\tkzDrawSegment(A,B)
\tkzDrawSegments[red](A,L B,C)
\tkzDrawPoints[red](D,L,G)
\tkzDrawPoints[fill=gray](A,B,C)
\tkzLabelPoints[left,red](A)
\tkzLabelPoints[below right,red](L)
\tkzLabelCircle[above](B,C)(20){$\mathcal{H}$}
\tkzLabelPoints[above left](D)
\tkzLabelPoints[above](G)
\tkzLabelPoints[above,red](C)
\tkzLabelPoints[right,red](B)
\tkzLabelCircle[below](D,G)(-90){$\mathcal{K}$}
\end{tikzpicture}
```

### 3.3. tkz-euclide 4 vs tkz-euclide 3

Now I am no longer a Mathematics teacher, and I only spend a few hours studying geometry. I wanted to avoid multiple complications by trying to make **tkz-euclide** independent of **tkz-base**. Thus was born **tkz-euclide 4**. The latter is a simplified version of its predecessor. The macros of **tkz-euclide 3** have been retained. The unit is now cm. If you need some macros from **tkz-base**, you may need to use the **\tkzInit**.

### 3.4. tkz-euclide 5 vs tkz-euclide 4

Nothing changes for the user. Compilation must be carried out using the LuaLaTeX engine, and the results are more precise and obtained more quickly. Simply load **tkz-euclide** like this `\usepackage[lua]{tkz-euclide}`.

### 3.5. How to use the tkz-euclide package ?

#### 3.5.1. Let's look at a classic example

In order to show the right way, we will see how to build an equilateral triangle. Several possibilities are open to us, we are going to follow the steps of Euclid.

- First of all, you have to use a document class. The best choice to test your code is to create a single figure with the class **standalone**.

```
\documentclass{standalone}
```

- Then load the **tkz-euclide** package:

```
\usepackage{tkz-euclide} or \usepackage[lua]{tkz-euclide}
```

You don't need to load TikZ because the **tkz-euclide** package works on top of TikZ and loads it.

- Start the document and open a TikZ picture environment:

```
\begin{document}
\begin{tikzpicture}
```

- Now we define two fixed points:

```
\tkzDefPoint(0,0){A}
\tkzDefPoint(5,2){B}
```

- Two points define two circles, let's use these circles:

circle with center A through B and circle with center B through A. These two circles have two points in common.

```
\tkzInterCC(A,B)(B,A)
```

We can get the points of intersection with

```
\tkzGetPoints{C}{D}
```

- All the necessary points are obtained, we can move on to the final steps including the plots.

```
\tkzDrawCircles[gray,dashed](A,B B,A)
\tkzDrawPolygon(A,B,C)% The triangle
```

- Draw all points A, B, C and D:

```
\tkzDrawPoints(A,...,D)
```


- The final step, we print labels to the points and use options for positioning:

```
\tkzLabelSegments[swap](A,B){$c$}
\tkzLabelPoints(A,B,D)
\tkzLabelPoints[above](C)
```

- We finally close both environments


```
\end{tikzpicture}
\end{document}
```

- The complete code



```
\begin{tikzpicture}[scale=.5]
  % fixed points
  \tkzDefPoint(0,0){A}
  \tkzDefPoint(5,2){B}
  % calculus
  \tkzInterCC(A,B)(B,A)
  \tkzGetPoints{C}{D}
  % drawings
  \tkzDrawCircles(A,B B,A)
  \tkzDrawPolygon(A,B,C)
  \tkzDrawPoints(A,...,D)
  % marking
  \tkzMarkSegments[mark=s||](A,B B,C C,A)
  % labelling
  \tkzLabelSegments[swap](A,B){$c$}
  \tkzLabelPoints(A,B,D)
  \tkzLabelPoints[above](C)
\end{tikzpicture}
```

## 3.5.2. Part I: golden triangle



Let's analyze the figure

1. CBD and DBE are isosceles triangles;
2.  $BC = BE$  and  $(BD)$  is a bisector of the angle CBE;
3. From this we deduce that the CBD and DBE angles are equal and have the same measure  $\alpha$

$$\widehat{BAC} + \widehat{ABC} + \widehat{BCA} = 180^\circ \text{ in the triangle BAC}$$

$$3\alpha + \widehat{BCA} = 180^\circ \text{ in the triangle CBD}$$

then

$$\alpha + 2\widehat{BCA} = 180^\circ$$

or

$$\widehat{BCA} = 90^\circ - \alpha/2$$

4. Finally


$$\widehat{CBD} = \alpha = 36^\circ$$

the triangle CBD is a golden triangle.

How construct a golden triangle or an angle of  $36^\circ$ ?

1. We place the fixed points C and D. `\tkzDefPoint(0,0){C}` and `\tkzDefPoint(4,0){D}`;
2. We construct a square CDef and we construct the midpoint m of [Cf];  
We can do all of this with a compass and a rule;
3. Then we trace an arc with center m through e. This arc cross the line (Cf) at n;
4. Now the two arcs with center C and D and radius Cn define the point B.





```
\begin{tikzpicture}
  \tkzDefPoint(0,0){C}
  \tkzDefPoint(4,0){D}
  \tkzDefSquare(C,D)
  \tkzGetPoints{e}{f}
  \tkzDefMidPoint(C,f)
  \tkzGetPoint{m}
  \tkzInterLC(C,f)(m,e)
  \tkzGetSecondPoint{n}
  \tkzInterCC[with nodes](C,C,n)(D,C,n)
  \tkzGetFirstPoint{B}
  \tkzDrawSegment[brown,dashed](f,n)
  \pgfinterruptboundingbox% from tikz
  \tkzDrawPolygon[brown,dashed](C,D,e,f)
  \tkzDrawArc[brown,dashed](m,e)(n)
  \tkzCompass[brown,dashed,delta=20](C,B)
  \tkzCompass[brown,dashed,delta=20](D,B)
  \endpgfinterruptboundingbox
  \tkzDrawPolygon(B,...,D)
  \tkzDrawPoints(B,C,D,e,f,m,n)
  \tkzLabelPoints[above](B)
  \tkzLabelPoints[left](f,m,n)
  \tkzLabelPoints(C,D)
  \tkzLabelPoints[right](e)
\end{tikzpicture}
```

After building the golden triangle BCD, we build the point A by noticing that  $BD = DA$ . Then we get the point E and finally the point F. This is done with already intersections of defined objects (line and circle).

### 3.5.3. Part II: two others methods with golden and euclid triangle

`tkz-euclide` knows how to define a golden or euclidean triangle. We can define BCD and BCA like gold triangles.

```
\begin{tikzpicture}
  \tkzDefPoint(0,0){C}
  \tkzDefPoint(4,0){D}
  \tkzDefTriangle[golden](C,D)
  \tkzGetPoint{B}
  \tkzDefTriangle[golden](B,C)
  \tkzGetPoint{A}
  \tkzInterLC[near](A,B)(B,D) \tkzGetFirstPoint{E}
  \tkzInterLL(B,D)(C,E) \tkzGetPoint{F}
  \tkzDrawPoints(C,D,B)
  \tkzDrawPolygon(B,...,D)
  \tkzDrawPolygon(B,C,D)
  \tkzDrawSegments(D,A A,B C,E)
  \tkzDrawArc[delta=10](B,C)(E)
  \tkzDrawPoints(A,...,F)
  \tkzMarkRightAngle(B,F,C)
  \tkzMarkAngles(C,B,D E,A,D)
  \tkzLabelAngles[pos=1.5](C,B,D E,A,D){$\alpha$}
  \tkzLabelPoints[below](A,C,D,E)
  \tkzLabelPoints[above right](B,F)
\end{tikzpicture}
```

Here is a final method that uses rotations:

```


\begin{tikzpicture}
\tkzDefPoint(0,0){C} % possible
% \tkzDefPoint[label=below:$C$](0,0){C}
% but don't do this
\tkzDefPoint(2,6){B}
% We get D and E with a rotation
\tkzDefPointBy[rotation= center B angle 36](C) \tkzGetPoint{D}
\tkzDefPointBy[rotation= center B angle 72](C) \tkzGetPoint{E}
% To get A we use an intersection of lines
\tkzInterLL(B,E)(C,D) \tkzGetPoint{A}
\tkzInterLL(C,E)(B,D) \tkzGetPoint{H}
% drawing
\tkzDrawArc[delta=10](B,C)(E)
\tkzDrawPolygon(C,B,D)
\tkzDrawSegments(D,A B,A C,E)
% angles
\tkzMarkAngles(C,B,D E,A,D) %this is to draw the arcs
\tkzLabelAngles[pos=1.5](C,B,D E,A,D){$\alpha$}
\tkzMarkRightAngle(B,H,C)
\tkzDrawPoints(A,...,E)
% Label only now
\tkzLabelPoints[below left](C,A)
\tkzLabelPoints[below right](D)
\tkzLabelPoints[above](B,E)
\end{tikzpicture}

```

### 3.5.4. Complete but minimal example

A unit of length being chosen, the example shows how to obtain a segment of length  $\sqrt{a}$  from a segment of length  $a$ , using a ruler and a compass.

$IB = a, AI = 1$



```

\begin{tikzpicture}[scale=1,ra/.style={fill=gray!20}]
  % fixed points
  \tkzDefPoint(0,0){A}
  \tkzDefPoint(1,0){I}
  % calculation
  \tkzDefPointBy[homothety=center A ratio 10 ](I) \tkzGetPoint{B}
  \tkzDefMidPoint(A,B) \tkzGetPoint{M}
  \tkzDefPointWith[orthogonal](I,M) \tkzGetPoint{H}
  \tkzInterLC(I,H)(M,B) \tkzGetFirstPoint{C}
  \tkzDrawSegment[style=purple](I,C)
  \tkzDrawArc(M,B)(A)
  \tkzDrawSegment[dim={1$, -16pt,}] (A,I)
  \tkzDrawSegment[dim={$(a-1)/2$, -10pt,}] (I,M)
  \tkzDrawSegment[dim={$(a+1)/2$, -16pt,}] (M,B)
  \tkzMarkRightAngle[ra](A,I,C)
  \tkzDrawPoints(I,A,B,C,M)
  \tkzLabelPoint[left](A){$A(0,0)$}
  \tkzLabelPoints[above right](I,M)
  \tkzLabelPoints[above left](C)
  \tkzLabelPoint[right](B){$B(10,0)$}
  \tkzLabelSegment[right=4pt](I,C){$\sqrt{a^2}=a \ (a>0)$}
\end{tikzpicture}

```

#### Comments

##### – The Preamble

Let us first look at the preamble. If you need it, you have to load `xcolor` before `tkz-euclide`, that is, before `TikZ`. `TikZ` may cause problems with the active characters, but... provides a library in its latest version that's supposed to solve these problems [babel](#).

```

\documentclass{standalone} % or another class
% \usepackage{xcolor} % before tikz or tkz-euclide if necessary
\usepackage{tkz-euclide} % no need to load TikZ
% \usetikzobj{all} is no longer necessary
% \usetikzlibrary{babel} if there are problems with the active characters

```

The following code consists of several parts:

- Definition of fixed points: the first part includes the definitions of the points necessary for the construction, these are the fixed points. The macros `\tkzInit` and `\tkzClip` in most cases are not necessary.

```

\tkzDefPoint(0,0){A}
\tkzDefPoint(1,0){I}

```

- The second part is dedicated to the creation of new points from the fixed points; a B point is placed at 10 cm from A. The middle of [AB] is defined by M and then the orthogonal line to the (AB) line is searched for at the I point. Then we look for the intersection of this line with the semi-circle of center M passing through A.

```

\tkzDefPointBy[homothety=center A ratio 10 ](I)
\tkzGetPoint{B}
\tkzDefMidPoint(A,B)
\tkzGetPoint{M}
\tkzDefPointWith[orthogonal](I,M)
\tkzGetPoint{H}
\tkzInterLC(I,H)(M,B)
\tkzGetSecondPoint{C}

```

- The third one includes the different drawings;

```
\tkzDrawSegment[style=purple](I,H)
\tkzDrawPoints(O,I,A,B,M)
\tkzDrawArc(M,A)(O)
\tkzDrawSegment[dim={1$, -16pt,}] (A,I)
\tkzDrawSegment[dim={a/2$, -10pt,}] (I,M)
\tkzDrawSegment[dim={a/2$, -16pt,}] (M,B)
```

- Marking: the fourth is devoted to marking;

```
\tkzMarkRightAngle[ra](A,I,C)
```

- Labelling: the latter only deals with the placement of labels.

```
\tkzLabelPoint[left](A){$A(0,0)$}
\tkzLabelPoint[right](B){$B(10,0)$}
\tkzLabelSegment[right=4pt](I,C){$\sqrt{a^2}=a \ \ (a>0)$}
```

#### 4. The Elements of tkz code

To work with my package, you need to have notions of  $\text{\LaTeX}$  as well as  $\text{TikZ}$ .

In this paragraph, we start looking at the rules and symbols used to create a figure with `tkz-euclide`.

##### 4.1. Objects and language

The primitive objects are points. You can refer to a point at any time using the name given when defining it. (it is possible to assign a different name later on).

To get new points you will use macros. `tkz-euclide` macros have a name beginning with `tkz`. There are four main categories starting with: `\tkzDef...` `\tkzDraw...` `\tkzMark...` and `\tkzLabel...`. The used points are passed as parameters between parentheses while the created points are between braces.

The code of the figures is placed in an environment `tikzpicture`

Contrary to  $\text{TikZ}$ , you should not end a macro with “;”. We thus lose the important notion which is the path. However, it is possible to place some code between the macros `tkz-euclide`.


Among the first category, `\tkzDefPoint` allows you to define fixed points. It will be studied in detail later. Here we will see in detail the macro `\tkzDefTriangle`.

This macro makes it possible to associate to a pair of points a third point in order to define a certain triangle `\tkzDefTriangle(A,B)`. The obtained point is referenced `tkzPointResult` and it is possible to choose another reference with `\tkzGetPoint{C}` for example.

```
\tkzDefTriangle[euclid](A,B) \tkzGetPoint{C}
```

Parentheses are used to pass arguments. In `(A,B)` `A` and `B` are the points with which a third will be defined. However, in `{C}` we use braces to retrieve the new point.

In order to choose a certain type of triangle among the following choices: `equilateral`, `isosceles` `right`, `half`, `pythagoras`, `school`, `golden` or `sublime`, `euclid`, `gold`, `cheops...` and two angles you just have to choose between hooks, for example:



```
\begin{tikzpicture}[scale=.5]
\tkzDefPoints{0/0/A,8/0/B}
\foreach \tr in {golden, equilateral}
{\tkzDefTriangle[\tr](A,B) \tkzGetPoint{C}
\tkzDrawPoint(C)
\tkzLabelPoint[right](C){\tr}
\tkzDrawSegments(A,C C,B)}
\tkzDrawPoints(A,B)
\tkzDrawSegments(A,B)
\tkzLabelPoints(A,B)
\end{tikzpicture}
```

#### 4.2. Notations and conventions

I deliberately chose to use the geometric French and personal conventions to describe the geometric objects represented. The objects defined and represented by `tkz-euclide` are points, lines and circles located in a plane. They are the primary objects of Euclidean geometry from which we will construct figures.

According to Euclid, these figures will only illustrate pure ideas produced by our brain. Thus a point has no dimension and therefore no real existence. In the same way the line has no width and therefore no existence in the real world. The objects that we are going to consider are only representations of ideal mathematical objects. `tkz-euclide` will follow the steps of the ancient Greeks to obtain geometrical constructions using the ruler and the compass.

Here are the notations that will be used:

- The points are represented geometrically either by a small disc or by the intersection of two lines (two straight lines, a straight line and a circle or two circles). In this case, the point is represented by a cross.



or else



```
\begin{tikzpicture}
\tkzDefPoints{0/0/A,4/2/B}
\tkzDrawPoints(A,B)
\tkzLabelPoints(A,B)
\end{tikzpicture}
```

```
\begin{tikzpicture}
\tkzSetUpPoint[shape=cross, color=red]
\tkzDefPoints{0/0/A,4/2/B}
\tkzDrawPoints(A,B)
\tkzLabelPoints(A,B)
\end{tikzpicture}
```

The existence of a point being established, we can give it a label which will be a capital letter (with some exceptions) of the Latin alphabet such as A, B or C. For example:

- O is a center for a circle, a rotation, etc.;
- M defined a midpoint;
- H defined the foot of an altitude;
- P' is the image of P by a transformation ;

It is important to note that the reference name of a point in the code may be different from the label to designate it in the text. So we can define a point A and give it as label P. In particular the style will be different, point A will be labeled A.

```

•
P
\begin{tikzpicture}
  \tkzDefPoint(0,0){A}
  \tkzDrawPoints(A)
  \tkzLabelPoint(A){P}
\end{tikzpicture}

```

Exceptions: some points such as the middle of the sides of a triangle share a characteristic, so it is normal that their names also share a common character. We will designate these points by  $M_a$ ,  $M_b$  and  $M_c$  or  $M_A$ ,  $M_B$  and  $M_C$ .

In the code, these points will be referred to as:  $M\_A$ ,  $M\_B$  and  $M\_C$ .

Another exception relates to intermediate construction points which will not be labelled. They will often be designated by a lowercase letter in the code.

- The line segments are designated by two points representing their ends in square brackets:  $[AB]$ .
- The straight lines are in Euclidean geometry defined by two points so A and B define the straight line (AB). We can also designate this straight line using the Greek alphabet and name it  $(\delta)$  or  $(\Delta)$ . It is also possible to designate the straight line with lowercase letters such as d and d'.
- The semi-straight line is designated as follows  $[AB)$ .
- Relation between the straight lines. Two perpendicular (AB) and (CD) lines will be written  $(AB) \perp (CD)$  and if they are parallel we will write  $(AB) \parallel (CD)$ .
- The lengths of the sides of triangle ABC are AB, AC and BC. The numbers are also designated by a lowercase letter so we will write:  $AB = c$ ,  $AC = b$  and  $BC = a$ . The letter a is also used to represent an angle, and r is frequently used to represent a radius, d a diameter, l a length, d a distance.
- Polygons are designated afterwards by their vertices so ABC is a triangle, EFGH a quadrilateral.
- Angles are generally measured in degrees (ex  $60^\circ$ ) and in an equilateral ABC triangle we will write  $\widehat{ABC} = \widehat{B} = 60^\circ$ .
- The arcs are designated by their extremities. For example if A and B are two points of the same circle then  $\widehat{AB}$ .
- Circles are noted either  $\mathcal{C}$  if there is no possible confusion or  $\mathcal{C}(O; A)$  for a circle with center O and passing through the point A or  $\mathcal{C}(O; 1)$  for a circle with center O and radius 1 cm.
- Name of the particular lines of a triangle: I used the terms bisector, bisector out, mediator (sometimes called perpendicular bisectors), altitude, median and symmedian.
- $(x_1, y_1)$  coordinates of the point  $A_1$ ,  $(x_A, y_A)$  coordinates of the point A.

#### 4.3. Set, Calculate, Draw, Mark, Label

The title could have been: Separation of Calculus and Drawings

When a document is prepared using the  $\text{\LaTeX}$  system, the source code of the document can be divided into two parts: the document body and the preamble. Under this methodology, publications can be structured, styled and typeset with minimal effort. I propose a similar methodology for creating figures with **tkz-euclide**.

The first part defines the fixed points, the second part allows the creation of new points. **Set** and **Calculate** are the two main parts. All that is left to do is to draw (or fill), mark and label. It is possible that **tkz-euclide** is insufficient for some of these latter actions but you can use **TikZ**

One last remark that I think is important, it is best to avoid introducing coordinates within a code as much as possible. I think that the coordinates should appear at the beginning of the code with the fixed points. Then the use of references is recommended. Most macros have the option `nodes` or with `nodes`. I also think it's best to define the styles of the different objects from the beginning.

## 5. About this documentation and the examples

It is obtained by compiling with `lualatex`. I use a class `doc.cls` based on `scrartcl`.

Below the list of styles used in the documentation. To understand how to use the styles see the section 38

```
\tkzSetUpColors[background=white,text=black]
\tkzSetUpCompass[color=orange, line width=.2pt,delta=10]
\tkzSetUpArc[color=gray,line width=.2pt]
\tkzSetUpPoint[size=2,color=teal]
\tkzSetUpLine[line width=.2pt,color=teal]
\tkzSetUpStyle[color=orange,line width=.2pt]{new}
\tikzset{every picture/.style={line width=.2pt}}
\tikzset{label angle style/.append style={color=teal,font=\footnotesize}}
\tikzset{label style/.append style={below,color=teal,font=\scriptsize}}
Some examples use predefined styles like
\tikzset{new/.style={color=orange,line width=.2pt}}
```

Part II.

Setting



## 6. First step: fixed points

The first step in a geometric construction is to define the fixed points from which the figure will be constructed. The general idea is to avoid manipulating coordinates and to prefer to use the references of the points fixed in the first step or obtained using the tools provided by the package. Even if it's possible, I think it's a bad idea to work directly with coordinates. Preferable is to use named points.

`tkz-euclide` uses macros and vocabulary specific to geometric construction. It is of course possible to use the tools of `TikZ` but it seems more logical to me not to mix the different syntaxes.

A point in `tkz-euclide` is a particular node for `TikZ`. In the next section we will see how to define points using coordinates. The style of the points (color and shape) will not be discussed. You will find some indications in some examples; for more information you can read the following section 38.

## 7. Definition of a point : `\tkzDefPoint` or `\tkzDefPoints`

Points can be specified in any of the following ways:

- Cartesian coordinates;
- Polar coordinates;
- Named points;
- Relative points.

A point is defined if it has a name linked to a unique pair of decimal numbers. Let (x,y) or (a:d) i.e. (x abscissa, y ordinate) or (a angle: d distance). This is possible because the plan has been provided with an orthonormed Cartesian coordinate system. The working axes are (ortho)normed with unity equal to 1 cm.

The Cartesian coordinate (a,b) refers to the point a centimeters in the x-direction and b centimeters in the y-direction.

A point in polar coordinates requires an angle  $\alpha$ , in degrees, and a distance d from the origin with a dimensional unit by default it's the cm.


The `\tkzDefPoint` macro is used to define a point by assigning coordinates to it. This macro is based on `\coordinate`, a macro of `TikZ`. It can use `TikZ`-specific options such as `shift`. If calculations are required then the `xfp` package is chosen. We can use Cartesian or polar coordinates.

Cartesian coordinates

Polar coordinates

```
\begin{tikzpicture}[scale=1]
  \tkzInit[xmax=5,ymax=5]
  % necessary to limit
  % the size of the axes
  \tkzDrawX[>=latex]
  \tkzDrawY[>=latex]
  \tkzDefPoints{0/0/0,1/0/I,0/1/J}
  \tkzDefPoint(3,4){A}
  \tkzDrawPoints(O,A)
  \tkzLabelPoint[above](A){$A_1(x_1,y_1)$}
  \tkzShowPointCoord[xlabel=$x_1$,
    ylabel=$y_1$](A)
  \tkzLabelPoints(O,I)
  \tkzLabelPoints[left](J)
  \tkzDrawPoints[shape=cross](I,J)
\end{tikzpicture}
```

```
\begin{tikzpicture}[scale=1]
  \tkzInit[xmax=5,ymax=5]
  \tkzDrawX[>=latex]
  \tkzDrawY[>=latex]
  \tkzDefPoints{0/0/0,1/0/I,0/1/J}
  \tkzDefPoint(40:4){P}
  \tkzDrawSegment[dim={d$,
    16pt,above=6pt}](O,P)
  \tkzDrawPoints(O,P)
  \tkzMarkAngle[mark=none,->](I,O,P)
  \tkzFillAngle[opacity=.5](I,O,P)
  \tkzLabelAngle[pos=1.25](I,O,P){%
    $\alpha$}
  \tkzLabelPoint[right](P){$P(\alpha:d)$}
  \tkzDrawPoints[shape=cross](I,J)
  \tkzLabelPoints(O,I)
  \tkzLabelPoints[left](J)
\end{tikzpicture}
```


7.1. Defining a named point `\tkzDefPoint`
`\tkzDefPoint[⟨local options⟩](⟨x,y⟩){⟨ref⟩} or (⟨α:d⟩){⟨ref⟩}`

arguments	default	definition
(x,y)	no default	x and y are two dimensions, by default in cm.
(α:d)	no default	α is an angle in degrees, d is a dimension
{ref}	no default	Reference assigned to the point: A, T_a ,P1 or P1

The obligatory arguments of this macro are two dimensions expressed with decimals, in the first case they are two measures of length, in the second case they are a measure of length and the measure of an angle in degrees. Do not confuse the reference with the name of a point. The reference is used by calculations, but frequently, the name is identical to the reference.


options	default	definition
label	no default	allows you to place a label at a predefined distance
shift	no default	adds (x,y) or (α:d) to all coordinates

## 7.1.1. Cartesian coordinates




```
\begin{tikzpicture}
\tkzInit[xmax=5,ymax=5] % limits the size of the axes
\tkzDrawX[>=latex]
\tkzDrawY[>=latex]
\tkzDefPoint(0,0){A}
\tkzDefPoint(4,0){B}
\tkzDefPoint(0,3){C}
\tkzDrawPolygon(A,B,C)
\tkzDrawPoints(A,B,C)
\end{tikzpicture}
```

## 7.1.2. Calculations with xfp



```
\begin{tikzpicture}[scale=1]
  \tkzInit[xmax=4,ymax=4]
  \tkzDrawX\tkzDrawY
  \tkzDefPoint(-1+2,sqrt(4)){O}
  \tkzDefPoint({3*ln(exp(1))},{exp(1)}){A}
  \tkzDefPoint({4*sin(pi/6)},{4*cos(pi/6)}){B}
  \tkzDrawPoints(O,B,A)
\end{tikzpicture}
```


## 7.1.3. Polar coordinates



```
\begin{tikzpicture}
  \foreach \an [count=\i] in {0,60,...,300}
  { \tkzDefPoint(\an:3){A_\i}}
  \tkzDrawPolygon(A_1,A_...,A_6)
  \tkzDrawPoints(A_1,A_...,A_6)
\end{tikzpicture}
```

## 7.1.4. Relative points

First, we can use the `scope` environment from TikZ. In the following example, we have a way to define an equilateral triangle.




```
\begin{tikzpicture}[scale=1]
  \begin{scope}[rotate=30]
    \tkzDefPoint(2,3){A}
    \begin{scope}[shift=(A)]
      \tkzDefPoint(90:5){B}
      \tkzDefPoint(30:5){C}
    \end{scope}
  \end{scope}
  \tkzDrawPolygon(A,B,C)
  \tkzLabelPoints[above](B,C)
  \tkzLabelPoints[below](A)
  \tkzDrawPoints(A,B,C)
\end{tikzpicture}
```

7.2. Point relative to another: `\tkzDefShiftPoint`

<code>\tkzDefShiftPoint[⟨Point⟩](⟨x,y⟩){⟨ref⟩}</code> or <code>(⟨α:d⟩){⟨ref⟩}</code>		
arguments	default	definition
<code>(x,y)</code>	no default	x and y are two dimensions, by default in cm.
<code>(α:d)</code>	no default	α is an angle in degrees, d is a dimension
<code>{ref}</code>	no default	Reference assigned to the point: A, T_a ,P <sub>1</sub> or P <sub>l</sub>
options	default	definition
<code>[pt]</code>	no default	<code>\tkzDefShiftPoint[A](0:4){B}</code>

### 7.2.1. Isosceles triangle


This macro allows you to place one point relative to another. This is equivalent to a translation. Here is how to construct an isosceles triangle with main vertex A and angle at vertex of 30°.



```
\begin{tikzpicture}[rotate=-30]
\tkzDefPoint(2,3){A}
\tkzDefShiftPoint[A](0:4){B}
\tkzDefShiftPoint[A](30:4){C}
\tkzDrawSegments(A,B B,C C,A)
\tkzMarkSegments[mark=|](A,B A,C)
\tkzDrawPoints(A,B,C)
\tkzLabelPoints[right](B,C)
\tkzLabelPoints[above left](A)
\end{tikzpicture}
```

### 7.2.2. Equilateral triangle


Let's see how to get an equilateral triangle (there is much simpler)



```
\begin{tikzpicture}[scale=1]
\tkzDefPoint(2,3){A}
\tkzDefShiftPoint[A](30:3){B}
\tkzDefShiftPoint[A](-30:3){C}
\tkzDrawPolygon(A,B,C)
\tkzDrawPoints(A,B,C)
\tkzLabelPoints[right](B,C)
\tkzLabelPoints[above left](A)
\tkzMarkSegments[mark=|](A,B A,C B,C)
\end{tikzpicture}
```

### 7.2.3. Parallelogram

There's a simpler way



```
\begin{tikzpicture}
\tkzDefPoint(0,0){A}
\tkzDefPoint(30:3){B}
\tkzDefShiftPointCoord[B](10:2){C}
\tkzDefShiftPointCoord[A](10:2){D}
\tkzDrawPolygon(A,...,D)
\tkzDrawPoints(A,...,D)
\end{tikzpicture}
```


7.3. Definition of multiple points: `\tkzDefPoints`

$$\text{\tkzDefPoints}[\langle\text{local options}\rangle]\{\langle x_1/y_1/n_1, x_2/y_2/r_2, \dots \rangle\}$$

$x_i$  and  $y_i$  are the coordinates of a referenced point  $r_i$

arguments	default	example
$x_i/y_i/r_i$		<code>\tkzDefPoints{0/0/0,2/2/A}</code>
options	default	definition
shift	no default	Adds (x,y) or ( $\alpha$ :d) to all coordinates


## 7.4. Create a triangle



```
\begin{tikzpicture}[scale=.75]
\tkzDefPoints{0/0/A,4/0/B,4/3/C}
\tkzDrawPolygon(A,B,C)
\tkzDrawPoints(A,B,C)
\end{tikzpicture}
```

## 7.5. Create a square

Note here the syntax for drawing the polygon.



```
\begin{tikzpicture}[scale=1]
\tkzDefPoints{0/0/A,2/0/B,2/2/C,0/2/D}
\tkzDrawPolygon(A,...,D)
\tkzDrawPoints(A,...,D)
\end{tikzpicture}
```

Part III.

Calculating

Now that the fixed points are defined, we can with their references using macros from the package or macros that you will create get new points. The calculations may not be apparent but they are usually done by the package. You may need to use some mathematical constants, here is the list of constants defined by the package.

## 8. Auxiliary tools

### 8.1. Constants

`tkz-euclide` knows some constants, here is the list:

```
\def\tkzPhi{1.618034}
\def\tkzInvPhi{0.618034}
\def\tkzSqrtPhi{1.27202}
\def\tkzSqrTwo{1.414213}
\def\tkzSqrThree{1.7320508}
\def\tkzSqrFive{2.2360679}
\def\tkzSqrTwobyTwo{0.7071065}
\def\tkzPi{3.1415926}
\def\tkzEuler{2.71828182}
```

### 8.2. New point by calculation

When a macro of `tkznameofpack` creates a new point, it is stored internally with the reference `tkzPointResult`. You can assign your own reference to it. This is done with the macro `\tkzGetPoint`. A new reference is created, your choice of reference must be placed between braces.

`\tkzGetPoint{<ref>}`

If the result is in `tkzPointResult`, you can access it with `\tkzGetPoint`.

arguments	default	example
ref	no default	<code>\tkzGetPoint{M}</code> see the next example

Sometimes you need to get two points. It's possible with

`\tkzGetPoints{<ref1>}{<ref2>}`

The result is in `tkzPointFirstResult` and `tkzPointSecondResult`.

arguments	default	example
{ref1,ref2}	no default	<code>\tkzGetPoints{M,N}</code> It's the case with <code>\tkzInterCC</code>

If you need only the first or the second point you can also use :

`\tkzGetFirstPoint{<ref1>}`

arguments	default	example
ref1	no default	<code>\tkzGetFirstPoint{M}</code>

`\tkzGetSecondPoint{<ref2>}`

arguments	default	example
ref2	no default	<code>\tkzGetSecondPoint{M}</code>

Sometimes the results consist of a point and a dimension. You get the point with `\tkzGetPoint` and the dimension with `\tkzGetLength`.

`\tkzGetLength{<name of a macro>}`

arguments	default	example
name of a macro	no default	<code>\tkzGetLength{rAB}</code> <code>rAB</code> gives the length in cm

## 9. Special points

Here are some special points.

### 9.1. Middle of a segment `\tkzDefMidPoint`

It is a question of determining the middle of a segment.


`\tkzDefMidPoint(<pt1,pt2>)`

The result is in `tkzPointResult`. We can access it with `\tkzGetPoint`.

arguments	default	definition
(pt1,pt2)	no default	pt1 and pt2 are two points

#### 9.1.1. Use of `\tkzDefMidPoint`

Review the use of `\tkzDefPoint`.



```
\begin{tikzpicture}[scale=1]
\tkzDefPoint(2,3){A}
\tkzDefPoint(6,2){B}
\tkzDefMidPoint(A,B)
\tkzGetPoint{M}
\tkzDrawSegment(A,B)
\tkzDrawPoints(A,B,M)
\tkzLabelPoints[below](A,B,M)
\end{tikzpicture}
```

### 9.2. Golden ratio `\tkzDefGoldenRatio`

From Wikipedia : In mathematics, two quantities are in the golden ratio if their ratio is the same as the ratio of their sum to the larger of the two quantities. Expressed algebraically, for quantities  $a, b$  such as  $a > b > 0$ ;  $a + b$  is to  $a$  as  $a$  is to  $b$ .



$$\frac{a+b}{a} = \frac{a}{b} = \phi = \frac{1+\sqrt{5}}{2}$$

One of the two solutions to the equation  $x^2 - x - 1 = 0$  is the golden ratio  $\phi$ ,  $\phi = \frac{1+\sqrt{5}}{2}$ .

`\tkzDefGoldenRatio(<pt1,pt2>)`

arguments	default	example
(pt1,pt2)	no default	<code>\tkzDefGoldenRatio(A,C) \tkzGetPoint{B}</code>


$AB = a$ ,  $BC = b$  and  $\frac{AC}{AB} = \frac{AB}{BC} = \phi$

### 9.2.1. Use the golden ratio to divide a line segment



```
\begin{tikzpicture}
\tkzDefPoints{0/0/A,6/0/C}
\tkzDefMidPoint(A,C) \tkzGetPoint{I}
%\tkzDefPointWith[linear,K=\tkzInvPhi](A,C)
\tkzDefGoldenRatio(A,C) \tkzGetPoint{B}
\tkzDrawSegments(A,C)
\tkzDrawPoints(A,B,C)
\tkzLabelPoints(A,B,C)
\end{tikzpicture}
```

### 9.2.2. Golden arbelos



```
\begin{tikzpicture}[scale=.6]
\tkzDefPoints{0/0/A,10/0/B}
\tkzDefGoldenRatio(A,B) \tkzGetPoint{C}
\tkzDefMidPoint(A,B) \tkzGetPoint{O_1}
\tkzDefMidPoint(A,C) \tkzGetPoint{O_2}
\tkzDefMidPoint(C,B) \tkzGetPoint{O_3}
\tkzDrawSemiCircles[fill=purple!15](O_1,B)
\tkzDrawSemiCircles[fill=teal!15](O_2,C)(O_3,B)
\end{tikzpicture}
```

It is also possible to use the following macro.

### 9.3. Barycentric coordinates with `\tkzDefBarycentricPoint`

$pt_1, pt_2, \dots, pt_n$  being  $n$  points, they define  $n$  vectors  $\vec{v}_1, \vec{v}_2, \dots, \vec{v}_n$  with the origin of the referential as the common endpoint.  $\alpha_1, \alpha_2, \dots, \alpha_n$  are  $n$  numbers, the vector obtained by:

$$\frac{\alpha_1 \vec{v}_1 + \alpha_2 \vec{v}_2 + \dots + \alpha_n \vec{v}_n}{\alpha_1 + \alpha_2 + \dots + \alpha_n}$$

defines a single point.

`\tkzDefBarycentricPoint(<pt1= $\alpha_1$ ,pt2= $\alpha_2$ ,...>)`


arguments	default	definition
(pt1= $\alpha_1$ ,pt2= $\alpha_2$ ,...)	no default	Each point has a assigned weight

*You need at least two points. Result in `tkzPointResult`.*

## 9.3.1. with two points

In the following example, we obtain the barycenter of points A and B with coefficients 1 and 2, in other words:

$$\vec{AI} = \frac{2}{3}\vec{AB}$$




```
\begin{tikzpicture}
  \tkzDefPoint(2,3){A}
  \tkzDefShiftPointCoord[2,3](30:4){B}
  \tkzDefBarycentricPoint(A=1,B=2)
  \tkzGetPoint{G}
  \tkzDrawLine(A,B)
  \tkzDrawPoints(A,B,G)
  \tkzLabelPoints(A,B,G)
\end{tikzpicture}
```

## 9.3.2. with three points

This time M is simply the center of gravity of the triangle.

For reasons of simplification and homogeneity, there is also `\tkzCentroid`.



```
\begin{tikzpicture}[scale=.8]
  \tkzDefPoints{2/1/A,5/3/B,0/6/C}
  \tkzDefBarycentricPoint(A=1,B=1,C=1)
  \tkzGetPoint{G}
  \tkzDefMidPoint(A,B) \tkzGetPoint{C'}
  \tkzDefMidPoint(A,C) \tkzGetPoint{B'}
  \tkzDefMidPoint(C,B) \tkzGetPoint{A'}
  \tkzDrawPolygon(A,B,C)
  \tkzDrawLines[add=0 and 1,new](A,G B,G C,G)
  \tkzDrawPoints[new](A',B',C',G)
  \tkzDrawPoints(A,B,C)
  \tkzLabelPoint[above right](G){G}
  \tkzAutoLabelPoints[center=G](A,B,C)
  \tkzLabelPoints[above right](A')
  \tkzLabelPoints[below](B',C')
\end{tikzpicture}
```


## 9.4. Internal and external Similitude Center

The centers of the two homotheties in which two circles correspond are called external and internal centers of similitude. You can use `\tkzDefIntSimilitudeCenter` and `\tkzDefExtSimilitudeCenter` but the next macro is better.

```
\tkzDefSimilitudeCenter[options](O,A)(O',B)
```

arguments	example	explanation
(pt1,pt2)(pt3,pt4)	(O,A)(O',B)	$r = OA, r' = O'B$
options	default	definition
ext	ext	external center
int	ext	internal center

## 9.4.1. Internal and external with node




```

\begin{tikzpicture}[scale=.7]
\tkzDefPoints{O/Q/O,4/-5/A,3/Q/B,5/-5/C}
\tkzDefSimilitudeCenter[int](O,B)(A,C)
\tkzGetPoint{I}
\tkzDefSimilitudeCenter[ext](O,B)(A,C)
\tkzGetPoint{J}
\tkzDefLine[tangent from = I](O,B)
\tkzGetPoints{D}{E}
\tkzDefLine[tangent from = I](A,C)
\tkzGetPoints{D'}{E'}
\tkzDefLine[tangent from = J](O,B)
\tkzGetPoints{F}{G}
\tkzDefLine[tangent from = J](A,C)
\tkzGetPoints{F'}{G'}
\tkzDrawCircles(O,B A,C)
\tkzDrawSegments[add = .5 and .5,new](D,D' E,E')
\tkzDrawSegments[add= Q and Q.25,new](J,F J,G)
\tkzDrawPoints(O,A,I,J,D,E,F,G,D',E',F',G')
\end{tikzpicture}

```

## 9.4.2. D'Alembert Theorem



```

\begin{tikzpicture}[scale=.6,rotate=90]
\tkzDefPoints{O/Q/A,3/Q/a,7/-1/B,5.5/-1/b}
\tkzDefPoints{5/-4/C,4.25/-4/c}
\tkzDrawCircles(A,a B,b C,c)
\tkzDefExtSimilitudeCenter(A,a)(B,b) \tkzGetPoint{I}
\tkzDefExtSimilitudeCenter(A,a)(C,c) \tkzGetPoint{J}
\tkzDefExtSimilitudeCenter(C,c)(B,b) \tkzGetPoint{K}
\tkzDefIntSimilitudeCenter(A,a)(B,b) \tkzGetPoint{I'}
\tkzDefIntSimilitudeCenter(A,a)(C,c) \tkzGetPoint{J'}
\tkzDefIntSimilitudeCenter(C,c)(B,b) \tkzGetPoint{K'}
\tkzDrawPoints(A,B,C,I,J,K,I',J',K')
\tkzDrawSegments[new](I,K A,I A,J B,I B,K C,J C,K)
\tkzDrawSegments[new](I,J' I',J I',K)
\end{tikzpicture}

```


You can use `\tkzDefBarycentricPoint` to find a homothetic center

```

\tkzDefBarycentricPoint(O=\r,A=\R) \tkzGetPoint{I}
\tkzDefBarycentricPoint(O={-\r},A=\R) \tkzGetPoint{J}

```

## 9.4.3. Example with node



```

\begin{tikzpicture}[rotate=60,scale=.5]
\tkzDefPoints{0/0/A,5/0/C}
\tkzDefGoldenRatio(A,C) \tkzGetPoint{B}
\tkzDefSimilitudeCenter(A,B)(C,B)\tkzGetPoint{J}
\tkzDefTangent[from = J](A,B) \tkzGetPoints{F}{G}
\tkzDefTangent[from = J](C,B) \tkzGetPoints{F'}{G'}
\tkzDrawCircles(A,B C,B)
\tkzDrawSegments[add= 0 and 0.25,cyan](J,F J,G)
\tkzDrawPoints(A,J,F,G,F',G')
\end{tikzpicture}

```

9.5. Harmonic division with `\tkzDefHarmonic`

<code>\tkzDefHarmonic[options](pt1,pt2,pt3)</code> or <code>(pt1,pt2,k)</code>
--

options	default	definition
both	both	$(\langle A,B,2 \rangle)$ we look for C and D such that $(A,B;C,D) = -1$ and $CA=2CB$
ext	both	$(\langle A,B,C \rangle)$ we look for D such that $(A,B;C,D) = -1$
int	both	$(\langle A,B,D \rangle)$ we look for C such that $(A,B;C,D) = -1$


9.5.1. options `ext` and `int`

```

\begin{tikzpicture}
\tkzDefPoints{0/0/A,6/0/B,4/0/C}
\tkzDefHarmonic[ext](A,B,C) \tkzGetPoint{J}
\tkzDefHarmonic[int](A,B,J) \tkzGetPoint{I}
\tkzDrawPoints(A,B,I,J)
\tkzDrawLine[add=.5 and 1](A,B)
\tkzLabelPoints(A,B,I,J)
\end{tikzpicture}

```

## 9.5.2. Bisector and harmonic division



```

\begin{tikzpicture}[scale=1.25]
\tkzDefPoints{0/0/A,4/0/C,5/3/X}
\tkzDefLine[bisector](A,X,C) \tkzGetPoint{x}
\tkzInterLL(X,x)(A,C) \tkzGetPoint{B}
\tkzDefHarmonic[ext](A,C,B) \tkzGetPoint{D}
\tkzDrawPolygon(A,X,C)
\tkzDrawSegments(X,B C,D D,X)
\tkzDrawPoints(A,B,C,D,X)
\tkzMarkAngles[mark=s](A,X,B B,X,C)
\tkzMarkRightAngle[size=.4,
  fill=gray!20,
  opacity=.3](B,X,D)
\tkzLabelPoints(A,B,C,D)
\tkzLabelPoints[above right](X)
\end{tikzpicture}

```

## 9.5.3. option both

`both` is the default option




```
\begin{tikzpicture}
\tkzDefPoints{0/0/A,6/0/B}
\tkzDefHarmonic(A,B,{1/2})\tkzGetPoints{I}{J}
\tkzDrawPoints(A,B,I,J)
\tkzDrawLine[add=1 and .5](A,B)
\tkzLabelPoints(A,B,I,J)
\end{tikzpicture}
```

9.6. Equidistant points with `\tkzDefEquiPoints`

`\tkzDefEquiPoints[⟨local options⟩](⟨pt1,pt2⟩)`

arguments	default	definition
(pt1,pt2)	no default	unordered list of two items
options	default	definition
dist	2 (cm)	half the distance between the two points
from=pt	no default	reference point
show	false	if true displays compass traces
/compass/delta	0	compass trace size

*This macro makes it possible to obtain two points on a straight line equidistant from a given point.*


9.6.1. Using `\tkzDefEquiPoints` with options

```
\begin{tikzpicture}
\tkzSetUpCompass[color=purple,line width=1pt]
\tkzDefPoints{0/1/A,5/2/B,3/4/C}
\tkzDefEquiPoints[from=C,dist=1,show,
\tkzcompass/delta=20](A,B)
\tkzGetPoints{E}{H}
\tkzDrawLines[color=blue](C,E C,H A,B)
\tkzDrawPoints[color=blue](A,B,C)
\tkzDrawPoints[color=red](E,H)
\tkzLabelPoints(E,H)
\tkzLabelPoints[color=blue](A,B,C)
\end{tikzpicture}
```

## 9.7. Middle of an arc

`\tkzDefMidArc(⟨pt1,pt2,pt3⟩)`

arguments	default	definition
pt1,pt2,pt3	no default	pt1 is the center, $\widehat{pt2pt3}$ the arc



```

\begin{tikzpicture}[scale=1]
\tkzDefPoints{0/0/A,10/0/B}
\tkzDefGoldenRatio(A,B)
\tkzDefMidPoint(A,B)
\tkzDefMidPoint(A,C)
\tkzDefMidPoint(C,B)
\tkzDefMidArc(0_3,B,C)
\tkzDefMidArc(0_2,C,A)
\tkzDefMidArc(0_1,B,A)
\tkzDefPointBy[rotation=center C angle 90](B)
\tkzInterCC[common=B](P,B)(0_1,B)
\tkzInterCC[common=C](P,C)(0_2,C)
\tkzInterCC[common=C](Q,C)(0_3,C)
\tkzInterLC[near](c,C)(0_1,A)
\tkzInterLL(A,P_1)(C,D)
\tkzDefPointBy[inversion = center A through D](P_2)
\tkzDefCircle[circum](P_3,P_2,P_1)
\tkzInterLL(B,Q)(A,P)
\tkzDefMidPoint(P_2',P_1')
\tkzDefPointBy[inversion = center A through D](S)
\tkzDrawArc[cyan,delta=0](Q,A)(P_1)
\tkzDrawArc[cyan,delta=0](P,P_1)(B)
\tkzDrawSemiCircles[teal](0_1,B 0_2,C 0_3,B)
\tkzDrawCircles[new](o,P 0_4,P_1)
\tkzDrawSegments(A,B)
\tkzDrawSegments[cyan](A,P_1 A,S' A,P_2')
\tkzDrawSegments[purple](B,L C,P_2' B,Q B,L S',P_1')
\tkzDrawLines[add=0 and .8](B,P_2')
\tkzDrawLines[add=0 and .4](C,D)
\tkzDrawPoints(A,B,C,P,Q,P_3,P_2,P_1,P_1',D,P_2',L,S,S')
\tkzLabelPoints(A,B,C,P_3)
\tkzLabelPoints[above](P,Q,P_1)
\tkzLabelPoints[above right](P_2,P_2',D,S')
\tkzLabelPoints[above left](L,S)
\tkzLabelPoints[below left](P_1')
\end{tikzpicture}

```

## 10. Point on line or circle


### 10.1. Point on a line with \tkzDefPointOnLine

`\tkzDefPointOnLine[⟨local options⟩](⟨A,B⟩)`

arguments	default	definition
pt1,pt2	no default	Two points to define a line
options	default	definition
pos=nb		nb is a decimal



## 10.1.1. Use of option pos



```
\begin{tikzpicture}
\tkzDefPoints{0/0/A,3/0/B}
\tkzDefPointOnLine[pos=1.2](A,B)\tkzGetPoint{P}
\tkzDefPointOnLine[pos=-.2](A,B)\tkzGetPoint{R}
\tkzDefPointOnLine[pos=.5](A,B)\tkzGetPoint{S}
\tkzDrawLine[new](A,B)
\tkzDrawPoints(A,B,P)
\tkzLabelPoints(A,B)
\tkzLabelPoint[above](P){pos=$1.2$}
\tkzLabelPoint[above](R){pos=$-.2$}
\tkzLabelPoint[above](S){pos=$.5$}
\tkzDrawPoints(A,B,P,R,S)
\tkzLabelPoints(A,B)
\end{tikzpicture}
```

## 10.2. Point on a circle with \tkzDefPointOnCircle

The order of the arguments has changed: now it is center, angle and point or radius. I have added two options for working with radians which are **through in rad** and **R in rad**.


`\tkzDefPointOnCircle[(local options)]`

options	default	examples definition
through		through = center K1 angle 30 point B]
R		R = center K1 angle 30 radius \rAp
through in rad		through in rad= center K1 angle pi/4 point B]
R in rad		R in rad = center K1 angle pi/6 radius \rAp


*The new order for arguments are : center, angle and point or radius.*

## 10.2.1. Altshiller's Theorem

The two lines joining the points of intersection of two orthogonal circles to a point on one of the circles met the other circle in two diametrically opposite points. Altshiller p 176



```
\begin{tikzpicture}[scale=.4]
\tkzDefPoints{0/0/P,5/0/Q,3/2/I}
\tkzDefCircle[orthogonal from=P](Q,I)
\tkzGetFirstPoint{E}
\tkzDrawCircles(P,E Q,E)
\tkzInterCC[common=E](P,E)(Q,E)\tkzGetFirstPoint{F}
\tkzDefPointOnCircle[through = center P angle 80 point E]
\tkzGetPoint{A}
\tkzInterLC[common=E](A,E)(Q,E)\tkzGetFirstPoint{C}
\tkzInterLL(A,F)(C,Q)\tkzGetPoint{D}
\tkzDrawLines[add=0 and .75](P,Q)
\tkzDrawLines[add=0 and 2](A,E)
\tkzDrawSegments(P,E E,F F,C A,F C,D)
\tkzDrawPoints(P,Q,E,F,A,C,D)
\tkzLabelPoints(P,Q,F,C,D)
\tkzLabelPoints[above](E,A)
\end{tikzpicture}
```

10.2.2. Use of `\tkzDefPointOnCircle`

```

\begin{tikzpicture}
\tkzDefPoints{0/0/A,4/0/B,0.8/3/C}
\tkzDefPointOnCircle[R = center B   angle 90 radius 1]
\tkzGetPoint{I}
\tkzDefCircle[circum](A,B,C)
\tkzGetPoints{G}{g}
\tkzDefPointOnCircle[through = center G angle 30 point g]
\tkzGetPoint{J}
\tkzDefCircle[R](B,1) \tkzGetPoint{b}
\tkzDrawCircle[teal](B,b)
\tkzDrawCircle(G,J)
\tkzDrawPoints(A,B,C,G,I,J)
\tkzAutoLabelPoints[center=G](A,B,C,J)
\tkzLabelPoints[below](G,I)
\end{tikzpicture}

```

## 11. Special points relating to a triangle

11.1. Triangle center: `\tkzDefTriangleCenter`

`\tkzDefTriangleCenter[(local options)](A,B,C)`




This macro allows you to define the center of a triangle.. Be careful, the arguments are lists of three points. This macro is used in conjunction with `\tkzGetPoint` to get the center you are looking for. You can use `\tkzPointResult` if it is not necessary to keep the results.

arguments	default	example
(pt1,pt2,pt3)	no default	<code>\tkzDefTriangleCenter[ortho](B,C,A)</code>
options	default	definition
ortho	circum	intersection of the altitudes
orthic	circum	...
centroid	circum	intersection of the medians
median	circum	...
circum	circum	circle center circumscribed
in	circum	center of the circle inscribed in a triangle
in	circum	intersection of the bisectors
ex	circum	center of a circle exinscribed to a triangle
euler	circum	center of Euler's circle
gergonne	circum	defined with the Contact triangle
symmedian	circum	Lemoine's point or symmedian center or Grebe's point
lemoine	circum	...
grebe	circum	...
spieker	circum	Spieker circle center
nagel	circum	Nagel Center
mittenpunkt	circum	Or middlespoint
feuerbach	circum	Feuerbach Point

11.1.1. Option `ortho` or `orthic`

The intersection H of the three altitudes of a triangle is called the orthocenter.




```

\begin{tikzpicture}
  \tkzDefPoint(0,0){A}
  \tkzDefPoint(5,1){B}
  \tkzDefPoint(1,4){C}
  \tkzDefTriangleCenter[ortho](B,C,A)
  \tkzGetPoint{H}
  \tkzDefSpcTriangle[orthic,name=H](A,B,C){a,b,c}
  \tkzDrawPolygon(A,B,C)
  \tkzDrawSegments[new](A,Ha B,Hb C,Hc)
  \tkzDrawPoints(A,B,C,H)
  \tkzLabelPoint(H){H}
  \tkzLabelPoints[below](A,B)
  \tkzLabelPoints[above](C)
  \tkzMarkRightAngles(A,Ha,B B,Hb,C C,Hc,A)
\end{tikzpicture}


```

## 11.1.2. Option centroid



```
\begin{tikzpicture}[scale=.75]
  \tkzDefPoints{0/0/A,5/0/B,1/4/C}
  \tkzDefTriangleCenter[centroid](A,B,C)
  \tkzGetPoint{G}
  \tkzDrawPolygon(A,B,C)
  \tkzDrawLines[add = 0 and 2/3,new](A,G B,G C,G)
  \tkzDrawPoints(A,B,C,G)
  \tkzLabelPoint(G){G}
\end{tikzpicture}
```

## 11.1.3. Option circum




```
\begin{tikzpicture}
  \tkzDefPoints{0/1/A,3/2/B,1/4/C}
  \tkzDefTriangleCenter[circum](A,B,C)
  \tkzGetPoint{O}
  \tkzDrawPolygon(A,B,C)
  \tkzDrawCircle(O,A)
  \tkzDrawPoints(A,B,C,O)
  \tkzLabelPoint(O){O}
\end{tikzpicture}
```

## 11.1.4. Option in

In geometry, the incircle or inscribed circle of a triangle is the largest circle contained in the triangle; it touches (is tangent to) the three sides. The center of the incircle is a triangle center called the triangle's incenter. The center of the incircle, called the incenter, can be found as the intersection of the three internal angle bisectors. The center of an excircle is the intersection of the internal bisector of one angle (at vertex A, for example) and the external bisectors of the other two. The center of this excircle is called the excenter relative to the vertex A, or the excenter of A. Because the internal bisector of an angle is perpendicular to its external bisector, it follows that the center of the incircle together with the three excircle centers form an orthocentric system.

(Article on [Wikipedia](#))

We get the center of the inscribed circle of the triangle. The result is of course in `tkzPointResult`. We can retrieve it with `\tkzGetPoint`.



```
\begin{tikzpicture}
  \tkzDefPoints{0/0/A,6/0/B,0.8/4/C}
  \tkzDefTriangleCenter[in](A,B,C)
  \tkzGetPoint{I}
  \tkzDrawLines(A,B B,C C,A)
  \tkzDefCircle[in](A,B,C) \tkzGetPoints{I}{i}
  \tkzDrawCircle(I,i)
  \tkzDrawPoint[red](I)
  \tkzDrawPoints(A,B,C)
  \tkzLabelPoint(I){I}
\end{tikzpicture}
```


## 11.1.5. Option ex

An excircle or escribed circle of the triangle is a circle lying outside the triangle, tangent to one of its sides and tangent to the extensions of the other two. Every triangle has three distinct excircles, each tangent to one of the

triangle's sides.

(Article on [Wikipedia](#))

We get the center of an inscribed circle of the triangle. The result is of course in `tkzPointResult`. We can retrieve it with `\tkzGetPoint`.




```
\begin{tikzpicture}[scale=.5]
\tkzDefPoints{0/1/A,3/2/B,1/4/C}
\tkzDefTriangleCenter[ex](B,C,A)
\tkzGetPoint{J_c}
\tkzDefPointBy[projection=onto A--B](J_c)
\tkzGetPoint{Tc}
\tkzDrawPolygon(A,B,C)
\tkzDrawCircle[new](J_c,Tc)
\tkzDrawLines[add=1.5 and 0](A,C B,C)
\tkzDrawPoints(A,B,C,J_c)
\tkzLabelPoints(J_c)
\end{tikzpicture}
```

#### 11.1.6. Option euler

This macro allows to obtain the center of the circle of the nine points or euler's circle or Feuerbach's circle. The nine-point circle, also called Euler's circle or the Feuerbach circle, is the circle that passes through the perpendicular feet  $H_A$ ,  $H_B$ , and  $H_C$  dropped from the vertices of any reference triangle  $ABC$  on the sides opposite them. Euler showed in 1765 that it also passes through the midpoints  $M_A$ ,  $M_B$ ,  $M_C$  of the sides of  $ABC$ . By Feuerbach's theorem, the nine-point circle also passes through the midpoints  $E_A$ ,  $E_B$ , and  $E_C$  of the segments that join the vertices and the orthocenter  $H$ . These points are commonly referred to as the Euler points.

(<https://mathworld.wolfram.com/Nine-PointCircle.html>)




```
\begin{tikzpicture}[scale=1.2,rotate=90]
\tkzDefPoints{0/0/A,6/0/B,0.8/4/C}
\tkzDefSpcTriangle[medial,name=M](A,B,C){_A,_B,_C}
\tkzDefTriangleCenter[euler](A,B,C)\tkzGetPoint{N}
% I= N nine points
\tkzDefTriangleCenter[ortho](A,B,C)\tkzGetPoint{H}
\tkzDefMidPoint(A,H)\tkzGetPoint{E_A}
\tkzDefMidPoint(C,H)\tkzGetPoint{E_C}
\tkzDefMidPoint(B,H)\tkzGetPoint{E_B}
\tkzDefSpcTriangle[ortho,name=H](A,B,C){_A,_B,_C}
\tkzDrawPolygon(A,B,C)
\tkzDrawCircle[new](N,E_A)
\tkzDrawSegments[new](A,H_A B,H_B C,H_C)
\tkzDrawPoints(A,B,C,N,H)
\tkzDrawPoints[new](M_A,M_B,M_C)
\tkzDrawPoints(H_A,H_B,H_C)
\tkzDrawPoints[green](E_A,E_B,E_C)
\tkzAutoLabelPoints[center=N,
font=\scriptsize](A,B,C,M_A,M_B,M_C,H_A,H_B,H_C,%
E_A,E_B,E_C)
\tkzLabelPoints[font=\scriptsize](H,N)
\tkzMarkSegments[mark=s|,size=3pt,
color=blue,line width=1pt](B,E_B E_B,H)
\end{tikzpicture}
```

#### 11.1.7. Option symmedian

The point of concurrence  $K$  of the symmedians, sometimes also called the Lemoine point (in England and France) or the Grebe point (in Germany).

Weisstein, Eric W. "Symmedian Point." From MathWorld—A Wolfram Web Resource.




```
\begin{tikzpicture}
\tkzDefPoint(0,0){A}
\tkzDefPoint(5,0){B}
\tkzDefPoint(1,4){C}
\tkzDefTriangleCenter[symmedian](A,B,C)
\tkzGetPoint{K}
\tkzDefTriangleCenter[median](A,B,C)
\tkzGetPoint{G}
\tkzDefTriangleCenter[in](A,B,C)\tkzGetPoint{I}
\tkzDefSpcTriangle[centroid,name=M](A,B,C){a,b,c}
\tkzDefSpcTriangle[incentral,name=I](A,B,C){a,b,c}
\tkzDrawPolygon(A,B,C)
\tkzDrawLines[add = 0 and 2/3,new](A,K B,K C,K)
\tkzDrawSegments[color=cyan](A,Ma B,Mb C,Mc)
\tkzDrawSegments[color=green](A,Ia B,Ib C,Ic)
\tkzDrawPoints(A,B,C,K,G,I)
\tkzLabelPoints[font=\scriptsize](A,B,K,G,I)
\tkzLabelPoints[above,font=\scriptsize](C)
\end{tikzpicture}
```

#### 11.1.8. Option spieker

The Spieker center is the center  $Sp$  of the Spieker circle, i.e., the incenter of the medial triangle of a reference triangle.


Weisstein, Eric W. "Spieker Center." From MathWorld—A Wolfram Web Resource.



```
\begin{tikzpicture}
\tkzDefPoints{0/0/A,6/0/B,5/5/C}
\tkzDefSpcTriangle[medial](A,B,C){Ma,Mb,Mc}
\tkzDefTriangleCenter[centroid](A,B,C)
\tkzGetPoint{G}
\tkzDefTriangleCenter[spieker](A,B,C)
\tkzGetPoint{Sp}
\tkzDrawPolygon[](A,B,C)
\tkzDrawPolygon[new](Ma,Mb,Mc)
\tkzDefCircle[in](Ma,Mb,Mc)\tkzGetPoints{I}{i}
\tkzDrawCircle(I,i)
\tkzDrawPoints(B,C,A,Sp,Ma,Mb,Mc)
\tkzAutoLabelPoints[center=G,dist=.3](Ma,Mb)
\tkzLabelPoints[right](Sp)
\tkzLabelPoints[below](A,B,Mc)
\tkzLabelPoints[above](C)
\end{tikzpicture}
```

#### 11.1.9. Option gergonne

The Gergonne Point is the point of concurrency which results from connecting the vertices of a triangle to the opposite points of tangency of the triangle's incircle. (Joseph Gergonne French mathematician)




```
\begin{tikzpicture}
\tkzDefPoints{0/0/B,3.6/0/C,2.8/4/A}
\tkzDefTriangleCenter[gergonne](A,B,C)
\tkzGetPoint{Ge}
\tkzDefSpcTriangle[intouch](A,B,C){C_1,C_2,C_3}
\tkzDefCircle[in](A,B,C) \tkzGetPoints{I}{i}
\tkzDrawLines[add=.25 and .25,teal](A,B A,C B,C)
\tkzDrawSegments[new](A,C_1 B,C_2 C,C_3)
\tkzDrawPoints(A,...,C,C_1,C_2,C_3)
\tkzDrawPoints[red](Ge)
\tkzLabelPoints(B,C,C_1,Ge)
\tkzLabelPoints[above](A,C_2,C_3)
\end{tikzpicture}
```

### 11.1.10. Option nagel

Let  $T_a$  be the point at which the excircle with center  $J_a$  meets the side  $BC$  of a triangle  $ABC$ , and define  $T_b$  and  $T_c$  similarly. Then the lines  $AT_a$ ,  $BT_b$ , and  $CT_c$  concur in the Nagel point  $N_a$ .

Weisstein, Eric W. "Nagel point." From MathWorld—A Wolfram Web Resource.




```
\begin{tikzpicture}[scale=.5]
\tkzDefPoints{0/0/A,6/0/B,4/6/C}
\tkzDefSpcTriangle[ex](A,B,C){Ja,Jb,Jc}
\tkzDefSpcTriangle[extouch](A,B,C){Ta,Tb,Tc}
\tkzDefTriangleCenter[nagel](A,B,C)
\tkzGetPoint{Na}
\tkzDrawPolygon[blue](A,B,C)
\tkzDrawLines[add=0 and 1](A,Ta B,Tb C,Tc)
\tkzDrawPoints[new](Ja,Jb,Jc,Ta,Tb,Tc)
\tkzClipBB
\tkzDrawLines[add=1 and 1,dashed](A,B B,C C,A)
\tkzDrawCircles[new](Ja,Ta Jb,Tb Jc,Tc)
\tkzDrawSegments[new,dashed](Ja,Ta Jb,Tb Jc,Tc)
\tkzDrawPoints(B,C,A)
\tkzDrawPoints[new](Na)
\tkzLabelPoints(B,C,A)
\tkzLabelPoints[new](Na)
\tkzLabelPoints[new](Ja,Jb,Jc,Ta,Tb,Tc)
\tkzMarkRightAngles[fill=gray!20](Ja,Ta,C
Jb,Tb,A Jc,Tc,B)
\end{tikzpicture}
```

### 11.1.11. Option mittenpunkt

The mittenpunkt (also called the middlespoint) of a triangle  $ABC$  is the symmedian point of the excentral triangle, i.e., the point of concurrence  $M$  of the lines from the excenters through the corresponding triangle side midpoints.


Weisstein, Eric W. "Mittenpunkt." From MathWorld—A Wolfram Web Resource.



```
\begin{tikzpicture}[scale=.5]
\tkzDefPoints{0/0/A,6/0/B,4/6/C}
\tkzDefSpcTriangle[centroid](A,B,C){Ma,Mb,Mc}
\tkzDefSpcTriangle[ex](A,B,C){Ja,Jb,Jc}
\tkzDefSpcTriangle[extouch](A,B,C){Ta,Tb,Tc}
\tkzDefTriangleCenter[mittenpunkt](A,B,C)
\tkzGetPoint{Mi}
\tkzDrawPoints[new](Ma,Mb,Mc,Ja,Jb,Jc)
\tkzClipBB
\tkzDrawPolygon[blue](A,B,C)
\tkzDrawLines[add=0 and 1](Ja,Ma
                        Jb,Mb Jc,Mc)
\tkzDrawLines[add=1 and 1](A,B A,C B,C)
\tkzDrawCircles[new](Ja,Ta Jb,Tb Jc,Tc)
\tkzDrawPoints(B,C,A)
\tkzDrawPoints[new](Mi)
\tkzLabelPoints(Mi)
\tkzLabelPoints[left](Mb)
\tkzLabelPoints[new](Ma,Mc,Jb,Jc)
\tkzLabelPoints[above left](Ja,Jc)
\end{tikzpicture}
```

### 11.1.12. Relation between gergonne, centroid and mittenpunkt

The Gergonne point  $Ge$ , triangle centroid  $G$ , and mittenpunkt  $M$  are collinear, with  $GeG/GM=2$ .



```
\begin{tikzpicture}
\tkzDefPoints{0/0/A,2/2/B,8/0/C}
\tkzDefTriangleCenter[gergonne](A,B,C) \tkzGetPoint{Ge}
\tkzDefTriangleCenter[centroid](A,B,C)
\tkzGetPoint{G}
\tkzDefTriangleCenter[mittenpunkt](A,B,C)
\tkzGetPoint{M}
\tkzDrawLines[add=.25 and .25,teal](A,B A,C B,C)
\tkzDrawLines[add=.25 and .25,new](Ge,M)
\tkzDrawPoints(A,...,C)
\tkzDrawPoints[red,size=2](G,M,Ge)
\tkzLabelPoints(A,...,C,M,G,Ge)
\tkzMarkSegment[mark=s||](Ge,G)
\tkzMarkSegment[mark=s|](G,M)
\end{tikzpicture}
```

## 12. Definition of points by transformation

These transformations are:

- translation;
- homothety;



- orthogonal reflection or symmetry;
- central symmetry;
- orthogonal projection;
- rotation (degrees or radians);
- inversion with respect to a circle.

### 12.1. `\tkzDefPointBy`

The choice of transformations is made through the options. There are two macros, one for the transformation of a single point `\tkzDefPointBy` and the other for the transformation of a list of points `\tkzDefPointsBy`. By default the image of A is A'. For example, we'll write:

```
\tkzDefPointBy[translation= from A to A'](B)
```

The result is in `tkzPointResult`

`\tkzDefPointBy[(local options)](<pt>)`

The argument is a simple existing point and its image is stored in `tkzPointResult`. If you want to keep this point then the macro `\tkzGetPoint{M}` allows you to assign the name M to the point.

arguments	definition	examples
-----------	------------	----------


pt	existing point name	(A)
----	---------------------	-----

options	examples
---------	----------

translation	= from #1 to #2	[translation=from A to B](E)
homothety	= center #1 ratio #2	[homothety=center A ratio .5](E)
reflection	= over #1--#2	[reflection=over A--B](E)
symmetry	= center #1	[symmetry=center A](E)
projection	= onto #1--#2	[projection=onto A--B](E)
rotation	= center #1 angle #2	[rotation=center O angle 30](E)
rotation in rad	= center #1 angle #2	[rotation in rad=center O angle pi/3](E)
rotation with nodes	= center #1 from #2 to #3	[center O from A to B](E)
inversion	= center #1 through #2	[inversion =center O through A](E)
inversion negative	= center #1 through #2	...


*The image is only defined and not drawn.*

#### 12.1.1. translation




```
\begin{tikzpicture}[>=latex]
\tkzDefPoints{0/0/A,3/1/B,3/0/C}
\tkzDefPointBy[translation= from B to A](C)
\tkzGetPoint{D}
\tkzDrawPoints[teal](A,B,C,D)
\tkzLabelPoints[color=teal](A,B,C,D)
\tkzDrawSegments[orange,->](A,B D,C)
\end{tikzpicture}
```

## 12.1.2. reflection (orthogonal symmetry)




```
\begin{tikzpicture}[scale=.75]
\tkzDefPoints{-2/-2/A,-1/-1/C,-4/2/D,-4/0/O}
\tkzDrawCircle(O,A)
\tkzDefPointBy[reflection = over C--D](A)
\tkzGetPoint{A'}
\tkzDefPointBy[reflection = over C--D](O)
\tkzGetPoint{O'}
\tkzDrawCircle(O',A')
\tkzDrawLine[add= .5 and .5](C,D)
\tkzDrawPoints(C,D,O,O')
\end{tikzpicture}
```

## 12.1.3. homothety and projection




```
\begin{tikzpicture}
\tkzDefPoints{0/1/A,5/3/B,3/4/C}
\tkzDefLine[bisector](B,A,C) \tkzGetPoint{a}
\tkzDrawLine[add=0 and 0,color=magenta!50](A,a)
\tkzDefPointBy[homothety=center A ratio .5](a)
\tkzGetPoint{a'}
\tkzDefPointBy[projection = onto A--B](a')
\tkzGetPoint{k'}
\tkzDefPointBy[projection = onto A--B](a)
\tkzGetPoint{k}
\tkzDrawLines[add= 0 and .3](A,k A,C)
\tkzDrawSegments[blue](a',k' a,k)
\tkzDrawPoints(a,a',k,k',A)
\tkzDrawCircles(a',k' a,k)
\tkzLabelPoints(a,a',k,A)
\end{tikzpicture}
```

## 12.1.4. projection




```
\begin{tikzpicture}[scale=1.25]
  \tkzDefPoints{0/0/A,0/4/B}
  \tkzDefTriangle[pythagore](B,A) \tkzGetPoint{C}
  \tkzDefLine[bisector](B,C,A) \tkzGetPoint{c}
  \tkzInterLL(C,c)(A,B) \tkzGetPoint{D}
  \tkzDefPointBy[projection=onto B--C](D)
  \tkzGetPoint{G}
  \tkzInterLC(C,D)(D,A) \tkzGetPoints{E}{F}
  \tkzDrawPolygon(A,B,C)
  \tkzDrawSegment(C,D)
  \tkzDrawCircle(D,A)
  \tkzDrawSegment[new](D,G)
  \tkzMarkRightAngle[fill=orange!10](D,G,B)
  \tkzDrawPoints(A,C,F) \tkzLabelPoints(A,C,F)
  \tkzDrawPoints(B,D,E,G)
  \tkzLabelPoints[above right](B,D,E)
  \tkzLabelPoints[above](G)
\end{tikzpicture}
```

## 12.1.5. symmetry




```
\begin{tikzpicture}[scale=1]
  \tkzDefPoints{2/-1/A,2/2/B,0/0/O}
  \tkzDefPointsBy[symmetry=center O](B,A){}
  \tkzDrawLine(A,A')
  \tkzDrawLine(B,B')
  \tkzMarkAngle[mark=s,arc=111,
    size=1.5,mkcolor=red](A,O,B)
  \tkzLabelAngle[pos=2,circle,draw,
    fill=blue!10,font=\scriptsize](A,O,B){$60^\circ$}
  \tkzDrawPoints(A,B,O,A',B')
  \tkzLabelPoints(B,B')
  \tkzLabelPoints[below](A,O,A')
\end{tikzpicture}
```

## 12.1.6. rotation




```
\begin{tikzpicture}[scale=0.75]
\tkzDefPoints{0/0/A,5/0/B}
\tkzDrawSegment(A,B)
\tkzDefPointBy[rotation=center A angle 60](B)
\tkzGetPoint{C}
\tkzDefPointBy[symmetry=center C](A)
\tkzGetPoint{D}
\tkzDrawSegment(A,t kzPointResult)
\tkzDrawLine(B,D)
\tkzDrawArc(A,B)(C) \tkzDrawArc(B,C)(A)
\tkzDrawArc(C,D)(D)
\tkzMarkRightAngle(D,B,A)
\tkzDrawPoints(A,B)
\tkzLabelPoints(A,B)
\tkzLabelPoints[above](C)
\tkzLabelPoints[right](D)
\end{tikzpicture}
```

## 12.1.7. rotation in radian



```
\begin{tikzpicture}
\tkzDefPoint["$A$" left](1,5){A}
\tkzDefPoint["$B$" right](4,3){B}
\tkzDefPointBy[rotation in rad= center A angle pi/3](B)
\tkzGetPoint{C}
\tkzDrawSegment(A,B)
\tkzDrawPoints(A,B,C)
\tkzCompass(A,C)
\tkzCompass(B,C)
\tkzLabelPoints(C)
\end{tikzpicture}
```

## 12.1.8. rotation with nodes



```
\begin{tikzpicture}
\tkzDefPoint(0,0){O}
\tkzDefPoint(0:2){A}
\tkzDefPoint(40:2){B}
\tkzDefPoint(20:4){C}
\tkzDrawLine(O,A)
\tkzDefPointBy[rotation with nodes%
=center O from A to B](C)
\tkzGetPoint{D}
\tkzDrawPoints(A,B,C,D)
\tkzDrawCircle(O,A)
\tkzLabelPoints(A,C,D)
\tkzLabelPoints[above](B)
\end{tikzpicture}
```

## 12.1.9. inversion

Inversion is the process of transforming points to a corresponding set of points known as their inverse points. Two points  $P$  and  $P'$  are said to be inverses with respect to an inversion circle having inversion center  $O$  and inversion radius  $k$  if  $P'$  is the perpendicular foot of the altitude of  $OQP$ , where  $Q$  is a point on the circle such that  $OQ$  is perpendicular to  $PQ$ .

The quantity  $k^2$  is known as the circle power (Coxeter 1969, p. 81).


(<https://mathworld.wolfram.com/Inversion.html>)

Some propositions :


- The inverse of a circle (not through the center of inversion) is a circle.
- The inverse of a circle through the center of inversion is a line.
- The inverse of a line (not through the center of inversion) is a circle through the center of inversion.
- A circle orthogonal to the circle of inversion is its own inverse.
- A line through the center of inversion is its own inverse.
- Angles are preserved in inversion.

Explanation:

Directly (Center  $O$  power =  $k^2 = OA^2 = OP \times OP'$ )




```
\begin{tikzpicture}[scale=.5]
  \tkzDefPoints{4/0/A,6/0/P,0/0/O}
  \tkzDefPointBy[inversion = center O through A](P)
  \tkzGetPoint{P'}
  \tkzDrawSegments(O,P)
  \tkzDrawCircle(O,A)
  \tkzLabelPoints[above right,font=\scriptsize](O,A,P,P')
  \tkzDrawPoints(O,A,P,P')
\end{tikzpicture}
```




```
\begin{tikzpicture}[scale=.5]
  \tkzDefPoints{4/0/A,6/0/P,0/0/O}
  \tkzDefLine[orthogonal=through P](O,P)
  \tkzGetPoint{L}
  \tkzDefLine[tangent from = P](O,A) \tkzGetPoints{R}{Q}
  \tkzDefPointBy[projection=onto O--A](Q) \tkzGetPoint{P'}
  \tkzDrawSegments(O,P O,A)
  \tkzDrawSegments[new](O,P O,Q P,Q Q,P')
  \tkzDrawCircle(O,A)
  \tkzDrawLines[add=1 and 0](P,L)
  \tkzLabelPoints[below,font=\scriptsize](O,P')
  \tkzLabelPoints[above right,font=\scriptsize](P,Q)
  \tkzDrawPoints(O,P) \tkzDrawPoints[new](Q,P')
  \tkzLabelSegment[above](O,Q){$k$}
  \tkzMarkRightAngles(A,P',Q P,Q,O)
  \tkzLabelCircle[above=.5cm,
    font=\scriptsize](O,A)(100){inversion circle}
  \tkzLabelPoint[left,font=\scriptsize](O){inversion center}
  \tkzLabelPoint[left,font=\scriptsize](L){polar}
\end{tikzpicture}
```

## 12.1.10. Inversion of lines ex 1




```
\begin{tikzpicture}[scale=.5]
\tkzDefPoints{O/0/0,3/0/I,4/3/P,6/-3/Q}
\tkzDrawCircle(O,I)
\tkzDefPointBy[projection= onto P--Q](O) \tkzGetPoint{A}
\tkzDefPointBy[inversion = center O through I](A)
\tkzGetPoint{A'}
\tkzDefPointBy[inversion = center O through I](P)
\tkzGetPoint{P'}
\tkzDefCircle[diameter](O,A')\tkzGetPoint{o}
\tkzDrawCircle[new](o,A')
\tkzDrawLines[add=.25 and .25,red](P,Q)
\tkzDrawLines[add=.25 and .25](O,A)
\tkzDrawSegments(O,P)
\tkzDrawPoints(A,P,O) \tkzDrawPoints[new](A',P')
\end{tikzpicture}
```

## 12.1.11. inversion of lines ex 2




```
\begin{tikzpicture}[scale=.8]
\tkzDefPoints{O/0/0,3/0/I,3/2/P,3/-2/Q}
\tkzDrawCircle(O,I)
\tkzDefPointBy[projection= onto P--Q](O) \tkzGetPoint{A}
\tkzDefPointBy[inversion = center O through I](A)
\tkzGetPoint{A'}
\tkzDefPointBy[inversion = center O through I](P)
\tkzGetPoint{P'}
\tkzDefCircle[diameter](O,A')\tkzGetPoint{o}
\tkzDrawCircle[new](o,A')
\tkzDrawLines[add=.25 and .25,red](P,Q)
\tkzDrawLines[add=.25 and .25](O,A)
\tkzDrawSegments(O,P)
\tkzDrawPoints(A,P,O) \tkzDrawPoints[new](A',P')
\end{tikzpicture}
```

## 12.1.12. inversion of lines ex 3



```
\begin{tikzpicture}[scale=.8]
\tkzDefPoints{O/0/0,3/0/I,2/1/P,2/-2/Q}
\tkzDrawCircle(O,I)
\tkzDefPointBy[projection= onto P--Q](O) \tkzGetPoint{A}
\tkzDefPointBy[inversion = center O through I](A)
\tkzGetPoint{A'}
\tkzDefPointBy[inversion = center O through I](P)
\tkzGetPoint{P'}
\tkzDefCircle[diameter](O,A')
\tkzDrawCircle[new](I,A')
\tkzDrawLines[add=.25 and .75,red](P,Q)
\tkzDrawLines[add=.25 and .25](O,A')
\tkzDrawSegments(O,P')
\tkzDrawPoints(A,P,O) \tkzDrawPoints[new](A',P')
\end{tikzpicture}
```

## 12.1.13. inversion of circle and homothety




```

\begin{tikzpicture}[scale=.7]
\tkzDefPoints{O/0/0,3/2/A,2/1/P}
\tkzDefLine[tangent from = O](A,P) \tkzGetPoints{T}{X}
\tkzDefPointsBy[homothety = center O%
ratio 1.25](A,P,T){}
\tkzInterCC(A,P)(A',P') \tkzGetPoints{C}{D}
\tkzCalcLength(A,P)
\tkzGetLength{rAP}
\tkzDefPointOnCircle[R=center A angle 190 radius \rAP]
\tkzGetPoint{M}
\tkzDefPointBy[inversion = center O through C](M)
\tkzGetPoint{M'}
\tkzDrawCircles[new](A,P A',P')
\tkzDrawCircle(O,C)
\tkzDrawLines[add=0 and .5](O,T' O,A' O,M' O,P')
\tkzDrawPoints(A,A',P,P',O,T,T',M,M')
\tkzLabelPoints(O,T,T',M,M')
\tkzLabelPoints[below](P,P')
\end{tikzpicture}

```

## 12.1.14. inversion of Triangle with respect to the Incircle



```


\begin{tikzpicture}[scale=1]
\tkzDefPoints{O/0/A,5/1/B,3/6/C}
\tkzDefTriangleCenter[in](A,B,C) \tkzGetPoint{O}
\tkzDefPointBy[projection= onto A--C](O) \tkzGetPoint{b}
\tkzDefPointBy[projection= onto A--C](O) \tkzGetPoint{b}
\tkzDefPointBy[projection= onto B--C](O) \tkzGetPoint{a}
\tkzDefPointBy[projection= onto A--B](O) \tkzGetPoint{c}
\tkzDefPointsBy[inversion = center O through b](a,b,c)%
{Ia,Ib,Ic}

\tkzDefMidPoint(O,Ia) \tkzGetPoint{Ja}
\tkzDefMidPoint(O,Ib) \tkzGetPoint{Jb}
\tkzDefMidPoint(O,Ic) \tkzGetPoint{Jc}
\tkzInterCC(Ja,O)(Jb,O) \tkzGetPoints{0}{x}
\tkzInterCC(Ja,O)(Jc,O) \tkzGetPoints{y}{0}
\tkzInterCC(Jb,O)(Jc,O) \tkzGetPoints{0}{z}
\tkzDrawPolygon(A,B,C)
\tkzDrawCircle(O,b)\tkzDrawPoints(A,B,C,O)
\tkzDrawCircles[dashed,gray](Ja,y Jb,x Jc,z)
\tkzDrawArc[line width=1pt,orange,delta=0](Jb,x)(z)
\tkzDrawArc[line width=1pt,orange,delta=0](Jc,z)(y)
\tkzDrawArc[line width=1pt,orange,delta=0](Ja,y)(x)
\tkzLabelPoint[below](A){A}\tkzLabelPoint[above](C){C}
\tkzLabelPoint[right](B){B}\tkzLabelPoint[below](O){O}
\end{tikzpicture}

```

## 12.1.15. inversion: orthogonal circle with inversion circle

The inversion circle itself, circles orthogonal to it, and lines through the inversion center are invariant under inversion. If the circle meets the reference circle, these invariant points of intersection are also on the inverse circle. See I and J in the next figure.




```
\begin{tikzpicture}[scale=1]
\tkzDefPoint(0,0){O}\tkzDefPoint(1,0){A}
\tkzDefPoint(-1.5,-1.5){z1}
\tkzDefPoint(1.5,-1.25){z2}
\tkzDefCircle[orthogonal through=z1 and z2](O,A)
\tkzGetPoint{c}
\tkzDrawCircle[new](c,z1)
\tkzDefPointBy[inversion = center O through A](z1)
\tkzGetPoint{Z1}
\tkzInterCC(O,A)(c,z1) \tkzGetPoints{I}{J}
\tkzDefPointBy[inversion = center O through A](I)
\tkzGetPoint{I'}
\tkzDrawCircle(O,A)
\tkzDrawPoints(O,A,z1,z2)
\tkzDrawPoints[new](c,Z1,I,J)
\tkzLabelPoints(O,A,z1,z2,c,Z1,I,J)
\end{tikzpicture}
```

For a more complex example see Pappus 47.25

### 12.1.16. inversion negative

It's an inversion followed by a symmetry of center O



```
\begin{tikzpicture}[scale=1.5]
\tkzDefPoints{1/0/A,0/0/O}
\tkzDefPoint(-1.5,-1.5){z1}
\tkzDefPoint(0.35,-2){z2}
\tkzDefPointBy[inversion negative = center O through A](z1)
\tkzGetPoint{Z1}
\tkzDefPointBy[inversion negative = center O through A](z2)
\tkzGetPoint{Z2}
\tkzDrawCircle(O,A)
\tkzDrawPoints[color=black, fill=red,size=4](Z1,Z2)
\tkzDrawSegments(z1,Z1 z2,Z2)
\tkzDrawPoints[color=black, fill=red,size=4](O,z1,z2)
\tkzLabelPoints[font=\scriptsize](O,A,z1,z2,Z1,Z2)
\end{tikzpicture}
```



### 12.2. Transformation of multiple points; `\tkzDefPointsBy`

Variant of the previous macro for defining multiple images. You must give the names of the images as arguments, or indicate that the names of the images are formed from the names of the antecedents, leaving the argument empty.

```
\tkzDefPointsBy[translation= from A to A'](B,C){}
```

The images are  $B'$  and  $C'$ .

```
\tkzDefPointsBy[translation= from A to A'](B,C){D,E}
```


The images are D and E.

```
\tkzDefPointsBy[translation= from A to A'](B)
```

The image is  $B'$ .


<code>\tkzDefPointsBy[local options](list of points){list of points}</code>	
arguments	examples
<code>(list of points){list of pts}</code>	<code>(A,B){E,F}</code> E,F images of A, B
If the list of images is empty then the name of the image is the name of the antecedent to which " ' " is added.	
options	examples
<code>translation = from #1 to #2</code>	<code>[translation=from A to B] (E){}</code>
<code>homothety = center #1 ratio #2</code>	<code>[homothety=center A ratio .5] (E){F}</code>
<code>reflection = over #1--#2</code>	<code>[reflection=over A--B] (E){F}</code>
<code>symmetry = center #1</code>	<code>[symmetry=center A] (E){F}</code>
<code>projection = onto #1--#2</code>	<code>[projection=onto A--B] (E){F}</code>
<code>rotation = center #1 angle #2</code>	<code>[rotation=center angle 30] (E){F}</code>
<code>rotation in rad = center #1 angle #2</code>	for instance angle <code>pi/3</code>
<code>rotation with nodes = center #1 from #2 to #3</code>	<code>[center O from A to B] (E){F}</code>
<code>inversion = center #1 through #2</code>	<code>[inversion = center O through A] (E){F}</code>
<code>inversion negative = center #1 through #2</code>	...
The points are only defined and not drawn.	

#### 12.2.1. translation of multiple points



```
\begin{tikzpicture}[>=latex]
\tkzDefPoints{0/0/A,3/0/B,3/1/C}{A',1/2/C'}
\tkzDefPointsBy[translation= from A to A'](B,C){}
\tkzDrawPolygon(A,B,C)
\tkzDrawPolygon[new] (A',B',C')
\tkzDrawPoints(A,B,C)
\tkzDrawPoints[new] (A',B',C')
\tkzLabelPoints(A,B,A',B')
\tkzLabelPoints[above] (C,C')
\tkzDrawSegments[color = gray,->,
style=dashed](A,A' B,B' C,C')
\end{tikzpicture}
```

## 12.2.2. symmetry of multiple points: an oval



```
\begin{tikzpicture}[scale=0.4]
  \tkzDefPoint(-4,0){I}
  \tkzDefPoint(4,0){J}
  \tkzDefPoint(0,0){O}
  \tkzInterCC(J,O)(O,J) \tkzGetPoints{L}{H}
  \tkzInterCC(I,O)(O,I) \tkzGetPoints{K}{G}
  \tkzInterLL(I,K)(J,H) \tkzGetPoint{M}
  \tkzInterLL(I,G)(J,L) \tkzGetPoint{N}
  \tkzDefPointsBy[symmetry=center J](L,H){D,E}
  \tkzDefPointsBy[symmetry=center I](G,K){C,F}
  \begin{scope}[line style/.style = {very thin,teal}]
    \tkzDrawLines[add=1.5 and 1.5](I,K I,G J,H J,L)
    \tkzDrawLines[add=.5 and .5](I,J)
    \tkzDrawCircles(O,I I,O J,O)
    \tkzDrawArc[delta=0,orange](N,D)(C)
    \tkzDrawArc[delta=0,orange](M,F)(E)
    \tkzDrawArc[delta=0,orange](J,E)(D)
    \tkzDrawArc[delta=0,orange](I,C)(F)
  \end{scope}
\end{tikzpicture}
```

## 13. Defining points using a vector

## 13.1. \tkzDefPointWith

There are several possibilities to create points that meet certain vector conditions. This can be done with `\tkzDefPointWith`. The general principle is as follows, two points are passed as arguments, i.e. a vector. The different options allow to obtain a new point forming with the first point (with some exceptions) a collinear vector or a vector orthogonal to the first vector. Then the length is either proportional to that of the first one, or proportional to the unit. Since this point is only used temporarily, it does not have to be named immediately. The result is in `tkzPointResult`. The macro `\tkzGetPoint` allows you to retrieve the point and name it differently. There are options to define the distance between the given point and the obtained point. In the general case this distance is the distance between the 2 points given as arguments if the option is of the "normed" type then the distance between the given point and the obtained point is 1 cm. Then the K option allows to obtain multiples.

`\tkzDefPointWith(<pt1,pt2>)`

It is in fact the definition of a point meeting vectorial conditions.


arguments	definition	explanation
(pt1,pt2)	point couple	the result is a point in <code>tkzPointResult</code>

In what follows, it is assumed that the point is recovered by `\tkzGetPoint{C}`

options	example	explanation
orthogonal	[orthogonal] (A,B)	$AC = AB$ and $\overrightarrow{AC} \perp \overrightarrow{AB}$
orthogonal normed	[orthogonal normed] (A,B)	$AC = 1$ and $\overrightarrow{AC} \perp \overrightarrow{AB}$
linear	[linear] (A,B)	$\overrightarrow{AC} = K \times \overrightarrow{AB}$
linear normed	[linear normed] (A,B)	$AC = K$ and $\overrightarrow{AC} = k \times \overrightarrow{AB}$
colinear= at #1	[colinear= at C] (A,B)	$\overrightarrow{CD} = \overrightarrow{AB}$
colinear normed= at #1	[colinear normed= at C] (A,B)	$\overrightarrow{CD} = \overrightarrow{AB}$
K	[linear] (A,B), K=2	$\overrightarrow{AC} = 2 \times \overrightarrow{AB}$


## 13.1.1. Option colinear at, simple example

$$(\overrightarrow{AB} = \overrightarrow{CD})$$



```
\begin{tikzpicture}[scale=1.2,
  vect/.style={->,shorten >=1pt,>=latex'}]
\tkzDefPoint(2,3){A}    \tkzDefPoint(4,2){B}
\tkzDefPoint(0,1){C}
\tkzDefPointWith[colinear=at C](A,B)
\tkzGetPoint{D}
\tkzDrawPoints[new](A,B,C,D)
\tkzLabelPoints[above right=3pt](A,B,C,D)
\tkzDrawSegments[vect](A,B C,D)
\end{tikzpicture}
```

## 13.1.2. Option colinear at, complex example




```

\begin{tikzpicture}[scale=.75]
\tkzDefPoints{0/0/B,3.6/0/C,1.5/4/A}
\tkzDefSpcTriangle[ortho](A,B,C){Ha,Hb,Hc}
\tkzDefTriangleCenter[ortho](A,B,C) \tkzGetPoint{H}
\tkzDefSquare(A,C) \tkzGetPoints{R}{S}
\tkzDefSquare(B,A) \tkzGetPoints{M}{N}
\tkzDefSquare(C,B) \tkzGetPoints{P}{Q}
\tkzDefPointWith[colinear= at M](A,S) \tkzGetPoint{A'}
\tkzDefPointWith[colinear= at P](B,N) \tkzGetPoint{B'}
\tkzDefPointWith[colinear= at Q](C,R) \tkzGetPoint{C'}
\tkzDefPointBy[projection=onto P--Q](Ha) \tkzGetPoint{Pa}
\tkzDrawPolygon[teal,thick](A,C,R,S)\tkzDrawPolygon[teal,thick](A,B,N,M)
\tkzDrawPolygon[teal,thick](C,B,P,Q)
\tkzDrawPoints[teal,size=2](A,B,C,Ha,Hb,Hc,A',B',C')
\tkzDrawSegments[ultra thin,red](M,A' A',S P,B' B',N Q,C' C',R B,S C,M C,N B,R A,P A,Q)
\tkzDrawSegments[ultra thin,teal,dashed](A,Ha B,Hb C,Hc)
\tkzDefPointBy[rotation=center A angle 90](S) \tkzGetPoint{S'}
\tkzDrawSegments[ultra thin,teal,dashed](B,S' A,S' A,A' M,S' B',Q P,C' M,S Ha,Pa)
\tkzDrawArc(A,S)(S')
\end{tikzpicture}

```

### 13.1.3. Option colinear at

How to use K




```

\begin{tikzpicture}[vect/.style={->,
shorten >=1pt,>=latex'}]
\tkzDefPoints{0/0/A,5/0/B,1/2/C}
\tkzDefPointWith[colinear=at C](A,B)
\tkzGetPoint{G}
\tkzDefPointWith[colinear=at C, K=0.5](A,B)
\tkzGetPoint{H}
\tkzLabelPoints(A,B,C,G,H)
\tkzDrawPoints(A,B,C,G,H)
\tkzDrawSegments[vect](A,B C,H)
\end{tikzpicture}

```

### 13.1.4. Option colinear at

With  $K = \frac{\sqrt{2}}{2}$



```

\begin{tikzpicture}[vect/.style={->,
shorten >=1pt,>=latex'}]
\tkzDefPoints{1/1/A,4/2/B,2/2/C}
\tkzDefPointWith[colinear=at C,K=sqrt(2)/2](A,B)
\tkzGetPoint{D}
\tkzDrawPoints[color=red](A,B,C,D)
\tkzDrawSegments[vect](A,B C,D)
\end{tikzpicture}


```

### 13.1.5. Option orthogonal

$AB=AC$  since  $K = 1$ .




## 13.1.8. Options colinear and orthogonal



```
\begin{tikzpicture}[scale=1.2,
  vect/.style={->,shorten >=1pt,>=latex'}]
\tkzDefPoints{2/1/A,6/2/B}
\tkzDefPointWith[orthogonal,K=.5](A,B)
\tkzGetPoint{C}
\tkzDefPointWith[colinear=at C,K=.5](A,B)
\tkzGetPoint{D}
\tkzMarkRightAngle[fill=gray!20](B,A,C)
\tkzDrawSegments[vect](A,B A,C C,D)
\tkzDrawPoints(A,...,D)
\end{tikzpicture}
```

## 13.1.9. Option orthogonal normed


$K = 1$   $AC = 1$ .



```
\begin{tikzpicture}[scale=1.2,
  vect/.style={->,shorten >=1pt,>=latex'}]
\tkzDefPoints{2/3/A,4/2/B}
\tkzDefPointWith[orthogonal normed](A,B)
\tkzGetPoint{C}
\tkzDrawPoints[color=red](A,B,C)
\tkzDrawSegments[vect](A,B A,C)
\tkzMarkRightAngle[fill=gray!20](B,A,C)
\end{tikzpicture}
```

13.1.10. Option orthogonal normed and  $K=2$ 

$K = 2$  therefore  $AC = 2$ .




```
\begin{tikzpicture}[scale=1.2,
  vect/.style={->,shorten >=1pt,>=latex'}]
\tkzDefPoints{2/3/A,5/1/B}
\tkzDefPointWith[orthogonal normed,K=2](A,B)
\tkzGetPoint{C}
\tkzDrawPoints[color=red](A,B,C)
\tkzDefCircle[R](A,2) \tkzGetPoint{a}
\tkzDrawCircle(A,a)
\tkzDrawSegments[vect](A,B A,C)
\tkzMarkRightAngle[fill=gray!20](B,A,C)
\tkzLabelPoints[above=3pt](A,B,C)
\end{tikzpicture}
```

## 13.1.11. Option linear

Here  $K = 0.5$ .


This amounts to applying a homothety or a multiplication of a vector by a real. Here is the middle of  $[AB]$ .



```
\begin{tikzpicture}[scale=1.2]
\tkzDefPoints{1/3/A,4/2/B}
\tkzDefPointWith[linear,K=0.5](A,B)
\tkzGetPoint{C}
\tkzDrawPoints[color=red](A,B,C)
\tkzDrawSegment(A,B)
\tkzLabelPoints[above right=3pt](A,B,C)
\end{tikzpicture}
```

## 13.1.12. Option linear normed

In the following example  $AC = 1$  and  $C$  belongs to  $(AB)$ .



```
\begin{tikzpicture}[scale=1.2]
\tkzDefPoints{1/3/A,4/2/B}
\tkzDefPointWith[linear normed](A,B)
\tkzGetPoint{C}
\tkzDrawPoints[color=red](A,B,C)
\tkzDrawSegment(A,B)
\tkzLabelSegment(A,C){$1$}
\tkzLabelPoints[above right=3pt](A,B,C)
\end{tikzpicture}
```

## 13.2. \tkzGetVectxy


Retrieving the coordinates of a vector.

`\tkzGetVectxy(<A,B>){<text>}`

Allows to obtain the coordinates of a vector.

arguments	example	explanation
(point){name of macro}	<code>\tkzGetVectxy(A,B){V}</code>	$\text{Vx}, \text{Vy}$ : coordinates of $\overrightarrow{AB}$

## 13.2.1. Coordinate transfer with \tkzGetVectxy



```
\begin{tikzpicture}
\tkzDefPoints{0/0/O,1/1/A,4/2/B}
\tkzGetVectxy(A,B){v}
\tkzDefPoint(\vx,\vy){V}
\tkzDrawSegment[->,color=red](O,V)
\tkzDrawSegment[->,color=blue](A,B)
\tkzDrawPoints(A,B,O)
\tkzLabelPoints(A,B,O,V)
\end{tikzpicture}
```

## 14. Straight lines

It is of course essential to draw straight lines, but before this can be done, it is necessary to be able to define certain particular lines such as mediators, bisectors, parallels or even perpendiculars. The principle is to determine two points on the straight line.

## 14.1. Definition of straight lines


`\tkzDefLine[<local options>](<pt1,pt2>) or (<pt1,pt2,pt3>)`

The argument is a list of two or three points. Depending on the case, the macro defines one or two points necessary to obtain the line sought. Either the macro `\tkzGetPoint` or the macro `\tkzGetPoints` must be used. I used the term "mediator" to designate the perpendicular bisector line at the middle of a line segment.

arguments	example	explanation
(<pt1,pt2>)	[mediator] (<A,B>)	mediator of the segment $[A,B]$
(<pt1,pt2,pt3>)	[bisector] (<A,B,C>)	bisector of $\widehat{ABC}$
(<pt1,pt2,pt3>)	[altitude] (<A,B,C>)	altitude from $B$
(<pt1>)	[tangent at=A] (<O>)	tangent at $A$ on the circle center $O$
(<pt1,pt2>)	[tangent from=A] (<O,B>)	circle center $O$ through $B$

options	default	definition
mediator		perpendicular bisector of a line segment
perpendicular=through...	mediator	perpendicular to a line passing through a point
orthogonal=through...	mediator	see above
parallel=through...	mediator	parallel to a line passing through a point
bisector	mediator	bisector of an angle defined by three points
bisector out	mediator	exterior angle bisector
symmedian	mediator	symmedian from a vertex
altitude	mediator	altitude from a vertex
euler	mediator	euler line of a triangle
tangent at	mediator	tangent at a point of a circle
tangent from	mediator	tangent from an exterior point
K	1	coefficient for the perpendicular line
normed	false	normalizes the created segment

#### 14.1.1. With mediator




```

\begin{tikzpicture}[rotate=25]
\tkzDefPoints{-2/0/A,1/2/B}
\tkzDefLine[mediator](A,B) \tkzGetPoints{C}{D}
\tkzDefPointWith[linear,K=.75](C,D) \tkzGetPoint{D}
\tkzDefMidPoint(A,B) \tkzGetPoint{I}
\tkzFillPolygon[color=teal!20](A,C,B,D)
\tkzDrawSegments(A,B C,D)
\tkzMarkRightAngle(B,I,C)
\tkzDrawSegments(D,B D,A)
\tkzDrawSegments(C,B C,A)
\end{tikzpicture}

```

#### 14.1.2. An envelope with option mediator

Based on a figure from O. Reboux with pst-eucl by D Rodriguez.



```


\begin{tikzpicture}[scale=.75]
% necessary
\tkzInit[xmin=-6,ymin=-4,xmax=6,ymax=6]
\tkzClip
\tkzSetUpLine[thin,color=magenta]
\tkzDefPoint(0,0){O}
\tkzDefPoint(132:4){A}
\tkzDefPoint(5,0){B}
\foreach \ang in {5,10,...,360}{%
\tkzDefPoint(\ang:5){M}
\tkzDefLine[mediator](A,M)
\tkzGetPoints{x}{y}
\tkzDrawLine[add= 3 and 3](x,y)}
\end{tikzpicture}

```




## 14.1.3. A parabola with option mediator

Based on a figure from O. Reboux with pst-eucl by D Rodriguez. It is not necessary to name the two points that define the mediator.



```
\begin{tikzpicture}[scale=.6]
\tkzInit[xmin=-6,ymin=-4,xmax=6,ymax=6]
\tkzClip
\tkzSetUpLine[thin,color=teal]
\tkzDefPoint(0,0){O}
\tkzDefPoint(132:5){A}
\tkzDefPoint(4,0){B}
\foreach \ang in {5,10,...,360}{%
\tkzDefPoint(\ang:4){M}
\tkzDefLine[mediator](A,M)
\tkzGetPoints{x}{y}
\tkzDrawLine[add= 3 and 3](x,y)}
\end{tikzpicture}
```


## 14.1.4. With options bisector and normed



```
\begin{tikzpicture}[rotate=25,scale=.75]
\tkzDefPoints{0/0/C, 2/-3/A, 4/0/B}
\tkzDefLine[bisector,normed](B,A,C) \tkzGetPoint{a}
\tkzDrawLines[add= 0 and .5](A,B A,C)
\tkzShowLine[bisector,gap=4,size=2,color=red](B,A,C)
\tkzDrawLines[new,dashed,add= 0 and 3](A,a)
\end{tikzpicture}
```


## 14.1.5. With option parallel=through

Archimedes' Book of Lemmas proposition 1




```
\begin{tikzpicture}
\tkzDefPoints{0/0/O_1,0/1/O_2,0/3/A}
\tkzDefPoint(15:3){F}
\tkzDefPointBy[symmetry=center O_1](F)
\tkzGetPoint{E}
\tkzDefLine[parallel=through O_2](E,F)
\tkzGetPoint{x}
\tkzInterLC(x,O_2)(O_2,A) \tkzGetPoints{D}{C}
\tkzDrawCircles(O_1,A O_2,A)
\tkzDrawSegments[new](O_1,A E,F C,D)
\tkzDrawSegments[purple](A,E A,F)
\tkzDrawPoints(A,O_1,O_2,E,F,C,D)
\tkzLabelPoints(A,O_1,O_2,E,F,C,D)
\end{tikzpicture}
```

## 14.1.6. With option orthogonal and parallel




```
\begin{tikzpicture}
\tkzDefPoints{-1.5/-0.25/A,1/-0.75/B,-0.7/1/C}
\tkzDrawLine(A,B)
\tkzLabelLine[pos=1.25,below left](A,B){$(d_1)$}
\tkzDrawPoints(A,B,C)
\tkzDefLine[orthogonal=through C](B,A) \tkzGetPoint{c}
\tkzDrawLine(C,c)
\tkzLabelLine[pos=1.25,left](C,c){$(\delta)$}
\tkzInterLL(A,B)(C,c) \tkzGetPoint{I}
\tkzMarkRightAngle(C,I,B)
\tkzDefLine[parallel=through C](A,B) \tkzGetPoint{c'}
\tkzDrawLine(C,c')
\tkzLabelLine[pos=1.25,below left](C,c'){$(d_2)$}
\tkzMarkRightAngle(I,C,c')
\end{tikzpicture}
```

## 14.1.7. With option altitude




```
\begin{tikzpicture}
\tkzDefPoints{0/0/A,6/0/B,0.8/4/C}
\tkzDefLine[altitude](A,B,C) \tkzGetPoint{b}
\tkzDefLine[altitude](B,C,A) \tkzGetPoint{c}
\tkzDefLine[altitude](C,A,B) \tkzGetPoint{a}
\tkzDrawPolygon(A,B,C)
\tkzDrawPoints[blue](a,b,c)
\tkzDrawSegments[blue](A,a B,b C,c)
\tkzLabelPoints(A,B,C)
\tkzLabelPoints[above](C,a)
\tkzLabelPoints[above left](b)
\end{tikzpicture}
```

## 14.1.8. With option euler



```
\begin{tikzpicture}[scale=.75]
\tkzDefPoints{0/0/A,6/0/B,0.8/4/C}
\tkzDefLine[euler](A,B,C)
\tkzGetPoints{h}{e}
\tkzDefTriangleCenter[circum](A,B,C)
\tkzGetPoint{o}
\tkzDrawPolygon[teal](A,B,C)
\tkzDrawPoints[red](A,B,C,h,e,o)
\tkzDrawLine[add= 2 and 2](h,e)
\tkzLabelPoints(A,B,C,h,e,o)
\tkzLabelPoints[above](C)
\end{tikzpicture}
```


## 14.1.9. Tangent passing through a point on the circle tangent at



```
\begin{tikzpicture}[scale=.75]
  \tkzDefPoint(0,0){O}
  \tkzDefPoint(6,6){E}
  \tkzDefRandPointOn[circle=center O radius 3]
  \tkzGetPoint{A}
  \tkzDrawSegment(O,A)
  \tkzDrawCircle(O,A)
  \tkzDefLine[tangent at=A](O)
  \tkzGetPoint{h}
  \tkzDrawLine[add = 4 and 3](A,h)
  \tkzMarkRightAngle[fill=teal!30](O,A,h)
\end{tikzpicture}
```


## 14.1.10. Choice of contact point with tangents passing through an external point option tangent from

The tangent is not drawn. With option `at`, a point of the tangent is given by `tkzPointResult`. With option `from` you get two points of the circle with `tkzFirstPointResult` and `tkzSecondPointResult`. You can choose between these two points by comparing the angles formed with the outer point, the contact point and the center. The two possible angles have different directions. Angle counterclockwise refers to `tkzFirstPointResult`.



```
\begin{tikzpicture}[scale=1,rotate=-30]
  \tkzDefPoints{0/0/Q,0/2/A,6/-1/O}
  \tkzDefLine[tangent from = O](Q,A)
  \tkzGetPoints{R}{S}
  \tkzInterLC[near](O,Q)(Q,A)
  \tkzGetPoints{M}{N}
  \tkzDrawCircle(Q,M)
  \tkzDrawSegments[new,add = 0 and .2](O,R O,S)
  \tkzDrawSegments[gray](N,O R,Q S,Q)
  \tkzDrawPoints(O,Q,R,S,M,N)
  \tkzMarkAngle[gray,-stealth,size=1](O,R,Q)
  \tkzFindAngle(O,R,Q) \tkzGetAngle{an}
  \tkzLabelAngle(O,R,Q){%
    $\pgfmathprintnumber{\an}^\circ$}
  \tkzMarkAngle[gray,-stealth,size=1](O,S,Q)
  \tkzFindAngle(O,S,Q) \tkzGetAngle{an}
  \tkzLabelAngle(O,S,Q){%
    $\pgfmathprintnumber{\an}^\circ$}
  \tkzLabelPoints(Q,O,M,N,R)
  \tkzLabelPoints[above,text=red](S)
\end{tikzpicture}
```

## 14.1.11. Example of tangents passing through an external point




```

\begin{tikzpicture}[scale=.8]
\tkzDefPoints{0/0/c,1/0/d,3/0/a0}
\def\tkzRadius{1}
\tkzDrawCircle(c,d)
\foreach \an in {0,10,...,350}{
\tkzDefPointBy[rotation=center c angle \an](a0)
\tkzGetPoint{a}
\tkzDefLine[tangent from = a](c,d)
\tkzGetPoints{e}{f}
\tkzDrawLines(a,f a,e)
\tkzDrawSegments(c,e c,f)}
\end{tikzpicture}

```

## 14.1.12. Example of Andrew Mertz




```

\begin{tikzpicture}[scale=.6]
\tkzDefPoint(100:8){A}\tkzDefPoint(50:8){B}
\tkzDefPoint(0,0){C} \tkzDefPoint(0,-4){R}
\tkzDrawCircle(C,R)
\tkzDefLine[tangent from = A](C,R) \tkzGetPoints{D}{E}
\tkzDefLine[tangent from = B](C,R) \tkzGetPoints{F}{G}
\tkzDrawSector[fill=teal!20,opacity=0.5](A,E)(D)
\tkzFillSector[color=teal,opacity=0.5](B,G)(F)
\end{tikzpicture}

```

<http://www.texample.net/tikz/examples/>

## 14.1.13. Drawing a tangent option tangent from



```
\begin{tikzpicture}[scale=.6]
\tkzDefPoint(0,0){B}
\tkzDefPoint(0,8){A}
\tkzDefSquare(A,B)
\tkzGetPoints{C}{D}
\tkzDrawPolygon(A,B,C,D)
\tkzClipPolygon(A,B,C,D)
\tkzDefPoint(4,8){F}
\tkzDefPoint(4,0){E}
\tkzDefPoint(4,4){Q}
\tkzFillPolygon[color = green](A,B,C,D)
\tkzDrawCircle[fill = orange](B,A)
\tkzDrawCircle[fill = purple](E,B)
\tkzDefLine[tangent from = B](F,A)
\tkzInterLL(F,t kzSecondPointResult)(C,D)
\tkzInterLL(A,t kzPointResult)(F,E)
\tkzDrawCircle[fill = yellow](tkzPointResult,Q)
\tkzDefPointBy[projection= onto B--A](tkzPointResult)
\tkzDrawCircle[fill = blue!50!black](tkzPointResult,A)
\end{tikzpicture}
```

## 15. Triangles

## 15.1. Definition of triangles \tkzDefTriangle

The following macros will allow you to define or construct a triangle from at least two points.

At the moment, it is possible to define the following triangles:

- **two angles** determines a triangle with two angles;
- **equilateral** determines an equilateral triangle;
- **isosceles right** determines an isosceles right triangle;
- **half** determines a right-angled triangle such that the ratio of the measurements of the two adjacent sides to the right angle is equal to 2;
- **pythagore** determines a right-angled triangle whose side measurements are proportional to 3, 4 and 5;
- **school** determines a right-angled triangle whose angles are 30, 60 and 90 degrees;
- **golden** determines a right-angled triangle such that the ratio of the measurements on the two adjacent sides to the right angle is equal to  $\Phi = 1.618034$ , I chose "golden triangle" as the denomination because it comes from the golden rectangle and I kept the denomination "gold triangle" or "Euclid's triangle" for the isosceles triangle whose angles at the base are 72 degrees;
- **euclid** or **gold** for the gold triangle; in the previous version the option was "euclide" with an "e".
- **cheops** determines a third point such that the triangle is isosceles with side measurements proportional to 2,  $\Phi$  and  $\Phi$ .


`\tkzDefTriangle[<local options>](<A,B>)`

The points are ordered because the triangle is constructed following the direct direction of the trigonometric circle. This macro is either used in partnership with `\tkzGetPoint` or by using `\tkzPointResult` if it is not necessary to keep the name.

options	default	definition
two angles= #1 and #2	no default	triangle knowing two angles
equilateral	equilateral	equilateral triangle
half	equilateral	B rectangle AB=2BC AC hypotenuse
isosceles right	equilateral	isosceles right triangle
pythagore	equilateral	proportional to the pythagorean triangle 3-4-5
pythagoras	equilateral	same as above
egyptian	equilateral	same as above
school	equilateral	angles of 30, 60 and 90 degrees
gold	equilateral	B rectangle and $AB/AC = \Phi$
euclid	equilateral	angles of 72, 72 and 36 degrees, A is the apex
golden	equilateral	angles of 72, 72 and 36 degrees, C is the apex
sublime	equilateral	angles of 72, 72 and 36 degrees, C is the apex
cheops	equilateral	AC=BC, AC and BC are proportional to 2 and $\Phi$ .
swap	false	gives the symmetric point with respect to AB


`\tkzGetPoint` allows you to store the point otherwise `\tkzPointResult` allows for immediate use.

#### 15.1.1. Option equilateral



```
\begin{tikzpicture}
  \tkzDefPoint(0,0){A}
  \tkzDefPoint(4,0){B}
  \tkzDefTriangle[equilateral](A,B)
  \tkzGetPoint{C}
  \tkzDrawPolygons(A,B,C)
  \tkzDefTriangle[equilateral](B,A)
  \tkzGetPoint{D}
  \tkzDrawPolygon(B,A,D)
  \tkzMarkSegments[mark=s](A,B B,C A,C A,D B,D)
\end{tikzpicture}
```


## 15.1.2. Option two angles



```
\begin{tikzpicture}
\tkzDefPoint(0,0){A}
\tkzDefPoint(5,0){B}
\tkzDefTriangle[two angles = 50 and 70](A,B)
\tkzGetPoint{C}
\tkzDrawSegment(A,B)
\tkzDrawPoints(A,B)
\tkzLabelPoints(A,B)
\tkzDrawSegments[new](A,C B,C)
\tkzDrawPoints[new](C)
\tkzLabelPoints[above,new](C)
\tkzLabelAngle[pos=1.4](B,A,C){$50^\circ$}
\tkzLabelAngle[pos=0.8](C,B,A){$70^\circ$}
\end{tikzpicture}
```

## 15.1.3. Option school


The angles are 30, 60 and 90 degrees.



```
\begin{tikzpicture}
\tkzDefPoints{0/0/A,4/0/B}
\tkzDefTriangle[school](A,B)
\tkzGetPoint{C}
\tkzMarkRightAngles(C,B,A)
\tkzLabelAngle[pos=0.8](B,A,C){$30^\circ$}
\tkzLabelAngle[pos=0.8](C,B,A){$90^\circ$}
\tkzLabelAngle[pos=0.8](A,C,B){$60^\circ$}
\tkzDrawSegments(A,B)
\tkzDrawSegments[new](A,C B,C)
\tkzLabelPoints(A,B)
\tkzLabelPoints[above](C)
\end{tikzpicture}
```

## 15.1.4. Option pythagore


This triangle has sides whose lengths are proportional to 3, 4 and 5.



```
\begin{tikzpicture}
\tkzDefPoints{0/0/A,4/0/B}
\tkzDefTriangle[pythagore](A,B)
\tkzGetPoint{C}
\tkzDrawSegments(A,B)
\tkzDrawSegments[new](A,C B,C)
\tkzMarkRightAngles(A,B,C)
\tkzDrawPoints[new](C)
\tkzDrawPoints(A,B)
\tkzLabelPoints[above](A,B)
\tkzLabelPoints[new](C)
\end{tikzpicture}
```


## 15.1.5. Option pythagore and swap

This triangle has sides whose lengths are proportional to 3, 4 and 5.



```
\begin{tikzpicture}
  \tkzDefPoints{0/0/A,4/0/B}
  \tkzDefTriangle[pythagore,swap](A,B)
  \tkzGetPoint{C}
  \tkzDrawSegments(A,B)
  \tkzDrawSegments[new](A,C B,C)
  \tkzMarkRightAngles(A,B,C)
  \tkzLabelPoint[above,new](C){$C$}
  \tkzDrawPoints[new](C)
  \tkzDrawPoints(A,B)
  \tkzLabelPoints(A,B)
\end{tikzpicture}
```


#### 15.1.6. Option golden



```
\begin{tikzpicture}[scale=.8]
  \tkzDefPoint(0,0){A} \tkzDefPoint(4,0){B}
  \tkzDefTriangle[golden](A,B)\tkzGetPoint{C}
  \tkzDefSpcTriangle[in,name=M](A,B,C){a,b,c}
  \tkzDrawPolygon(A,B,C)
  \tkzDrawPoints(A,B)
  \tkzDrawSegment(C,Mc)
  \tkzDrawPoints[new](C)
  \tkzLabelPoints(A,B)
  \tkzLabelPoints[above,new](C)
\end{tikzpicture}
```


#### 15.1.7. Option euclid

Euclid and golden are identical but the segment AB is a base in one and a side in the other.




```
\begin{tikzpicture}[scale=.75]
  \tkzDefPoint(0,0){A} \tkzDefPoint(4,0){B}
  \tkzDefTriangle[euclid](A,B)\tkzGetPoint{C}
  \tkzDrawPolygon(A,B,C)
  \tkzDrawPoints(A,B,C)
  \tkzLabelPoints(C)
  \tkzLabelPoints[above](A,B)
  \tkzLabelAngle[pos=0.8](A,B,C){$72^\circ$}
  \tkzLabelAngle[pos=0.8](B,C,A){$72^\circ$}
  \tkzLabelAngle[pos=0.8](C,A,B){$36^\circ$}
\end{tikzpicture}
```



15.1.8. Option `isosceles right`

```
\begin{tikzpicture}
  \tkzDefPoint(0,0){A}
  \tkzDefPoint(4,0){B}
  \tkzDefTriangle[isosceles right](A,B)
  \tkzGetPoint{C}
  \tkzDrawPolygons(A,B,C)
  \tkzDrawPoints(A,B,C)
  \tkzMarkRightAngles(A,C,B)
  \tkzLabelPoints(A,B)
  \tkzLabelPoints[above](C)
\end{tikzpicture}
```

15.1.9. Option `gold`

```
\begin{tikzpicture}
  \tkzDefPoints{0/0/A,4/0/B}
  \tkzDefTriangle[gold](A,B)
  \tkzGetPoint{C}
  \tkzDrawPolygon(A,B,C)
  \tkzDrawPoints(A,B,C)
  \tkzLabelPoints[above](A,B)
  \tkzLabelPoints[below](C)
  \tkzMarkRightAngle(A,B,C)
  \tkzText(0,-2){$\dfrac{AC}{AB}=\varphi$}
\end{tikzpicture}
```

### 15.2. Specific triangles with `\tkzDefSpcTriangle`

The centers of some triangles have been defined in the "points" section, here it is a question of determining the three vertices of specific triangles.

```
\tkzDefSpcTriangle[{local options}]({p1,p2,p3}){{r1,r2,r3}}
```

The order of the points is important! `p1p2p3` defines a triangle then the result is a triangle whose vertices have as reference a combination with `name` and `r1,r2,r3`. If `name` is empty then the references are `r1,r2` and `r3`.

options	default	definition
orthic	centroid	determined by endpoints of the altitudes ...
centroid or medial	centroid	intersection of the triangle's three triangle medians
in or incentral	centroid	determined with the angle bisectors
ex or excentral	centroid	determined with the excenters
extouch	centroid	formed by the points of tangency with the excircles
intouch or contact	centroid	formed by the points of tangency of the incircle each of the vertices
euler	centroid	formed by Euler points on the nine-point circle
symmedial	centroid	intersection points of the symmedians
tangential	centroid	formed by the lines tangent to the circumcircle
feuerbach	centroid	formed by the points of tangency of the nine-point ... circle with the excircles
name	empty	used to name the vertices

#### 15.2.1. How to name the vertices

With `\tkzDefSpcTriangle[medial,name=M](A,B,C){_A,_B,_C}` you get three vertices named  $M_A$ ,  $M_B$  and  $M_C$ .

With `\tkzDefSpcTriangle[medial](A,B,C){a,b,c}` you get three vertices named and labeled `a`, `b` and `c`.


Possible `\tkzDefSpcTriangle[medial,name=M_](A,B,C){A,B,C}` you get three vertices named  $M_A$ ,  $M_B$  and  $M_C$ .

### 15.3. Option `medial` or `centroid`

The geometric centroid of the polygon vertices of a triangle is the point `G` (sometimes also denoted `M`) which is also the intersection of the triangle's three triangle medians. The point is therefore sometimes called the median point. The centroid is always in the interior of the triangle.

Weisstein, Eric W. "Centroid triangle" From MathWorld—A Wolfram Web Resource.

In the following example, we obtain the Euler circle which passes through the previously defined points.




```
\begin{tikzpicture}[rotate=90,scale=.75]
\tkzDefPoints{0/0/A,6/0/B,0.8/4/C}
\tkzDefTriangleCenter[centroid](A,B,C)
\tkzGetPoint{M}
\tkzDefSpcTriangle[medial,name=M](A,B,C){_A,_B,_C}
\tkzDrawPolygon(A,B,C)
\tkzDrawSegments[dashed,new](A,M_A B,M_B C,M_C)
\tkzDrawPolygon[new](M_A,M_B,M_C)
\tkzDrawPoints(A,B,C)
\tkzDrawPoints[new](M,M_A,M_B,M_C)
\tkzLabelPoints[above](B)
\tkzLabelPoints[below](A,C,M_B)
\tkzLabelPoints[right](M_C)
\tkzLabelPoints[left](M_A)
\tkzLabelPoints[font=\scriptsize](M)
\end{tikzpicture}
```

### 15.3.1. Option in or incentral

The incentral triangle is the triangle whose vertices are determined by the intersections of the reference triangle's angle bisectors with the respective opposite sides.


Weisstein, Eric W. "Incentral triangle" From MathWorld—A Wolfram Web Resource.



```
\begin{tikzpicture}[scale=1]
\tkzDefPoints{0/0/A,5/0/B,2/3/C}
\tkzDefSpcTriangle[in,name=I](A,B,C){_a,_b,_c}
\tkzDefCircle[in](A,B,C) \tkzGetPoints{I}{a}
\tkzDrawCircle(I,a)
\tkzDrawPolygon(A,B,C)
\tkzDrawPolygon[new](I_a,I_b,I_c)
\tkzDrawSegments[dashed,new](A,I_a B,I_b C,I_c)
\tkzDrawPoints(A,B,C,I,I_a,I_b,I_c)
\tkzLabelPoints[below](A,B,I_c)
\tkzLabelPoints[above left](I_b)
\tkzLabelPoints[above right](C,I_a)
\end{tikzpicture}
```

### 15.3.2. Option ex or excentral

The excentral triangle of a triangle ABC is the triangle  $J_a J_b J_c$  with vertices corresponding to the excenters of ABC.




```
\begin{tikzpicture}[scale=.6]
\tkzDefPoints{0/Q/A,6/Q/B,0.8/4/C}
\tkzDefSpcTriangle[excentral,name=J](A,B,C){_a,_b,_c}
\tkzDefSpcTriangle[extouch,name=T](A,B,C){_a,_b,_c}
\tkzDrawPolygon(A,B,C)
\tkzDrawPolygon[new](J_a,J_b,J_c)
\tkzClipBB
\tkzDrawPoints(A,B,C)
\tkzDrawPoints[new](J_a,J_b,J_c)
\tkzLabelPoints(A,B,C)
\tkzLabelPoints[new](J_b,J_c)
\tkzLabelPoints[new,above](J_a)
\tkzDrawCircles[gray](J_a,T_a J_b,T_b J_c,T_c)
\end{tikzpicture}
```

### 15.3.3. Option intouch or contact

The contact triangle of a triangle  $ABC$ , also called the intouch triangle, is the triangle formed by the points of tangency of the incircle of  $ABC$  with  $ABC$ .

Weisstein, Eric W. "Contact triangle" From MathWorld—A Wolfram Web Resource.

We obtain the intersections of the bisectors with the sides.




```
\begin{tikzpicture}[scale=.75]
\tkzDefPoints{0/Q/A,6/Q/B,0.8/4/C}
\tkzDefSpcTriangle[intouch,name=X](A,B,C){_a,_b,_c}
\tkzInCenter(A,B,C)\tkzGetPoint{I}
\tkzDefCircle[in](A,B,C)\tkzGetPoints{I}{i}
\tkzDrawCircle(I,i)
\tkzDrawPolygon(A,B,C)
\tkzDrawPolygon[new](X_a,X_b,X_c)
\tkzDrawPoints(A,B,C)
\tkzDrawPoints[new](X_a,X_b,X_c)
\tkzLabelPoints[right](X_a)
\tkzLabelPoints[left](X_b)
\tkzLabelPoints[above](C)
\tkzLabelPoints[below](A,B,X_c)
\end{tikzpicture}
```

### 15.3.4. Option extouch

The extouch triangle  $T_a T_b T_c$  is the triangle formed by the points of tangency of a triangle  $ABC$  with its excircles  $J_a$ ,  $J_b$ , and  $J_c$ . The points  $T_a$ ,  $T_b$ , and  $T_c$  can also be constructed as the points which bisect the perimeter of  $A_1 A_2 A_3$  starting at  $A$ ,  $B$ , and  $C$ .

Weisstein, Eric W. "Extouch triangle" From MathWorld—A Wolfram Web Resource.

We obtain the points of contact of the exinscribed circles as well as the triangle formed by the centers of the exinscribed circles.




```

\begin{tikzpicture}[scale=.7]
\tkzDefPoints{0/0/A,6/0/B,0.8/4/C}
\tkzDefSpcTriangle[excentral,
  name=J](A,B,C){_a,_b,_c}
\tkzDefSpcTriangle[extouch,
  name=T](A,B,C){_a,_b,_c}
\tkzDefTriangleCenter[nagel](A,B,C)
\tkzGetPoint{N_a}
\tkzDefTriangleCenter[centroid](A,B,C)
\tkzGetPoint{G}
\tkzDrawPoints[new](J_a,J_b,J_c)
\tkzClipBB \tkzShowBB
\tkzDrawCircles[gray](J_a,T_a J_b,T_b J_c,T_c)
\tkzDrawLines[add=1 and 1](A,B B,C C,A)
\tkzDrawSegments[new](A,T_a B,T_b C,T_c)
\tkzDrawSegments[new](J_a,T_a J_b,T_b J_c,T_c)
\tkzDrawPolygon(A,B,C)
\tkzDrawPolygon[new](T_a,T_b,T_c)
\tkzDrawPoints(A,B,C,N_a)
\tkzDrawPoints[new](T_a,T_b,T_c)
\tkzLabelPoints[below left](A)
\tkzLabelPoints[below](N_a,B)
\tkzLabelPoints[above](C)
\tkzLabelPoints[new,below left](T_b)
\tkzLabelPoints[new,below right](T_c)
\tkzLabelPoints[new,right=6pt](T_a)
\tkzMarkRightAngles[fill=gray!15](J_a,T_a,B
  J_b,T_b,C J_c,T_c,A)
\end{tikzpicture}

```

### 15.3.5. Option orthic

Given a triangle  $ABC$ , the triangle  $H_A H_B H_C$  whose vertices are endpoints of the altitudes from each of the vertices of  $ABC$  is called the orthic triangle, or sometimes the altitude triangle. The three lines  $AH_A$ ,  $BH_B$ , and  $CH_C$  are concurrent at the orthocenter  $H$  of  $ABC$ .



```

\begin{tikzpicture}[scale=.75]
\tkzDefPoints{1/5/A,0/0/B,7/0/C}
\tkzDefSpcTriangle[orthic](A,B,C){H_A,H_B,H_C}
\tkzDefTriangleCenter[ortho](B,C,A)
\tkzGetPoint{H}
\tkzDefPointWith[orthogonal,normed](H_A,B)
\tkzGetPoint{a}
\tkzDrawSegments[new](A,H_A B,H_B C,H_C)
\tkzMarkRightAngles[fill=gray!20,
  opacity=.5](A,H_A,C B,H_B,A C,H_C,A)
\tkzDrawPolygon[fill=teal!20,opacity=.3](A,B,C)
\tkzDrawPoints(A,B,C)
\tkzDrawPoints[new](H_A,H_B,H_C)
\tkzDrawPolygon[new,fill=orange!20,
  opacity=.3](H_A,H_B,H_C)
\tkzLabelPoints(C)
\tkzLabelPoints[left](B)
\tkzLabelPoints[above](A)
\tkzLabelPoints[new](H_A)
\tkzLabelPoints[new,above left](H_C)
\tkzLabelPoints[new,above right](H_B,H)
\end{tikzpicture}


```

### 15.3.6. Option feuerbach

The Feuerbach triangle is the triangle formed by the three points of tangency of the nine-point circle with the excircles.

Weisstein, Eric W. "Feuerbach triangle" From MathWorld—A Wolfram Web Resource.

The points of tangency define the Feuerbach triangle.




```
\begin{tikzpicture}[scale=1]
  \tkzDefPoint(0,0){A}
  \tkzDefPoint(3,0){B}
  \tkzDefPoint(0.5,2.5){C}
  \tkzDefCircle[euler](A,B,C) \tkzGetPoint{N}
  \tkzDefSpcTriangle[feuerbach,
    name=F](A,B,C){_a,_b,_c}
  \tkzDefSpcTriangle[excentral,
    name=J](A,B,C){_a,_b,_c}
  \tkzDefSpcTriangle[extouch,
    name=T](A,B,C){_a,_b,_c}
  \tkzLabelPoints[below left](J_a,J_b,J_c)
  \tkzClipBB \tkzShowBB
  \tkzDrawCircle[purple](N,F_a)
  \tkzDrawPolygon(A,B,C)
  \tkzDrawPolygon[new](F_a,F_b,F_c)
  \tkzDrawCircles[gray](J_a,F_a J_b,F_b J_c,F_c)
  \tkzDrawPoints[blue](J_a,J_b,J_c,%
    F_a,F_b,F_c,A,B,C)
  \tkzLabelPoints(A,B,F_c)
  \tkzLabelPoints[above](C)
  \tkzLabelPoints[right](F_a)
  \tkzLabelPoints[left](F_b)
\end{tikzpicture}
```

### 15.3.7. Option tangential

The tangential triangle is the triangle  $T_a T_b T_c$  formed by the lines tangent to the circumcircle of a given triangle ABC at its vertices. It is therefore antipedal triangle of ABC with respect to the circumcenter O.

Weisstein, Eric W. "Tangential Triangle." From MathWorld—A Wolfram Web Resource.




```
\begin{tikzpicture}[scale=.5,rotate=80]
  \tkzDefPoints{0/0/A,6/0/B,1.8/4/C}
  \tkzDefSpcTriangle[tangential,
    name=T](A,B,C){_a,_b,_c}
  \tkzDrawPolygon(A,B,C)
  \tkzDrawPolygon[new](T_a,T_b,T_c)
  \tkzDrawPoints(A,B,C)
  \tkzDrawPoints[new](T_a,T_b,T_c)
  \tkzDefCircle[circum](A,B,C)
  \tkzGetPoint{O}
  \tkzDrawCircle(O,A)
  \tkzLabelPoints(A)
  \tkzLabelPoints[above](B)
  \tkzLabelPoints[left](C)
  \tkzLabelPoints[new](T_b,T_c)
  \tkzLabelPoints[new,left](T_a)
\end{tikzpicture}
```

## 15.3.8. Option euler


The Euler triangle of a triangle  $ABC$  is the triangle  $E_A E_B E_C$  whose vertices are the midpoints of the segments joining the orthocenter  $H$  with the respective vertices. The vertices of the triangle are known as the Euler points, and lie on the nine-point circle.

Weisstein, Eric W. "Euler Triangle." From MathWorld—A Wolfram Web Resource.



```
\begin{tikzpicture}[rotate=90,scale=1.25]
\tkzDefPoints{0/0/A,6/0/B,0.8/4/C}
\tkzDefSpcTriangle[medial,
name=M](A,B,C){_A,_B,_C}
\tkzDefTriangleCenter[euler](A,B,C)
\tkzGetPoint{N} % I= N nine points
\tkzDefTriangleCenter[ortho](A,B,C)
\tkzGetPoint{H}
\tkzDefMidPoint(A,H) \tkzGetPoint{E_A}
\tkzDefMidPoint(C,H) \tkzGetPoint{E_C}
\tkzDefMidPoint(B,H) \tkzGetPoint{E_B}
\tkzDefSpcTriangle[ortho,name=H](A,B,C){_A,_B,_C}
\tkzDrawPolygon(A,B,C)
\tkzDrawCircle(N,E_A)
\tkzDrawSegments[new](A,H_A B,H_B C,H_C)
\tkzDrawPoints(A,B,C,N,H)
\tkzDrawPoints[red](M_A,M_B,M_C)
\tkzDrawPoints[blue](H_A,H_B,H_C)
\tkzDrawPoints[green](E_A,E_B,E_C)
\tkzAutoLabelPoints[center=N,font=\scriptsize]%
(A,B,C,M_A,M_B,M_C,H_A,H_B,H_C,E_A,E_B,E_C)
\tkzLabelPoints[font=\scriptsize](H,N)
\tkzMarkSegments[mark=s|,size=3pt,
color=blue,line width=1pt](B,E_B E_B,H)
\tkzDrawPolygon[color=cyan](M_A,M_B,M_C)
\end{tikzpicture}
```

## 15.3.9. Option euler and Option orthic






```

\begin{tikzpicture}[scale=1.25]
\tkzDefPoints{0/0/A,6/0/B,0.8/4/C}
\tkzDefSpcTriangle[euler,name=E](A,B,C){a,b,c}
\tkzDefSpcTriangle[orthic,name=H](A,B,C){a,b,c}
\tkzDefExCircle(A,B,C) \tkzGetPoints{I}{i}
\tkzDefExCircle(C,A,B) \tkzGetPoints{J}{j}
\tkzDefExCircle(B,C,A) \tkzGetPoints{K}{k}
\tkzDrawPoints[orange](I,J,K)
\tkzLabelPoints[font=\scriptsize](A,B,C,I,J,K)
\tkzClipBB
\tkzInterLC(I,C)(I,i) \tkzGetSecondPoint{Fc}
\tkzInterLC(J,B)(J,j) \tkzGetSecondPoint{Fb}
\tkzInterLC(K,A)(K,k) \tkzGetSecondPoint{Fa}
\tkzDrawLines[add=1.5 and 1.5](A,B A,C B,C)
\tkzDefCircle[euler](A,B,C) \tkzGetPoints{E}{e}
\tkzDrawCircle[orange](E,e)
\tkzDrawSegments[orange](E,I E,J E,K)
\tkzDrawSegments[dashed](A,Ha B,Hb C,Hc)
\tkzDrawCircles(J,j I,i K,k)
\tkzDrawPoints(A,B,C)
\tkzDrawPoints[orange](E,I,J,K,Ha,Hb,Hc,Ea,Eb,Ec,Fa,Fb,Fc)
\tkzLabelPoints[font=\scriptsize](E,Ea,Eb,Ec,Ha,Hb,Hc,Fa,Fb,Fc)
\end{tikzpicture}

```

### 15.3.10. Option symmedial

The symmedial triangle  $K_A K_B K_C$  is the triangle whose vertices are the intersection points of the symmedians with the reference triangle  $ABC$ .



```

\begin{tikzpicture}
\tkzDefPoint(0,0){A}
\tkzDefPoint(5,0){B}
\tkzDefPoint(.75,4){C}
\tkzDefTriangleCenter[symmedian](A,B,C)\tkzGetPoint{K}
\tkzDefSpcTriangle[symmedial,name=K_](A,B,C){A,B,C}
\tkzDrawPolygon(A,B,C)
\tkzDrawSegments[new](A,K_A B,K_B C,K_C)
\tkzDrawPoints(A,B,C,K,K_A,K_B,K_C)
\tkzLabelPoints(A,B,K,K_C)
\tkzLabelPoints[above](C)
\tkzLabelPoints[right](K_A)
\tkzLabelPoints[left](K_B)
\end{tikzpicture}

```


### 15.4. Permutation of two points of a triangle

<code>\tkzPermute(&lt;pt1,pt2,pt3&gt;)</code>		
arguments	example	explanation
<code>(pt1,pt2,pt3)</code>	<code>\tkzPermute(A,B,C)</code>	$A, \widehat{B,A,C}$ are unchanged, $B, C$ exchange their position
<i>The triangle is unchanged.</i>		

## 15.4.1. Modification of the school triangle

This triangle is constructed from the segment  $[AB]$  on  $[A, x]$ .

If we want the segment  $[AC]$  to be on  $[A, x]$ , we just have to swap  $B$  and  $C$ .



```
\begin{tikzpicture}
\tkzDefPoints{0/0/A,4/0/B,6/0/x}
\tkzDefTriangle[school](A,B)
\tkzGetPoint{C}
\tkzPermute(A,B,C)
\tkzDrawSegments(A,B C,x)
\tkzDrawSegments(A,C B,C)
\tkzDrawPoints(A,B,C)
\tkzLabelPoints(A,C,x)
\tkzLabelPoints[above](B)
\tkzMarkRightAngles(C,B,A)
\end{tikzpicture}
```

Remark: Only the first point is unchanged. The order of the last two parameters is not important.

## 16. Definition of polygons

## 16.1. Defining the points of a square

We have seen the definitions of some triangles. Let us look at the definitions of some quadrilaterals and regular polygons.

```
\tkzDefSquare(<pt1,pt2>)
```

The square is defined in the forward direction. From two points, two more points are obtained such that the four taken in order form a square. The square is defined in the forward direction.


The results are in `tkzFirstPointResult` and `tkzSecondPointResult`.

We can rename them with `\tkzGetPoints`.

Arguments	example	explanation
<code>&lt;pt1,pt2&gt;</code>	<code>\tkzDefSquare(&lt;A,B&gt;)</code>	The square is defined in the direct direction.


16.1.1. Using `\tkzDefSquare` with two points

Note the inversion of the first two points and the result.




```
\begin{tikzpicture}[scale=.5]
\tkzDefPoint(0,0){A} \tkzDefPoint(3,0){B}
\tkzDefSquare(A,B)
\tkzDrawPolygon[new](A,B,tkzFirstPointResult,%
tkzSecondPointResult)
\tkzDefSquare(B,A)
\tkzDrawPolygon(B,A,tkzFirstPointResult,%
tkzSecondPointResult)
\end{tikzpicture}
```

We may only need one point to draw an isosceles right-angled triangle so we use `\tkzGetFirstPoint` or `\tkzGetSecondPoint`.

16.1.2. Use of `\tkzDefSquare` to obtain an isosceles right-angled triangle

```
\begin{tikzpicture}[scale=1]
  \tkzDefPoint(0,0){A}
  \tkzDefPoint(3,0){B}
  \tkzDefSquare(A,B) \tkzGetFirstPoint{C}
  \tkzDrawSegment(A,B)
  \tkzDrawSegments[new] (A,C B,C)
  \tkzMarkRightAngles(A,B,C)
  \tkzDrawPoints(A,B) \tkzDrawPoint[new] (C)
  \tkzLabelPoints(A,B)
  \tkzLabelPoints[new,above] (C)
\end{tikzpicture}
```

16.1.3. Pythagorean Theorem and `\tkzDefSquare`

```
\begin{tikzpicture}[scale=.5]
  \tkzDefPoint(0,0){C}
  \tkzDefPoint(4,0){A}
  \tkzDefPoint(0,3){B}
  \tkzDefSquare(B,A)\tkzGetPoints{E}{F}
  \tkzDefSquare(A,C)\tkzGetPoints{G}{H}
  \tkzDefSquare(C,B)\tkzGetPoints{I}{J}
  \tkzDrawPolygon(A,B,C)
  \tkzDrawPolygon(A,C,G,H)
  \tkzDrawPolygon(C,B,I,J)
  \tkzDrawPolygon(B,A,E,F)
  \tkzLabelSegment(A,C){$a$}
  \tkzLabelSegment[right] (C,B){$b$}
  \tkzLabelSegment[swap] (A,B){$c$}
\end{tikzpicture}
```

## 16.2. Defining the points of a rectangle

.

`\tkzDefRectangle( $\langle pt1, pt2 \rangle$ )`


The rectangle is defined in the forward direction. From two points, two more points are obtained such that the four taken in order form a rectangle. The two points passed in arguments are the ends of a diagonal of the rectangle. The sides are parallel to the axes.

The results are in `tkzFirstPointResult` and `tkzSecondPointResult`.

We can rename them with `\tkzGetPoints`.

Arguments	example	explanation
$\langle pt1, pt2 \rangle$	<code>\tkzDefRectangle(<math>\langle A, B \rangle</math>)</code>	The rectangle is defined in the direct direction.

## 16.2.1. Example of a rectangle definition



```
\begin{tikzpicture}
  \tkzDefPoints{0/0/A,5/2/C}
  \tkzDefRectangle(A,C) \tkzGetPoints{B}{D}
  \tkzDrawPolygon[fill=teal!15] (A,...,D)
\end{tikzpicture}
```

## 16.3. Definition of parallelogram

Defining the points of a parallelogram. It is a matter of completing three points in order to obtain a parallelogram.


<code>\tkzDefParallelogram(&lt;pt1,pt2,pt3&gt;)</code>
--

arguments	default	definition
<code>(&lt;pt1,pt2,pt3&gt;)</code>	no default	Three points are necessary

From three points, another point is obtained such that the four taken in order form a parallelogram. The result is in `tkzPointResult`.

We can rename it with the name `\tkzGetPoint...`

## 16.3.1. Example of a parallelogram definition



```
\begin{tikzpicture}[scale=1]
\tkzDefPoints{0/0/A,3/0/B,4/2/C}
\tkzDefParallelogram(A,B,C)
% or \tkzDefPointWith[colinear= at C](B,A)
\tkzGetPoint{D}
\tkzDrawPolygon(A,B,C,D)
\tkzLabelPoints(A,B)
\tkzLabelPoints[above right](C,D)
\tkzDrawPoints(A,...,D)
\end{tikzpicture}
```

## 16.4. The golden rectangle

<code>\tkzDefGoldenRectangle(&lt;point,point&gt;)</code>
--

The macro determines a rectangle whose size ratio is the number  $\Phi$ .


The created points are in `tkzFirstPointResult` and `tkzSecondPointResult`.

They can be obtained with the macro `\tkzGetPoints`. The following macro is used to draw the rectangle.

arguments	example	explanation
<code>(&lt;pt1,pt2&gt;)</code>	<code>(&lt;A,B&gt;)</code>	If C and D are created then $AB/BC = \Phi$ .

`\tkzDefGoldenRectangle` or `\tkzDefGoldRectangle`


## 16.4.1. Golden Rectangles



```
\begin{tikzpicture}[scale=.6]
\tkzDefPoint(0,0){A} \tkzDefPoint(8,0){B}
\tkzDefGoldRectangle(A,B) \tkzGetPoints{C}{D}
\tkzDefGoldRectangle(B,C) \tkzGetPoints{E}{F}
\tkzDefGoldRectangle(C,E) \tkzGetPoints{G}{H}
\tkzDrawPolygon(A,B,C,D)
\tkzDrawSegments(E,F G,H)
\end{tikzpicture}
```

## 16.4.2. Construction of the golden rectangle

Without the previous macro here is how to get the golden rectangle.



```
\begin{tikzpicture}[scale=.5]
\tkzDefPoint(0,0){A}
\tkzDefPoint(8,0){B}
\tkzDefMidPoint(A,B)
\tkzGetPoint{I}
\tkzDefSquare(A,B)\tkzGetPoints{C}{D}
\tkzInterLC(A,B)(I,C)\tkzGetPoints{G}{E}
\tkzDefPointWith[colinear= at C](E,B)
\tkzGetPoint{F}
\tkzDefPointBy[projection=onto D--C](E)
\tkzGetPoint{H}
\tkzDrawArc[style=dashed](I,E)(D)
\tkzDrawPolygon(A,B,C,D)
\tkzDrawPoints(C,D,E,F,H)
\tkzLabelPoints(A,B,C,D,E,F,H)
\tkzLabelPoints[above](C,D,F,H)
\tkzDrawSegments[style=dashed,color=gray](E,F)(C,F)(B,E)(F,H)(H,C)(E,H)
\end{tikzpicture}
```

## 16.5. Regular polygon


`\tkzDefRegPolygon[⟨local options⟩](⟨pt1,pt2⟩)`

From the number of sides, depending on the options, this macro determines a regular polygon according to its center or one side.

arguments	example	explanation
<code>(⟨pt1,pt2⟩)</code>	<code>(⟨O,A⟩)</code>	with option center, O is the center of the polygon.
<code>(⟨pt1,pt2⟩)</code>	<code>(⟨A,B⟩)</code>	with option side, [AB] is a side.


options	default	example
name	P	The vertices are named P1,P2,...
sides	5	number of sides.
center	center	The first point is the center.
side	center	The two points are vertices.
Options TikZ	...	

## 16.5.1. Option center



```
\begin{tikzpicture}
\tkzDefPoints{0/0/P0,0/0/Q0,2/0/P1}
\tkzDefMidPoint(P0,P1)\tkzGetPoint{Q1}
\tkzDefRegPolygon[center,sides=7](P0,P1)
\tkzDefMidPoint(P1,P2)\tkzGetPoint{Q1}
\tkzDefRegPolygon[center,sides=7,name=Q](P0,Q1)
\tkzFillPolygon[teal!20](Q0,Q1,P2,Q2)
\tkzDrawPolygon(P1,P...,P7)
\foreach \j in {1,...,7} {
\tkzDrawSegment[black](P0,Q\j)}
\end{tikzpicture}
```

## 16.5.2. Option side



```
\begin{tikzpicture}[scale=1]
  \tkzDefPoints{-4/0/A, -1/0/B}
  \tkzDefRegPolygon[side,sides=5,name=P](A,B)
  \tkzDrawPolygon[thick](P1,P...,P5)
\end{tikzpicture}
```

## 17. Circles

Among the following macros, one will allow you to draw a circle, which is not a real feat. To do this, you will need to know the center of the circle and either the radius of the circle or a point on the circumference. It seemed to me that the most frequent use was to draw a circle with a given center passing through a given point. This will be the default method, otherwise you will have to use the `R` option. There are a large number of special circles, for example the circle circumscribed by a triangle.

- I have created a first macro `\tkzDefCircle` which allows, according to a particular circle, to retrieve its center and the measurement of the radius in cm. This recovery is done with the macros `\tkzGetPoint` and `\tkzGetLength`;
- then a macro `\tkzDrawCircle`;
- then a macro that allows you to color in a disc, but without drawing the circle `\tkzFillCircle`;
- sometimes, it is necessary for a drawing to be contained in a disk, this is the role assigned to `\tkzClipCircle`;
- it finally remains to be able to give a label to designate a circle and if several possibilities are offered, we will see here `\tkzLabelCircle`.

17.1. Characteristics of a circle: `\tkzDefCircle`

This macro allows you to retrieve the characteristics (center and radius) of certain circles.

```
\tkzDefCircle[⟨local options⟩](⟨A,B⟩) or (⟨A,B,C⟩)
```



Attention the arguments are lists of two or three points. This macro is either used in partnership with `\tkzGetPoints` to obtain the center and a point on the circle, or by using `\tkzFirstPointResult` and `\tkzSecondPointResult` if it is not necessary to keep the results. You can also use `\tkzGetLength` to get the radius.

arguments	example	explanation
<code>(⟨pt1,pt2⟩)</code> or <code>(⟨pt1,pt2,pt3⟩)</code>	<code>(⟨A,B⟩)</code>	<code>[AB]</code> is radius <code>A</code> is the center


  

options	default	definition
<code>R</code>	<code>circum</code>	circle characterized by a center and a radius
<code>diameter</code>	<code>circum</code>	circle characterized by two points defining a diameter
<code>circum</code>	<code>circum</code>	circle circumscribed of a triangle
<code>in</code>	<code>circum</code>	incircle a triangle
<code>ex</code>	<code>circum</code>	excircle of a triangle
<code>euler or nine</code>	<code>circum</code>	Euler's Circle
<code>spieker</code>	<code>circum</code>	Spieker Circle
<code>apollonius</code>	<code>circum</code>	circle of Apollonius
<code>orthogonal from</code>	<code>circum</code>	<code>[orthogonal from = A ](O,M)</code>
<code>orthogonal through</code>	<code>circum</code>	<code>[orthogonal through = A and B](O,M)</code>
<code>K</code>	<code>1</code>	coefficient used for a circle of Apollonius

*In the following examples, I draw the circles with a macro not yet presented. You may only need the center and a point on the circle.*

## 17.1.1. Example with option R


We obtain with the macro `\tkzGetPoint` a point of the circle which is the East pole.



```
\begin{tikzpicture}[scale=1]
  \tkzDefPoint(3,3){C}
  \tkzDefPoint(5,5){A}
  \tkzCalcLength(A,C) \tkzGetLength{rAC}
  \tkzDefCircle[R](C,\rAC) \tkzGetPoint{B}
  \tkzDrawCircle(C,B)
  \tkzDrawSegment(C,A)
  \tkzLabelSegment[above left](C,A){$2\sqrt{2}$}
  \tkzDrawPoints(A,B,C)
  \tkzLabelPoints(A,C,B)
\end{tikzpicture}
```


## 17.1.2. Example with option diameter

It is simpler here to search directly for the middle of [AB]. The result is the center and if necessary



```
\begin{tikzpicture}
  \tkzDefPoint(0,0){O}
  \tkzDefPoint(2,2){B}
  \tkzDefCircle[diameter](O,B) \tkzGetPoint{A}
  \tkzDrawCircle(A,B)
  \tkzDrawPoints(O,A,B)
  \tkzDrawSegment(O,B)
  \tkzLabelPoints(O,A,B)
  \tkzLabelSegment[above left](O,A){$\sqrt{2}$}
  \tkzLabelSegment[above left](A,B){$\sqrt{2}$}
  \tkzMarkSegments[mark=s||](O,A A,B)
\end{tikzpicture}
```

## 17.1.3. Circles inscribed and circumscribed for a given triangle




```
\begin{tikzpicture}[scale=.75]
  \tkzDefPoint(2,2){A} \tkzDefPoint(5,-2){B}
  \tkzDefPoint(1,-2){C}
  \tkzDefCircle[in](A,B,C)
  \tkzGetPoints{I}{x}
  \tkzDefCircle[circum](A,B,C)
  \tkzGetPoint{K}
  \tkzDrawCircles[new](I,x K,A)
  \tkzLabelPoints[below](B,C)
  \tkzLabelPoints[above left](A,I,K)
  \tkzDrawPolygon(A,B,C)
  \tkzDrawPoints(A,B,C,I,K)
\end{tikzpicture}
```

## 17.1.4. Example with option ex

We want to define an excircle of a triangle relatively to point C






```
\begin{tikzpicture}[scale=.75]
\tkzDefPoints{ 0/0/A,4/0/B,0.8/4/C}
\tkzDefCircle[ex] (B,C,A)
\tkzGetPoints{J_c}{h}
\tkzDefPointBy[projection=onto A--C ](J_c)
\tkzGetPoint{X_c}
\tkzDefPointBy[projection=onto A--B ](J_c)
\tkzGetPoint{Y_c}
\tkzDefCircle[in] (A,B,C)
\tkzGetPoints{I}{y}
\tkzDrawCircles[color=lightgray](J_c,h I,y)
\tkzDefPointBy[projection=onto A--C ](I)
\tkzGetPoint{F}
\tkzDefPointBy[projection=onto A--B ](I)
\tkzGetPoint{D}
\tkzDrawPolygon(A,B,C)
\tkzDrawLines[add=0 and 1.5](C,A C,B)
\tkzDrawSegments(J_c,X_c I,D I,F J_c,Y_c)
\tkzMarkRightAngles(A,F,I B,D,I J_c,X_c,A%
J_c,Y_c,B)
\tkzDrawPoints(B,C,A,I,D,F,X_c,J_c,Y_c)
\tkzLabelPoints(B,A,J_c,I,D)
\tkzLabelPoints[above](Y_c)
\tkzLabelPoints[left](X_c)
\tkzLabelPoints[above left](C)
\tkzLabelPoints[left](F)
\end{tikzpicture}
```


#### 17.1.5. Euler's circle for a given triangle with option euler

We verify that this circle passes through the middle of each side.



```
\begin{tikzpicture}[scale=.75]
\tkzDefPoint(5,3.5){A}
\tkzDefPoint(0,0){B} \tkzDefPoint(7,0){C}
\tkzDefCircle[euler] (A,B,C)
\tkzGetPoints{E}{e}
\tkzDefSpcTriangle[medial] (A,B,C){M_a,M_b,M_c}
\tkzDrawCircle[new] (E,e)
\tkzDrawPoints(A,B,C,E,M_a,M_b,M_c)
\tkzDrawPolygon(A,B,C)
\tkzLabelPoints[below](B,C)
\tkzLabelPoints[left](A,E)
\end{tikzpicture}
```


## 17.1.6. Apollonius circles for a given segment option apollonius



```
\begin{tikzpicture}[scale=0.75]
  \tkzDefPoint(0,0){A}
  \tkzDefPoint(4,0){B}
  \tkzDefCircle[apollonius,K=2](A,B)
  \tkzGetPoints{K1}{x}
  \tkzDrawCircle[color = teal!50!black,
    fill=teal!20,opacity=.4](K1,x)
  \tkzDefCircle[apollonius,K=3](A,B)
  \tkzGetPoints{K2}{y}
  \tkzDrawCircle[color=orange!50,
    fill=orange!20,opacity=.4](K2,y)
  \tkzLabelPoints[below](A,B,K1,K2)
  \tkzDrawPoints(A,B,K1,K2)
  \tkzDrawLine[add=.2 and 1](A,B)
\end{tikzpicture}
```

## 17.1.7. Circles exinscribed to a given triangle option ex


You can also get the center and the projection of it on one side of the triangle.  
with `\tkzGetFirstPoint{Jb}` and `\tkzGetSecondPoint{Tb}`.



```
\begin{tikzpicture}[scale=.6]
  \tkzDefPoint(0,0){A}
  \tkzDefPoint(3,0){B}
  \tkzDefPoint(1,2.5){C}
  \tkzDefCircle[ex](A,B,C) \tkzGetPoints{I}{i}
  \tkzDefCircle[ex](C,A,B) \tkzGetPoints{J}{j}
  \tkzDefCircle[ex](B,C,A) \tkzGetPoints{K}{k}
  \tkzDefCircle[in](B,C,A) \tkzGetPoints{O}{o}
  \tkzDrawCircles[new](J,j I,i K,k O,o)
  \tkzDrawLines[add=1.5 and 1.5](A,B A,C B,C)
  \tkzDrawPolygon[purple](I,J,K)
  \tkzDrawSegments[new](A,K B,J C,I)
  \tkzDrawPoints(A,B,C)
  \tkzDrawPoints[new](I,J,K)
  \tkzLabelPoints(A,B,C,I,J,K)
\end{tikzpicture}
```

## 17.1.8. Spieker circle with option spieker

The incircle of the medial triangle  $M_a M_b M_c$  is the Spieker circle:



```
\begin{tikzpicture}[scale=1.25]
  \tkzDefPoints{ 0/0/A,4/0/B,0.8/4/C}
  \tkzDefSpcTriangle[medial](A,B,C){M_a,M_b,M_c}
  \tkzDefTriangleCenter[spieker](A,B,C)
  \tkzGetPoint{S_p}
  \tkzDrawPolygon(A,B,C)
  \tkzDrawPolygon[cyan](M_a,M_b,M_c)
  \tkzDrawPoints(B,C,A)
  \tkzDefCircle[spieker](A,B,C)
  \tkzDrawPoints[new](M_a,M_b,M_c,S_p)
  \tkzDrawCircle[new](tkzFirstPointResult,%
    tkzSecondPointResult)
  \tkzLabelPoints[right](M_a)
  \tkzLabelPoints[left](M_b)
  \tkzLabelPoints[below](A,B,M_c,S_p)
  \tkzLabelPoints[above](C)
\end{tikzpicture}
```

## 17.2. Projection of excenters


```
\tkzDefProjExcenter[⟨local options⟩](⟨A,B,C⟩)(⟨a,b,c⟩){⟨X,Y,Z⟩}
```

Each excenter has three projections on the sides of the triangle ABC. We can do this with one macro

```
\tkzDefProjExcenter[name=J](A,B,C)(a,b,c){Y,Z,X}.
```

options	default	definition
name	no default	used to name the vertices
arguments	default	definition
(pt1= $\alpha_1$ ,pt2= $\alpha_2$ ,...)	no default	Each point has a assigned weight

## 17.2.1. Excircles




```

\begin{tikzpicture}[scale=.6]
\tikzset{line style/.append style={line width=.2pt}}
\tikzset{label style/.append style={color=teal,font=\footnotesize}}
\tikzDefPoints{0/0/A,5/0/B,0.8/4/C}
\tikzDefSpcTriangle[excentral,name=J](A,B,C){a,b,c}
\tikzDefSpcTriangle[intouch,name=I](A,B,C){a,b,c}
\tikzDefProjExcenter[name=J](A,B,C)(a,b,c){X,Y,Z}
\tikzDefCircle[in](A,B,C)\tkzGetPoint{I}\tkzGetSecondPoint{T}
\tikzDrawCircles[red](Ja,Xa Jb,Yb Jc,Zc)
\tikzDrawCircle(I,T)
\tikzDrawPolygon[dashed,color=blue](Ja,Jb,Jc)
\tikzDrawLines[add=1.5 and 1.5](A,C A,B B,C)
\tikzDrawSegments(Ja,Xa Ja,Ya Ja,Za
                  Jb,Xb Jb,Yb Jb,Zb
                  Jc,Xc Jc,Yc Jc,Zc
                  I,Ia I,Ib I,Ic)
\tikzMarkRightAngles[size=.2,fill=gray!15](Ja,Za,B Ja,Xa,B Ja,Ya,C Jb,Yb,C)
\tikzMarkRightAngles[size=.2,fill=gray!15](Jb,Zb,B Jb,Xb,C Jc,Yc,A Jc,Zc,B)
\tikzMarkRightAngles[size=.2,fill=gray!15](Jc,Xc,C I,Ia,B I,Ib,C I,Ic,A)
\tikzDrawSegments[blue](Jc,C Ja,A Jb,B)
\tikzDrawPoints(A,B,C,Xa,Xb,Xc,Ja,Jb,Jc,Ia,Ib,Ic,Ya,Yb,Yc,Za,Zb,Zc)
\tikzLabelPoints(A,Ya,Yb,Ja,I)
\tikzLabelPoints[left](Jb,Ib,Yc)
\tikzLabelPoints[below](Zb,Ic,Jc,B,Za,Xa)
\tikzLabelPoints[above right](C,Zc,Yb)
\tikzLabelPoints[right](Xb,Ia,Xc)
\end{tikzpicture}

```

### 17.2.2. Orthogonal from

Orthogonal circle of given center. `\tkzGetPoints{z1}{z2}` gives two points of the circle.




```

\begin{tikzpicture}[scale=.75]
\tikzDefPoints{0/0/0,1/0/A}
\tikzDefPoints{1.5/1.25/B,-2/-3/C}
\tikzDefCircle[orthogonal from=B](O,A)
\tikzGetPoints{z1}{z2}
\tikzDefCircle[orthogonal from=C](O,A)
\tikzGetPoints{t1}{t2}
\tikzDrawCircle(O,A)
\tikzDrawCircles[new](B,z1 C,t1)
\tikzDrawPoints(t1,t2,C)
\tikzDrawPoints(z1,z2,O,A,B)
\tikzLabelPoints[right](O,A,B,C)
\end{tikzpicture}

```

### 17.2.3. Orthogonal through

Orthogonal circle passing through two given points.



```
\begin{tikzpicture}[scale=1]
  \tkzDefPoint(0,0){O}
  \tkzDefPoint(1,0){A}
  \tkzDrawCircle(O,A)
  \tkzDefPoint(-1.5,-1.5){z1}
  \tkzDefPoint(1.5,-1.25){z2}
  \tkzDefCircle[orthogonal through=z1 and z2](O,A)
  \tkzGetPoint{c}
  \tkzDrawCircle[new](tkzPointResult,z1)
  \tkzDrawPoints[new](O,A,z1,z2,c)
  \tkzLabelPoints[right](O,A,z1,z2,c)
\end{tikzpicture}
```

### 17.3. Definition of circle by transformation; `\tkzDefCircleBy`

These transformations are:

- translation;
- homothety;
- orthogonal reflection or symmetry;
- central symmetry;
- orthogonal projection;
- rotation (degrees);
- inversion.

The choice of transformations is made through the options. The macro is `\tkzDefCircleBy` and the other for the transformation of a list of points `\tkzDefCirclesBy`. For example, we'll write:

```
\tkzDefCircleBy[translation= from A to A'](O,M)
```

O is the center and M is a point on the circle. The image is a circle. The new center is `tkzFirstPointResult` and `tkzSecondPointResult` is a point on the new circle. You can get the results with the macro `\tkzGetPoints`.


`\tkzDefCircleBy[local options](pt1,pt2)`

The argument is a couple of points. The results is a couple of points. If you want to keep these points then the macro `\tkzGetPoints{O'}{M'}` allows you to assign the name O' to the center and M' to the point on the circle.

arguments	definition	examples
pt1,pt2	existing points	(O,M)
options	examples	
translation	= from #1 to #2	[translation=from A to B](O,M)
homothety	= center #1 ratio #2	[homothety=center A ratio .5](O,M)
reflection	= over #1--#2	[reflection=over A--B](O,M)
symmetry	= center #1	[symmetry=center A](O,M)
projection	= onto #1--#2	[projection=onto A--B](O,M)
rotation	= center #1 angle #2	[rotation=center O angle 30](O,M)
inversion	= center #1 through #2	[inversion =center O through A](O,M)


*The image is only defined and not drawn.*

## 17.3.1. Translation




```
\begin{tikzpicture}[>=latex]
\tkzDefPoint(0,0){A} \tkzDefPoint(3,1){B}
\tkzDefPoint(3,2){C} \tkzDefPoint(4,3){D}
\tkzDefCircleBy[translation= from B to A](C,D)
\tkzGetPoints{C'}{D'}
\tkzDrawPoints[teal](A,B,C,D,C',D')
\tkzDrawSegments[orange,->](A,B)
\tkzDrawCircles(C,D C',D')
\tkzLabelPoints[color=teal](A,B,C,C')
\tkzLabelPoints[color=teal,above](D,D')
\end{tikzpicture}
```

## 17.3.2. Reflection (orthogonal symmetry)




```
\begin{tikzpicture}[>=latex]
\tkzDefPoint(0,0){A} \tkzDefPoint(3,1){B}
\tkzDefPoint(3,2){C} \tkzDefPoint(4,3){D}
\tkzDefCircleBy[reflection = over A--B](C,D)
\tkzGetPoints{C'}{D'}
\tkzDrawPoints[teal](A,B,C,D,C',D')
\tkzDrawLine[add =0 and 1][orange](A,B)
\tkzDrawCircles(C,D C',D')
\tkzLabelPoints[color=teal](A,B,C,C')
\tkzLabelPoints[color=teal,right](D,D')
\end{tikzpicture}
```

## 17.3.3. Homothety




```
\begin{tikzpicture}[scale=1.2]
\tkzDefPoint(0,0){A} \tkzDefPoint(3,1){B}
\tkzDefPoint(3,2){C} \tkzDefPoint(4,3){D}
\tkzDefCircleBy[homothety=center A ratio .5](C,D)
\tkzGetPoints{C'}{D'}
\tkzDrawPoints[teal](A,C,D,C',D')
\tkzDrawCircles(C,D C',D')
\tkzLabelPoints[color=teal](A,C,C')
\tkzLabelPoints[color=teal,right](D,D')
\end{tikzpicture}
```

## 17.3.4. Symmetry




```
\begin{tikzpicture}[scale=1]
\tkzDefPoint(3,1){B}
\tkzDefPoint(3,2){C} \tkzDefPoint(4,3){D}
\tkzDefCircleBy[symmetry=center B](C,D)
\tkzGetPoints{C'}{D'}
\tkzDrawPoints[teal](B,C,D,C',D')
\tkzDrawLines[orange](C,C' D,D')
\tkzDrawCircles(C,D C',D')
\tkzLabelPoints[color=teal](C,C')
\tkzLabelPoints[color=teal,above](D)
\tkzLabelPoints[color=teal,below](D')
\end{tikzpicture}
```

## 17.3.5. Rotation



```
\begin{tikzpicture}[scale=0.5]
\tkzDefPoint(3,-1){B}
\tkzDefPoint(3,2){C} \tkzDefPoint(4,3){D}
\tkzDefCircleBy[rotation=center B angle 90](C,D)
\tkzGetPoints{C'}{D'}
\tkzDrawPoints[teal](B,C,D,C',D')
\tkzLabelPoints[color=teal](B,C,D,C',D')
\tkzDrawCircles(C,D C',D')
\end{tikzpicture}
```

## 17.3.6. Inversion



```
\begin{tikzpicture}[scale=1.5]
\tkzSetUpPoint[size=3,color=red,fill=red!20]
\tkzSetUpStyle[color=purple,ultra thin]{st1}
\tkzSetUpStyle[color=cyan,ultra thin]{st2}
\tkzDefPoint(2,0){A} \tkzDefPoint(3,0){B}
\tkzDefPoint(3,2){C} \tkzDefPoint(4,2){D}
\tkzDefCircleBy[inversion = center B through A](C,D)
\tkzGetPoints{C'}{D'}
\tkzDrawPoints(A,B,C,D,C',D')
\tkzLabelPoints(A,B,C,D,C',D')
\tkzDrawCircles(B,A)
\tkzDrawCircles[st1](C,D)
\tkzDrawCircles[st2](C',D')
\end{tikzpicture}
```

## 18. Intersections

It is possible to determine the coordinates of the points of intersection between two straight lines, a straight line and a circle, and two circles.


The associated commands have no optional arguments and the user must determine the existence of the intersection points himself.



18.1. Intersection of two straight lines `\tkzInterLL`
 $\text{\tkzInterLL}(\langle A,B \rangle)(\langle C,D \rangle)$ 

Defines the intersection point `\tkzPointResult` of the two lines (AB) and (CD). The known points are given in pairs (two per line) in brackets, and the resulting point can be retrieved with the macro `\tkzDefPoint`.

## 18.1.1. Example of intersection between two straight lines



```
\begin{tikzpicture}[rotate=-45,scale=.75]
\tkzDefPoint(2,1){A}
\tkzDefPoint(6,5){B}
\tkzDefPoint(3,6){C}
\tkzDefPoint(5,2){D}
\tkzDrawLines(A,B C,D)
\tkzInterLL(A,B)(C,D)
\tkzGetPoint{I}
\tkzDrawPoints[color=blue](A,B,C,D)
\tkzDrawPoint[color=red](I)
\end{tikzpicture}
```

18.2. Intersection of a straight line and a circle `\tkzInterLC`

As before, the line is defined by a couple of points. The circle is also defined by a couple:

- (O,C) which is a pair of points, the first is the center and the second is any point on the circle.
- (O,r) The r measure is the radius measure.

 $\text{\tkzInterLC}[\langle \text{options} \rangle](\langle A,B \rangle)(\langle O,C \rangle) \text{ or } (\langle O,r \rangle) \text{ or } (\langle O,C,D \rangle)$ 

So the arguments are two couples.


options	default	definition
N	N	(O,C) determines the circle
R	N	(O, 1 ) unit 1 cm
with nodes	N	(O,C,D) CD is a radius
common=pt		pt is common point; <code>\tkzFirstPoint</code> gives the other point
near		<code>\tkzFirstPoint</code> is the closest point to the first point of the line

The macro defines the intersection points I and J of the line (AB) and the center circle O with radius r if they exist; otherwise, an error will be reported in the .log file. **with nodes** avoids you to calculate the radius which is the length of [CD]. If **common** and **near** are not used then `\tkzFirstPoint` is the smallest angle (angle with `\tkzSecondPoint` and the center of the circle).

 $\text{\tkzTestInterLC}(\langle O,A \rangle)(\langle O',B \rangle)$ 

So the arguments are two couples which define a line and a circle with a center and a point on the circle. If there is a non empty intersection between these the line and the circle then the test `\if\tkzFlagLC` gives true.

## 18.2.1. test line-circle intersection




```
\begin{tikzpicture}[scale=1]
  \tkzDefPoints{% x    y    name
    3    /4    /I,
    3    /2    /P,
    0    /2    /La,
    8    /3    /Lb}

  \tkzDrawCircle(I,P)
  \foreach \i in {1,...,3}{%
    \coordinate (Lb) at (8,\i);
    \tkzDrawLine(La,Lb)
    \tkzTestInterLC(La,Lb)(I,P)
    \iftkzFlagLC
      \tkzInterLC(La,Lb)(I,P)
      \tkzGetPoints{a}{b}
      \tkzDrawPoints(a,b)
    \fi
  }
\end{tikzpicture}
```

## 18.2.2. Line-circle intersection


In the following example, the drawing of the circle uses two points and the intersection of the straight line and the circle uses two pairs of points. We will compare the angles  $\widehat{D,E,O}$  and  $\widehat{E,D,O}$ . These angles are in opposite directions. `tkzFirstPoint` is assigned to the point that forms the angle with the smallest measure (counterclockwise direction). The counterclockwise angle  $\widehat{D,E,O}$  has a measure equal to  $360^\circ$  minus the measure of  $\widehat{O,E,D}$ .



```
\begin{tikzpicture}[scale=.75]
  \tkzInit[xmax=5,ymax=4]
  \tkzDefPoint(1,1){O}
  \tkzDefPoint(-2,4){La}
  \tkzDefPoint(5,0){Lb}
  \tkzDefPoint(3,3){C}
  \tkzInterLC(La,Lb)(O,C) \tkzGetPoints{D}{E}
  \tkzMarkAngle[->,size=1.5](E,D,O)
  \tkzDrawPolygons[new](O,D,E)
  \tkzMarkAngle[->,size=1.5](D,E,O)
  \tkzDrawCircle(O,C)
  \tkzDrawPoints[color=teal](O,La,Lb,C)
  \tkzDrawPoints[color=red](D,E)
  \tkzDrawLine(La,Lb)
  \tkzLabelPoints[above right](O,La,Lb,C,D,E)
\end{tikzpicture}
```

## 18.2.3. Line passing through the center option common

This case is special. You cannot compare the angles. In this case, the option `near` must be used. `tkzFirstPoint` is assigned to the point closest to the first point given for the line. Here we want A to be closest to Lb.




```
\begin{tikzpicture}
\tkzDefPoints{% x    y    name
0      /1    /D,
6      /0    /B,
3      /3    /O,
2      /2    /La,
5      /5    /Lb}

\tkzDrawCircle(O,D)
\tkzDrawLine(La,Lb)
\tkzInterLC[near](Lb,La)(O,D)
\tkzGetFirstPoint{A}
\tkzDrawSegments(O,A)
\tkzDrawPoints(O,D,A,La,Lb)
\tkzLabelPoints(O,D,A,La,Lb)
\end{tikzpicture}
```

#### 18.2.4. Line-circle intersection with option common

A special case that we often meet, a point of the line is on the circle and we are looking for the other common point.




```
\begin{tikzpicture}[scale=.5]
\tkzDefPoints{0/0/O,-5/0/A,2/-2/B,0/5/D}
\tkzInterLC[common=A](B,A)(O,D)
\tkzGetFirstPoint{C}
\tkzDrawPoints(O,A,B)
\tkzDrawCircle(O,A)
\tkzDrawLine(A,C)
\tkzDrawPoint(C)
\tkzLabelPoints(A,B,C)
\end{tikzpicture}
```

#### 18.2.5. Line-circle intersection order of points


The idea is to compare the angles formed with the first defining point of the line, a resultant point and the center of the circle. The first point is the one that corresponds to the smallest angle.

As you can see  $\widehat{BCO} < \widehat{BEO}$ . To tell the truth,  $\widehat{BEO}$  is counterclockwise.



```
\begin{tikzpicture}[scale=.5]
\tkzDefPoints{0/0/0,5/1/A,2/2/B,3/1/D}
\tkzInterLC[common=A](B,D)(O,A)\tkzGetPoints{C}{E}
\tkzDrawPoints(O,A,B,D)
\tkzDrawCircle(O,A)\tkzDrawLine(E,C)
\tkzDrawSegments[dashed](B,O)(O,C)
\tkzMarkAngle[->,size=1.5](B,C,O)
\tkzDrawSegments[dashed](O,E)
\tkzMarkAngle[->,size=1.5](B,E,O)
\tkzDrawPoints(C,E)
\tkzLabelPoints[above](O,E)
\tkzLabelPoints[right](A,B,C,D)
\end{tikzpicture}
```


### 18.2.6. Example with \foreach



```
\begin{tikzpicture}[scale=3,rotate=180]
\tkzDefPoint(0,1){J}
\tkzDefPoint(0,0){O}
\foreach \i in {0,-5,-10,...,-90}{
\tkzDefPoint({2.5*cos(\i*pi/180)},%
{1+2.5*sin(\i*pi/180)}){P}
\tkzInterLC[R](P,J)(O,1)\tkzGetPoints{N}{M}
\tkzDrawSegment[color=orange](J,N)
\tkzDrawPoints[red](N)}
\foreach \i in {-90,-95,...,-175,-180}{
\tkzDefPoint({2.5*cos(\i*pi/180)},%
{1+2.5*sin(\i*pi/180)}){P}
\tkzInterLC[R](P,J)(O,1)\tkzGetPoints{N}{M}
\tkzDrawSegment[color=orange](J,M)
\tkzDrawPoints[red](M)}
\end{tikzpicture}
```

### 18.2.7. Line-circle intersection with option near

D is the point closest to b.




```

\begin{tikzpicture}
\tkzDefPoints{Q/Q/A,12/Q/C}
\tkzDefGoldenRatio(A,C)
\tkzDefMidPoint(A,C)
\tkzDefMidPoint(A,B)
\tkzDefMidPoint(B,C)
\tkzDefPointBy[rotation=center O_2 angle 90](C)
\tkzDefPointBy[rotation=center O_1 angle 90](B)
\tkzDefPointBy[rotation=center B angle 90](C)
\tkzInterLC[near](b,B)(O,A)
\tkzInterCC(D,B)(O,C)
\tkzDefPointBy[projection=onto U--V](O_1)
\tkzDefPointBy[projection=onto U--V](O_2)
\tkzDrawPoints(A,B,C,O,O_1,O_2,D,U,V,M,N,b)
\tkzDrawSemiCircles[teal](O,C O_1,B O_2,C)
\tkzDrawSegments(A,C B,D U,V A,D C,D M,B B,N)
\tkzDrawArc(D,U)(V)
\tkzLabelPoints(A,B,C,O,O_1,O_2)
\tkzLabelPoints[above](D,U,V,M,N)
\end{tikzpicture}

```

### 18.2.8. More complex example of a line-circle intersection

Figure from [http://gogeometry.com/problem/p190\\_tangent\\_circle](http://gogeometry.com/problem/p190_tangent_circle)




```

\begin{tikzpicture}[scale=.75]
\tkzDefPoint{Q,Q}{A}
\tkzDefPoint{8,Q}{B}
\tkzDefMidPoint(A,B)
\tkzDefMidPoint(O,B)
\tkzDefLine[tangent from=A](O',B)
\tkzInterLC(A,E)(O,B)
\tkzDefPointBy[projection=onto A--B](D)
\tkzGetPoint{F}
\tkzDrawCircles(O,B O',B)
\tkzDrawSegments(A,D A,B D,F)
\tkzDrawSegments[color=red,line width=1pt,opacity=.4](A,O F,B)
\tkzDrawPoints(A,B,O,O',E,D)
\tkzMarkRightAngle(D,F,B)
\tkzLabelPoints[below right](A,B,O,O',E,D)
\end{tikzpicture}

```

### 18.2.9. Circle defined by a center and a measure, and special cases

Let's look at some special cases like straight lines tangent to the circle.




```
\begin{tikzpicture}[scale=.5]
\tkzDefPoint(0,8){A}      \tkzDefPoint(8,0){B}
\tkzDefPoint(8,8){C}      \tkzDefPoint(4,4){D}
\tkzDefPoint(2,4){E}      \tkzDefPoint(4,2){F}
\tkzDefPoint(8,4){G}
\tkzInterLC(A,C)(D,G)      \tkzGetPoints{I1}{I2}
\tkzInterLC(B,C)(D,G)      \tkzGetPoints{J1}{J2}
\tkzInterLC[near](A,B)(D,G) \tkzGetPoints{K1}{K2}
\tkzInterLC(E,F)(D,G)      \tkzGetPoints{E1}{E2}
\tkzDrawCircle(D,G)
\tkzDrawPoints[color=red](I1,J1,K1,K2,E1,E2)
\tkzDrawLines(A,B B,C A,C I2,J2 E1,E2)
\tkzDrawPoints[color=blue](A,...,F)
\tkzDrawPoints[color=red](I2,J2)
\tkzLabelPoints[left](B,D,E,F)
\tkzLabelPoints[below left](A,C)
\tkzLabelPoints[below=4pt](I1,K1,K2,E2)
\tkzLabelPoints[left](J1,E1)
\end{tikzpicture}
```

### 18.2.10. Calculation of radius

With `pgfmath` and `\pgfmathsetmacro`


The radius measurement may be the result of a calculation that is not done within the intersection macro, but before. A length can be calculated in several ways. It is possible of course, to use the module `pgfmath` and the macro `\pgfmathsetmacro`. In some cases, the results obtained are not precise enough, so the following calculation  $0.0002 \div 0.0001$  gives 1.98 with `pgfmath` while `xfp` will give 2.

With `xfp` and `\fpeval`:



```
\begin{tikzpicture}
\tkzDefPoint(2,2){A}
\tkzDefPoint(5,4){B}
\tkzDefPoint(4,4){O}
\pgfmathsetmacro\tkzLen{\fpeval{0.0002/0.0001}}
% or \edef\tkzLen{\fpeval{0.0002/0.0001}}
\tkzInterLC[R](A,B)(O,\tkzLen)
\tkzGetPoints{I}{J}
\tkzDrawCircle(O,I)
\tkzDrawPoints[color=blue](A,B)
\tkzDrawPoints[color=red](I,J)
\tkzDrawLine(I,J)
\end{tikzpicture}
```

## 18.2.11. Option with nodes



```
\begin{tikzpicture}[scale=.75]
\tkzDefPoints{0/0/A,4/0/B,1/1/D,2/0/E}
\tkzDefTriangle[equilateral](A,B)
\tkzGetPoint{C}
\tkzInterLC[with nodes](D,E)(C,A,B)
\tkzGetPoints{F}{G}
\tkzDrawCircle(C,A)
\tkzDrawPolygon(A,B,C)
\tkzDrawPoints(A,...,G)
\tkzDrawLine(F,G)
\end{tikzpicture}
```

18.3. Intersection of two circles `\tkzInterCC`

The most frequent case is that of two circles defined by their center and a point, but as before the option `R` allows to use the radius measurements.

`\tkzInterCC[options](O,A)(O',A')` or `(O,r)(O',r')` or `(O,A,B)(O',C,D)`


options	default	definition
<code>N</code>	<code>N</code>	<code>OA</code> and <code>O'A'</code> are radii, <code>O</code> and <code>O'</code> are the centers.
<code>R</code>	<code>N</code>	<code>r</code> and <code>r'</code> are dimensions and measure the radii.
<code>with nodes</code>	<code>N</code>	in <code>(A,A,C)(C,B,F)</code> <code>AC</code> and <code>BF</code> give the radii.
<code>common=pt</code>		<code>pt</code> is common point; <code>tkzFirstPoint</code> gives the other point.

This macro defines the intersection point(s) `I` and `J` of the two center circles `O` and `O'`. If the two circles do not have a common point then the macro ends with an error that is not handled. If the centers are `O` and `O'` and the intersections are `A` and `B` then the angles  $\widehat{O,A,O'}$  and  $\widehat{O,B,O'}$  are in opposite directions. `tkzFirstPoint` is assigned to the point that forms the clockwise angle.

`\tkzTestInterCC(O,A)(O',B)`


So the arguments are two couples which define two circles with a center and a point on the circle. If there is a non empty intersection between these two circles then the test `\iftkzFlagCC` gives true.

## 18.3.1. test circle-circle intersection



```
\begin{tikzpicture}[scale=.75]
  \tkzDefPoints{% x y name
    0 /0 /A,
    2 /0 /B,
    4 /0 /I,
    1 /0 /P}
  \tkzDrawCircle(A,B)
  \foreach \i in {1,...,3}{%
    \coordinate (P) at (\i,0);
    \tkzDrawCircle[new](I,P)
    \tkzTestInterCC(A,B)(I,P)
    \iftkzFlagCC
      \tkzInterCC(A,B)(I,P) \tkzGetPoints{a}{b}
      \tkzDrawPoints(a,b)
    \fi
  }
\end{tikzpicture}
```

## 18.3.2. circle-circle intersection with common point.




```
\begin{tikzpicture}[scale=.5]
  \tkzDefPoints{0/0/0,5/-1/A,2/2/B}
  \tkzDrawPoints(O,A,B)
  \tkzDrawCircles(O,B A,B)
  \tkzInterCC[common=B](O,B)(A,B)
  \tkzGetFirstPoint{C}
  \tkzDrawPoint(C)
  \tkzLabelPoints[above](O,A,B,C)
\end{tikzpicture}
```

## 18.3.3. circle-circle intersection order of points.

The idea is to compare the angles formed with the first center, a resultant point and the center of the second circle. The first point is the one that corresponds to the smallest angle.

As you can see  $\widehat{ODB} < \widehat{OBE}$




```
\begin{tikzpicture}[scale=.5]
  \pgfkeys{/pgf/number format/.cd,fixed relative,
    precision=4}
  \tkzDefPoints{0/0/0,5/-1/A,2/2/B,2/-1/C}
  \tkzDrawPoints(O,A,B)
  \tkzDrawCircles(O,A B,C)
  \tkzInterCC(O,A)(B,C)\tkzGetPoints{D}{E}
  \tkzDrawPoints(C,D,E)
  \tkzLabelPoints(O,A,B,C)
  \tkzLabelPoints[above](D,E)
  \tkzDrawSegments[cyan](D,O D,B)
  \tkzMarkAngle[red,->,size=1.5](O,D,B)
  \tkzFindAngle(O,D,B) \tkzGetAngle{an}
  \tkzLabelAngle(O,D,B){$\pgfmathprintnumber{\an}$}
  \tkzDrawSegments[cyan](E,O E,B)
  \tkzMarkAngle[red,->,size=1.5](O,E,B)
  \tkzFindAngle(O,E,B) \tkzGetAngle{an}
  \tkzLabelAngle(O,E,B){$\pgfmathprintnumber{\an}$}
\end{tikzpicture}
```



## 18.3.4. Construction of an equilateral triangle.


$\widehat{A,C,B}$  is a clockwise angle



```
\begin{tikzpicture}[trim left=-1cm,scale=.5]
\tkzDefPoint(1,1){A}
\tkzDefPoint(5,1){B}
\tkzInterCC(A,B)(B,A)\tkzGetPoints{C}{D}
\tkzDrawPoint[color=black](C)
\tkzDrawCircles(A,B B,A)
\tkzCompass[color=red](A,C)
\tkzCompass[color=red](B,C)
\tkzDrawPolygon(A,B,C)
\tkzMarkSegments[mark=s|](A,C B,C)
\tkzLabelPoints[](A,B)
\tkzLabelPoint[above](C){C}
\end{tikzpicture}
```


## 18.3.5. Segment trisection

The idea here is to divide a segment with a ruler and a compass into three segments of equal length.




```
\begin{tikzpicture}[scale=.6]
\tkzDefPoint(0,0){A}
\tkzDefPoint(3,2){B}
\tkzInterCC(A,B)(B,A) \tkzGetSecondPoint{D}
\tkzInterCC(D,B)(B,A) \tkzGetPoints{A}{C}
\tkzInterCC(D,B)(A,B) \tkzGetPoints{E}{B}
\tkzInterLC[common=D](C,D)(E,D)\tkzGetFirstPoint{F}
\tkzInterLL(A,F)(B,C) \tkzGetPoint{O}
\tkzInterLL(O,D)(A,B) \tkzGetPoint{H}
\tkzInterLL(O,E)(A,B) \tkzGetPoint{G}
\tkzDrawCircles(D,E A,B B,A E,A)
\tkzDrawSegments[] (O,F O,B O,D O,E)
\tkzDrawPoints(A,...,H)
\tkzDrawSegments(A,B B,D A,D A,E E,F C,F B,C)
\tkzMarkSegments[mark=s|](A,G G,H H,B)
\end{tikzpicture}
```

## 18.3.6. With the option with nodes



```
\begin{tikzpicture}[scale=.5]
\tkzDefPoints{0/0/A,0/5/B,5/0/C}
\tkzDefPoint(54:5){F}
\tkzInterCC[with nodes](A,A,C)(C,B,F)
\tkzGetPoints{a}{e}
\tkzInterCC(A,C)(a,e)\tkzGetFirstPoint{b}
\tkzInterCC(A,C)(b,a)\tkzGetFirstPoint{c}
\tkzInterCC(A,C)(c,b)\tkzGetFirstPoint{d}
\tkzDrawCircle[new](A,C)
\tkzDrawPoints(a,b,c,d,e)
\tkzDrawPolygon(a,b,c,d,e)
\foreach \vertex/\num in {a/36,b/108,c/180,
d/252,e/324}{%
\tkzDrawPoint(\vertex)
\tkzLabelPoint[label=\num:$\vertex$](\vertex){}
\tkzDrawSegment(A,\vertex)
}
\end{tikzpicture}
```


## 18.3.7. Mix of intersections



```
\begin{tikzpicture}[scale = .7]
\tkzDefPoint(2,2){A}
\tkzDefPoint(0,0){B}
\tkzDefPoint(-2,2){C}
\tkzDefPoint(0,4){D}
\tkzDefPoint(4,2){E}
\tkzCircumCenter(A,B,C)\tkzGetPoint{O}
\tkzInterCC[R](0,2)(D,2)\tkzGetPoints{M1}{M2}
\tkzInterCC(0,A)(D,0)\tkzGetPoints{1}{2}
\tkzInterLC(A,E)(B,M1)\tkzGetSecondPoint{M3}
\tkzInterLC(0,C)(M3,D)\tkzGetSecondPoint{L}
\tkzDrawSegments(C,L)
\tkzDrawPoints(A,B,C,D,E,M1,M2,M3,O,L)
\tkzDrawSegments(O,E)
\tkzDrawSegments[new](C,A D,B)
\tkzDrawPoint(O)
\tkzDrawCircles[new](M3,D B,M2 D,0)
\tkzDrawCircle(0,A)
\tkzLabelPoints[below right](A,B,C,D,E,M1,M2,M3,O,L)
\end{tikzpicture}
```

## 18.3.8. Altshiller-Court's theorem

The two lines joining the points of intersection of two orthogonal circles to a point on one of the circles met the other circle in two diametrically opposite points. Altshiller p 176



```


\begin{tikzpicture}
  \tkzDefPoints{0/0/P,5/0/Q,3/2/I}
  \tkzDefCircle[orthogonal from=P](Q,I)
  \tkzGetFirstPoint{E}
  \tkzDrawCircles(P,E Q,E)
  \tkzInterCC[common=E](P,E)(Q,E) \tkzGetFirstPoint{F}
  \tkzDefPointOnCircle[through = center P angle 80 point E]
  \tkzGetPoint{A}
  \tkzInterLC[common=E](A,E)(Q,E) \tkzGetFirstPoint{C}
  \tkzInterLL(A,F)(C,Q) \tkzGetPoint{D}
  \tkzDrawLines[add=0 and 1](P,Q)
  \tkzDrawLines[add=0 and 2](A,E)
  \tkzDrawSegments(P,E E,F F,C A,F C,D)
  \tkzDrawPoints(P,Q,E,F,A,C,D)
  \tkzLabelPoints(P,Q,F)
  \tkzLabelPoints[above](E,A)
  \tkzLabelPoints[left](D)
  \tkzLabelPoints[above right](C)
\end{tikzpicture}

```

## 19. Angles

### 19.1. Definition and usage with tkz-euclide

In Euclidean geometry, an angle is the figure formed by two rays, called the sides of the angle, sharing a common endpoint, called the vertex of the angle.[Wikipedia]. A ray with `tkz-euclide` is defined by two points also each angle is defined with three points like  $\widehat{AOB}$ . The vertex O is the second point. Their order is important because it is assumed that the angle is specified in the direct order (counterclockwise). In trigonometry and mathematics in general, plane angles are conventionally measured counterclockwise, starting with  $0^\circ$  pointing directly to the right (or east), and  $90^\circ$  pointing straight up (or north)[Wikipedia]. Let us agree that an angle measured counterclockwise is positive.



Angles are involved in several macros like `\tkzDefPoint`, `\tkzDefPointBy[rotation = ...]`, `\tkzDrawArc` and the next one `\tkzGetAngle`. With the exception of the last one, all these macros accept negative angles.

<p>Rotation <math>80^\circ</math> from (O,A) to (O,B)  <code>\tkzDefPointBy[rotation=center O angle 80]</code></p>	<p>Rotation <math>-80^\circ</math> from (O,A) to (O,B)  <code>\tkzDefPointBy[rotation=center O angle -80]</code></p>
<p><code>\tkzFindAngle(A,O,B)</code> gives 80</p>	<p><code>\tkzFindAngle(A,O,B)</code> gives <math>280^\circ</math></p>

As we can see, the  $-80^\circ$  rotation defines a clockwise angle but the macro `\tkzFindAngle` recovers a counter-clockwise angle.

### 19.2. Recovering an angle `\tkzGetAngle`

<code>\tkzGetAngle(&lt;name of macro&gt;)</code>		
Assigns the value in degree of an angle to a macro. The value is positive and between $0^\circ$ and $360^\circ$ . This macro retrieves <code>\tkzAngleResult</code> and stores the result in a new macro.		
arguments	example	explanation
name of macro	<code>\tkzGetAngle{ang}</code>	<code>\ang</code> contains the value of the angle.


This is an auxiliary macro that allows you to retrieve the result of the following macro `\tkzFindAngle`.

### 19.3. Angle formed by three points

<code>\tkzFindAngle(&lt;pt1,pt2,pt3&gt;)</code>		
The result is stored in a macro <code>\tkzAngleResult</code> .		
arguments	example	explanation
(pt1,pt2,pt3)	<code>\tkzFindAngle(A,B,C)</code>	<code>\tkzAngleResult</code> gives the angle $(\overrightarrow{BA}, \overrightarrow{BC})$


The measure is always positive and between  $0^\circ$  and  $360^\circ$ . With the usual conventions, a counterclockwise angle smaller than a straight angle has always a measure between  $0^\circ$  and  $180^\circ$ , while a clockwise angle smaller than a straight angle will have a measurement greater than  $180^\circ$ . `\tkzGetAngle` can retrieve the angle.

### 19.3.1. Verification of angle measurement



```
\begin{tikzpicture}[scale=.75]
  \tkzDefPoint(-1,1){A}
  \tkzDefPoint(5,2){B}
  \tkzDefEquilateral(A,B)
  \tkzGetPoint{C}
  \tkzDrawPolygon(A,B,C)
  \tkzFindAngle(B,A,C) \tkzGetAngle{angleBAC}
  \edef\angleBAC{\fpeval{round(\angleBAC)}}
  \tkzDrawPoints(A,B,C)
  \tkzLabelPoints(A,B)
  \tkzLabelPoint[right](C){$C$}
  \tkzLabelAngle(B,A,C){\angleBAC^\circ}
  \tkzMarkAngle[size=1.5](B,A,C)
\end{tikzpicture}
```


### 19.3.2. Determination of the three angles of a triangle



```
\begin{tikzpicture}
  \tikzset{label angle style/.append style={pos=1.4}}
  \tkzDefPoints{0/0/a,5/3/b,3/6/c}
  \tkzDrawPolygon(a,b,c)
  \tkzFindAngle(c,b,a)\tkzGetAngle{angleCBA}
  \pgfmathparse{round(1+\angleCBA)}
  \let\angleCBA\pgfmathresult
  \tkzFindAngle(a,c,b)\tkzGetAngle{angleACB}
  \pgfmathparse{round(\angleACB)}
  \let\angleACB\pgfmathresult
  \tkzFindAngle(b,a,c)\tkzGetAngle{angleBAC}
  \pgfmathparse{round(\angleBAC)}
  \let\angleBAC\pgfmathresult
  \tkzMarkAngle(c,b,a)
  \tkzLabelAngle(c,b,a){\tiny $\angleCBA^\circ$}
  \tkzMarkAngle(a,c,b)
  \tkzLabelAngle(a,c,b){\tiny $\angleACB^\circ$}
  \tkzMarkAngle(b,a,c)
  \tkzLabelAngle(b,a,c){\tiny $\angleBAC^\circ$}
\end{tikzpicture}
```

### 19.3.3. Angle between two circles

We are looking for the angle formed by the tangents at a point of intersection



```
\begin{tikzpicture}[scale=.4]
\pgfkeys{/pgf/number format/.cd,%
  fixed,precision=1}
\tkzDefPoints{0/0/A,6/0/B,4/2/C}
\tkzDrawCircles(A,C B,C)
\tkzDefLine[tangent at=C](A)\tkzGetPoint{a}
\tkzDefPointsBy[symmetry=center C](a){d}
\tkzDefLine[tangent at=C](B)\tkzGetPoint{b}
\tkzDrawLines[add=1 and 4](a,C C,b)
\tkzFillAngle[fill=teal,opacity=.2%
,size=2](b,C,d)
\tkzFindAngle(b,C,d)\tkzGetAngle{bcd}
\tkzLabelAngle[pos=1.25](b,C,d){%
  \tiny $\pgfmthprintnumber{\bcd}^\circ$}
\end{tikzpicture}
```

#### 19.4. Angle formed by a straight line with the horizontal axis `\tkzFindSlopeAngle`

Much more interesting than the last one. The result is between -180 degrees and +180 degrees.

`\tkzFindSlopeAngle( $\langle A, B \rangle$ )`


Determines the slope of the straight line (AB). The result is stored in a macro `\tkzAngleResult`.

arguments	example	explanation
(pt1,pt2)	<code>\tkzFindSlopeAngle(A,B)</code>	

`\tkzGetAngle` can retrieve the result. If retrieval is not necessary, you can use `\tkzAngleResult`.

##### 19.4.1. How to use `\tkzFindSlopeAngle`


The point here is that (AB) is the bisector of  $\widehat{CAD}$ , such that the AD slope is zero. We recover the slope of (AB) and then rotate twice.



```
\begin{tikzpicture}
\tkzDefPoint(1,5){A}\tkzDefPoint(5,2){B}
\tkzFindSlopeAngle(A,B)\tkzGetAngle{tkzang}
\tkzDefPointBy[rotation=center A angle \tkzang](B)
\tkzGetPoint{C}
\tkzDefPointBy[rotation=center A angle -\tkzang](B)
\tkzGetPoint{D}
\tkzDrawSegment(A,B)
\tkzDrawSegments[new](A,C A,D)
\tkzDrawPoints(A,B,C,D)
\tkzCompass[length=1](A,C)
\tkzCompass[delta=10,brown](B,C)
\tkzLabelPoints(B,C,D)
\tkzLabelPoints[above left](A)
\end{tikzpicture}
```

##### 19.4.2. Use of `\tkzFindSlopeAngle` and `\tkzGetAngle`

Here is another version of the construction of a mediator




```
\begin{tikzpicture}
\tkzInit
\tkzDefPoint(0,0){A}      \tkzDefPoint(3,2){B}
\tkzDefLine[mediator](A,B) \tkzGetPoints{I}{J}
\tkzCalcLength(A,B)       \tkzGetLength{dAB}
\tkzFindSlopeAngle(A,B)   \tkzGetAngle{tkzangle}
\begin{scope}[rotate=tkzangle]
\tkzSetUpArc[color=gray,line width=0.2pt,%
/tkzcompass/delta=10]
\tkzDrawArc[R,arc](B,3/4*dAB)(120,240)
\tkzDrawArc[R,arc](A,3/4*dAB)(-45,60)
\tkzDrawLine(I,J)         \tkzDrawSegment(A,B)
\end{scope}
\tkzDrawPoints(A,B,I,J)   \tkzLabelPoints(A,B)
\tkzLabelPoints[right](I,J)
\end{tikzpicture}
```

### 19.4.3. Another use of \tkzFindSlopeAngle

The slope of (AB) is :  $45^\circ$

The slope of (AC) is :  $0^\circ$

The slope of (AD) is :  $333.43^\circ$



```
\begin{tikzpicture}[scale=1.5]
\tkzDefPoint(1,2){A}      \tkzDefPoint(3,4){B}
\tkzDefPoint(3,2){C}      \tkzDefPoint(3,1){D}
\tkzDrawSegments(A,B A,C A,D)
\tkzDrawPoints[color=red](A,B,C,D)
\tkzLabelPoints(A,B,C,D)
\tkzFindSlopeAngle(A,B)\tkzGetAngle{SAB}
\tkzFindSlopeAngle(A,C)\tkzGetAngle{SAC}
\tkzFindSlopeAngle(A,D)\tkzGetAngle{SAD}
\pgfkeys{/pgf/number format/.cd,fixed,precision=2}
\tkzText(1,5){The slope of (AB) is :
  $\pgfmathprintnumber{\SAB}^\circ$}
\tkzText(1,4.5){The slope of (AC) is :
  $\pgfmathprintnumber{\SAC}^\circ$}
\tkzText(1,4){The slope of (AD) is :
  $\pgfmathprintnumber{\SAD}^\circ$}
\end{tikzpicture}
```

## 20. Random point definition

At the moment there are four possibilities:

1. point in a rectangle;
2. on a segment;
3. on a straight line;
4. on a circle.

### 20.1. Obtaining random points

This is the new version that replaces `\tkzGetRandPointOn`.

`\tkzDefRandPointOn[⟨local options⟩]`

The result is a point with a random position that can be named with the macro `\tkzGetPoint`. It is possible to use `\tkzPointResult` if it is not necessary to retain the results.


options	default	definition
<code>rectangle=pt1 and pt2</code>		<code>[rectangle=A and B]</code>
<code>segment= pt1--pt2</code>		<code>[segment=A--B]</code>
<code>line=pt1--pt2</code>		<code>[line=A--B]</code>
<code>circle =center pt1 radius dim</code>		<code>[circle = center A radius 2]</code>
<code>circle through=center pt1 through pt2</code>		<code>[circle through= center A through B]</code>
<code>disk through=center pt1 through pt2</code>		<code>[disk through=center A through B]</code>

### 20.1.1. Random point in a rectangle




```
\begin{tikzpicture}
\tkzDefPoints{0/0/A,5/3/C}
\tkzDefRandPointOn[rectangle = A and C]
\tkzGetPoint{E}
\tkzDefRectangle(A,C)\tkzGetPoints{B}{D}
\tkzDrawPolygon[red](A,...,D)
\tkzDrawPoints(A,...,E)
\tkzLabelPoints(A,B)
\tkzLabelPoints[above](C,D,E)
\end{tikzpicture}
```

### 20.1.2. Random point on a segment or a line



```
\begin{tikzpicture}
\tkzDefPoints{0/0/A,5/2/C}
\tkzDefRandPointOn[segment = A--C]\tkzGetPoint{B}
\tkzDrawLine(A,C)
\tkzDrawPoints(A,C) \tkzDrawPoint[red](B)
\tkzLabelPoints(A,C) \tkzLabelPoints[red](B)
\end{tikzpicture}
```

### 20.1.3. Random point on a circle or a disk



```
\begin{tikzpicture}
\tkzDefPoints{3/2/A,1/1/B}
\tkzCalcLength(A,B) \tkzGetLength{rAB}
\tkzDefRandPointOn[circle = center A radius \rAB]
\tkzGetPoint{C}
\tkzDefRandPointOn[circle through= center A through B]
\tkzGetPoint{D}
\tkzDefRandPointOn[disk through=center A through B]
\tkzGetPoint{E}
\tkzDrawCircle(A,B)
\tkzDrawPoints(A,B)
\tkzLabelPoints(A,B)
\tkzDrawPoints[red](C,D,E)
\tkzLabelPoints[red,right](C,D,E)
\end{tikzpicture}
```



## Part IV.

### Drawing and Filling

## 21. Drawing

`tkz-euclide` can draw 5 types of objects : point, line or line segment, circle, arc and sector.

### 21.1. Draw a point or some points

There are two possibilities : `\tkzDrawPoint` for a single point or `\tkzDrawPoints` for one or more points.

#### 21.1.1. Drawing points `\tkzDrawPoint`


<code>\tkzDrawPoint[⟨local options⟩](⟨name⟩)</code>		
arguments	default	definition
name of point	no default	Only one point name is accepted
The argument is required. The disc takes the color of the circle, but lighter. It is possible to change everything. The point is a node and therefore it is invariant if the drawing is modified by scaling.		
options	default	definition
TikZ options		all TikZ options are valid.
shape	circle	Possible <b>cross</b> or <b>cross out</b>
size	6	$6 \times \text{\pgflinewidth}$
color	black	the default color can be changed
We can create other forms such as <b>cross</b>		

By default, `point style` is defined like this :

```
\tikzset{point style/.style = {%
    draw      = black,
    inner sep = 0pt,
    shape     = circle,
    minimum size = 3 pt,
    fill      = black
  }
}
```

#### 21.1.2. Example of point drawings

Note that `scale` does not affect the shape of the dots. Which is normal. Most of the time, we are satisfied with a single point shape that we can define from the beginning, either with a macro or by modifying a configuration file.




```
\begin{tikzpicture}[scale=.5]
  \tkzDefPoint(1,3){A}
  \tkzDefPoint(4,1){B}
  \tkzDefPoint(0,0){O}
  \tkzDrawPoint[color=red](A)
  \tkzDrawPoint[fill=blue!20,draw=blue](B)
  \tkzDrawPoint[shape=cross,size=8pt,color=teal](O)
\end{tikzpicture}
```


It is possible to draw several points at once but this macro is a little slower than the previous one. Moreover, we have to make do with the same options for all the points.

```
\tkzDrawPoints[⟨local options⟩](⟨liste⟩)
```

arguments	default	definition
points list	no default	example <code>\tkzDrawPoints(A,B,C)</code>
options	default	definition
shape	circle	Possible <b>cross</b> or <b>cross out</b>
size	6	$6 \times \text{\pgflinewidth}$
color	black	the default color can be changed

 Beware of the final s, an oversight leads to cascading errors if you try to draw multiple points. The options are the same as for the previous macro.

### 21.1.3. Example



```

\begin{tikzpicture}
\tkzDefPoints{1/3/A,4/1/B,0/0/C}
\tkzDrawPoints[size=3,color=red,fill=red!50](A,B,C)
\end{tikzpicture}

```

## 22. Drawing the lines

The following macros are simply used to draw, name lines.

### 22.1. Draw a straight line

To draw a normal straight line, just give a couple of points. You can use the `add` option to extend the line (This option is due to Mark Wibrow, see the code below).

The style of a line is by default :

```

\tikzset{line style/.style = {%
  line width = 0.6pt,
  color      = black,
  style      = solid,
  add        = {.2} and {.2}%
}}

```

with

```

\tikzset{%
  add/.style args={#1 and #2}{
    to path={%
      ($(\tikztostart)!-#1!(\tikztotarget)$)--($(\tikztotarget)!-#2!(\tikztostart)$)%
    }
  }
\tikztonodes}}

```

You can modify this style with `\tkzSetUpLine` see 40.1


`\tkzDrawLine[⟨local options⟩](⟨pt1,pt2⟩)`

The arguments are a list of two points or three points. It would be possible, as for a half line, to create a style with `\add`.

options	default	definition
TikZ options		all TikZ options are valid.
add	0.2 and 0.2	add = kl and kr, ...
...	...	allows the segment to be extended to the left and right.

`add` defines the length of the line passing through the points `pt1` and `pt2`. Both numbers are percentages. The styles of TikZ are accessible for plots.

### 22.1.1. Examples with add




It is possible to draw several lines, but with the same options.

`\tkzDrawLines[⟨local options⟩](⟨pt1,pt2 pt3,pt4 ...⟩)`

Arguments are a list of pairs of points separated by spaces. The styles of TikZ are available for the draws.

### 22.1.2. Example with \tkzDrawLines



## 23. Drawing a segment

There is, of course, a macro to simply draw a segment.

### 23.1. Draw a segment \tkzDrawSegment


```
\tkzDrawSegment[⟨local options⟩](⟨pt1,pt2⟩)
```

The arguments are a list of two points. The styles of TikZ are available for the drawings.

argument	example	definition
(pt1,pt2)	(A,B)	draw the segment [A,B]
options	example	definition
TikZ options		all TikZ options are valid.
dim	no default	dim = {label,dim,option}, ...
...	...	allows you to add dimensions to a figure.


This is of course equivalent to `\draw (A)--(B);`. You can also use the option `add`.

### 23.1.1. Example with point references



```
\begin{tikzpicture}[scale=1.5]
\tkzDefPoint(0,0){A}
\tkzDefPoint(2,1){B}
\tkzDrawSegment[color=red,thin](A,B)
\tkzDrawPoints(A,B)
\tkzLabelPoints(A,B)
\end{tikzpicture}
```

### 23.1.2. Example of extending an segment with option add




```
\begin{tikzpicture}
\tkzDefPoints{0/0/A,6/0/B,0.8/4/C}
\tkzDefTriangleCenter[euler](A,B,C)
\tkzGetPoint{E}
\tkzDefCircle[euler](A,B,C)\tkzGetPoints{E}{e}
\tkzDrawCircle[red](E,e)
\tkzDrawLines[add=.5 and .5](A,B A,C B,C)
\tkzDrawPoints(A,B,C,E)
\tkzLabelPoints(A,B,C,E)
\end{tikzpicture}
```

### 23.1.3. Adding dimensions with option dim new code from Muzimuzhi Z


This code comes from an answer to this question on [tex.stackexchange.com](https://tex.stackexchange.com/questions/444444/change-color-and-style-of-dimension-lines-in-tikz-euclide) (change-color-and-style-of-dimension-lines-in-tikz-euclide). The code of `dim` is based on options of TikZ, you must add the units. You can use now two styles: `dim style` and `dim fence style`. You have several ways to use them. I'll let you look at the examples to see what you can do with these styles.

```
\tikzset{dim style/.append style={dashed}} % append if you want to keep precedent style.
or
\begin{scope}[ dim style/.append style={orange},
               dim fence style/.style={dashed}]
```




```
\begin{tikzpicture}[scale=.75]
\tkzDefPoints{0/3/A, 1/-3/B}
\tkzDrawPoints(A,B)
\tkzDrawSegment[dim={\ (l_0\)},1cm,right=2mm],
  dim style/.append style={red,
  dash pattern={on 2pt off 2pt}}](A,B)
\tkzDrawSegment[dim={\ (l_1\)},2cm,right=2mm],
  dim style/.append style={blue}](A,B)
\begin{scope}[ dim style/.style={orange},
               dim fence style/.style={dashed}]
\tkzDrawSegment[dim={\ (l_2\)},3cm,right=2mm](A,B)
\tkzDrawSegment[dim={\ (l_3\)},-2cm,right=2mm](A,B)
\end{scope}
\tkzLabelPoints[left](A,B)
\end{tikzpicture}
```

#### 23.1.4. Adding dimensions with option dim partI



```
\begin{tikzpicture}[scale=2]
\pgfkeys{/pgf/number format/.cd,fixed,precision=2}
\tkzDefPoint(0,0){A}
\tkzDefPoint(3.07,0){B}
\tkzInterCC[R](A,2.37)(B,1.82)
\tkzGetPoints{C}{C'}
\tkzDefCircle[in](A,B,C) \tkzGetPoints{G}{g}
\tkzDrawCircle(G,g)
\tkzDrawPolygon(A,B,C)
\tkzDrawPoints(A,B,C)
\tkzCalcLength(A,B)\tkzGetLength{ABl}
\tkzCalcLength(B,C)\tkzGetLength{BCl}
\tkzCalcLength(A,C)\tkzGetLength{ACl}
\begin{scope}[dim style/.style={dashed,sloped,teal}]
\tkzDrawSegment[dim={\pgfmathprintnumber\BCl,6pt,%
  text=red}](C,B)
\tkzDrawSegment[dim={\pgfmathprintnumber\ACl,%
  6pt,}](A,C)
\tkzDrawSegment[dim={\pgfmathprintnumber\ABl,%
  -6pt,}](A,B)
\end{scope}
\tkzLabelPoints(A,B) \tkzLabelPoints[above](C)
\end{tikzpicture}
```

## 23.1.5. Adding dimensions with option dim part II




```
\begin{tikzpicture}[scale=.5]
  \tkzDefPoints{0/0/O,-2/0/A,2/0/B,
    -2/4/C,2/4/D,2/-4/E,-2/-4/F}
  \tkzDrawPolygon(C,...,F)
  \tkzDrawSegments(A,B)
  \tkzDrawPoints(A,...,F,O)
  \tkzLabelPoints[below left](A,...,F,O)
  \tkzDrawSegment[dim={ $\sqrt{5}$,2cm,}] (C,E)
  \tkzDrawSegment[dim={ $\frac{\sqrt{5}}{2}$,1cm,}] (O,E)
  \tkzDrawSegment[dim={ $2$,2cm,left=8pt}] (F,C)
  \tkzDrawSegment[dim={ $1$,1cm,left=8pt}] (F,A)
\end{tikzpicture}
```

## 23.2. Drawing segments \tkzDrawSegments

If the options are the same we can plot several segments with the same macro.


```
\tkzDrawSegments[<local options>](<pt1,pt2 pt3,pt4 ...>)
```

The arguments are a two-point couple list. The styles of TikZ are available for the plots.



```
\begin{tikzpicture}
  \tkzInit[xmin=-1,xmax=3,ymin=-1,ymax=2]
  \tkzClip[space=1]
  \tkzDefPoint(0,0){A}
  \tkzDefPoint(2,1){B}
  \tkzDefPoint(3,0){C}
  \tkzDrawSegments(A,B B,C)
  \tkzDrawPoints(A,B,C)
  \tkzLabelPoints(A,C)
  \tkzLabelPoints[above](B)
\end{tikzpicture}
```


## 23.2.1. Place an arrow on segment



```
\begin{tikzpicture}
  \tkzSetUpStyle[postaction=decorate,
    decoration={markings,
      mark=at position .5 with {\arrow[thick]{#1}}
    }]{myarrow}
  \tkzDefPoint(0,0){A}
  \tkzDefPoint(4,-4){B}
  \tkzDrawSegments[myarrow=stealth](A,B)
  \tkzDrawPoints(A,B)
\end{tikzpicture}
```

## 23.3. Drawing line segment of a triangle

## 23.3.1. How to draw Altitude



```
\begin{tikzpicture}[rotate=-90]
\tkzDefPoint(0,1){A}
\tkzDefPoint(2,4){C}
\tkzDefPointWith[orthogonal normed,K=7](C,A)
\tkzGetPoint{B}
\tkzDefSpcTriangle[orthic,name=H](A,B,C){a,b,c}
\tkzDrawLine[dashed,color=magenta](C,Hc)
\tkzDrawSegment[green!60!black](A,C)
\tkzDrawSegment[green!60!black](C,B)
\tkzDrawSegment[green!60!black](B,A)
\tkzLabelPoint[left](A){$A$}
\tkzLabelPoint[right](B){$B$}
\tkzLabelPoint[above](C){$C$}
\tkzLabelPoint[left](Hc){$Hc$}
\tkzLabelSegment[auto](B,A){$c$}
\tkzLabelSegment[auto,swap](B,C){$a$}
\tkzLabelSegment[auto,swap](C,A){$b$}
\tkzMarkAngle[size=1,color=cyan,mark=|](C,B,A)
\tkzMarkAngle[size=1,color=cyan,mark=|](A,C,Hc)
\tkzMarkAngle[size=0.75,
               color=orange,mark=|](Hc,C,B)
\tkzMarkAngle[size=0.75,
               color=orange,mark=|](B,A,C)
\tkzMarkRightAngle(A,C,B)
\tkzMarkRightAngle(B,Hc,C)
\end{tikzpicture}
```


## 23.4. Drawing a polygon

`\tkzDrawPolygon[local options](points list)`

Just give a list of points and the macro plots the polygon using the TikZ options present. You can replace (A,B,C,D,E) by (A,...,E) and (P<sub>1</sub>,P<sub>2</sub>,P<sub>3</sub>,P<sub>4</sub>,P<sub>5</sub>) by (P<sub>1</sub>,P...,P<sub>5</sub>)

arguments	example	explanation
(pt1,pt2,pt3,...)	<code>\tkzDrawPolygon[gray,dashed](A,B,C)</code>	Drawing a triangle
options	default	example
Options TikZ ...		<code>\tkzDrawPolygon[red,line width=2pt](A,B,C)</code>


## 23.4.1. \tkzDrawPolygon



```
\begin{tikzpicture}[rotate=18,scale=1]
\tkzDefPoints{0/0/A,2.25/0.2/B,2.5/2.75/C,-0.75/2/D}
\tkzDrawPolygon(A,B,C,D)
\tkzDrawSegments[style=dashed](A,C B,D)
\end{tikzpicture}
```



## 23.4.2. Option two angles



```
\begin{tikzpicture}
\tkzDefPoint(0,0){A}
\tkzDefPoint(6,0){B}
\tkzDefTriangle[two angles = 50 and 70](A,B) \tkzGetPoint{C}
\tkzDrawPolygon(A,B,C)
\tkzLabelAngle[pos=1.4](B,A,C){$50^\circ$}
\tkzLabelAngle[pos=0.8](C,B,A){$70^\circ$}
\end{tikzpicture}
```

## 23.4.3. Style of line



```
\begin{tikzpicture}[scale=.6]
\tkzSetUpLine[line width=5mm,color=teal]
\tkzDefPoint(0,0){O}
\foreach \i in {0,...,5}{%
\tkzDefPoint({30+60*\i}:4){p\i}}
\tkzDefMidPoint(p1,p3) \tkzGetPoint{m1}
\tkzDefMidPoint(p3,p5) \tkzGetPoint{m3}
\tkzDefMidPoint(p5,p1) \tkzGetPoint{m5}
\tkzDrawPolygon[line join=round](p1,p3,p5)
\tkzDrawPolygon[teal!80,
line join=round](p0,p2,p4)
\tkzDrawSegments(m1,p3 m3,p5 m5,p1)
\tkzDefCircle[R](0,4.8)\tkzGetPoint{o}
\tkzDrawCircle[teal](0,o)
\end{tikzpicture}
```


## 23.5. Drawing a polygonal chain

`\tkzDrawPolySeg[⟨local options⟩](⟨points list⟩)`

Just give a list of points and the macro plots the polygonal chain using the TikZ options present.

arguments	example	explanation
<code>(⟨pt1,pt2,pt3,...⟩)</code>	<code>\tkzDrawPolySeg[gray,dashed](A,B,C)</code>	Drawing a triangle
options	default	example
Options TikZ	...	<code>\tkzDrawPolySeg[red,line width=2pt](A,B,C)</code>


## 23.5.1. Polygonal chain



```
\begin{tikzpicture}
\tkzDefPoints{0/0/A,6/0/B,3/4/C,2/2/D}
\tkzDrawPolySeg(A,...,D)
\tkzDrawPoints(A,...,D)
\end{tikzpicture}
```


## 23.5.2. The idea is to inscribe two squares in a semi-circle.

A Sangaku look! It is a question of proving that one can inscribe in a half-disc, two squares, and to determine the length of their respective sides according to the radius.



```
\begin{tikzpicture}[scale=.75]
\tkzDefPoints{0/0/A,8/0/B,4/0/I}
\tkzDefSquare(A,B) \tkzGetPoints{C}{D}
\tkzInterLC(I,C)(I,B) \tkzGetPoints{E'}{E}
\tkzInterLC(I,D)(I,B) \tkzGetPoints{F'}{F}
\tkzDefPointsBy[projection=onto A--B](E,F){H,G}
\tkzDefPointsBy[symmetry = center H](I){J}
\tkzDefSquare(H,J) \tkzGetPoints{K}{L}
\tkzDrawSector(I,B)(A)
\tkzDrawPolySeg(H,E,F,G)
\tkzDrawPolySeg(J,K,L)
\tkzDrawPoints(E,G,H,F,J,K,L)
\end{tikzpicture}
```

## 23.5.3. Polygonal chain: index notation



```
\begin{tikzpicture}
\foreach \pt in {1,2,...,8} {%
\tkzDefPoint(\pt*20:3){P_\pt}}
\tkzDrawPolySeg(P_1,P_...,P_8)
\tkzDrawPoints(P_1,P_...,P_8)
\end{tikzpicture}
```

24. Draw a circle with `\tkzDrawCircle`

## 24.1. Draw one circle

```
\tkzDrawCircle[(local options)]((A,B))
```




Attention you need only two points to define a radius. An additional option **R** is available to give a measure directly.

arguments	example	explanation
<code>(\pt1,\pt2)</code>	<code>(A,B)</code>	A center through B

Of course, you have to add all the styles of TikZ for the tracings...

## 24.1.1. Circles and styles, draw a circle and color the disc

We'll see that it's possible to colour in a disc while tracing the circle.



```
\begin{tikzpicture}
  \tkzDefPoint(0,0){O}
  \tkzDefPoint(3,0){A}
  % circle with center O and passing through A
  \tkzDrawCircle(O,A)
  % diameter circle  $[OA]$ 
  \tkzDefCircle[diameter](O,A) \tkzGetPoint{I}
  \tkzDrawCircle[new,fill=orange!10,opacity=.5](I,A)
  % circle with center O and radius =  $\exp(1)$  cm
  \edef\rayon{\fpeval{0.25*exp(1)}}
  \tkzDefCircle[R](O,\rayon) \tkzGetPoint{o}
  \tkzDrawCircle[color=orange](O,o)
\end{tikzpicture}
```

## 24.2. Drawing circles

```
\tkzDrawCircles[<local options>](<A,B C,D ...>)
```




Attention, the arguments are lists of two points. The circles that can be drawn are the same as in the previous macro. An additional option **R** is available to give a measure directly.

arguments	example	explanation
<code>(&lt;pt1,pt2 pt3,pt4 ...&gt;)</code>	<code>(&lt;A,B C,D&gt;)</code>	List of two points
options	default	definition
<code>through</code>	<code>through</code>	circle with two points defining a radius


You do not need to use the default option **through**. Of course, you have to add all the styles of TikZ for the tracings...

## 24.2.1. Circles defined by a triangle.




```
\begin{tikzpicture}
\tkzDefPoints{0/0/A,2/0/B,3/2/C}
\tkzDrawPolygon(A,B,C)
\tkzDrawCircles(A,B B,C C,A)
\tkzDrawPoints(A,B,C)
\tkzLabelPoints(A,B,C)
\end{tikzpicture}
```

## 24.2.2. Concentric circles.



```
\begin{tikzpicture}
\tkzDefPoints{0/0/A,1/0/a,2/0/b,3/0/c}
\tkzDrawCircles(A,a A,b A,c)
\tkzDrawPoint(A)
\tkzLabelPoints(A)
\end{tikzpicture}
```

## 24.2.3. Exinscribed circles.



```


\begin{tikzpicture}[scale=1]
\tkzDefPoints{0/0/A,4/0/B,1/2.5/C}
\tkzDrawPolygon(A,B,C)
\tkzDefCircle[ex](B,C,A)
\tkzGetPoint{J_c} \tkzGetSecondPoint{T_c}
\tkzDrawCircle(J_c,T_c)
\tkzDrawLines[add=0 and 1](C,A C,B)
\tkzDrawSegment(J_c,T_c)
\tkzMarkRightAngle(J_c,T_c,B)
\tkzDrawPoints(A,B,C,J_c,T_c)
\end{tikzpicture}

```

## 24.2.4. Cardioid

Based on an idea by O. Reboux made with pst-eucl (Pstricks module) by D. Rodriguez.

Its name comes from the Greek *kardia* (*heart*), in reference to its shape, and was given to it by Johan Castillon (Wikipedia).



```


\begin{tikzpicture}[scale=.5]
\tkzDefPoint(0,0){O}
\tkzDefPoint(2,0){A}
\foreach \ang in {5,10,...,360}{%
\tkzDefPoint(\ang:2){M}
\tkzDrawCircle(M,A)
}
\end{tikzpicture}

```

## 24.3. Drawing semicircle

<code>\tkzDrawSemiCircle[⟨local options⟩](⟨O,A⟩)</code>
---

arguments	example	explanation
<code>(⟨pt1,pt2⟩)</code>	<code>(⟨O,A⟩)</code>	OA= radius
O center A extremity of the semicircle		

24.3.1. Use of `\tkzDrawSemiCircle`

```


\begin{tikzpicture}
\tkzDefPoint(0,0){A} \tkzDefPoint(6,0){B}
\tkzDefMidPoint(A,B) \tkzGetPoint{O}
\tkzDrawSemiCircle[blue](O,B)
\tkzDrawSemiCircle[red](O,A)
\tkzDrawPoints(O,A,B)
\tkzLabelPoints[below right](O,A,B)
\end{tikzpicture}

```

## 24.4. Drawing semicircles

<code>\tkzDrawSemiCircles[⟨local options⟩](⟨A,B C,D ...⟩)</code>
--

arguments	example	explanation
<code>(⟨pt1,pt2 pt3,pt4 ...⟩)</code>	<code>(⟨A,B C,D⟩)</code>	List of two points

24.4.1. Use of `\tkzDrawSemiCircles` : Golden arbelos

```

\begin{tikzpicture}[scale=.75]
\tkzDefPoints{0/0/A,10/0/B}
\tkzDefGoldenRatio(A,B) \tkzGetPoint{C}
\tkzDefMidPoint(A,B) \tkzGetPoint{O_0}
\tkzDefMidPoint(A,C) \tkzGetPoint{O_1}
\tkzDefMidPoint(C,B) \tkzGetPoint{O_2}
\tkzLabelPoints(A,B,C)
\tkzDrawSegment(A,B)
\tkzDrawPoints(A,B,C)
\begin{scope}[local bounding box = graph]
\tkzDrawSemiCircles[color=black](O_0,B)
\end{scope}
\useasboundingbox (graph.south west) rectangle (graph.north east);
\tkzClipCircle[out](O_1,C)\tkzClipCircle[out](O_2,B)
\tkzDrawSemiCircles[draw=none,fill=teal!15](O_0,B)
\tkzDrawSemiCircles[color=black](O_1,C O_2,B)
\end{tikzpicture}

```

## 25. Draw an ellipse with `\tkzDrawEllipse`


### 25.1. Draw an ellipse

`\tkzDrawEllipse[local options](C,a,b,An)`

arguments	example	explanation
<code>(C,a,b,An)</code>	<code>(C,4,2,45)</code>	C center; 4 and 2 lengths of half-axis 45 slope of main axis

Of course, you have to add all the styles of TikZ for the tracings...

#### 25.1.1. Example of drawing an ellipse



```

\begin{tikzpicture}[scale=.75]
\tkzDefPoint(0,4){C}
\tkzDrawEllipse[blue](C,4,2,45)
\tkzLabelPoints(C)
\end{tikzpicture}

```

## 26. Drawing arcs

### 26.1. Macro: `\tkzDrawArc`

`\tkzDrawArc[⟨local options⟩](⟨O,...⟩)(⟨...⟩)`

This macro traces the arc of center O. Depending on the options, the arguments differ. It is a question of determining a starting point and an end point. Either the starting point is given, which is the simplest, or the radius of the arc is given. In the latter case, it is necessary to have two angles. Either the angles can be given directly, or nodes associated with the center can be given to determine them. The angles are in degrees.

options	default	definition
towards	towards	O is the center and the arc from A to (OB)
rotate	towards	the arc starts from A and the angle determines its length
R	towards	We give the radius and two angles
R with nodes	towards	We give the radius and two points
angles	towards	We give the radius and two points
delta	0	angle added on each side
reverse	false	inversion of the arc's path, interesting to inverse arrow


Of course, you have to add all the styles of TikZ for the tracings...

options	arguments	example
towards	(⟨pt,pt⟩)(⟨pt⟩)	<code>\tkzDrawArc[delta=10](O,A)(B)</code>
rotate	(⟨pt,pt⟩)(⟨an⟩)	<code>\tkzDrawArc[rotate,color=red](O,A)(90)</code>
R	(⟨pt,r⟩)(⟨an,an⟩)	<code>\tkzDrawArc[R](O,2)(30,90)</code>
R with nodes	(⟨pt,r⟩)(⟨pt,pt⟩)	<code>\tkzDrawArc[R with nodes](O,2)(A,B)</code>
angles	(⟨pt,pt⟩)(⟨an,an⟩)	<code>\tkzDrawArc[angles](O,A)(0,90)</code>

Here are a few examples:

#### 26.1.1. Option towards

It's useless to put `towards`. In this first example the arc starts from A and goes to B. The arc going from B to A is different. The salient is obtained by going in the direct direction of the trigonometric circle.




```
\begin{tikzpicture}[scale=.75]
  \tkzDefPoint(0,0){O}
  \tkzDefPoint(2,-1){A}
  \tkzDefPointBy[rotation= center O angle 90](A)
  \tkzGetPoint{B}
  \tkzDrawArc[color=orange,<->](O,A)(B)
  \tkzDrawArc(O,B)(A)
  \tkzDrawLines[add = 0 and .5](O,A O,B)
  \tkzDrawPoints(O,A,B)
  \tkzLabelPoints[below](O,A,B)
\end{tikzpicture}
```

#### 26.1.2. Option towards


In this one, the arc starts from A but stops on the right (OB).






```
\begin{tikzpicture}[scale=0.75]
  \tkzDefPoint(0,0){O}
  \tkzDefPoint(2,-1){A}
  \tkzDefPoint(1,1){B}
  \tkzDrawArc[color=blue,->](O,A)(B)
  \tkzDrawArc[color=gray](O,B)(A)
  \tkzDrawArc(O,B)(A)
  \tkzDrawLines[add = 0 and .5](O,A O,B)
  \tkzDrawPoints(O,A,B)
  \tkzLabelPoints[below](O,A,B)
\end{tikzpicture}
```

### 26.1.3. Option rotate




```
\begin{tikzpicture}[scale=0.75]
  \tkzDefPoint(0,0){O}
  \tkzDefPoint(2,-2){A}
  \tkzDefPoint(60:2){B}
  \tkzDrawLines[add = 0 and .5](O,A O,B)
  \tkzDrawArc[rotate,color=red](O,A)(180)
  \tkzDrawPoints(O,A,B)
  \tkzLabelPoints[below](O,A,B)
\end{tikzpicture}
```

### 26.1.4. Option R



```
\begin{tikzpicture}[scale=0.75]
  \tkzDefPoints{0/0/0}
  \tkzSetUpCompass[<->]
  \tkzDrawArc[R,color=teal,double](O,3)(270,360)
  \tkzDrawArc[R,color=orange,double](O,2)(0,270)
  \tkzDrawPoint(O)
  \tkzLabelPoint[below](O){$O$}
\end{tikzpicture}
```


### 26.1.5. Option R with nodes



```
\begin{tikzpicture}[scale=0.75]
  \tkzDefPoint(0,0){O}
  \tkzDefPoint(2,-1){A}
  \tkzDefPoint(1,1){B}
  \tkzCalcLength(B,A)\tkzGetLength{radius}
  \tkzDrawArc[R with nodes](B,\radius)(A,O)
\end{tikzpicture}
```

### 26.1.6. Option delta

This option allows a bit like `\tkzCompass` to place an arc and overflow on either side. `delta` is a measure in degrees.



```


\begin{tikzpicture}
  \tkzDefPoint(0,0){A}
  \tkzDefPoint(3,0){B}
  \tkzDefPointBy[rotation= center A angle 60](B)
  \tkzGetPoint{C}

  \begin{scope}% style only local
    \tkzDefPointBy[symmetry= center C](A)
    \tkzGetPoint{D}
    \tkzDrawSegments(A,B A,D)
    \tkzDrawLine(B,D)
    \tkzSetUpCompass[color=orange]
    \tkzDrawArc[orange,delta=10](A,B)(C)
    \tkzDrawArc[orange,delta=10](B,C)(A)
    \tkzDrawArc[orange,delta=10](C,D)(D)
  \end{scope}

  \tkzDrawPoints(A,B,C,D)
  \tkzLabelPoints[below right](A,B,C,D)
  \tkzMarkRightAngle(D,B,A)
\end{tikzpicture}


```

### 26.1.7. Option angles: example 1




```
\begin{tikzpicture}[scale=.75]
\tkzDefPoint(0,0){A}
\tkzDefPoint(5,0){B}
\tkzDefPoint(2.5,0){O}
\tkzDefPointBy[rotation=center O angle 60](B)
\tkzGetPoint{D}
\tkzDefPointBy[symmetry=center D](O)
\tkzGetPoint{E}
\begin{scope}
\tkzDrawArc[angles](O,B)(0,180)
\tkzDrawArc[angles,](B,O)(180,180)
\tkzCompass[delta=20](D,E)
\tkzDrawLines(A,B O,E B,E)
\tkzDrawPoints(A,B,O,D,E)
\end{scope}
\tkzLabelPoints[below right](A,B,O,D,E)
\tkzMarkRightAngle(O,B,E)
\end{tikzpicture}
```

## 26.1.8. Option angles: example 2



```
\begin{tikzpicture}
\tkzDefPoint(0,0){O}
\tkzDefPoint(5,0){I}
\tkzDefPoint(0,5){J}
\tkzInterCC(0,I)(I,0)\tkzGetPoints{B}{C}
\tkzInterCC(0,I)(J,0)\tkzGetPoints{D}{A}
\tkzInterCC(I,0)(J,0)\tkzGetPoints{L}{K}
\tkzDrawArc[angles](O,I)(0,90)
\tkzDrawArc[angles,color=gray,
style=dashed](I,0)(90,180)
\tkzDrawArc[angles,color=gray,
style=dashed](J,0)(-90,0)
\tkzDrawPoints(A,B,K)
\foreach \point in {I,A,B,J,K}{%
\tkzDrawSegment(O,\point)}
\end{tikzpicture}
```

## 26.1.9. Option reverse: inversion of the arrow



```
\begin{tikzpicture}
\tkzDefPoints{0/0/0,3/0/U}
\tkzDefPoint(10:1){A}
\tkzDefPoint(90:1){B}
\tkzLabelPoints(A,B)
\tkzDrawArc[reverse,tkz arrow={Stealth}](O,A)(B)
\tkzDrawPoints(A,B,O)
\end{tikzpicture}
```

## 27. Drawing a sector or sectors

## 27.1. \tkzDrawSector




Attention the arguments vary according to the options.

\tkzDrawSector[ <i>local options</i> ]( <i>O</i> ,...)( <i>A</i> ,...)		
options	default	definition
towards	towards	O is the center and the arc from A to (OB)
rotate	towards	the arc starts from A and the angle determines its length
R	towards	We give the radius and two angles
R with nodes	towards	We give the radius and two points
<i>You have to add, of course, all the styles of TikZ for tracings...</i>		
options	arguments	example
towards	( <i>pt</i> , <i>pt</i> )( <i>pt</i> )	\tkzDrawSector(O,A)(B)
rotate	( <i>pt</i> , <i>pt</i> )( <i>an</i> )	\tkzDrawSector[rotate,color=red](O,A)(90)
R	( <i>pt</i> , <i>r</i> )( <i>an</i> , <i>an</i> )	\tkzDrawSector[R,color=teal](0,2)(30,90)
R with nodes	( <i>pt</i> , <i>r</i> )( <i>pt</i> , <i>pt</i> )	\tkzDrawSector[R with nodes](0,2)(A,B)


Here are a few examples:

27.1.1. `\tkzDrawSector` and `towards`


There's no need to put `towards`. You can use `fill` as an option.



```
\begin{tikzpicture}
  \tkzDefPoint(0,0){O}
  \tkzDefPoint(-30:1){A}
  \tkzDefPointBy[rotation = center O angle -60](A)
  \tkzDrawSector[teal](O,A)(tkzPointResult)
  \begin{scope}[shift={(-60:1)}]
    \tkzDefPoint(0,0){O}
    \tkzDefPoint(-30:1){A}
    \tkzDefPointBy[rotation = center O angle -60](A)
    \tkzDrawSector[red](O,tkzPointResult)(A)
  \end{scope}
\end{tikzpicture}
```

27.1.2. `\tkzDrawSector` and `rotate`


```
\begin{tikzpicture}[scale=2]
  \tkzDefPoints{0/0/0,2/2/A,2/1/B}
  \tkzDrawSector[rotate,orange](O,A)(20)
  \tkzDrawSector[rotate,teal](O,B)(-20)
\end{tikzpicture}
```

27.1.3. `\tkzDrawSector` and `R`

```
\begin{tikzpicture}[scale=1.25]
  \tkzDefPoint(0,0){O}
  \tkzDefPoint(2,-1){A}
  \tkzDrawSector[R](O,1)(30,90)
  \tkzDrawSector[R](O,1)(90,180)
  \tkzDrawSector[R](O,1)(180,270)
  \tkzDrawSector[R](O,1)(270,360)
\end{tikzpicture}
```


27.1.4. `\tkzDrawSector` and `R` with `nodes`

In this example I use the option `fill` but `\tkzFillSector` is possible.



```
\begin{tikzpicture}[scale=1.25]
\tkzDefPoint(0,0){O}
\tkzDefPoint(4,-2){A}
\tkzDefPoint(4,1){B}
\tkzDefPoint(3,3){C}
\tkzDrawSector[R with nodes,%
fill=teal!20](O,1)(B,C)
\tkzDrawSector[R with nodes,%
fill=orange!20](O,1.25)(A,B)
\tkzDrawSegments(O,A O,B O,C)
\tkzDrawPoints(O,A,B,C)
\tkzLabelPoints(A,B,C)
\tkzLabelPoints[left](O)
\end{tikzpicture}
```

### 27.1.5. `\tkzDrawSector` and R with nodes



```
\begin{tikzpicture} [scale=.4]
\tkzDefPoints{-1/-2/A,1/3/B}
\tkzDefRegPolygon[side,sides=6](A,B)
\tkzGetPoint{O}
\tkzDrawPolygon[fill=black!10, draw=blue](P1,P...,P6)
\tkzLabelRegPolygon[sep=1.05](O){A,...,F}
\tkzDrawCircle[dashed](O,A)
\tkzLabelSegment[above,sloped,
midway](A,B){\((A B = 16m\))}
\foreach \i [count=\xi from 1] in {2,...,6,1}
{%
\tkzDefMidPoint(P\xi,P\i)
\path (O) to [pos=1.1] node {\xi} (tkzPointResult) ;
}
\tkzDefRandPointOn[segment = P3--P5]
\tkzGetPoint{S}
\tkzDrawSegments[thick,dashed,red](A,S S,B)
\tkzDrawPoints(P1,P...,P6,S)
\tkzLabelPoint[left,above](S){S}
\tkzDrawSector[R with nodes,fill=red!20](S,2)(A,B)
\tkzLabelAngle[pos=1.5](A,S,B){\(\alpha\)}
\end{tikzpicture}
```

## 27.2. Coloring a disc

This was possible with the macro `\tkzDrawCircle`, but disk tracing was mandatory, this is no longer the case.

`\tkzFillCircle[(local options)]((A,B))`

options	default	definition
radius	radius	two points define a radius
R	radius	a point and the measurement of a radius


You don't need to put **radius** because that's the default option. Of course, you have to add all the styles of TikZ for the plots.

## 27.2.1. Yin and Yang



```
\begin{tikzpicture}[scale=.75]
  \tkzDefPoint(0,0){O}
  \tkzDefPoint(-4,0){A}
  \tkzDefPoint(4,0){B}
  \tkzDefPoint(-2,0){I}
  \tkzDefPoint(2,0){J}
  \tkzDrawSector[fill=teal](O,A)(B)
  \tkzFillCircle[fill=white](J,B)
  \tkzFillCircle[fill=teal](I,A)
  \tkzDrawCircle(O,A)
\end{tikzpicture}
```

## 27.2.2. From a sangaku




```
\begin{tikzpicture}
  \tkzDefPoint(0,0){B}   \tkzDefPoint(6,0){C}%
  \tkzDefSquare(B,C)     \tkzGetPoints{D}{A}
  \tkzClipPolygon(B,C,D,A)
  \tkzDefMidPoint(A,D)   \tkzGetPoint{F}
  \tkzDefMidPoint(B,C)   \tkzGetPoint{E}
  \tkzDefMidPoint(B,D)   \tkzGetPoint{Q}
  \tkzDefLine[tangent from = B](F,A)
  \tkzGetPoints{H}{G}
  \tkzInterLL(F,G)(C,D) \tkzGetPoint{J}
  \tkzInterLL(A,J)(F,E) \tkzGetPoint{K}
  \tkzDefPointBy[projection=onto B--A](K)
  \tkzGetPoint{M}
  \tkzDrawPolygon(A,B,C,D)
  \tkzFillCircle[red!20](E,B)
  \tkzFillCircle[blue!20](M,A)
  \tkzFillCircle[green!20](K,Q)
  \tkzDrawCircles(B,A M,A E,B K,Q)
\end{tikzpicture}
```

## 27.2.3. Clipping and filling part I




```
\begin{tikzpicture}
\tkzDefPoints{0/0/A,4/0/B,2/2/O,3/4/X,4/1/Y,1/0/Z,
              0/3/W,3/0/R,4/3/S,1/4/T,0/1/U}
\tkzDefSquare(A,B)\tkzGetPoints{C}{D}
\tkzDefPointWith[colinear normed=at X,K=1](O,X)
\tkzGetPoint{F}
\begin{scope}
\tkzFillCircle[fill=teal!20](O,F)
\tkzFillPolygon[white](A,...,D)
\tkzClipPolygon(A,...,D)
\foreach \c/\t in {S/C,R/B,U/A,T/D}
{\tkzFillCircle[teal!20](\c,\t)}
\end{scope}
\foreach \c/\t in {X/C,Y/B,Z/A,W/D}
{\tkzFillCircle[white](\c,\t)}
\foreach \c/\t in {S/C,R/B,U/A,T/D}
{\tkzFillCircle[teal!20](\c,\t)}
\end{tikzpicture}
```

## 27.2.4. Clipping and filling part II



```
\begin{tikzpicture}[scale=.75]
\tkzDefPoints{0/0/A,8/0/B,8/8/C,0/8/D}
\tkzDefMidPoint(A,B) \tkzGetPoint{F}
\tkzDefMidPoint(B,C) \tkzGetPoint{E}
\tkzDefMidPoint(D,B) \tkzGetPoint{I}
\tkzDefMidPoint(I,B) \tkzGetPoint{a}
\tkzInterLC(B,I)(B,C) \tkzGetSecondPoint{K}
\tkzDefMidPoint(I,K) \tkzGetPoint{b}
\begin{scope}
\tkzFillSector[fill=blue!10](B,C)(A)
\tkzDefMidPoint(A,B) \tkzGetPoint{x}
\tkzDrawSemiCircle[fill=white](x,B)
\tkzDefMidPoint(B,C) \tkzGetPoint{y}
\tkzDrawSemiCircle[fill=white](y,C)
\tkzClipCircle(E,B)
\tkzClipCircle(F,B)
\tkzFillCircle[fill=blue!10](B,A)
\end{scope}
\tkzDrawSemiCircle[thick](F,B)
\tkzDrawSemiCircle[thick](E,C)
\tkzDrawArc[thick](B,C)(A)
\tkzDrawSegments[thick](A,B)(B,C)
\tkzDrawPoints(A,B,C,E,F)
\tkzLabelPoints[centered](a,b)
\tkzLabelPoints(A,B,C,E,F)
\end{tikzpicture}
```

## 27.2.5. Clipping and filling part III




```
\begin{tikzpicture}
  \tkzDefPoint(0,0){A} \tkzDefPoint(1,0){B}
  \tkzDefPoint(2,0){C} \tkzDefPoint(-3,0){a}
  \tkzDefPoint(3,0){b} \tkzDefPoint(0,3){c}
  \tkzDefPoint(0,-3){d}
\begin{scope}
  \tkzClipPolygon(a,b,c,d)
  \tkzFillCircle[teal!20](A,C)
\end{scope}
  \tkzFillCircle[white](A,B)
  \tkzDrawCircle[color=red](A,C)
  \tkzDrawCircle[color=red](A,B)
\end{tikzpicture}
```

## 27.3. Coloring a polygon

`\tkzFillPolygon[local options](points list)`

You can color by drawing the polygon, but in this case you color the inside of the polygon without drawing it.

arguments	example	explanation
<code>(pt1,pt2,...)</code>	<code>(A,B,...)</code>	

27.3.1. `\tkzFillPolygon`

```
\begin{tikzpicture}[scale=.5]
  \tkzDefPoint(0,0){C} \tkzDefPoint(4,0){A}
  \tkzDefPoint(0,3){B}
  \tkzDefSquare(B,A) \tkzGetPoints{E}{F}
  \tkzDefSquare(A,C) \tkzGetPoints{G}{H}
  \tkzDefSquare(C,B) \tkzGetPoints{I}{J}
  \tkzFillPolygon[color = orange!30](A,C,G,H)
  \tkzFillPolygon[color = teal!40](C,B,I,J)
  \tkzFillPolygon[color = purple!20](B,A,E,F)
  \tkzDrawPolygon[line width = 1pt](A,B,C)
  \tkzDrawPolygon[line width = 1pt](A,C,G,H)
  \tkzDrawPolygon[line width = 1pt](C,B,I,J)
  \tkzDrawPolygon[line width = 1pt](B,A,E,F)
  \tkzLabelSegment[above](C,A){$a$}
  \tkzLabelSegment[right](B,C){$b$}
  \tkzLabelSegment[below left](B,A){$c$}
\end{tikzpicture}
```

27.4. `\tkzFillSector`

Attention the arguments vary according to the options.



```
\tkzFillSector[⟨local options⟩](⟨O,...⟩)(⟨...⟩)
```

options	default	definition
towards	towards	O is the center and the arc from A to (OB)
rotate	towards	the arc starts from A and the angle determines its length
R	towards	We give the radius and two angles
R with nodes	towards	We give the radius and two points

Of course, you have to add all the styles of TikZ for the tracings...

options	arguments	example
towards	(⟨pt,pt⟩)(⟨pt⟩)	<code>\tkzFillSector(O,A)(B)</code>
rotate	(⟨pt,pt⟩)(⟨an⟩)	<code>\tkzFillSector[rotate,color=red](O,A)(90)</code>
R	(⟨pt,r⟩)(⟨an,an⟩)	<code>\tkzFillSector[R,color=blue](O,2)(30,90)</code>
R with nodes	(⟨pt,r⟩)(⟨pt,pt⟩)	<code>\tkzFillSector[R with nodes](O,2)(A,B)</code>


#### 27.4.1. \tkzFillSector and towards

It is useless to put `towards` and you will notice that the contours are not drawn, only the surface is colored.



```
\begin{tikzpicture}[scale=.6]
\tkzDefPoint(0,0){O}
\tkzDefPoint(-30:3){A}
\tkzDefPointBy[rotation = center O angle -60](A)
\tkzFillSector[fill=purple!20](O,A)(tkzPointResult)
\begin{scope}[shift={(-60:1)}]
\tkzDefPoint(0,0){O}
\tkzDefPoint(-30:3){A}
\tkzDefPointBy[rotation = center O angle -60](A)
\tkzGetPoint{A'}
\tkzFillSector[color=teal!40](O,A')(A)
\end{scope}
\end{tikzpicture}
```

#### 27.4.2. \tkzFillSector and rotate



```
\begin{tikzpicture}[scale=1.5]
\tkzDefPoint(0,0){O} \tkzDefPoint(2,2){A}
\tkzFillSector[rotate,color=purple!20](O,A)(30)
\tkzFillSector[rotate,color=teal!40](O,A)(-30)
\end{tikzpicture}
```

#### 27.5. Colour an angle: \tkzFillAngle

The simplest operation


```
\tkzFillAngle[⟨local options⟩](⟨A,O,B⟩)
```

O is the vertex of the angle. OA and OB are the sides. Attention the angle is determined by the order of the points.

options	default	definition
size	1	this option determines the radius of the coloured angular sector.


Of course, you have to add all the styles of TikZ, like the use of fill and shade...

### 27.5.1. Example with size




```
\begin{tikzpicture}
\tkzInit
\tkzDefPoints{0/0/0,2.5/0/A,1.5/2/B}
\tkzFillAngle[size=2, fill=gray!10](A,O,B)
\tkzDrawLines(O,A O,B)
\tkzDrawPoints(O,A,B)
\end{tikzpicture}
```

### 27.5.2. Changing the order of items



```
\begin{tikzpicture}
\tkzInit
\tkzDefPoints{0/0/0,2.5/0/A,1.5/2/B}
\tkzFillAngle[size=2,fill=gray!10](B,O,A)
\tkzDrawLines(O,A O,B)
\tkzDrawPoints(O,A,B)
\end{tikzpicture}
```




```
\begin{tikzpicture}
\tkzInit
\tkzDefPoints{0/0/0,5/0/A,3/4/B}
% Don't forget {} to get, () to use
\tkzFillAngle[size=4,left color=white,
right color=red!50](A,O,B)
\tkzDrawLines(O,A O,B)
\tkzDrawPoints(O,A,B)
\end{tikzpicture}
```

```
\tkzFillAngles[⟨local options⟩](⟨A,O,B⟩)(⟨A',O',B'⟩)etc.
```

With common options, there is a macro for multiple angles.

## 27.5.3. Multiples angles



```
\begin{tikzpicture}[scale=0.5]
\tkzDefPoints{0/0/B,8/0/C,0/8/A,8/8/D}
\tkzDrawPolygon(B,C,D,A)
\tkzDefTriangle[equilateral](B,C) \tkzGetPoint{M}
\tkzInterLL(D,M)(A,B) \tkzGetPoint{N}
\tkzDefPointBy[rotation=center N angle -60](D)
\tkzGetPoint{L}
\tkzInterLL(N,L)(M,B) \tkzGetPoint{P}
\tkzInterLL(M,C)(D,L) \tkzGetPoint{Q}
\tkzDrawSegments(D,N N,L L,D B,M M,C)
\tkzDrawPoints(L,N,P,Q,M,A,D)
\tkzLabelPoints[left](N,P,Q)
\tkzLabelPoints[above](M,A,D)
\tkzLabelPoints(L,B,C)
\tkzMarkAngles(C,B,M B,M,C M,C,B D,L,N L,N,D N,D,L)
\tkzFillAngles[fill=red!20,opacity=.2](C,B,M%
B,M,C M,C,B D,L,N L,N,D N,D,L)
\end{tikzpicture}
```

## 28. Controlling Bounding Box

From the PgfManual :

"When you add the clip option, the current path is used for clipping subsequent drawings. Clipping never enlarges the clipping area. Thus, when you clip against a certain path and then clip again against another path, you clip against the intersection of both. The only way to enlarge the clipping path is to end the pgfscope in which the clipping was done. At the end of a pgfscope the clipping path that was in force at the beginning of the scope is reinstalled."

First of all, you don't have to deal with TikZ the size of the bounding box. Early versions of `tkz-euclide` did not control the size of the bounding box, now with `tkz-euclide 4` the size of the bounding box is limited.

The initial bounding box after using the macro `\tkzInit` is defined by the rectangle based on the points (0,0) and (10,10). The `\tkzInit` macro allows this initial bounding box to be modified using the arguments (`xmin`, `xmax`, `ymin`, and `ymax`). Of course any external trace modifies the bounding box. TikZ maintains that bounding box. It is possible to influence this behavior either directly with commands or options in TikZ such as a command like `\useasboundingbox` or the option `use as bounding box`. A possible consequence is to reserve a box for a figure but the figure may overflow the box and spread over the main text. The following command `\pgfresetboundingbox` clears a bounding box and establishes a new one.

28.1. Utility of `\tkzInit`

However, it is sometimes necessary to control the size of what will be displayed. To do this, you need to have prepared the bounding box you are going to work in, this is the role of the macro `\tkzInit`. For some drawings, it is interesting to fix the extreme values (`xmin`, `xmax`, `ymin` and `ymax`) and to clip the definition rectangle in order to control the size of the figure as well as possible.

The two macros that are useful for controlling the bounding box:

- `\tkzInit`
- `\tkzClip`

To this, I added macros directly linked to the bounding box. You can now view it, backup it, restore it (see the section Bounding Box).

## 28.2. \tkzInit

`\tkzInit[⟨local options⟩]`

options	default	definition
xmin	0	minimum value of the abscissae in cm
xmax	10	maximum value of the abscissae in cm
xstep	1	difference between two graduations in x
ymin	0	minimum y-axis value in cm
ymax	10	maximum y-axis value in cm
ystep	1	difference between two graduations in y

The role of `\tkzInit` is to define a **orthogonal** coordinates system and a rectangular part of the plane in which you will place your drawings using Cartesian coordinates. This macro allows you to define your working environment as with a calculator. With `tkz-euclide 4` `\xstep` and `\ystep` are always 1. Logically it is no longer useful to use `\tkzInit`, except for an action like `Clipping Out`.

## 28.3. \tkzClip


`\tkzClip[⟨local options⟩]`

The role of this macro is to make invisible what is outside the rectangle defined by (xmin ; ymin) and (xmax ; ymax).

options	default	definition
space	1	added value on the right, left, bottom and top of the background

The role of the **space** option is to enlarge the visible part of the drawing. This part becomes the rectangle defined by (xmin-space ; ymin-space) and (xmax+space ; ymax+space). **space** can be negative! The unit is cm and should not be specified.

The role of this macro is to clip the initial rectangle so that only the paths contained in this rectangle are drawn.



```

\begin{tikzpicture}
  \tkzInit[xmax=4, ymax=3]
  \tkzDefPoints{-1/-1/A,5/2/B}
  \tkzDrawX \tkzDrawY
  \tkzGrid
  \tkzClip
  \tkzDrawSegment(A,B)
\end{tikzpicture}


```

It is possible to add a bit of space

```
\tkzClip[space=1]
```

## 28.4. \tkzClip and the option space

This option allows you to add some space around the clipped rectangle.



```
\begin{tikzpicture}
\tkzInit[xmax=4, ymax=3]
\tkzDefPoints{-1/-1/A,5/2/B}
\tkzDrawX \tkzDrawY
\tkzGrid
\tkzClip[space=1]
\tkzDrawSegment(A,B)
\end{tikzpicture}
```

The dimensions of the clipped rectangle are  $x_{min}-1$ ,  $y_{min}-1$ ,  $x_{max}+1$  and  $y_{max}+1$ .


### 28.5. `tkzShowBB`

The simplest macro.

```
\tkzShowBB[<local options>]
```

This macro displays the bounding box. A rectangular frame surrounds the bounding box. This macro accepts TikZ options.

#### 28.5.1. Example with `\tkzShowBB`




```
\begin{tikzpicture}[scale=.5]
\tkzInit[ymax=5,xmax=8]
\tkzGrid
\tkzDefPoint(3,0){A}
\begin{scope}
\tkzClipBB
\tkzDefCircle[R](A,5) \tkzGetPoint{a}
\tkzDrawCircle(A,a)
\tkzShowBB[line width = 4pt,fill=teal!10,%
opacity=.4]
\end{scope}
\tkzDefCircle[R](A,4) \tkzGetPoint{b}
\tkzDrawCircle[red](A,b)
\end{tikzpicture}
```

### 28.6. `tkzClipBB`

```
\tkzClipBB
```

The idea is to limit future constructions to the current bounding box.

28.6.1. Example with `\tkzClipBB` and the bisectors

```

\begin{tikzpicture}
\tkzInit[xmin=-3,xmax=6, ymin=-1,ymax=6]
\tkzDefPoint(0,0){O}\tkzDefPoint(3,1){I}
\tkzDefPoint(1,4){J}
\tkzDefLine[bisector](I,O,J) \tkzGetPoint{i}
\tkzDefLine[bisector out](I,O,J) \tkzGetPoint{j}
\tkzDrawPoints(O,I,J,i,j)
\tkzClipBB
\tkzDrawLines[add = 1 and 2,color=orange](O,I O,J)
\tkzDrawLines[add = 1 and 2](O,i O,j)
\tkzShowBB
\end{tikzpicture}

```


## 29. Clipping different objects

## 29.1. Clipping a polygon


<code>\tkzClipPolygon[⟨local options⟩](⟨points list⟩)</code>
--

This macro makes it possible to contain the different plots in the designated polygon.

arguments	example	explanation
(⟨pt1,pt2,pt3,...⟩)	(⟨A,B,C⟩)	
options	default	definition
out		allows to clip the outside of the object


29.1.1. `\tkzClipPolygon`

```
\begin{tikzpicture}[scale=1.25]
\tkzDefPoint(0,0){A}
\tkzDefPoint(4,0){B}
\tkzDefPoint(1,3){C}
\tkzDrawPolygon(A,B,C)
\tkzDefPoint(0,2){D}
\tkzDefPoint(2,0){E}
\tkzDrawPoints(D,E)
\tkzLabelPoints(D,E)
\tkzClipPolygon(A,B,C)
\tkzDrawLine[new](D,E)
\end{tikzpicture}
```

29.1.2. `\tkzClipPolygon[out]`

```
\begin{tikzpicture}[scale=1]
\tkzDefPoint(0,0){P1}
\tkzDefPoint(4,0){P2}
\tkzDefPoint(4,4){P3}
\tkzDefPoint(0,4){P4}
\tkzDefPoint(1,1){Q1}
\tkzDefPoint(3,1){Q2}
\tkzDefPoint(3,3){Q3}
\tkzDefPoint(1,3){Q4}
\tkzDrawPolygon(P1,P2,P3,P4)
\begin{scope}
\tkzClipPolygon[out](Q1,Q2,Q3,Q4)
\tkzFillPolygon[teal!20](P1,P2,P3,P4)
\end{scope}
\tkzDrawPolygon(Q1,Q2,Q3,Q4)
\end{tikzpicture}
```

## 29.1.3. Example: use of Clip for Sangaku in a square



```
\begin{tikzpicture}[scale=.75]
\tkzDefPoint(0,0){A} \tkzDefPoint(8,0){B}
\tkzDefSquare(A,B) \tkzGetPoints{C}{D}
\tkzDefPoint(4,8){F}
\tkzDefTriangle[equilateral](C,D)
\tkzGetPoint{I}
\tkzDefPointBy[projection=onto B--C](I)
\tkzGetPoint{J}
\tkzInterLL(D,B)(I,J) \tkzGetPoint{K}
\tkzDefPointBy[symmetry=center K](B)
\tkzGetPoint{M}
\tkzClipPolygon(B,C,D,A)
\tkzFillPolygon[color = orange](A,B,C,D)
\tkzFillCircle[color = yellow](M,I)
\tkzFillCircle[color = blue!50!black](F,D)
\end{tikzpicture}
```

## 29.2. Clipping a disc


```
\tkzClipCircle[(local options)](A,B)
```

arguments	example	explanation
(A,B)	(A,B)	AB radius

options	default	definition
out		allows to clip the outside of the object

It is not necessary to put **radius** because that is the default option.

## 29.2.1. Simple clip



```
\begin{tikzpicture}[scale=.5]
\tkzDefPoint(0,0){A} \tkzDefPoint(2,2){O}
\tkzDefPoint(4,4){B} \tkzDefPoint(5,5){C}
\tkzDrawPoints(O,A,B,C)
\tkzLabelPoints(O,A,B,C)
\tkzDrawCircle(O,A)
\tkzClipCircle(O,A)
\tkzDrawLine(A,C)
\tkzDrawCircle[fill=teal!10,opacity=.5](C,O)
\end{tikzpicture}
```



## 29.3. Clip out



```
\begin{tikzpicture}
\tkzInit[xmin=-3,ymin=-2,xmax=4,ymax=3]
\tkzDefPoint(0,0){O}
\tkzDefPoint(-4,-2){A}
\tkzDefPoint(3,1){B}
\tkzDefCircle[R](O,2) \tkzGetPoint{o}
\tkzDrawPoints(A,B) % to have a good bounding box
\begin{scope}
\tkzClipCircle[out](O,o)
\tkzDrawLines(A,B)
\end{scope}
\end{tikzpicture}
```

## 29.4. Intersection of disks



```
\begin{tikzpicture}
\tkzDefPoints{O/0/0,4/A/0,0/4/B}
\tkzDrawPolygon[fill=teal](O,A,B)
\tkzClipPolygon(O,A,B)
\tkzClipCircle(A,O)
\tkzClipCircle(B,O)
\tkzFillPolygon[white](O,A,B)
\end{tikzpicture}
```

see a more complex example about clipping here : [47.6](#)

## 29.5. Clipping a sector



Attention the arguments vary according to the options.


```
\tkzClipSector[local options](O,...)(...)
```

options	default	definition
towards	towards	O is the center and the sector starts from A to (OB)
rotate	towards	The sector starts from A and the angle determines its amplitude.
R	towards	We give the radius and two angles

You have to add, of course, all the styles of TikZ for tracings...

options	arguments	example
towards	( <i>pt,pt</i> )( <i>pt</i> )	\tkzClipSector(O,A)(B)
rotate	( <i>pt,pt</i> )( <i>angle</i> )	\tkzClipSector[rotate](O,A)(90)
R	( <i>pt,r</i> )( <i>angle 1,angle 2</i> )	\tkzClipSector[R](O,2)(30,90)

## 29.5.1. Example 1




```

\begin{tikzpicture}[scale=0.5]
\tkzDefPoint(0,0){a}
\tkzDefPoint(12,0){b}
\tkzDefPoint(4,10){c}
\tkzInterCC[R](a,6)(b,8)
\tkzGetFirstPoint{AB1} \tkzGetSecondPoint{AB2}
\tkzInterCC[R](a,6)(c,6)
\tkzGetFirstPoint{AC1} \tkzGetSecondPoint{AC2}
\tkzInterCC[R](b,8)(c,6)
\tkzGetFirstPoint{BC1} \tkzGetSecondPoint{BC2}
\tkzDrawArc(a,AB2)(AB1)
\tkzDrawArc(b,AB1)(AB2)
\tkzDrawArc(a,AC2)(AC1)
\tkzDrawArc(c,AC1)(AC2)
\tkzDrawArc(b,BC2)(BC1)
\tkzDrawArc(c,BC1)(BC2)
\begin{scope}
\tkzClipSector(b,BC2)(BC1)
\tkzFillSector[teal!40!white](c,BC1)(BC2)
\end{scope}
\begin{scope}
\tkzClipSector(a,AB2)(AB1)
\tkzFillSector[teal!40!white](b,AB1)(AB2)
\end{scope}
\begin{scope}
\tkzClipSector(a,AC2)(AC1)
\tkzFillSector[teal!40!white](c,AC1)(AC2)
\end{scope}
\end{tikzpicture}

```

## 29.5.2. Example 2



```

\begin{tikzpicture}[scale=1.5]
\tkzDefPoint(0,0){O}
\tkzDefPoint(2,-1){A}
\tkzDefPoint(1,1){B}
\tkzDrawSector[new,dashed](O,A)(B)
\tkzDrawSector[new](O,B)(A)
\begin{scope}
\tkzClipSector(O,B)(A)
\tkzDefSquare(O,B) \tkzGetPoints{B'}{O'}
\tkzDrawPolygon[color=teal,fill=teal!20](O,B,B',O')
\end{scope}
\tkzDrawPoints(A,B,O)
\end{tikzpicture}

```


## 29.6. Options from TikZ: trim left or right

See the pgfmanual

29.7. TikZ Controls `\pgfinterruptboundingbox` and `\endpgfinterruptboundingbox`

This command temporarily interrupts the calculation of the box and configures a new box. See the pgfmanual

## 29.7.1. Example about controlling the bounding box



```
\begin{tikzpicture}
\tkzDefPoint(0,5){A}\tkzDefPoint(5,4){B}
\tkzDefPoint(0,0){C}\tkzDefPoint(5,1){D}
\tkzDrawSegments(A,B C,D A,C)
\pgfinterruptboundingbox
\tkzInterLL(A,B)(C,D)\tkzGetPoint{I}
\endpgfinterruptboundingbox
\tkzClipBB
\tkzDrawCircle(I,B)
\end{tikzpicture}
```


## 29.8. Reverse clip: tkzreverseclip

In order to use this option, a bounding box must be defined.

```
\tikzset{tkzreverseclip/.style={insert path={
(current bounding box.south west) --(current bounding box.north west)
--(current bounding box.north east) -- (current bounding box.south east)
-- cycle} }}
```

## 29.8.1. Example with \tkzClipPolygon[out]

\tkzClipPolygon[out], \tkzClipCircle[out] use this option.



```
\begin{tikzpicture}[scale=1]
\tkzInit[xmin=-5,xmax=5,ymin=-4,ymax=6]
\tkzClip
\tkzDefPoints{-.5/0/P1,.5/0/P2}
\foreach \i [count=\j from 3] in {2,...,7}{%
  \tkzDefShiftPoint[P\i]({45*(\i-1)}:1){P\j}}
\tkzClipPolygon[out](P1,P...,P8)
\tkzCalcLength(P1,P5)\tkzGetLength{r}
\begin{scope}[blend group=screen]
  \foreach \i in {1,...,8}{%
    \tkzDefCircle[R](P\i,\r) \tkzGetPoint{x}
    \tkzFillCircle[color=teal](P\i,x)}
  \end{scope}
\end{tikzpicture}
```

Part V.

Marking

## 29.9. Mark a segment `\tkzMarkSegment`


`\tkzMarkSegment[⟨local options⟩](⟨pt1,pt2⟩)`

The macro allows you to place a mark on a segment.

options	default	definition
pos	.5	position of the mark
color	black	color of the mark
mark	none	choice of the mark
size	4pt	size of the mark


Possible marks are those provided by TikZ, but other marks have been created based on an idea by Yves Combe.

### 29.9.1. Several marks



```
\begin{tikzpicture}
\tkzDefPoint(2,1){A}
\tkzDefPoint(6,4){B}
\tkzDrawSegment(A,B)
\tkzMarkSegment[color=brown,size=2pt,pos=0.4, mark=z](A,B)
\tkzMarkSegment[color=blue,pos=0.2, mark=oo](A,B)
\tkzMarkSegment[pos=0.8,mark=s,color=red](A,B)
\end{tikzpicture}
```

### 29.9.2. Use of mark




```
\begin{tikzpicture}
\tkzDefPoint(2,1){A}
\tkzDefPoint(6,4){B}
\tkzDrawSegment(A,B)
\tkzMarkSegment[color=gray,pos=0.2,mark=s](A,B)
\tkzMarkSegment[color=gray,pos=0.4,mark=s](A,B)
\tkzMarkSegment[color=brown,pos=0.6,mark=||](A,B)
\tkzMarkSegment[color=red,pos=0.8,mark=|||](A,B)
\end{tikzpicture}
```

## 29.10. Marking segments `\tkzMarkSegments`

`\tkzMarkSegments[⟨local options⟩](⟨pt1,pt2 pt3,pt4 ...⟩)`


Arguments are a list of pairs of points separated by spaces. The styles of TikZ are available for plots.

### 29.10.1. Marks for an isosceles triangle



```
\begin{tikzpicture}[scale=1]
\tkzDefPoints{0/0/0,2/2/A,4/0/B,6/2/C}
\tkzDrawSegments(O,A A,B)
\tkzDrawPoints(O,A,B)
\tkzDrawLine(O,B)
\tkzMarkSegments[mark=||,size=6pt](O,A A,B)
\end{tikzpicture}
```

### 29.11. Another marking



```
\begin{tikzpicture}[scale=1]
\tkzDefPoint(0,0){A}\tkzDefPoint(3,2){B}
\tkzDefPoint(4,0){C}\tkzDefPoint(2.5,1){P}
\tkzDrawPolygon(A,B,C)
\tkzDefEquilateral(A,P) \tkzGetPoint{P'}
\tkzDefPointsBy[rotation=center A angle 60](P,B){P',C'}
\tkzDrawPolygon(A,P,P')
\tkzDrawPolySeg(P',C',A,P,B)
\tkzDrawSegment(C,P)
\tkzDrawPoints(A,B,C,C',P,P')
\tkzMarkSegments[mark=s|,size=6pt,
color=blue](A,P P,P' P',A)
\tkzMarkSegments[mark=||,color=orange](B,P P',C')
\tkzLabelPoints(A,C) \tkzLabelPoints[below](P)
\tkzLabelPoints[above right](P',C',B)
\end{tikzpicture}
```

### 29.12. Mark an arc \tkzMarkArc

`\tkzMarkArc[local options](pt1,pt2,pt3)`


The macro allows you to place a mark on an arc. *pt1* is the center, *pt2* and *pt3* are the endpoints of the arc.

options	default	definition
pos	.5	position of the mark
color	black	color of the mark
mark	none	choice of the mark
size	4pt	size of the mark

Possible marks are those provided by TikZ, but other marks have been created based on an idea by Yves Combe.

|, ||,|||, z, s, x, o, oo

#### 29.12.1. Several marks



```
\begin{tikzpicture}
\tkzDefPoint(0,0){O}
\pgfmathsetmacro\r{2}
\tkzDefPoint(30:\r){A}
\tkzDefPoint(85:\r){B}
\tkzDrawCircle(O,A)
\tkzMarkArc[color=red,mark=||](O,A,B)
\tkzDrawPoints(B,A,O)
\end{tikzpicture}
```

### 29.13. Mark an angle mark : \tkzMarkAngle

More delicate operation because there are many options. The symbols used for marking in addition to those of TikZ are defined in the file `tkz-lib-marks.tex` and designated by the following characters:


|, ||, |||, z, s, x, o, oo

`\tkzMarkAngle[⟨local options⟩](⟨A,O,B⟩)`

O is the vertex. Attention the arguments vary according to the options. Several markings are possible. You can simply draw an arc or add a mark on this arc. The style of the arc is chosen with the option `arc`, the radius of the arc is given by `mksize`, the arc can, of course, be colored.

options	default	definition
<code>arc</code>	1	choice of 1, ll and lll (single, double or triple).
<code>size</code>	1 (cm)	arc radius.
<code>mark</code>	none	choice of mark.
<code>mksize</code>	4pt	symbol size (mark).
<code>mkcolor</code>	black	symbol color (mark).
<code>mkpos</code>	0.5	position of the symbol on the arc.

### 29.13.1. Example with `mark = x` and with `mark = ||`



```
\begin{tikzpicture}[scale=.75]
\tkzDefPoints{0/0/0,5/0/A,3/4/B}
\tkzMarkAngle[size = 4,mark = x,
               arc=ll,mkcolor = red,mkpos=.33](A,O,B)
\tkzMarkAngle[size = 2,mark = ||,
               arc=ll,mkcolor = blue,mkpos=.66](A,O,B)
\tkzDrawLines(O,A O,B)
\tkzDrawPoints(O,A,B)
\end{tikzpicture}
```


`\tkzMarkAngles[⟨local options⟩](⟨A,O,B⟩)(⟨A',O',B'⟩)etc.`

With common options, there is a macro for multiple angles.

### 29.14. Problem to mark a small angle: Option `vecLen`

The problem comes from the "decorate" action and from the value used in `size` in `\tkzMarkAngle`. The solution is to enclose the macro `\tkzMarkAngle`. In the next example without the "scope" the result is : Latex Error: Dimension too large.





```
\begin{tikzpicture}[scale=1]
  \tkzDefPoint(0,0){O}
  \tkzDefPoint(2.5,0){N}
  \tkzDefPoint(-4.2,0.5){M}
  \tkzDefPointBy[rotation=center O angle 30](N)
  \tkzGetPoint{B}
  \tkzDefPointBy[rotation=center O angle -50](N)
  \tkzGetPoint{A}
  \tkzInterLC[common=B](M,B)(O,B) \tkzGetFirstPoint{C}
  \tkzInterLC[common=A](M,A)(O,A) \tkzGetFirstPoint{A'}
  \tkzDrawSegments(A,C M,A M,B A,B)
  \tkzDrawCircle(O,N)
  \begin{scope}[vecclen]
    \tkzMarkAngle[mkpos=.2, size=1.2](C,A,M)
  \end{scope}
  \tkzDrawPoints(O, A, B, M, B, C, A')
  \tkzLabelPoints[right](O,A,B)
  \tkzLabelPoints[above left](M,C)
  \tkzLabelPoint[below left](A'){$A'$}
\end{tikzpicture}
```


### 29.15. Marking a right angle: `\tkzMarkRightAngle`

`\tkzMarkRightAngle[⟨local options⟩](⟨A,O,B⟩)`

The **german** option allows you to change the style of the drawing. The option **size** allows to change the size of the drawing.


options	default	definition
german	normal	german arc with inner point.
size	0.2	side size.

#### 29.15.1. Example of marking a right angle




```
\begin{tikzpicture}
  \tkzDefPoints{0/0/A,3/1/B,0.9/-1.2/P}
  \tkzDefPointBy[projection = onto B--A](P) \tkzGetPoint{H}
  \tkzDrawLines[add=.5 and .5](P,H)
  \tkzMarkRightAngle[fill=blue!20,size=.5,draw](A,H,P)
  \tkzDrawLines[add=.5 and .5](A,B)
  \tkzMarkRightAngle[fill=red!20,size=.8](B,H,P)
  \tkzDrawPoints[] (A,B,P,H)
\end{tikzpicture}
```

### 29.15.2. Example of marking a right angle, german style




```
\begin{tikzpicture}
  \tkzDefPoints{0/0/A,3/1/B,0.9/-1.2/P}
  \tkzDefPointBy[projection = onto B--A](P) \tkzGetPoint{H}
  \tkzDrawLines[add=.5 and .5](P,H)
  \tkzMarkRightAngle[german,size=.5,draw](A,H,P)
  \tkzDrawPoints[] (A,B,P,H)
  \tkzDrawLines[add=.5 and .5](A,B)
  \tkzMarkRightAngle[german,size=.8](P,H,B)
\end{tikzpicture}
```

### 29.15.3. Mix of styles



```
\begin{tikzpicture}[scale=.75]
  \tkzDefPoint(0,0){A}
  \tkzDefPoint(4,1){B}
  \tkzDefPoint(2,5){C}
  \tkzDefPointBy[projection=onto B--A](C)
  \tkzGetPoint{H}
  \tkzDrawLine(A,B)
  \tkzDrawLine[add = .5 and .2,color=red](C,H)
  \tkzMarkRightAngle[,size=1,color=red](C,H,A)
  \tkzMarkRightAngle[german,size=.8,color=blue](B,H,C)
  \tkzFillAngle[opacity=.2,fill=blue!20,size=.8](B,H,C)
  \tkzLabelPoints(A,B,C,H)
  \tkzDrawPoints(A,B,C,H)
\end{tikzpicture}
```

## 29.15.4. Full example



```

\begin{tikzpicture}[rotate=-90]
\tkzDefPoint(0,1){A}
\tkzDefPoint(2,4){C}
\tkzDefPointWith[orthogonal normed,K=7](C,A)
\tkzGetPoint{B}
\tkzDrawSegment[green!60!black](A,C)
\tkzDrawSegment[green!60!black](C,B)
\tkzDrawSegment[green!60!black](B,A)
\tkzDefSpcTriangle[orthic](A,B,C){N,O,P}
\tkzDrawLine[dashed,color=magenta](C,P)
\tkzLabelPoint[left](A){$A$}
\tkzLabelPoint[right](B){$B$}
\tkzLabelPoint[above](C){$C$}
\tkzLabelPoint[left](P){$P$}
\tkzLabelSegment[auto](B,A){$c$}
\tkzLabelSegment[auto,swap](B,C){$a$}
\tkzLabelSegment[auto,swap](C,A){$b$}
\tkzMarkAngle[size=1,color=cyan,mark=|](C,B,A)
\tkzMarkAngle[size=1,color=cyan,mark=|](A,C,P)
\tkzMarkAngle[size=0.75,color=orange,
mark=||](P,C,B)
\tkzMarkAngle[size=0.75,color=orange,
mark=||](B,A,C)
\tkzMarkRightAngle[german](A,C,B)
\tkzMarkRightAngle[german](B,P,C)
\end{tikzpicture}

```

29.16. `\tkzMarkRightAngles`

```
\tkzMarkRightAngles[⟨local options⟩](⟨A,O,B⟩)(⟨A',O',B'⟩)etc.
```

With common options, there is a macro for multiple angles.

## 29.17. Angles Library

If you prefer to use TikZ library `angles`, you can mark angles with the macro `\tkzPicAngle` and `\tkzPicRightAngle`.

```
\tkzPicAngle[⟨tikz options⟩](⟨A,O,B⟩)
```


options	example	definition
tikz option	see below	drawing of the angle $\widehat{AOB}$ .

```
\tkzPicRightAngle[⟨tikz options⟩](⟨A,O,B⟩)
```

options	example	definition
tikz option	see below	drawing of the right angle $\widehat{AOB}$ .

You need to know possible options of the `angles` library

## 29.17.1. Angle with TikZ



```

\begin{tikzpicture}
\tkzDefPoints{0/0/A,4/0/B}
\tkzDefTriangle[right,swap](A,B) \tkzGetPoint{C}
\tkzDrawPolygon(A,B,C)
\tkzDrawPoints(A,B,C)
\tkzLabelPoints[below](B,A)
\tkzLabelPoints[above right](C)
\tkzPicAngle["$\alpha$",draw=orange,
             <->,angle eccentricity=1.2,
             angle radius=1cm](B,A,C)
\tkzPicRightAngle[draw,red,thick,
                  angle eccentricity=.5,
                  pic text=.](C,B,A)
\end{tikzpicture}

```

Part VI.

Labelling

## 30. Labelling


## 30.1. Label for a point

It is possible to add several labels at the same point by using this macro several times.

<code>\tkzLabelPoint[<i>(local options)</i>](<i>(point)</i>){<i>(label)</i>}</code>
---

arguments	example	
point	<code>\tkzLabelPoint(A){\$A_1\$}</code>	
options	default	definition
TikZ options	colour, position etc.	

Optionally, we can use any style of TikZ, especially placement with above, right, dots...

30.1.1. Example with `\tkzLabelPoint`

```
\begin{tikzpicture}
\tkzDefPoint(0,0){A}
\tkzDefPoint(4,0){B}
\tkzDefPoint(0,3){C}
\tkzDrawSegments(A,B B,C C,A)
\tkzDrawPoints(A,B,C)
\tkzLabelPoint[left,red](A){$A$}
\tkzLabelPoint[right,blue](B){$B$}
\tkzLabelPoint[above,purple](C){$C$}
\end{tikzpicture}
```

## 30.1.2. Label and reference

The reference of a point is the object that allows to use the point, the label is the name of the point that will be displayed.



```
\begin{tikzpicture}
\tkzDefPoint(2,0){A}
\tkzDrawPoint(A)
\tkzLabelPoint[above](A){$A_1$}
\end{tikzpicture}
```


30.2. Add labels to points `\tkzLabelPoints`

It is possible to place several labels quickly when the point references are identical to the labels and when the labels are placed in the same way in relation to the points. By default, below right is chosen.

<code>\tkzLabelPoints[<i>(local options)</i>](<i>(A_1,A_2,...)</i>)</code>
--

arguments	example	result
list of points	<code>\tkzLabelPoints(A,B,C)</code>	Display of A, B and C

This macro reduces the number of lines of code, but it is not obvious that all points need the same label positioning.

30.2.1. Example with `\tkzLabelPoints`30.3. Automatic position of labels `\tkzAutoLabelPoints`


The label of a point is placed in a direction defined by a center and a point `center`. The distance to the point is determined by a percentage of the distance between the center and the point. This percentage is given by `dist`.

`\tkzLabelPoints[<local options>](<A1,A2,...>)`

arguments	example	result
list of points	<code>\tkzLabelPoint(A,B,C)</code>	Display of A, B and C

30.3.1. Label for points with `\tkzAutoLabelPoints`

Here the points are positioned relative to the center of gravity of A, B, C and O.



```

\begin{tikzpicture}[scale=1]
  \tkzDefPoint(2,1){O}
  \tkzDefRandPointOn[circle=center O radius 1.5]\tkzGetPoint{A}
  \tkzDefPointBy[rotation=center O angle 100](A)\tkzGetPoint{C}
  \tkzDefPointBy[rotation=center O angle 78](A)\tkzGetPoint{B}
  \tkzDrawCircle(O,A)
  \tkzDrawPoints(O,A,B,C)
  \tkzDrawSegments(C,B B,A A,O O,C)
  \tkzDefTriangleCenter[centroid](A,B,C) \tkzGetPoint{O}
  \tkzDrawPoint(tkzPointResult)
  \tkzLabelPoints(O,A,C,B)
\end{tikzpicture}

```

## 31. Label for a segment

`\tkzLabelSegment[<local options>](<pt1,pt2>){<label>}`

This macro allows you to place a label along a segment or a line. The options are those of TikZ for example `pos`.


argument	example	definition
label	<code>\tkzLabelSegment(A,B){5}</code>	label text
(pt1,pt2)	(A,B)	label along [AB]
options	default	definition
pos	.5	label's position

## 31.0.1. First example




```
\begin{tikzpicture}
\tkzDefPoint(0,0){A}
\tkzDefPoint(6,0){B}
\tkzDrawSegment(A,B)
\tkzLabelSegment[above,pos=.8](A,B){$a$}
\tkzLabelSegment[below,pos=.2](A,B){$4$}
\end{tikzpicture}
```

## 31.0.2. Example : blackboard



```
\tikzstyle{background rectangle}=[fill=black]
\begin{tikzpicture}[show background rectangle,scale=.4]
\tkzDefPoint(0,0){O}
\tkzDefPoint(1,0){I}
\tkzDefPoint(10,0){A}
\tkzDefPointWith[orthogonal normed,K=4](I,A)
\tkzGetPoint{H}
\tkzDefMidPoint(O,A)\tkzGetPoint{M}
\tkzInterLC(I,H)(M,A)\tkzGetPoints{B}{C}
\tkzDrawSegments[color=white,line width=1pt](I,H O,A)
\tkzDrawPoints[color=white](O,I,A,B,M)
\tkzMarkRightAngle[color=white,line width=1pt](A,I,B)
\tkzDrawArc[color=white,line width=1pt,
style=dashed](M,A)(O)
\tkzLabelSegment[white,right=1ex,pos=.5](I,B){$\sqrt{a}$}
\tkzLabelSegment[white,below=1ex,pos=.5](O,I){$1$}
\tkzLabelSegment[pos=.6,white,below=1ex](I,A){$a$}
\end{tikzpicture}
```

## 31.0.3. Labels and option : swap




```
\begin{tikzpicture}[rotate=-60]
\tkzSetUpStyle[red,auto]{label style}
\tkzDefPoint(0,1){A}
\tkzDefPoint(2,4){C}
\tkzDefPointWith[orthogonal normed,K=7](C,A)
\tkzGetPoint{B}
\tkzDefSpcTriangle[orthic](A,B,C){N,O,P}
\tkzDefTriangleCenter[circum](A,B,C)
\tkzGetPoint{O}
\tkzDrawPolygon[green!60!black](A,B,C)
\tkzDrawLine[dashed,color=magenta](C,P)
\tkzLabelSegment(B,A){$c$}
\tkzLabelSegment[swap](B,C){$a$}
\tkzLabelSegment[swap](C,A){$b$}
\tkzMarkAngles[size=1,
color=cyan,mark=|](C,B,A A,C,P)
\tkzMarkAngle[size=0.75,
color=orange,mark=||](P,C,B)
\tkzMarkAngle[size=0.75,
color=orange,mark=||](B,A,C)
\tkzMarkRightAngles[german](A,C,B B,P,C)
\tkzAutoLabelPoints[center = 0,dist= .1](A,B,C)
\tkzLabelPoint[below left](P){$P$}
\end{tikzpicture}
```



```
\tkzLabelSegments[⟨local options⟩](⟨pt1,pt2 pt3,pt4 ...⟩)
```

The arguments are a two-point couple list. The styles of TikZ are available for plotting.

#### 31.0.4. Labels for an isosceles triangle



```
\begin{tikzpicture}[scale=1]
\tkzDefPoints{0/0/0,2/2/A,4/0/B,6/2/C}
\tkzDrawSegments(0,A A,B)
\tkzDrawPoints(0,A,B)
\tkzDrawLine(0,B)
\tkzLabelSegments[color=red,above=4pt](0,A A,B){$a$}
\end{tikzpicture}
```

### 32. Add labels on a straight line `\tkzLabelLine`

```
\tkzLabelLine[⟨local options⟩](⟨pt1,pt2⟩){⟨label⟩}
```


arguments	default	definition
label		<code>\tkzLabelLine(A,B){\$\Delta\$}</code>
options		
pos	.5	pos is an option for TikZ, but essential in this case...

As an option, and in addition to the **pos**, you can use all styles of TikZ, especially the placement with **above**, **right**, ...

#### 32.0.1. Example with `\tkzLabelLine`

An important option is **pos**, it's the one that allows you to place the label along the right. The value of **pos** can be greater than 1 or negative.

again ( $\delta$ )



```
\begin{tikzpicture}
\tkzDefPoints{0/0/A,3/0/B,1/1/C}
\tkzDefLine[perpendicular=through C,K=-1](A,B)
\tkzGetPoint{c}
\tkzDrawLines(A,B C,c)
\tkzLabelLine[pos=1.25,blue,right](C,c){$(\delta)$}
\tkzLabelLine[pos=-0.25,red,left](C,c){again $(\delta)$}
\end{tikzpicture}
```

#### 32.1. Label at an angle : `\tkzLabelAngle`


```
\tkzLabelAngle[⟨local options⟩](⟨A,0,B⟩)
```

There is only one option, **dist** (with or without unit), which can be replaced by the TikZ's **pos** option (without unit for the latter). By default, the value is in centimeters.

options	default	definition
pos	1	or dist, controls the distance from the top to the label.

It is possible to move the label with all TikZ options : rotate, shift, below, etc.

## 32.1.1. Example author js bibra stackexchange




```

\begin{tikzpicture}[scale=.75]
  \tkzDefPoint(0,0){C}
  \tkzDefPoint(20:9){B}
  \tkzDefPoint(80:5){A}
  \tkzDefPointsBy[projection=onto B--C](A){a}
  \tkzDrawPolygon[thick,fill=yellow!15](A,B,C)
  \tkzDrawSegment[dashed, red](A,a)
  \tkzDrawSegment[style=red, dashed,
    dim={\$10$,15pt,midway,font=\scriptsize,
    rotate=90}](A,a)
  \tkzMarkAngle(B,C,A)
  \tkzMarkRightAngle(A,a,C)
  \tkzMarkRightAngle(C,A,B)
  \tkzFillAngle[fill=blue!20, opacity=0.5](B,C,A)
  \tkzFillAngle[fill=red!20, opacity=0.5](A,B,C)
  \tkzLabelAngle[pos=1.25](A,B,C){\$ \beta \$}
  \tkzLabelAngle[pos=1.25](B,C,A){\$ \alpha \$}
  \tkzMarkAngle(A,B,C)
  \tkzDrawPoints(A,B,C)
  \tkzLabelPoints(B,C)
  \tkzLabelPoints[above](A)
\end{tikzpicture}

```

## 32.1.2. With pos




```

\begin{tikzpicture}[scale=.75]
  \tkzDefPoints{0/0/0,5/0/A,3/4/B}
  \tkzMarkAngle[size = 4,mark = ||,
    arc=ll,color = red](A,0,B)%
  \tkzDrawLines(0,A 0,B)
  \tkzDrawPoints(0,A,B)
  \tkzLabelAngle[pos=2,draw,circle,
    fill=blue!10](A,0,B){\$ \alpha \$}
\end{tikzpicture}

```

## 32.1.3. pos and \tkzLabelAngles



```

\begin{tikzpicture}[rotate=30]
  \tkzDefPoint(2,1){S}
  \tkzDefPoint(7,3){T}
  \tkzDefPointBy[rotation=center S angle 60](T)
  \tkzGetPoint{P}
  \tkzDefLine[bisector, normed](T,S,P)
  \tkzGetPoint{s}
  \tkzDrawPoints(S,T,P)
  \tkzDrawPolygon[color=blue](S,T,P)
  \tkzDrawLine[dashed,color=blue,add=0 and 3](S,s)
  \tkzLabelPoint[above right](P){P}
  \tkzLabelPoints(S,T)
  \tkzMarkAngle[size = 1.8, mark = |, arc=11,
    color = blue](T,S,P)
  \tkzMarkAngle[size = 2.1, mark = |, arc=1,
    color = blue](T,S,s)
  \tkzMarkAngle[size = 2.3, mark = |, arc=1,
    color = blue](s,S,P)
  \tkzLabelAngle[pos = 1.5](T,S,P){60^\circ}
  \tkzLabelAngles[pos = 2.7](T,S,s s,S,P){%
    30^\circ}
\end{tikzpicture}

```

`\tkzLabelAngles[local options](A,O,B)(A',O',B')etc.`

With common options, there is a macro for multiple angles.

It finally remains to be able to give a label to designate a circle and if several possibilities are offered, we will see here \tkzLabelCircle.


## 32.2. Giving a label to a circle

`\tkzLabelCircle[tikz options](O,A)(angle){label}`

options	default	definition
tikz options		circle O center through A

*We can use the styles from TikZ. The label is created and therefore passed between braces.*

## 32.2.1. Example



```
\begin{tikzpicture}
\tkzDefPoint(0,0){O} \tkzDefPoint(2,0){N}
\tkzDefPointBy[rotation=center O angle 50](N)
\tkzGetPoint{M}
\tkzDefPointBy[rotation=center O angle -20](N)
\tkzGetPoint{P}
\tkzDefPointBy[rotation=center O angle 125](N)
\tkzGetPoint{P'}
\tkzLabelCircle[above=4pt](O,N)(120){$\mathcal{C}$}
\tkzDrawCircle(O,M)
\tkzFillCircle[color=blue!10,opacity=.4](O,M)
\tkzLabelCircle[draw,
text width=2cm,text centered,left=24pt](O,M)(-120)%
{The circle\ \ $\mathcal{C}$}
\tkzDrawPoints(M,P)\tkzLabelPoints[right](M,P)
\end{tikzpicture}
```


## 33. Label for an arc

`\tkzLabelArc[⟨local options⟩](⟨pt1,pt2,pt3⟩){⟨label⟩}`

This macro allows you to place a label along an arc. The options are those of TikZ for example `pos`.

argument	example	definition
label	<code>\tkzLabelArc(A,B){5}</code>	label text
(pt1,pt2,pt3)	(O,A,B)	label along the arc $\widehat{AB}$
options	default	definition
pos	.5	label's position

## 33.0.1. Label on arc



```
\begin{tikzpicture}
\tkzDefPoint(0,0){O}
\pgfmathsetmacro\r{2}
\tkzDefPoint(30:\r){A}
\tkzDefPoint(85:\r){B}
\tkzDrawCircle(O,A)
\tkzDrawPoints(B,A,O)
\tkzLabelArc[right=2pt](O,A,B){$\widehat{AB}$}
\tkzLabelPoints(A,B,O)
\end{tikzpicture}
```

Part VII.

Complements

## 34. Using the compass


34.1. Main macro `\tkzCompass`

`\tkzCompass[⟨local options⟩](⟨A,B⟩)`


This macro allows you to leave a compass trace, i.e. an arc at a designated point. The center must be indicated. Several specific options will modify the appearance of the arc as well as TikZ options such as style, color, line thickness etc.

You can define the length of the arc with the option `length` or the option `delta`.

options	default	definition
<code>delta</code>	0 (deg)	Increases the angle of the arc symmetrically
<code>length</code>	1 (cm)	Changes the length (in cm)

34.1.1. Option `length`

```
\begin{tikzpicture}
\tkzDefPoint(1,1){A}
\tkzDefPoint(6,1){B}
\tkzInterCC[R](A,4)(B,3)
\tkzGetPoints{C}{D}
\tkzDrawPoint(C)
\tkzCompass[length=1.5](A,C)
\tkzCompass(B,C)
\tkzDrawSegments(A,B A,C B,C)
\end{tikzpicture}
```

34.1.2. Option `delta`

```
\begin{tikzpicture}
\tkzDefPoint(0,0){A}
\tkzDefPoint(5,0){B}
\tkzInterCC[R](A,4)(B,3)
\tkzGetPoints{C}{D}
\tkzDrawPoints(A,B,C)
\tkzCompass[delta=20](A,C)
\tkzCompass[delta=20](B,C)
\tkzDrawPolygon(A,B,C)
\tkzMarkAngle(A,C,B)
\end{tikzpicture}
```


34.2. Multiple constructions `\tkzCompass`

`\tkzCompass[⟨local options⟩](⟨pt1,pt2 pt3,pt4,...⟩)`



Attention the arguments are lists of two points. This saves a few lines of code.

options	default	definition
<code>delta</code>	0	Modifies the angle of the arc by increasing it symmetrically
<code>length</code>	1	Changes the length

34.2.1. Use `\tkzCompass`

```
\begin{tikzpicture}[scale=.6]
\tkzDefPoint(2,2){A} \tkzDefPoint(5,-2){B}
\tkzDefPoint(3,4){C} \tkzDrawPoints(A,B)
\tkzDrawPoint[shape=cross out](C)
\tkzCompass[new](A,B A,C B,C C,B)
\tkzShowLine[mediator,new,dashed,length = 2](A,B)
\tkzShowLine[parallel = through C,
              color=purple,length=2](A,B)
\tkzDefLine[mediator](A,B)
\tkzGetPoints{i}{j}
\tkzDefLine[parallel=through C](A,B)
\tkzGetPoint{D}
\tkzDrawLines[add=.6 and .6](C,D A,C B,D)
\tkzDrawLines(i,j) \tkzDrawPoints(A,B,C,i,j,D)
\tkzLabelPoints(A,B,C,i,j,D)
\end{tikzpicture}
```

## 35. The Show


35.1. Show the constructions of some lines `\tkzShowLine`

`\tkzShowLine[local options](<pt1,pt2>) or (<pt1,pt2,pt3>)`


These constructions concern mediatrices, perpendicular or parallel lines passing through a given point and bisectors. The arguments are therefore lists of two or three points. Several options allow the adjustment of the constructions. The idea of this macro comes from Yves Combe.

options	default	definition
mediator	mediator	displays the constructions of a mediator
perpendicular	mediator	constructions for a perpendicular
orthogonal	mediator	idem
bisector	mediator	constructions for a bisector
K	1	circle within a triangle
length	1	in cm, length of a arc
ratio	.5	arc length ratio
gap	2	placing the point of construction
size	1	radius of an arc (see bisector)


You have to add, of course, all the styles of TikZ for tracings...

35.1.1. Example of `\tkzShowLine` and `parallel`


```
\begin{tikzpicture}
\tkzDefPoints{-1.5/-0.25/A,1/-0.75/B,-1.5/2/C}
\tkzDrawLine(A,B)
\tkzDefLine[parallel=through C](A,B) \tkzGetPoint{c}
\tkzShowLine[parallel=through C](A,B)
\tkzDrawLine(C,c) \tkzDrawPoints(A,B,C,c)
\end{tikzpicture}
```

35.1.2. Example of `\tkzShowLine` and perpendicular

```
\begin{tikzpicture}
\tkzDefPoints{0/0/A, 3/2/B, 2/2/C}
\tkzDefLine[perpendicular=through C,K=-.5](A,B)
\tkzGetPoint{c}
\tkzShowLine[perpendicular=through C,K=-.5,gap=3](A,B)
\tkzDefPointBy[projection=onto A--B](c)
\tkzGetPoint{h}
\tkzMarkRightAngle[fill=lightgray](A,h,C)
\tkzDrawLines[add=.5 and .5](A,B,C,c)
\tkzDrawPoints(A,B,C,h,c)
\end{tikzpicture}
```

35.1.3. Example of `\tkzShowLine` and bisector

```
\begin{tikzpicture}[scale=1.25]
\tkzDefPoints{0/0/A, 4/2/B, 1/4/C}
\tkzDrawPolygon(A,B,C)
\tkzSetUpCompass[color=brown,line width=.1 pt]
\tkzDefLine[bisector](B,A,C) \tkzGetPoint{a}
\tkzDefLine[bisector](C,B,A) \tkzGetPoint{b}
\tkzInterLL(A,a)(B,b) \tkzGetPoint{I}
\tkzDefPointBy[projection = onto A--B](I)
\tkzGetPoint{H}
\tkzShowLine[bisector,size=2,gap=3,blue](B,A,C)
\tkzShowLine[bisector,size=2,gap=3,blue](C,B,A)
\tkzDrawCircle[color=blue,%
line width=.2pt](I,H)
\tkzDrawSegments[color=red!50](I,tikzPointResult)
\tkzDrawLines[add=0 and -0.3,color=red!50](A,a B,b)
\end{tikzpicture}
```

35.1.4. Example of `\tkzShowLine` and mediator

```
\begin{tikzpicture}
\tkzDefPoint(2,2){A}
\tkzDefPoint(5,4){B}
\tkzDrawPoints(A,B)
\tkzShowLine[mediator,color=orange,length=1](A,B)
\tkzGetPoints{i}{j}
\tkzDrawLines[add=-0.1 and -0.1](i,j)
\tkzDrawLines(A,B)
\tkzLabelPoints[below =3pt](A,B)
\end{tikzpicture}
```

35.2. Constructions of certain transformations `\tkzShowTransformation`


<code>\tkzShowTransformation[local options](\langle pt1,pt2\rangle) or (\langle pt1,pt2,pt3\rangle)</code>
--

These constructions concern orthogonal symmetries, central symmetries, orthogonal projections and translations. Several options allow the adjustment of the constructions. The idea of this macro comes from Yves Combe.



options	default	definition
reflection= over pt1--pt2	reflection	constructions of orthogonal symmetry
symmetry=center pt	reflection	constructions of central symmetry
projection=onto pt1--pt2	reflection	constructions of a projection
translation=from pt1 to pt2	reflection	constructions of a translation
K	1	circle within a triangle
length	1	arc length
ratio	.5	arc length ratio
gap	2	placing the point of construction
size	1	radius of an arc (see bisector)

### 35.2.1. Example of the use of `\tkzShowTransformation`




```

\begin{tikzpicture}[scale=.5]
  \tkzDefPoint(0,0){O} \tkzDefPoint(2,-2){A}
  \tkzDefPoint(70:4){B} \tkzDrawPoints(A,O,B)
  \tkzLabelPoints(A,O,B)
  \tkzDrawLine[add= 2 and 2](O,A)
  \tkzDefPointBy[translation=from O to A](B)
  \tkzGetPoint{C}
  \tkzDrawPoint[color=orange](C) \tkzLabelPoints(C)
  \tkzShowTransformation[translation=from O to A,%
    length=2](B)
  \tkzDrawSegments[->,color=orange](O,A B,C)
  \tkzDefPointBy[reflection=over O--A](B) \tkzGetPoint{E}
  \tkzDrawSegment[blue](B,E)
  \tkzDrawPoint[color=blue](E)\tkzLabelPoints(E)
  \tkzShowTransformation[reflection=over O--A,size=2](B)
  \tkzDefPointBy[symmetry=center O](B) \tkzGetPoint{F}
  \tkzDrawSegment[color=green](B,F)
  \tkzDrawPoint[color=green](F)\tkzLabelPoints(F)
  \tkzShowTransformation[symmetry=center O,%
    length=2](B)
  \tkzDefPointBy[projection=onto O--A](C)
  \tkzGetPoint{H}
  \tkzDrawSegments[color=magenta](C,H)
  \tkzDrawPoint[color=magenta](H)\tkzLabelPoints(H)
  \tkzShowTransformation[projection=onto O--A,%
    color=red,size=3,gap=-2](C)
\end{tikzpicture}

```

### 35.2.2. Another example of the use of `\tkzShowTransformation`

You'll find this figure again, but without the construction features.



```
\begin{tikzpicture}[scale=.6]
\tkzDefPoints{Q/Q/A,8/Q/B,3.5/1Q/I}
\tkzDefMidPoint(A,B) \tkzGetPoint{O}
\tkzDefPointBy[projection=onto A--B](I)
\tkzGetPoint{J}
\tkzInterLC(I,A)(O,A) \tkzGetPoints{M}{M'}
\tkzInterLC(I,B)(O,A) \tkzGetPoints{N}{N'}
\tkzDefMidPoint(A,B) \tkzGetPoint{M}
\tkzDrawSemiCircle(M,B)
\tkzDrawSegments(I,A I,B A,B B,M A,N)
\tkzMarkRightAngles(A,M,B A,N,B)
\tkzDrawSegment[style=dashed,color=blue](I,J)
\tkzShowTransformation[projection=onto A--B,
color=red,size=3,gap=-3](I)
\tkzDrawPoints[color=red](M,N)
\tkzDrawPoints[color=blue](O,A,B,I,M)
\tkzLabelPoints(O)
\tkzLabelPoints[above right](N,I)
\tkzLabelPoints[below left](M,A)
\end{tikzpicture}
```

## 36. Protractor

Based on an idea by Yves Combe, the following macro allows you to draw a protractor. The operating principle is even simpler. Just name a half-line (a ray). The protractor will be placed on the origin O, the direction of the half-line is given by A. The angle is measured in the direct direction of the trigonometric circle.


### 36.1. The macro `\tkzProtractor`

`\tkzProtractor[⟨local options⟩](⟨O,A⟩)`

options	default	definition
lw	0.4 pt	line thickness
scale	1	ratio: adjusts the size of the protractor
return	false	trigonometric circle indirect


#### 36.1.1. The circular protractor

Measuring in the forward direction



```
\begin{tikzpicture}[scale=.5]
\tkzDefPoint(2,0){A}\tkzDefPoint(0,0){O}
\tkzDefShiftPoint[A](31:5){B}
\tkzDefShiftPoint[A](158:5){C}
\tkzDrawPoints(A,B,C)
\tkzDrawSegments[color = red,
line width = 1pt](A,B A,C)
\tkzProtractor[scale = 1](A,B)
\end{tikzpicture}
```

## 36.1.2. The circular protractor, transparent and returned



```
\begin{tikzpicture}[scale=.5]
  \tkzDefPoint(2,3){A}
  \tkzDefShiftPoint[A](31:5){B}
  \tkzDefShiftPoint[A](158:5){C}
  \tkzDrawSegments[color=red,line width=1pt](A,B A,C)
  \tkzProtractor[return](A,C)
\end{tikzpicture}
```

## 37. Miscellaneous tools and mathematical tools

## 37.1. Duplicate a segment


This involves constructing a segment on a given half-line of the same length as a given segment.

```
\tkzDuplicateSegment(<pt1,pt2>)(<pt3,pt4>){<pt5>}
```


This involves creating a segment on a given half-line of the same length as a given segment. It is in fact the definition of a point. `\tkzDuplicateSegment` is the new name of `\tkzDuplicateLen`.

arguments	example	explanation
<code>(pt1,pt2)(pt3,pt4){pt5}</code>	<code>\tkzDuplicateSegment(A,B)(E,F){C}</code>	$AC=EF$ and $C \in [AB]$

*The macro `\tkzDuplicateLength` is identical to this one.*


37.1.1. Use of `\tkzDuplicateSegment`

```
\begin{tikzpicture}[scale=.5]
  \tkzDefPoints{0/0/A,2/-3/B,2/5/C}
  \tkzDuplicateSegment(A,B)(A,C)
  \tkzGetPoint{D}
  \tkzDrawSegments[new](A,B A,C)
  \tkzDrawSegment[teal](A,D)
  \tkzDrawPoints[new](A,B,C,D)
  \tkzLabelPoints[above right=3pt](A,B,C,D)
\end{tikzpicture}
```

37.1.2. Proportion of gold with `\tkzDuplicateSegment`

```
\begin{tikzpicture}[rotate=-90,scale=.4]
\tkzDefPoints{0/0/A,10/0/B}
\tkzDefMidPoint(A,B)
\tkzGetPoint{I}
\tkzDefPointWith[orthogonal,K=-.75](B,A)
\tkzGetPoint{C}
\tkzInterLC(B,C)(B,I)\tkzGetSecondPoint{D}
\tkzDuplicateSegment(B,D)(D,A)\tkzGetPoint{E}
\tkzInterLC(A,B)(A,E)\tkzGetPoints{N}{M}
\tkzDrawArc[orange,delta=10](D,E)(B)
\tkzDrawArc[orange,delta=10](A,M)(E)
\tkzDrawLines(A,B B,C A,D)
\tkzDrawArc[orange,delta=10](B,D)(I)
\tkzDrawPoints(A,B,D,C,M,I)
\tkzLabelPoints[below left](A,B,D,C,M,I)
\end{tikzpicture}
```

## 37.1.3. Golden triangle or sublime triangle



```
\begin{tikzpicture}[scale=.75]
\tkzDefPoints{0/0/A,5/0/C,0/5/B}
\tkzDefMidPoint(A,C)\tkzGetPoint{H}
\tkzDuplicateSegment(H,B)(H,A)\tkzGetPoint{D}
\tkzDuplicateSegment(A,D)(A,B)\tkzGetPoint{E}
\tkzDuplicateSegment(A,D)(B,A)\tkzGetPoint{G}
\tkzInterCC(A,C)(B,G)\tkzGetSecondPoint{F}
\tkzDrawLine(A,C)
\tkzDrawArc(A,C)(B)
\begin{scope}[arc style/.style={color=gray,%
style=dashed}]
\tkzDrawArc(H,B)(D)
\tkzDrawArc(A,D)(B)
\tkzDrawArc(B,G)(F)
\end{scope}
\tkzDrawSegment[dashed](H,B)
\tkzCompass(B,F)
\tkzDrawPolygon[new](A,B,F)
\tkzDrawPoints(A,...,H)
\tkzLabelPoints[below left](A,...,H)
\end{tikzpicture}
```

37.2. Segment length `\tkzCalcLength`

There's an option in TikZ named `vecLen`. This option is used to calculate AB if A and B are two points. The only problem for me is that the version of TikZ is not accurate enough in some cases. My version uses the `xfp` package and is slower, but more accurate.

```
\tkzCalcLength[local options](pt1,pt2)
```


You can store the result with the macro `\tkzGetLength` for example `\tkzGetLength{dAB}` defines the macro `\dAB`.

arguments	example	explanation
<code>(pt1,pt2){name of macro}</code>	<code>\tkzCalcLength(A,B)</code>	<code>\dAB</code> gives AB in cm

## Only one option

options	default	example
cm	true	<code>\tkzCalcLength(A,B)</code> After <code>\tkzGetLength{dAB}</code> <code>\dAB</code> gives AB in cm

## 37.2.1. Compass square construction




```

\begin{tikzpicture}[scale=1]
\tkzDefPoint(0,0){A} \tkzDefPoint(4,0){B}
\tkzCalcLength(A,B)\tkzGetLength{dAB}
\tkzDefLine[perpendicular=through A](A,B)
\tkzGetPoint{D}
\tkzDefPointWith[orthogonal,K=-1](B,A)
\tkzGetPoint{F}
\tkzGetPoint{C}
\tkzDrawLine[add=.6 and .2](A,B)
\tkzDrawLine(A,D)
\tkzShowLine[orthogonal=through A,gap=2](A,B)
\tkzMarkRightAngle(B,A,D)
\tkzCompass(A,D D,C)
\tkzDrawArc[R](B,\dAB)(80,110)
\tkzDrawPoints(A,B,C,D)
\tkzDrawSegments[color=gray,style=dashed](B,C C,D)
\tkzLabelPoints[below left](A,B,C,D)
\end{tikzpicture}

```

## 37.2.2. Example

The macro `\tkzDefCircle[radius](A,B)` defines the radius that we retrieve with `\tkzGetLength`, this result is in cm.



```

\begin{tikzpicture}[scale=.5]
\tkzDefPoint(0,0){A}
\tkzDefPoint(3,-4){B}
\tkzDefMidPoint(A,B) \tkzGetPoint{M}
\tkzCalcLength(M,B)\tkzGetLength{rAB}
\tkzDrawCircle(A,B)
\tkzDrawPoints(A,B)
\tkzLabelPoints(A,B)
\tkzDrawSegment[dashed](A,B)
\tkzLabelSegment(A,B){$\pgfmathprintnumber{\rAB}$}
\end{tikzpicture}

```

## 37.3. Transformation from pt to cm or cm to pt

Not sure if this is necessary and it is only a division by 28.45274 and a multiplication by the same number. The macros are:

```
\tkzpttocm(<number>){<name of macro>}
```

The result is stored in a macro.

arguments	example	explanation
<code>(number){name of macro}</code>	<code>\tkzpttocm(120){len}</code>	<code>\len</code> gives a number of tkznamecm

You'll have to use `\len` along with `cm`.

### 37.4. Change of unit

```
\tkzcmtopt(<number>){<name of macro>}
```

The result is stored in a macro.

arguments	example	explanation
(number){name of macro}	<code>\tkzcmtopt(5){len}</code>	<code>\len</code> length in <b>pts</b>

The result can be used with `\len pt`


### 37.5. Get point coordinates

```
\tkzGetPointCoord(<A>){<name of macro>}
```

arguments	example	explanation
(point){name of macro}	<code>\tkzGetPointCoord(A){A}</code>	<code>\Ax</code> and <code>\Ay</code> give coordinates for A


Stores in two macros the coordinates of a point. If the name of the macro is `p`, then `\px` and `\py` give the coordinates of the chosen point with the `cm` as unit.

#### 37.5.1. Coordinate transfer with `\tkzGetPointCoord`



```
\begin{tikzpicture}
\tkzInit[xmax=5,ymax=3]
\tkzGrid[sub,orange]
\tkzDrawX \tkzDrawY
\tkzDefPoint(1,0){A}
\tkzDefPoint(4,2){B}
\tkzGetPointCoord(A){a}
\tkzGetPointCoord(B){b}
\tkzDefPoint(\ax,\ay){C}
\tkzDefPoint(\bx,\by){D}
\tkzDrawPoints[color=red](C,D)
\end{tikzpicture}
```

#### 37.5.2. Sum of vectors with `\tkzGetPointCoord`



```
\begin{tikzpicture}[>=latex]
\tkzDefPoint(1,4){a}
\tkzDefPoint(3,2){b}
\tkzDefPoint(1,1){c}
\tkzDrawSegment[->,red](a,b)
\tkzGetPointCoord(c){c}
\draw[color=blue,->](a) -- ([shift=(b)]\cx,\cy) ;
\draw[color=purple,->](b) -- ([shift=(b)]\cx,\cy) ;
\tkzDrawSegment[->,blue](a,c)
\tkzDrawSegment[->,purple](b,c)
\end{tikzpicture}
```

## 37.6. Swap labels of points

`\tkzSwapPoints(<pt1,pt2>)`

arguments      example

explanation

(pt1,pt2)    `\tkzSwapPoints(A,B)`    now A has the coordinates of B  
*The points have exchanged their coordinates.*

37.6.1. Use of `\tkzSwapPoints`


```

\begin{tikzpicture}
\tkzDefPoints{O/Q/0,5/-1/A,2/2/B}
\tkzSwapPoints(A,B)
\tkzDrawPoints(O,A,B)
\tkzLabelPoints(O,A,B)
\end{tikzpicture}

```

## 37.7. Dot Product

In Euclidean geometry, the dot product of the Cartesian coordinates of two vectors is widely used.

`\tkzDotProduct(<pt1,pt2,pt3>)`

The dot product of two vectors  $\vec{u} = [a, b]$  and  $\vec{v} = [a', b']$  is defined as:  $\vec{u} \cdot \vec{v} = aa' + bb'$

$\vec{u} = \overrightarrow{\text{pt1pt2}}$   $\vec{v} = \overrightarrow{\text{pt1pt3}}$


arguments

example

explanation

(pt1,pt2,pt3)    `\tkzDotProduct(A,B,C)`    the result is  $\overrightarrow{AB} \cdot \overrightarrow{AC}$   
*The result is a number that can be retrieved with `\tkzGetResult`.*


## 37.7.1. Simple example



$$PA \times PH = 0.2$$

```
\begin{tikzpicture}
  \tkzDefPoints{-2/-3/A,4/0/B,1/3/C}
  \tkzDefPointBy[projection= onto A--B](C)
  \tkzGetPoint{H}
  \tkzDrawSegment(C,H)
  \tkzMarkRightAngle(C,H,A)
  \tkzDrawSegments[vector style](A,B A,C)
  \tkzDrawPoints(A,H) \tkzLabelPoints(A,B,H)
  \tkzLabelPoints[above](C)
  \tkzDotProduct(A,B,C) \tkzGetResult{pabc}
  % \pgfmathparse{round(10*\pabc)/10}
  \let\pabc\pgfmathresult
  \node at (1,-3) {\$\overrightarrow{PA}\cdot \overrightarrow{PB}=\pabc$};
  \tkzDotProduct(A,H,B) \tkzGetResult{phab}
  % \pgfmathparse{round(10*\phab)/10}
  \let\phab\pgfmathresult
  \node at (1,-4) {\$PA \times PH = \phab \$};
\end{tikzpicture}
```

## 37.7.2. Cocyclic points



$$\vec{PA} \cdot \vec{PB} = \vec{PC} \cdot \vec{PD}$$

$$\vec{PA} \cdot \vec{PB} = -15.0$$

$$\vec{PC} \cdot \vec{PD} = -15.0$$

```
\begin{tikzpicture}[scale=.75]
  \tkzDefPoints{1/2/0,5/2/B,2/2/P,3/3/Q}
  \tkzInterLC[common=B](0,B)(0,B) \tkzGetFirstPoint{A}
  \tkzInterLC[common=B](P,Q)(0,B) \tkzGetPoints{C}{D}
  \tkzDrawCircle(0,B)
  \tkzDrawSegments(A,B C,D)
  \tkzDrawPoints(A,B,C,D,P)
  \tkzLabelPoints(P)
  \tkzLabelPoints[below left](A,C)
  \tkzLabelPoints[above right](B,D)
  \tkzDotProduct(P,A,B) \tkzGetResult{pab}
  \pgfmathparse{round(10*\pab)/10}
  \let\pab\pgfmathresult
  \tkzDotProduct(P,C,D) \tkzGetResult{pcd}
  \pgfmathparse{round(10*\pcd)/10}
  \let\pcd\pgfmathresult
  \node at (1,-3) {%
    $\overrightarrow{PA}\cdot \overrightarrow{PB} = $
    $\overrightarrow{PC}\cdot \overrightarrow{PD}$};
  \node at (1,-4) {%
    $\overrightarrow{PA}\cdot \overrightarrow{PB}=\pab$};
  \node at (1,-5) {%
    $\overrightarrow{PC}\cdot \overrightarrow{PD}=\pcd$};
\end{tikzpicture}
```




## 37.8. Power of a point with respect to a circle

<code>\tkzPowerCircle(&lt;pt1&gt;)(&lt;pt2,pt3&gt;)</code>		
arguments	example	explanation
<code>(pt1)(pt2,pt3)</code>	<code>\tkzPowerCircle(A)(O,M)</code>	power of A with respect to the circle (O,A) <i>The result is a number that represents the power of a point with respect to a circle.</i>

## 37.8.1. Power from the radical axis

In this example, the radical axis (EF) has been drawn. A point H has been chosen on (EF) and the power of the point H with respect to the circle of center A has been calculated as well as  $PS^2$ . You can check that the power of H with respect to the circle of center C as well as  $HS^2$ ,  $HT^2$ ,  $HT'^2$  give the same result.



```

\begin{tikzpicture}[scale=.5]
  \tkzDefPoints{-1/0/A,0/5/B,5/-1/C,7/1/D}
  \tkzDrawCircles(A,B C,D)
  \tkzDefRadicalAxis(A,B)(C,D) \tkzGetPoints{E}{F}
  \tkzDrawLine[add=1 and 2](E,F)
  \tkzDefPointOnLine[pos=1.5](E,F)
  \tkzGetPoint{H}
  \tkzDefLine[tangent from = H](A,B)
  \tkzGetPoints{T}{T'}
  \tkzDefLine[tangent from = H](C,D)
  \tkzGetPoints{S}{S'}
  \tkzDrawSegments(H,T H,T' H,S H,S')
  \tkzDrawPoints(A,B,C,D,E,F,H,T,T',S,S')
  \tkzPowerCircle(H)(A,B) \tkzGetResult{pw}
  \tkzDotProduct(H,S,S) \tkzGetResult{phtt}
  \node {Power $\approx \backslash pw \approx \backslash phtt$};
\end{tikzpicture}


```

## 37.9. Radical axis

In geometry, the radical axis of two non-concentric circles is the set of points whose power with respect to the circles are equal. Here `\tkzDefRadicalAxis(A,B)(C,D)` gives the radical axis of the two circles  $\mathcal{C}(A,B)$  and  $\mathcal{C}(C,D)$ .


<code>\tkzDefRadicalAxis(&lt;pt1,pt2&gt;)(&lt;pt3,pt4&gt;)</code>		
arguments	example	explanation
<code>(pt1,pt2)(pt3,pt4)</code>	<code>\tkzDefRadicalAxis(A,B)(C,D)</code>	Two circles with centers A and C <i>The result is two points of the radical axis.</i>

## 37.9.1. Two circles disjoint




```
\begin{tikzpicture}[scale=.75]
  \tkzDefPoints{-1/0/A,0/2/B,4/-1/C,4/0/D}
  \tkzDrawCircles(A,B C,D)
  \tkzDefRadicalAxis(A,B)(C,D)
  \tkzGetPoints{E}{F}
  \tkzDrawLine[add=1 and 2](E,F)
  \tkzDrawLine[add=.5 and .5](A,C)
\end{tikzpicture}
```

## 37.10. Two intersecting circles




```
\begin{tikzpicture}[scale=.5]
  \tkzDefPoints{-1/0/A,0/2/B,3/-1/C,3/-2/D}
  \tkzDrawCircles(A,C B,D)
  \tkzDefRadicalAxis(A,C)(B,D)
  \tkzGetPoints{E}{F}
  \tkzDrawPoints(A,B,C,D,E,F)
  \tkzLabelPoints(A,B,C,D,E,F)
  \tkzDrawLine[add=.25 and .5](E,F)
  \tkzDrawLine[add=.25 and .25](A,B)
\end{tikzpicture}
```

## 37.11. Two externally tangent circles




```
\begin{tikzpicture}[scale=.5]
  \tkzDefPoints{0/0/A,4/0/B,6/0/C}
  \tkzDrawCircles(A,B C,B)
  \tkzDefRadicalAxis(A,B)(C,B)
  \tkzGetPoints{E}{F}
  \tkzDrawPoints(A,B,C,E,F)
  \tkzLabelPoints(A,B,C,E,F)
  \tkzDrawLine[add=1 and 1](E,F)
  \tkzDrawLine[add=.5 and .5](A,B)
\end{tikzpicture}
```

## 37.12. Two circles tangent internally



```
\begin{tikzpicture}[scale=.5]
\tkzDefPoints{0/0/A,3/0/B,5/0/C}
\tkzDrawCircles(A,C B,C)
\tkzDefRadicalAxis(A,C)(B,C)
\tkzGetPoints{E}{F}
\tkzDrawPoints(A,B,C,E,F)
\tkzLabelPoints[below right](A,B,C,E,F)
\tkzDrawLine[add=1 and 1](E,F)
\tkzDrawLine[add=.5 and .5](A,B)
\end{tikzpicture}
```

## 37.12.1. Three circles



```
\begin{tikzpicture}[scale=.4]
\tkzDefPoints{0/0/A,5/0/a,7/-1/B,3/-1/b,5/-4/C,2/-4/c}
\tkzDrawCircles(A,a B,b C,c)
\tkzDefRadicalAxis(A,a)(B,b) \tkzGetPoints{i}{j}
\tkzDefRadicalAxis(A,a)(C,c) \tkzGetPoints{k}{l}
\tkzDefRadicalAxis(C,c)(B,b) \tkzGetPoints{m}{n}
\tkzDrawLines[new](i,j k,l m,n)
\end{tikzpicture}
```

37.13. `\tkzIsLinear`, `\tkzIsOrtho`

`\tkzIsLinear( $\langle$ pt1,pt2,pt3 $\rangle$ )`


arguments	example	explanation
$\langle$ pt1,pt2,pt3 $\rangle$	<code>\tkzIsLinear(A,B,C)</code>	A,B,C aligned ?

*`\tkzIsLinear` allows to test the alignment of the three points pt1,pt2,pt3.*

`\tkzIsOrtho( $\langle$ pt1,pt2,pt3 $\rangle$ )`

arguments	example	explanation
$\langle$ pt1,pt2,pt3 $\rangle$	<code>\tkzIsOrtho(A,B,C)</code>	$(AB) \perp (AC)$ ?

*`\tkzIsOrtho` allows to test the orthogonality of lines (pt1pt2) and (pt1pt3).*

37.13.1. Use of `\tkzIsOrtho` and `\tkzIsLinear`

```

\begin{tikzpicture}
\tkzDefPoints{1/-2/A,5/0/B}
\tkzDefCircle[diameter](A,B) \tkzGetPoint{O}
\tkzDrawCircle(O,A)
\tkzDefPointBy[rotation= center O angle 60](B)
\tkzGetPoint{C}
\tkzDefPointBy[rotation= center O angle 60](A)
\tkzGetPoint{D}
\tkzDrawCircle(O,A)
\tkzDrawPoints(A,B,C,D,O)
\tkzIsOrtho(C,A,B)
\iftkzOrtho
\tkzDrawPolygon[blue](A,B,C)
\tkzDrawPoints[blue](A,B,C,D)
\else
\tkzDrawPoints[red](A,B,C,D)
\fi
\tkzIsLinear(O,C,D)
\iftkzLinear
\tkzDrawSegment[orange](C,D)
\fi
\end{tikzpicture}

```

## Part VIII.

### Working with style

## 38. Predefined styles

The way to proceed will depend on your use of the package. A method that seems to me to be correct is to use as much as possible predefined styles in order to separate the content from the form. This method will be the right one if you plan to create a document (like this documentation) with many figures. We will see how to define a global style for a document. We will see how to use a style locally.

The file `tkz-euclide.cfg` contains the predefined styles of the main objects. Among these the most important are points, lines, segments, circles, arcs and compass traces. If you always use the same styles and if you create many figures then it is interesting to create your own styles. To do this you need to know what features you can modify. It will be necessary to know some notions of TikZ.

The predefined styles are global styles. They exist before the creation of the figures. It is better to avoid changing them between two figures. On the other hand these styles can be modified in a figure temporarily. There the styles are defined locally and do not influence the other figures.

For the document you are reading here is how I defined the different styles.

```
\tkzSetUpColors[background=white,text=black]
\tkzSetUpPoint[size=2,color=teal]
\tkzSetUpLine[line width=.4pt,color=teal]
\tkzSetUpCompass[color=orange, line width=.4pt,delta=10]
\tkzSetUpArc[color=gray,line width=.4pt]
\tkzSetUpStyle[orange]{new}
```

The macro `\tkzSetUpColors` allows you to set the background color as well as the text color. If you don't use it, the colors of your document will be used as well as the fonts. Let's see how to define the styles of the main objects.

## 39. Points style

This is how the points are defined :

```
\tikzset{point style/.style = {%
  draw      = \tkz@euc@pointcolor,
  inner sep = 0pt,
  shape     = \tkz@euc@pointshape,
  minimum size = \tkz@euc@pointsize,
  fill      = \tkz@euc@pointcolor}}
```

It is of course possible to use `\tikzset` but you can use a macro provided by the package. You can use the macro `\tkzSetUpPoint` globally or locally, Let's look at this possibility.

### 39.1. Use of `\tkzSetUpPoint`

`\tkzSetUpPoint[(local options)]`


options	default	definition
color	black	point color
size	3	point size
fill	black!50	inside point color
shape	circle	point shape circle, cross or cross out

### 39.1.1. Global style or local style

First of all here is a figure created with the styles of my documentation, then the style of the points is modified within the environment `tikzpicture`.

You can use the macro `\tkzSetUpPoint` globally or locally, If you place this macro in your preamble or before your first figure then the point style will be valid for all figures in your document. It will be possible to use another style locally by using this command within an environment `tikzpicture`.


Let's look at this possibility.



```
\begin{tikzpicture}
  \tkzDefPoints{0/0/A,5/0/B,3/2/C,3/1/D}
  \tkzDrawPolygon(A,B,C)
  \tkzDrawPoints(A,B,C)
  \tkzLabelPoints(A,B)
  \tkzLabelPoints[above right](C)
\end{tikzpicture}
```

### 39.1.2. Local style


The style of the points is modified locally in the second figure



```
\begin{tikzpicture}
  \tkzSetUpPoint[size=4,color=red,fill=red!20]
  \tkzDefPoints{0/0/A,5/0/B,3/2/C,3/1/D}
  \tkzDrawPolygon(A,B,C)
  \tkzDrawPoints(A,B,C)
  \tkzDrawPoint[shape=cross out,thick](D)
  \tkzLabelPoints(A,B)
  \tkzLabelPoints[above right](C)
\end{tikzpicture}
```


### 39.1.3. Style and scope

The points get back the initial style. Point D has a new style limited by the environment `scope`. It is also possible to use `{...}` or `\begin{group} ... \end{group}`. The points get back the initial style. Point D has a new style limited by the environment `scope`. It is also possible to use `{...}` or `\begin{group} ... \end{group}`.




```
\begin{tikzpicture}
  \tkzDefPoints{0/0/A,5/0/B,3/2/C,3/1/D}
  \tkzDrawPolygon(A,B,C)
  \tkzDrawPoints(A,B,C)
  \begin{scope}
    \tkzSetUpPoint[size=4,color=red,fill=red!20]
    \tkzDrawPoint(D)
  \end{scope}
  \tkzLabelPoints(A,B)
  \tkzLabelPoints[above right](C)
\end{tikzpicture}
```

### 39.1.4. Simple example with `\tkzSetUpPoint`



```
\begin{tikzpicture}
  \tkzSetUpPoint[shape = cross out,color=blue]
  \tkzDefPoint(2,1){A}
  \tkzDefPoint(4,0){B}
  \tkzDrawLine(A,B)
  \tkzDrawPoints(A,B)
\end{tikzpicture}
```

39.1.5. Use of `\tkzSetUpPoint` inside a group

```
\begin{tikzpicture}
\tkzDefPoints{0/0/A,2/4/B,4/0/C,3/2/D}
\tkzDrawSegments(A,B A,C A,D)
{\tkzSetUpPoint[shape=cross out,
fill= teal!50,
size=4,color=teal]
\tkzDrawPoints(A,B)}
\tkzSetUpPoint[fill= teal!50,size=4,
color=teal]
\tkzDrawPoints(C,D)
\tkzLabelPoints(A,B,C,D)
\end{tikzpicture}
```

## 40. Lines style

You have several possibilities to change the style of a line. You can modify the style of a line with `\tkzSetUpLine` or directly modify the style of the lines with `\tikzset{line style/.style = ... }`

Reminder about `line width`: There are a number of predefined styles that provide more “natural” ways of setting the line width. You can also redefine these styles.

predefined style	value of <code>line width</code>
ultra thin	0.1 pt
very thin	0.2 pt
thin	0.4 pt
semithick	0.6 pt
thick	0.8 pt
very thick	1.2 pt
ultra thick	1.6 pt


40.1. Use of `\tkzSetUpLine`

It is a macro that allows you to define the style of all the lines.

<code>\tkzSetUpLine[<i>(local options)</i>]</code>		
options	default	definition
color	black	colour of the construction lines
line width	0.4pt	thickness of the construction lines
style	solid	style of construction lines
add	.2 and .2	changing the length of a line segment




## 40.1.1. Change line width




```
\begin{tikzpicture}[scale=.75]
\tkzSetUpLine[line width=1pt]
\begin{scope}[rotate=-90]
\tkzDefPoints{0/6/A,10/0/B,10/6/C}
\tkzDefPointBy[projection = onto B--A](C)
\tkzGetPoint{H}
\tkzMarkRightAngle[size=.4,
fill=teal!20](B,C,A)
\tkzMarkRightAngle[size=.4,
fill=orange!20](B,H,C)
\tkzDrawPolygon(A,B,C)
\tkzDrawSegment[new](C,H)
\end{scope}
\tkzLabelSegment[below](C,B){$a$}
\tkzLabelSegment[right](A,C){$b$}
\tkzLabelSegment[left](A,B){$c$}
\tkzLabelSegment[color=red](C,H){$h$}
\tkzDrawPoints(A,B,C)
\tkzLabelPoints[above left](H)
\tkzLabelPoints(B,C)
\tkzLabelPoints[above](A)
\end{tikzpicture}
```

## 40.1.2. Change style of line



```
\begin{tikzpicture}[scale=.5]
\tikzset{line style/.style = {color = gray,
style=dashed}}
\tkzDefPoints{1/0/A,4/0/B,1/1/C,5/1/D}
\tkzDefPoints{1/2/E,6/2/F,0/4/A',3/4/B'}
\tkzCalcLength(C,D)
\tkzGetLength{rCD}
\tkzCalcLength(E,F)
\tkzGetLength{rEF}
\tkzInterCC[R](A',\rCD)(B',\rEF)
\tkzGetPoints{I}{J}
\tkzDrawLine(A',B')
\tkzCompass(A',B')
\tkzDrawSegments(A,B C,D E,F)
\tkzDefCircle[R](A',\rCD) \tkzGetPoint{a'}
\tkzDefCircle[R](B',\rEF) \tkzGetPoint{b'}
\tkzDrawCircles(A',a' B',b')
\begin{scope}
\tkzSetUpLine[color=red]
\tkzDrawSegments(A',I B',I)
\end{scope}
\tkzDrawPoints(A,B,C,D,E,F,A',B',I,J)
\tkzLabelPoints(A,B,C,D,E,F,A',B',I,J)
\end{tikzpicture}
```

## 40.1.3. Example 3: extend lines



```
\begin{tikzpicture}[scale=.75]
\tkzSetUpLine[add=.5 and .5]
\tkzDefPoints{0/0/A,4/0/B,1/3/C}
\tkzDrawLines(A,B B,C A,C)
\tkzDrawPolygon[red,thick](A,B,C)
\tkzSetUpPoint[size=4,circle,color=red,fill=red!20]
\tkzDrawPoints(A,B,C)
\end{tikzpicture}
```


## 41. Arc style

## 41.1. The macro \tkzSetUpArc

`\tkzSetUpArc[<local options>]`

options	default	definition
color	black	colour of the lines
line width	0.4pt	thickness of the lines
style	solid	style of construction lines

## 41.1.1. Use of \tkzSetUpArc




```
\begin{tikzpicture}
\def\r{3} \def\angle{200}
\tkzSetUpArc[delta=10,color=purple,line width=.2pt]
\tkzSetUpLabel[font=\scriptsize,red]
\tkzDefPoint(0,0){O}
\tkzDefPoint(\angle:\r){A}
\tkzInterCC(O,A)(A,0) \tkzGetPoints{C'}{C}
\tkzInterCC(O,A)(C,0) \tkzGetPoints{D'}{D}
\tkzInterCC(O,A)(D,0) \tkzGetPoints{X'}{X}
\tkzDrawCircle(O,A)
\tkzDrawArc(A,C')(C)
\tkzDrawArc(C,O)(D)
\tkzDrawArc(D,O)(X)
\tkzDrawLine[add=.1 and .1](A,X)
\tkzDrawPoints(O,A)
\tkzSetUpPoint[size=3,color=purple,fill=purple!10]
\tkzDrawPoints(C,C',D,X)
\tkzLabelPoints[below left](O,A)
\tkzLabelPoints[below](C')
\tkzLabelPoints[below right](X)
\tkzLabelPoints[above](C,D)
\end{tikzpicture}
```

42. Compass style, configuration macro `\tkzSetUpCompass`


The following macro will help to understand the construction of a figure by showing the compass traces necessary to obtain certain points.

42.1. The macro `\tkzSetUpCompass`

<code>\tkzSetUpCompass[<i>local options</i>]</code>		
options	default	definition
color	black	colour of the construction lines
line width	0.4pt	thickness of the construction lines
style	solid	style of lines : solid, dashed,dotted,...
delta	0	changes the length of the arc

42.1.1. Use of `\tkzSetUpCompass`

```
\begin{tikzpicture}
  \tkzSetUpCompass[color=red,delta=15]
  \tkzDefPoint(1,1){A}
  \tkzDefPoint(6,1){B}
  \tkzInterCC[R](A,4)(B,4) \tkzGetPoints{C}{D}
  \tkzCompass(A,C)
  \tkzCompass(B,C)
  \tkzDrawPolygon(A,B,C)
  \tkzDrawPoints(A,B,C)
\end{tikzpicture}
```

42.1.2. Use of `\tkzSetUpCompass` with `\tkzShowLine`

```
\begin{tikzpicture}[scale=.75]
  \tkzSetUpStyle[bisector,size=2,gap=3]{showbi}
  \tkzSetUpCompass[color=teal,line width=.3 pt]
  \tkzDefPoints{0/1/A, 8/3/B, 3/6/C}
  \tkzDrawPolygon(A,B,C)
  \tkzDefLine[bisector](B,A,C) \tkzGetPoint{a}
  \tkzDefLine[bisector](C,B,A) \tkzGetPoint{b}
  \tkzShowLine[showbi](B,A,C)
  \tkzShowLine[showbi](C,B,A)
  \tkzInterLL(A,a)(B,b) \tkzGetPoint{I}
  \tkzDefPointBy[projection= onto A--B](I)
  \tkzGetPoint{H}
  \tkzDrawCircle[new](I,H)
  \tkzDrawSegments[new](I,H)
  \tkzDrawLines[add=0 and .2,new](A,I B,I)
\end{tikzpicture}
```

## 43. Label style


43.1. The macro `\tkzSetUpLabel`

The macro `\tkzSetUpLabel` is used to define the style of the point labels.

`\tkzSetUpStyle[⟨local options⟩]`

The options are the same as those of TikZ

#### 43.1.1. Use of `\tkzSetUpLabel`



```
\begin{tikzpicture}[scale=.75]
  \tkzSetUpLabel[font=\scriptsize,red]
  \tkzSetUpStyle[line width=1pt,teal]{XY}
  \tkzInit[xmin=-3,xmax=3,ymin=-3,ymax=3]
  \tkzDrawX[noticks,XY]
  \tkzDrawY[noticks,XY]
  \tkzDefPoints{1/0/A,0/1/B,-1/0/C,0/-1/D}
  \tkzDrawPoints[teal,fill=teal!30,size=6](A,...,D)
  \tkzLabelPoint[above right](A){$A(1,0)$}
  \tkzLabelPoint[above right](B){$B(0,1)$}
  \tkzLabelPoint[above left](C){$C(-1,0)$}
  \tkzLabelPoint[below left](D){$D(0,-1)$}
\end{tikzpicture}
```

### 44. Own style

You can set your own style with `\tkzSetUpStyle`

#### 44.1. The macro `\tkzSetUpStyle`

`\tkzSetUpStyle[⟨local options⟩]`

The options are the same as those of TikZ

#### 44.1.1. Use of `\tkzSetUpStyle`

```
○ \begin{tikzpicture}
A   \tkzSetUpStyle[color=blue!20!black,fill=blue!20]{mystyle}
    \tkzDefPoint(0,0){O}
    \tkzDefPoint(0,1){A}
    \tkzDrawPoints(O) % general style
    \tkzDrawPoints[mystyle,size=4](A) % my style
    \tkzLabelPoints(O,A)
\end{tikzpicture}
```

### 45. How to use arrows

In some countries, arrows are used to indicate the parallelism of lines, to represent half-lines or the sides of an angle (rays).

Here are some examples of how to place these arrows. `tkz-euclide` loads a library called `arrows.meta`.

```
\usetikzlibrary{arrows.meta}
```

This library is used to produce different styles of arrow heads. The next examples use some of them.

## 45.1. Arrows at endpoints on segment, ray or line

Stealth, Triangle, To, Latex and ...which can be combined with `reversed`. That's easy to place an arrow at one or two endpoints.

1. `-Triangle` and Segment

```
\begin{tikzpicture}
  \tkzDefPoints{0/0/A,4/0/B}
  \tkzDrawSegment[-Triangle] (A,B)
\end{tikzpicture}
```

2. `Stealth-Stealth` and Segment

```
\begin{tikzpicture}
  \tkzDefPoints{0/0/A,4/0/B}
  \tkzDrawSegment[Stealth-Stealth] (A,B)
\end{tikzpicture}
```

3. `Latex-Latex` and Line

```
\begin{tikzpicture}
  \tkzDefPoints{0/0/A,4/0/B}
  \tkzDrawLine[red,Latex-Latex] (A,B)
  \tkzDrawPoints(A,B)
\end{tikzpicture}
```

4. `To-To` and Segment


```
\begin{tikzpicture}
  \tkzDefPoints{0/0/A,4/0/B}
  \tkzDrawSegment[To-To] (A,B)
\end{tikzpicture}
```

5. `Latex-Latex` and Segment

```
\begin{tikzpicture}
  \tkzDefPoints{0/0/A,4/0/B}
  \tkzDrawSegment[Latex-Latex] (A,B)
\end{tikzpicture}
```

6. `Latex-` and Segment

```
\begin{tikzpicture}
  \tkzDefPoints{0/0/A,4/0/B}
  \tkzDrawSegment[Latex-] (A,B)
\end{tikzpicture}
```

7. `-Latex` and Segments

```
\begin{tikzpicture}
  \tkzDefPoints{0/0/A,4/0/B,5/-2/C}
  \tkzDrawSegments[-Latex] (A,B A,C)
\end{tikzpicture}
```

## 45.1.1. Scaling an arrow head



```
\begin{tikzpicture}
\tkzDefPoints{0/0/A,4/0/B}
\tkzDrawSegment[{\Latex[scale=2]}--{\Latex[scale=2]}](A,B)
\end{tikzpicture}
```

## 45.1.2. Using vector style

```
\tikzset{vector style/.style={>=Latex,->}}
```

You can redefine this style.



```
\begin{tikzpicture}
\tkzDefPoints{0/0/A,4/0/B}
\tkzDrawSegment[vector style](A,B)
\end{tikzpicture}
```

## 45.2. Arrows on middle point of a line segment

Arrows on lines are used to indicate that those lines are parallel. It depends on the country, in France we prefer to indicate outside the figure that  $(A,B) \parallel (D,C)$ . The code is an adaptation of an answer by Muzimuzhi Z on the site [tex.stackexchange.com](https://tex.stackexchange.com).


Syntax:

- tkz arrow (Latex by default)
- tkz arrow=<arrow end tip>
- tkz arrow=<arrow end tip> at <pos> (<pos> = .5 by default)
- tkz arrow={<arrow end tip>[<arrow options>] at <pos>} option possible scale

Example usages:


```
\tkzDrawSegment[tkz arrow=Stealth] (A,B)
\tkzDrawSegment[tkz arrow={To[scale=3] at .4}](A,B)
\tkzDrawSegment[tkz arrow={Latex[scale=5,blue] at .6}](A,B)
```

## 45.2.1. In a parallelogram



```
\begin{tikzpicture}
\tkzDefPoints{0/0/A,3/0/B,4/2/C}
\tkzDefParallelogram(A,B,C)
\tkzGetPoint{D}
\tkzDrawSegments[tkz arrow](A,B D,C)
\tkzDrawSegments(B,C D,A)
\tkzLabelPoints(A,B)
\tkzLabelPoints[above right](C,D)
\tkzDrawPoints(A,...,D)
\end{tikzpicture}
```


## 45.2.2. A line parallel to another one



```
\begin{tikzpicture}
\tkzDefPoints{0/0/A,3/0/B,1/2/C}
\tkzDefPointWith[colinear= at C](A,B)
\tkzGetPoint{D}
\tkzDrawSegments[tkz arrow=Triangle](A,B C,D)
\tkzLabelPoints(A,B,C)
\tkzDrawPoints(A,...,C)
\end{tikzpicture}
```

## 45.2.3. Arrow on a circle

It is possible to place an arrow on the first quarter of a circle. A rotation allows you to move the arrow.



```
\begin{tikzpicture}
\tkzDefPoints{0/0/A,3/0/B}
\begin{scope}[rotate=15]
\tkzDrawCircle[tkz arrow={Latex[scale=2,red]}](A,B)
\end{scope}
\end{tikzpicture}
```


## 45.3. Arrows on all segments of a polygon

Some users of my package have asked me to be able to place an arrow on each side of a polygon. I used a style proposed by Paul Gaborit on the site [tex.stackexchange.com](https://tex.stackexchange.com).

```
\tikzset{tkz arrows/.style=
```


```
{postaction={on each path={tkz arrow={Latex[scale=2,color=black]}}}}
```

You can change this style. With **tkz arrows** you can an arrow on each segment of a polygon

45.3.1. Arrow on each segment with **tkz arrows**

```
\begin{tikzpicture}
\tkzDefPoints{0/0/A,3/0/B}
\tkzDefSquare(A,B) \tkzGetPoints{C}{D}
\tkzDrawPolygon[tkz arrows](A,...,D)
\end{tikzpicture}
```

## 45.3.2. Using tkz arrows with a circle



```
\begin{tikzpicture}
\tkzDefPoints{0/0/A,3/0/B}
\tkzDrawCircle[tkz arrows](A,B)
\end{tikzpicture}
```




Part IX.

Examples

## 46. Different authors

## 46.1. Code from Andrew Swan




```

\begin{tikzpicture}[scale=1.25]
\def\radius{4}
\def\angle{40}
\pgfmathsetmacro{\htan}{\tan(\angle)}
\tkzDefPoint(0,0){A} \tkzDefPoint(0,\radius){F}
\tkzDefPoint(\radius,0){B}
\tkzDefPointBy[rotation= center A angle \angle](B)
\tkzGetPoint{C}
\tkzDefLine[perpendicular=through B,K=1](A,B)
\tkzGetPoint{b}
\tkzInterLL(A,C)(B,b) \tkzGetPoint{D}
\tkzDefLine[perpendicular=through C,K=-1](A,B)
\tkzGetPoint{c}
\tkzInterLL(C,c)(A,B) \tkzGetPoint{E}
\tkzDrawSector[fill=blue,opacity=0.1](A,B)(C)
\tkzDrawArc[thin](A,B)(F)
\tkzMarkAngle(B,A,C)
\tkzLabelAngle[pos=0.8](B,A,C){$x$}
\tkzDrawPolygon(A,B,D)
\tkzDrawSegments(C,B)
\tkzDrawSegments[dashed,thin](C,E)
\tkzLabelPoints[below left](A)
\tkzLabelPoints[below right](B)
\tkzLabelPoints[above](C)
\tkzLabelPoints[above right](D)
\begin{scope}[pgf/decoration/raise=5pt]
\draw [decorate,decoration={brace,mirror,
amplitude=10pt},xshift=0pt,yshift=-4pt]
(A) -- (B) node [black,midway,yshift=-20pt]
{\footnotesize $1$};
\draw [decorate,decoration={brace,amplitude=10pt},
xshift=4pt,yshift=0pt]
(D) -- (B) node [black,midway,xshift=27pt]
{\footnotesize $\tan x$};
\draw [decorate,decoration={brace,amplitude=10pt},
xshift=4pt,yshift=0pt]
(E) -- (C) node [black,midway,xshift=-27pt]
{\footnotesize $\sin x$};
\end{scope}
\end{tikzpicture}

```

## 46.2. Example: Dimitris Kapeta

You need in this example to use `mkpos=.2` with `\tkzMarkAngle` because the measure of  $\widehat{CAM}$  is too small. Another possibility is to use `\tkzFillAngle`.




```
\begin{tikzpicture}[scale=1]
  \tkzDefPoint(0,0){O}
  \tkzDefPoint(2.5,0){N}
  \tkzDefPoint(-4.2,0.5){M}
  \tkzDefPointBy[rotation=center O angle 30](N)
  \tkzGetPoint{B}
  \tkzDefPointBy[rotation=center O angle -50](N)
  \tkzGetPoint{A}
  \tkzInterLC[common=B](M,B)(O,B) \tkzGetFirstPoint{C}
  \tkzInterLC[common=A](M,A)(O,A) \tkzGetFirstPoint{A'}
  \tkzMarkAngle[mkpos=.2, size=0.5](A,C,B)
  \tkzMarkAngle[mkpos=.2, size=0.5](A,M,C)
  \tkzDrawSegments(A,C M,A M,B A,B)
  \tkzDrawCircle(O,N)
  \tkzLabelCircle[above left](O,N)(120){%
    $\mathcal{C}$}
  \begin{scope}[veclen]
    \tkzMarkAngle[mkpos=.2, size=1.2](C,A,M)
  \end{scope}
  \tkzDrawPoints(O, A, B, M, B, C)
  \tkzLabelPoints[right](O,A,B)
  \tkzLabelPoints[above left](M,C)
  \tkzLabelPoint[below left](A'){$A'$}
\end{tikzpicture}
```

### 46.3. Example : John Kitzmiller

Prove that  $\frac{AC}{CE} = \frac{BD}{DF}$ .

Another interesting example from John, you can see how to use some extra options like `decoration` and `postaction` from TikZ with `tkz-euclide`.




```

\begin{tikzpicture}[scale=1.5,decoration={markings,
mark=at position 3cm with {\arrow[scale=2]{>}}}]
\tkzDefPoints{0/0/E, 6/0/F, 0/1.8/P, 6/1.8/Q, 0/3/R, 6/3/S}
\tkzDrawLines[postaction={decorate}](E,F P,Q R,S)
\tkzDefPoints{3.5/3/A, 5/3/B}
\tkzDrawSegments(E,A F,B)
\tkzInterLL(E,A)(P,Q) \tkzGetPoint{C}
\tkzInterLL(B,F)(P,Q) \tkzGetPoint{D}
\tkzLabelPoints[above right](A,B)
\tkzLabelPoints[below](E,F)
\tkzLabelPoints[above left](C)
\tkzDrawSegments[style=dashed](A,F)
\tkzInterLL(A,F)(P,Q) \tkzGetPoint{G}
\tkzLabelPoints[above right](D,G)
\tkzDrawSegments[color=teal, line width=3pt, opacity=0.4](A,C A,G)
\tkzDrawSegments[color=magenta, line width=3pt, opacity=0.4](C,E G,F)
\tkzDrawSegments[color=teal, line width=3pt, opacity=0.4](B,D)
\tkzDrawSegments[color=magenta, line width=3pt, opacity=0.4](D,F)
\end{tikzpicture}

```

#### 46.4. Example 1: from Indonesia



```

\begin{tikzpicture}[scale=3]
  \tkzDefPoints{0/0/A,2/0/B}
  \tkzDefSquare(A,B) \tkzGetPoints{C}{D}
  \tkzDefPointBy[rotation=center D angle 45](C)\tkzGetPoint{G}
  \tkzDefSquare(G,D)\tkzGetPoints{E}{F}
  \tkzInterLL(B,C)(E,F)\tkzGetPoint{H}
  \tkzFillPolygon[gray!10](D,E,H,C,D)
  \tkzDrawPolygon(A,...,D)\tkzDrawPolygon(D,...,G)
  \tkzDrawSegment(B,E)
  \tkzMarkSegments[mark=|,size=3pt,color=gray](A,B B,C C,D D,A E,F F,G G,D D,E)
  \tkzMarkSegments[mark=||,size=3pt,color=gray](B,E E,H)
  \tkzLabelPoints[left](A,D)
  \tkzLabelPoints[right](B,C,F,H)
  \tkzLabelPoints[above](G)\tkzLabelPoints[below](E)
  \tkzMarkRightAngles(D,A,B D,G,F)
\end{tikzpicture}


```

#### 46.5. Example 2: from Indonesia


```

\begin{tikzpicture}[pol/.style={fill=brown!40,opacity=.2},
  seg/.style={tkzdotted,color=gray}, hidden pt/.style={fill=gray!40},
  mra/.style={color=gray!70,tikzdotted,/tkzrightangle/size=.2},scale=2]
\tkzDefPoints{0/0/A,2.5/0/B,1.33/0.75/D,0/2.5/E,2.5/2.5/F}
\tkzDefLine[parallel=through D](A,B) \tkzGetPoint{I1}
\tkzDefLine[parallel=through B](A,D) \tkzGetPoint{I2}
\tkzInterLL(D,I1)(B,I2) \tkzGetPoint{C}
\tkzDefLine[parallel=through E](A,D) \tkzGetPoint{I3}
\tkzDefLine[parallel=through D](A,E) \tkzGetPoint{I4}
\tkzInterLL(E,I3)(D,I4) \tkzGetPoint{H}
\tkzDefLine[parallel=through F](E,H) \tkzGetPoint{I5}
\tkzDefLine[parallel=through H](E,F) \tkzGetPoint{I6}
\tkzInterLL(F,I5)(H,I6) \tkzGetPoint{G}
\tkzDefMidPoint(G,H) \tkzGetPoint{P} \tkzDefMidPoint(G,C) \tkzGetPoint{Q}
\tkzDefMidPoint(B,C) \tkzGetPoint{R} \tkzDefMidPoint(A,B) \tkzGetPoint{S}
\tkzDefMidPoint(A,E) \tkzGetPoint{T} \tkzDefMidPoint(E,H) \tkzGetPoint{U}
\tkzDefMidPoint(A,D) \tkzGetPoint{M} \tkzDefMidPoint(D,C) \tkzGetPoint{N}
\tkzInterLL(B,D)(S,R)\tkzGetPoint{L} \tkzInterLL(H,F)(U,P) \tkzGetPoint{K}
\tkzDefLine[parallel=through K](D,H) \tkzGetPoint{I7}
\tkzInterLL(K,I7)(B,D) \tkzGetPoint{O}
\tkzFillPolygon[pol](P,Q,R,S,T,U)
\tkzDrawSegments[seg](K,O K,L P,Q R,S T,U C,D H,D A,D M,N B,D)
\tkzDrawSegments(E,H B,C G,F G,H G,C Q,R S,T U,P H,F)
\tkzDrawPolygon(A,B,F,E)
\tkzDrawPoints(A,B,C,E,F,G,H,P,Q,R,S,T,U,K) \tkzDrawPoints[hidden pt](M,N,O,D)
\tkzMarkRightAngle[mra](L,O,K)
\tkzMarkSegments[mark=|,size=1pt,thick,color=gray](A,S B,S B,R C,R
  Q,C Q,G G,P H,P E,U H,U E,T A,T)
\tkzLabelAngle[pos=.3](K,L,O){$\alpha$}
\tkzLabelPoints[below](O,A,S,B) \tkzLabelPoints[above](H,P,G)
\tkzLabelPoints[left](T,E) \tkzLabelPoints[right](C,Q)
\tkzLabelPoints[above left](U,D,M) \tkzLabelPoints[above right](L,N)
\tkzLabelPoints[below right](F,R) \tkzLabelPoints[below left](K)
\end{tikzpicture}

```



## 46.6. Illustration of the Morley theorem by Nicolas François



```


\begin{tikzpicture}
  \tkzInit[ymin=-3,ymax=5,xmin=-5,xmax=7]
  \tkzClip
  \tkzDefPoints{-2.5/-2/A,2/4/B,5/-1/C}
  \tkzFindAngle(C,A,B) \tkzGetAngle{anglea}
  \tkzDefPointBy[rotation=center A angle 1*\anglea/3](C) \tkzGetPoint{TA1}
  \tkzDefPointBy[rotation=center A angle 2*\anglea/3](C) \tkzGetPoint{TA2}
  \tkzFindAngle(A,B,C) \tkzGetAngle{angleb}
  \tkzDefPointBy[rotation=center B angle 1*\angleb/3](A) \tkzGetPoint{TB1}
  \tkzDefPointBy[rotation=center B angle 2*\angleb/3](A) \tkzGetPoint{TB2}
  \tkzFindAngle(B,C,A) \tkzGetAngle{anglec}
  \tkzDefPointBy[rotation=center C angle 1*\anglec/3](B) \tkzGetPoint{TC1}
  \tkzDefPointBy[rotation=center C angle 2*\anglec/3](B) \tkzGetPoint{TC2}
  \tkzInterLL(A,TA1)(B,TB2) \tkzGetPoint{U1}
  \tkzInterLL(A,TA2)(B,TB1) \tkzGetPoint{V1}
  \tkzInterLL(B,TB1)(C,TC2) \tkzGetPoint{U2}
  \tkzInterLL(B,TB2)(C,TC1) \tkzGetPoint{V2}
  \tkzInterLL(C,TC1)(A,TA2) \tkzGetPoint{U3}
  \tkzInterLL(C,TC2)(A,TA1) \tkzGetPoint{V3}
  \tkzDrawPolygons(A,B,C U1,U2,U3 V1,V2,V3)
  \tkzDrawLines[add=2 and 2,very thin,dashed](A,TA1 B,TB1 C,TC1 A,TA2 B,TB2 C,TC2)
  \tkzDrawPoints(U1,U2,U3,V1,V2,V3)
  \tkzLabelPoint[left](V1){$s_a$} \tkzLabelPoint[right](V2){$s_b$}
  \tkzLabelPoint[below](V3){$s_c$} \tkzLabelPoint[above left](A){$A$}
  \tkzLabelPoints[above right](B,C) \tkzLabelPoint(U1){$t_a$}
  \tkzLabelPoint[below left](U2){$t_b$} \tkzLabelPoint[above](U3){$t_c$}
\end{tikzpicture}

```

## 46.7. Gou gu theorem / Pythagorean Theorem by Zhao Shuang

## Gou gu theorem / Pythagorean Theorem by Zhao Shuang

*Pythagoras was not the first person who discovered this theorem around the world. Ancient China discovered this theorem much earlier than him. So there is another name for the Pythagorean theorem in China, the Gou-Gu theorem. Zhao Shuang was an ancient Chinese mathematician. He rediscovered the “Gou gu theorem”, which is actually the Chinese version of the “Pythagorean theorem”. Zhao Shuang used a method called the “cutting and compensation principle”, he created a picture of “Pythagorean Round Square” Below the figure used to illustrate the proof of the “Gou gu theorem.” (code from Nan Geng)*




```
\begin{tikzpicture}[scale=.8]
\tkzDefPoint(0,0){A} \tkzDefPoint(4,0){A'}
\tkzInterCC[R](A, 5)(A', 3)
\tkzGetSecondPoint{B}
\tkzDefSquare(A,B) \tkzGetPoints{C}{D}
\tkzCalcLength(A,A') \tkzGetLength{a}
\tkzCalcLength(A',B) \tkzGetLength{b}
\pgfmathparse{\a-\b}
\tkzInterLC[R](A,A')(A',\pgfmathresult)
\tkzGetFirstPoint{D'}
\tkzDefSquare(D',A')\tkzGetPoints{B'}{C'}
\tkzDefLine[orthogonal=through D](D,D')
\tkzGetPoint{d}
\tkzDefLine[orthogonal=through A](A,A')
\tkzGetPoint{a}
\tkzDefLine[orthogonal=through C](C,C')
\tkzGetPoint{c}
\tkzInterLL(D,d)(C,c) \tkzGetPoint{E}
\tkzInterLL(D,d)(A,a) \tkzGetPoint{F}
\tkzDefSquare(E,F)\tkzGetPoints{G}{H}
\tkzDrawPolygons[fill=teal!10](A,B,A' B,C,B'
C,D,C' A,D',D)
\tkzDrawPolygons(A,B,C,D E,F,G,H)
\tkzDrawPolygon[fill=green!10](A',B',C',D')
\tkzDrawSegment[dim={a$, -10pt,}] (D,C')
\tkzDrawSegment[dim={b$, -10pt,}] (C,C')
\tkzDrawSegment[dim={c$, -10pt,}] (C,D)
\tkzDrawPoints[size=2](A,B,C,D,A',B',C',D')
\tkzLabelPoints[left](A)
\tkzLabelPoints[below](B)
\tkzLabelPoints[right](C)
\tkzLabelPoints[above](D)
\tkzLabelPoints[right](A')
\tkzLabelPoints[below right](B')
\tkzLabelPoints[below left](C')
\tkzLabelPoints[below](D')
\end{tikzpicture}
```



## 46.8. Reuleaux-Triangle

## Reuleaux-triangle by Stefan Kottwitz

A well-known classic field of mathematics is geometry. You may know Euclidean geometry from school, with constructions by compass and ruler. Math teachers may be very interested in drawing geometry constructions and explanations. Underlying constructions can help us with general drawings where we would need intersections and tangents of lines and circles, even if it does not look like geometry. So, here, we will remember school geometry drawings. We will use the `tkz-euclide` package, which works on top of TikZ. We will construct an equilateral triangle. Then we extend it to get a Reuleaux triangle, and add annotations. The code is fully explained in the *LaTeX Cookbook*, Chapter 10, Advanced Mathematics, Drawing geometry pictures. Stefan Kottwitz



```

\begin{tikzpicture}
\tkzDefPoint(0,0){A} \tkzDefPoint(4,1){B}
\tkzInterCC(A,B)(B,A) \tkzGetPoints{C}{D}
\tkzInterLC(A,B)(B,A) \tkzGetPoints{F}{E}
\tkzDrawCircles[dashed](A,B B,A)
\tkzDrawPolygons(A,B,C A,E,D)
\tkzCompass[color=red, very thick](A,C B,C A,D B,D)
\begin{scope}
\tkzSetUpArc[thick,delta=0]
\tkzDrawArc[fill=blue!10](A,B)(C)
\tkzDrawArc[fill=blue!10](B,C)(A)
\tkzDrawArc[fill=blue!10](C,A)(B)
\end{scope}
\tkzMarkAngles(D,A,E A,E,D)
\tkzFillAngles[fill=yellow,opacity=0.5](D,A,E A,E,D)
\tkzMarkRightAngle[size=0.65,fill=red!20,opacity=0.2](A,D,E)
\tkzLabelAngle[pos=0.7](D,A,E){$\alpha$}
\tkzLabelAngle[pos=0.8](A,E,D){$\beta$}
\tkzLabelAngle[pos=0.5,xshift=-1.4mm](A,D,D){$90^\circ$}
\begin{scope}[font=\small]
\tkzLabelSegment[below=0.6cm,align=center](A,B){Reuleaux\triangle}
\tkzLabelSegment[above right,sloped](A,E){hypotenuse}
\tkzLabelSegment[below,sloped](D,E){opposite}
\tkzLabelSegment[below,sloped](A,D){adjacent}
\tkzLabelSegment[below right=4cm](A,E){Thales circle}
\end{scope}
\tkzLabelPoints[below left](A)
\tkzLabelPoints(B,D)
\tkzLabelPoint[above](C){$C$}
\tkzLabelPoints(E)
\tkzDrawPoints(A,...,E)
\end{tikzpicture}


```

## 47. Some interesting examples

### 47.1. Square root of the integers

#### Square root of the integers

*How to get  $1, \sqrt{2}, \sqrt{3}$  with a rule and a compass.*



```


\begin{tikzpicture}
\tkzDefPoint(0,0){0}
\tkzDefPoint(1,0){a0}
\tkzDrawSegment(0,a0)
\foreach \i [count=\j] in {0,...,16}{%
\tkzDefPointWith[orthogonal normed](a\i,0)
\tkzGetPoint{a\j}
\tkzLabelPoint{a\j}
\tkzLabelAngle[pos=0.5,xshift=-1.4mm](a\i,a\j){$90^\circ$}
\tkzDrawPolySeg[fill=teal!10](a\i,a\j,0)}
\end{tikzpicture}

```

## 47.2. About right triangle

## About right triangle

We have a segment  $[AB]$  and we want to determine a point  $C$  such that  $AC = 8$  cm and  $ABC$  is a right triangle in  $B$ .




```
\begin{tikzpicture}[scale=.5]
  \tkzDefPoint["$A$" left](2,1){A}
  \tkzDefPoint["$B$" right](6,4){B}
  \tkzDefPointWith[orthogonal,K=-1](B,A)
  \tkzDrawLine[add = .5 and .5](B,t kzPointResult)
  \tkzInterLC[R](B,t kzPointResult)(A,8)
  \tkzGetPoints{J}{C}
  \tkzDrawSegment(A,B)
  \tkzDrawPoints(A,B,C)
  \tkzCompass(A,C)
  \tkzMarkRightAngle(A,B,C)
  \tkzDrawLine[color=gray,style=dashed](A,C)
  \tkzLabelPoint[above](C){C$}
\end{tikzpicture}
```

## 47.3. Archimedes

## Archimedes

This is an ancient problem proved by the great Greek mathematician Archimedes. The figure below shows a semicircle, with diameter  $AB$ . A tangent line is drawn and touches the semicircle at  $B$ . Another tangent line at a point,  $C$ , on the semicircle is drawn. We project the point  $C$  on the line segment  $[AB]$  on a point  $D$ . The two tangent lines intersect at the point  $T$ . Prove that the line  $(AT)$  bisects  $(CD)$ .



```


\begin{tikzpicture}[scale=1]
  \tkzDefPoint(0,0){A}\tkzDefPoint(6,0){D}
  \tkzDefPoint(8,0){B}\tkzDefPoint(4,0){I}
  \tkzDefLine[orthogonal=through D](A,D)
  \tkzInterLC[R](D,\tkzPointResult)(I,4)\tkzGetSecondPoint{C}
  \tkzDefLine[orthogonal=through C](I,C)\tkzGetPoint{c}
  \tkzDefLine[orthogonal=through B](A,B)\tkzGetPoint{b}
  \tkzInterLL(C,c)(B,b)\tkzGetPoint{T}
  \tkzInterLL(A,T)(C,D)\tkzGetPoint{P}
  \tkzDrawArc(I,B)(A)
  \tkzDrawSegments(A,B A,T C,D I,C)\tkzDrawSegment[new](I,C)
  \tkzDrawLine[add = 1 and 0](C,T)\tkzDrawLine[add = 0 and 1](B,T)
  \tkzMarkRightAngle(I,C,T)
  \tkzDrawPoints(A,B,I,D,C,T)
  \tkzLabelPoints(A,B,I,D)\tkzLabelPoints[above right](C,T)
  \tkzMarkSegment[pos=.25,mark=s|](C,D)\tkzMarkSegment[pos=.75,mark=s|](C,D)
\end{tikzpicture}

```

## 47.3.1. Square and rectangle of same area; Golden section

Book II, proposition XI \_Euclid's Elements\_

*To construct Square and rectangle of same area.*




```
\begin{tikzpicture}[scale=.75]
\tkzDefPoint(0,0){D} \tkzDefPoint(8,0){A}
\tkzDefSquare(D,A) \tkzGetPoints{B}{C}
\tkzDefMidPoint(D,A) \tkzGetPoint{E}
\tkzInterLC(D,A)(E,B)\tkzGetSecondPoint{F}
\tkzInterLC[near](B,A)(A,F)\tkzGetFirstPoint{G}
\tkzDefSquare(A,F)\tkzGetFirstPoint{H}
\tkzInterLL(C,D)(H,G)\tkzGetPoint{I}
\tkzFillPolygon[teal!10](I,G,B,C)
\tkzFillPolygon[teal!10](A,F,H,G)
\tkzDrawArc[angles](E,B)(0,120)
\tkzDrawSemiCircle(A,F)
\tkzDrawSegments(A,F E,B H,I F,H)
\tkzDrawPolygons(A,B,C,D)
\tkzDrawPoints(A,...,I)
\tkzLabelPoints[below right](A,E,D,F,I)
\tkzLabelPoints[above right](C,B,G,H)
\end{tikzpicture}
```

## 47.3.2. Steiner Line and Simson Line

## Steiner Line and Simson Line

Consider the triangle  $ABC$  and a point  $M$  on its circumcircle. The projections of  $M$  on the sides of the triangle are on a line (Steiner Line), The three closest points to  $M$  on lines  $AB$ ,  $AC$ , and  $BC$  are collinear. It's the Simson Line.




```
\begin{tikzpicture}[scale=.75,rotate=-20]
  \tkzDefPoint(0,0){B}
  \tkzDefPoint(2,4){A} \tkzDefPoint(7,0){C}
  \tkzDefCircle[circum](A,B,C)
  \tkzGetPoint{O}
  \tkzDrawCircle(0,A)
  \tkzCalcLength(0,A)
  \tkzGetLength{rOA}
  \tkzDefShiftPoint[O](40:\rOA){M}
  \tkzDefShiftPoint[O](60:\rOA){N}
  \tkzDefTriangleCenter[orthic](A,B,C)
  \tkzGetPoint{H}
  \tkzDefSpcTriangle[orthic,name=H](A,B,C){a,b,c}
  \tkzDefPointsBy[reflection=over A--B](M,N){P,P'}
  \tkzDefPointsBy[reflection=over A--C](M,N){Q,Q'}
  \tkzDefPointsBy[reflection=over C--B](M,N){R,R'}
  \tkzDefMidPoint(M,P)\tkzGetPoint{I}
  \tkzDefMidPoint(M,Q)\tkzGetPoint{J}
  \tkzDefMidPoint(M,R)\tkzGetPoint{K}
  \tkzDrawSegments[new](P,R M,P M,Q M,R N,P'%
    N,Q' N,R' P',R' I,K)
  \tkzDrawPolygons(A,B,C)
  \tkzDrawPoints(A,B,C,H,M,N,P,Q,R,P',Q',R',I,J,K)
  \tkzLabelPoints(A,B,C,H,M,N,P,Q,R,P',Q',R',I,J,K)
\end{tikzpicture}
```

## 47.4. Lune of Hippocrates

## Lune of Hippocrates

From wikipedia : In geometry, the lune of Hippocrates, named after Hippocrates of Chios, is a lune bounded by arcs of two circles, the smaller of which has as its diameter a chord spanning a right angle on the larger circle. In the first figure, the area of the lune is equal to the area of the triangle ABC. Hippocrates of Chios (ancient Greek mathematician,)




```
\begin{tikzpicture}
\tkzInit[xmin=-2,xmax=5,ymin=-1,ymax=6]
\tkzClip % allows you to define a bounding box
% large enough
\tkzDefPoint(0,0){A}\tkzDefPoint(4,0){B}
\tkzDefSquare(A,B)
\tkzGetFirstPoint{C}
\tkzDrawPolygon[fill=green!5](A,B,C)
\begin{scope}
\tkzClipCircle[out](B,A)
\tkzDefMidPoint(C,A)\tkzGetPoint{M}
\tkzDrawSemiCircle[fill=teal!5](M,C)
\end{scope}
\tkzDrawArc[delta=90](B,C)(A)
\end{tikzpicture}
```

## 47.5. Lunes of Hasan Ibn al-Haytham

## Lune of Hippocrates

From wikipedia : the Arab mathematician Hasan Ibn al-Haytham (Latinized name Alhazen) showed that two lunes, formed on the two sides of a right triangle, whose outer boundaries are semicircles and whose inner boundaries are formed by the circumcircle of the triangle, then the areas of these two lunes added together are equal to the area of the triangle. The lunes formed in this way from a right triangle are known as the lunes of Alhazen.



```

\begin{tikzpicture}[scale=.5,rotate=180]
  \tkzInit[xmin=-1,xmax=11,ymin=-4,ymax=7]
  \tkzClip
  \tkzDefPoints{0/0/A,8/0/B}
  \tkzDefTriangle[pythagore,swap](A,B)
  \tkzGetPoint{C}
  \tkzDrawPolygon[fill=green!5](A,B,C)
  \tkzDefMidPoint(C,A) \tkzGetPoint{I}
  \begin{scope}
    \tkzClipCircle[out](I,A)
    \tkzDefMidPoint(B,A) \tkzGetPoint{x}
    \tkzDrawSemiCircle[fill=teal!5](x,A)
    \tkzDefMidPoint(B,C) \tkzGetPoint{y}
    \tkzDrawSemiCircle[fill=teal!5](y,B)
  \end{scope}
  \tkzSetUpCompass[/tkzcompass/delta=0]
  \tkzDefMidPoint(C,A) \tkzGetPoint{z}
  \tkzDrawSemiCircle(z,A)
\end{tikzpicture}


```



## 47.6. About clipping circles

## About clipping circles

*The problem is the management of the bounding box. First you have to define a rectangle in which the figure will be inserted. This is done with the first two lines.*



```
\begin{tikzpicture}
  \tkzInit[xmin=0,xmax=6,ymin=0,ymax=6]
  \tkzClip
  \tkzDefPoints{0/0/A, 6/0/B}
  \tkzDefSquare(A,B)      \tkzGetPoints{C}{D}
  \tkzDefMidPoint(A,B)    \tkzGetPoint{M}
  \tkzDefMidPoint(A,D)    \tkzGetPoint{N}
  \tkzDefMidPoint(B,C)    \tkzGetPoint{O}
  \tkzDefMidPoint(C,D)    \tkzGetPoint{P}
  \begin{scope}
    \tkzClipCircle[out](M,B) \tkzClipCircle[out](P,D)
    \tkzFillPolygon[teal!20](M,N,P,O)
  \end{scope}
  \begin{scope}
    \tkzClipCircle[out](N,A) \tkzClipCircle[out](O,C)
    \tkzFillPolygon[teal!20](M,N,P,O)
  \end{scope}
  \begin{scope}
    \tkzClipCircle(P,C) \tkzClipCircle(N,A)
    \tkzFillPolygon[teal!20](N,P,D)
  \end{scope}
  \begin{scope}
    \tkzClipCircle(O,C) \tkzClipCircle(P,C)
    \tkzFillPolygon[teal!20](P,C,O)
  \end{scope}
  \begin{scope}
    \tkzClipCircle(M,B) \tkzClipCircle(O,B)
    \tkzFillPolygon[teal!20](O,B,M)
  \end{scope}
  \begin{scope}
    \tkzClipCircle(N,A) \tkzClipCircle(M,A)
    \tkzFillPolygon[teal!20](A,M,N)
  \end{scope}
  \tkzDrawSemiCircles(M,B N,A O,C P,D)
  \tkzDrawPolygons(A,B,C,D M,N,P,O)
\end{tikzpicture}
```

## 47.7. Similar isosceles triangles

## Similar isosceles triangles

The following is from the excellent site **Descartes et les Mathématiques**. I did not modify the text and I am only the author of the programming of the figures. <http://debart.pagesperso-orange.fr/seconde/triangle.html>

The following is from the excellent site **Descartes et les Mathématiques**. I did not modify the text and I am only the author of the programming of the figures.

<http://debart.pagesperso-orange.fr/seconde/triangle.html>

Bibliography:

- Géométrie au Bac - Tangente, special issue no. 8 - Exercice 11, page 11
- Elisabeth Busser and Gilles Cohen: 200 nouveaux problèmes du "Monde" - POLE 2007 (200 new problems of "Le Monde")
- Affaire de logique n° 364 - Le Monde February 17, 2004

Two statements were proposed, one by the magazine *Tangente* and the other by *Le Monde*.


*Editor of the magazine "Tangente":* Two similar isosceles triangles AXB and BYC are constructed with main vertices X and Y, such that A, B and C are aligned and that these triangles are "indirect". Let  $\alpha$  be the angle at vertex  $\widehat{AXB} = \widehat{BYC}$ . We then construct a third isosceles triangle XZY similar to the first two, with main vertex Z and "indirect". We ask to demonstrate that point Z belongs to the straight line (AC).

*Editor of "Le Monde":* We construct two similar isosceles triangles AXB and BYC with principal vertices X and Y, such that A, B and C are aligned and that these triangles are "indirect". Let  $\alpha$  be the angle at vertex  $\widehat{AXB} = \widehat{BYC}$ . The point Z of the line segment [AC] is equidistant from the two vertices X and Y. At what angle does he see these two vertices?

The constructions and their associated codes are on the next two pages, but you can search before looking. The programming respects (it seems to me ...) my reasoning in both cases.



## 47.9. "Le Monde" version



```


\begin{tikzpicture}[scale=1.25]
  \tkzDefPoint(0,0){A}
  \tkzDefPoint(3,0){B}
  \tkzDefPoint(9,0){C}
  \tkzDefPoint(1.5,2){X}
  \tkzDefPoint(6,4){Y}
  \tkzDefCircle[circum](X,Y,B) \tkzGetPoint{O}
  \tkzDefMidPoint(X,Y) \tkzGetPoint{I}
  \tkzDefPointWith[orthogonal](I,Y) \tkzGetPoint{i}
  \tkzDrawLines[add = 2 and 1,color=orange](I,i)
  \tkzInterLL(I,i)(A,B) \tkzGetPoint{Z}
  \tkzInterLC(I,i)(O,B) \tkzGetFirstPoint{M}
  \tkzDefPointWith[orthogonal](B,Z) \tkzGetPoint{b}
  \tkzDrawCircle(O,B)
  \tkzDrawLines[add = 0 and 2,color=orange](B,b)
  \tkzDrawSegments(A,X B,X B,Y C,Y A,C X,Y)
  \tkzDrawSegments[color=red](X,Z Y,Z)
  \tkzDrawPoints(A,B,C,X,Y,Z,M,I)
  \tkzLabelPoints(A,B,C,Z)
  \tkzLabelPoints[above right](X,Y,M,I)
\end{tikzpicture}

```

## 47.10. Triangle altitudes


## Triangle altitudes

From Wikipedia : The following is again from the excellent site *Descartes et les Mathématiques* (Descartes and the Mathematics). [http://debart.pagesperso-orange.fr/geoplan/geometrie\\_triangle.html](http://debart.pagesperso-orange.fr/geoplan/geometrie_triangle.html). The three altitudes of a triangle intersect at the same H-point.



```
\begin{tikzpicture}
  \tkzDefPoint(0,0){C} \tkzDefPoint(7,0){B}
  \tkzDefPoint(5,6){A}
  \tkzDefMidPoint(C,B) \tkzGetPoint{I}
  \tkzInterLC(A,C)(I,B)
  \tkzGetFirstPoint{B'}
  \tkzInterLC(A,B)(I,C)
  \tkzGetSecondPoint{C'}
  \tkzInterLL(B,B')(C,C') \tkzGetPoint{H}
  \tkzInterLL(A,H)(C,B) \tkzGetPoint{A'}
  \tkzDefCircle[circum](A,B',C') \tkzGetPoint{O}
  \tkzDrawArc(I,B)(C)
  \tkzDrawPolygon(A,B,C)
  \tkzDrawCircle[color=red](O,A)
  \tkzDrawSegments[color=orange](B,B' C,C' A,A')
  \tkzMarkRightAngles(C,B',B B',C' C C',A',A)
  \tkzDrawPoints(A,B,C,A',B',C',H)
  \tkzLabelPoints[above right](A,B',C',H)
  \tkzLabelPoints[below right](B,C,A')
\end{tikzpicture}
```

## 47.11. Altitudes - other construction



```


\begin{tikzpicture}
\tkzDefPoint(0,0){A} \tkzDefPoint(8,0){B}
\tkzDefPoint(5,6){C}
\tkzDefMidPoint(A,B)\tkzGetPoint{O}
\tkzDefPointBy[projection=onto A--B](C) \tkzGetPoint{P}
\tkzInterLC[common=A](C,A)(O,A)
\tkzGetFirstPoint{M}
\tkzInterLC(C,B)(O,A)
\tkzGetSecondPoint{N}
\tkzInterLL(B,M)(A,N)\tkzGetPoint{I}
\tkzDefCircle[diameter](A,B)\tkzGetPoint{x}
\tkzDefCircle[diameter](I,C)\tkzGetPoint{y}
\tkzDrawCircles(x,A y,C)
\tkzDrawSegments(C,A C,B A,B B,M A,N)
\tkzMarkRightAngles[fill=brown!20](A,M,B A,N,B A,P,C)
\tkzDrawSegment[style=dashed,color=orange](C,P)
\tkzLabelPoints(O,A,B,P)
\tkzLabelPoint[left](M){M}
\tkzLabelPoint[right](N){N}
\tkzLabelPoint[above](C){C}
\tkzLabelPoint[above right](I){I}
\tkzDrawPoints[color=red](M,N,P,I)
\tkzDrawPoints[color=brown](O,A,B,C)
\end{tikzpicture}

```

## 47.12. Three circles in an Equilateral Triangle

## Three circles in an Equilateral Triangle

From Wikipedia : In geometry, the Malfatti circles are three circles inside a given triangle such that each circle is tangent to the other two and to two sides of the triangle. They are named after Gian Francesco Malfatti, who made early studies of the problem of constructing these circles in the mistaken belief that they would have the largest possible total area of any three disjoint circles within the triangle. Below is a study of a particular case with an equilateral triangle and three identical circles.




```
\begin{tikzpicture}[scale=.8]
  \tkzDefPoints{0/0/A,8/0/B,0/4/a,8/4/b,8/8/c}
  \tkzDefTriangle[equilateral](A,B) \tkzGetPoint{C}
  \tkzDefMidPoint(A,B) \tkzGetPoint{M}
  \tkzDefMidPoint(B,C) \tkzGetPoint{N}
  \tkzDefMidPoint(A,C) \tkzGetPoint{P}
  \tkzInterLL(A,N)(M,a) \tkzGetPoint{Ia}
  \tkzDefPointBy[projection = onto A--B](Ia)
  \tkzGetPoint{ha}
  \tkzInterLL(B,P)(M,b) \tkzGetPoint{Ib}
  \tkzDefPointBy[projection = onto A--B](Ib)
  \tkzGetPoint{hb}
  \tkzInterLL(A,c)(M,C) \tkzGetPoint{Ic}
  \tkzDefPointBy[projection = onto A--C](Ic)
  \tkzGetPoint{hc}
  \tkzInterLL(A,Ia)(B,Ib) \tkzGetPoint{G}
  \tkzDefSquare(A,B) \tkzGetPoints{D}{E}
  \tkzDrawPolygon(A,B,C)
  \tkzClipBB
  \tkzDrawSemiCircles[gray,dashed](M,B A,M
  A,B B,A G,Ia)
  \tkzDrawCircles[gray](Ia,ha Ib,hb Ic,hc)
  \tkzDrawPolySeg(A,E,D,B)
  \tkzDrawPoints(A,B,C,G,Ia,Ib,Ic)
  \tkzDrawSegments[gray,dashed](C,M A,N B,P
  M,a M,b A,a a,b b,B A,D Ia,ha)
\end{tikzpicture}
```

## 47.13. Law of sines

## Law of sines

From wikipedia : *In trigonometry, the law of sines, sine law, sine formula, or sine rule is an equation relating the lengths of the sides of a triangle (any shape) to the sines of its angles.*



```
\begin{tikzpicture}
\tkzDefPoints{O/Q/A,5/1/B,2/6/C}
\tkzDefTriangleCenter[circum](A,B,C)
\tkzGetPoint{O}
\tkzDefPointBy[symmetry= center O](B)
\tkzGetPoint{D}
\tkzDrawPolygon[color=brown](A,B,C)
\tkzDrawCircle(O,A)
\tkzDrawPoints(A,B,C,D,O)
\tkzDrawSegments[dashed](B,D A,D)
\tkzLabelPoint[left](D){D}
\tkzLabelPoint[below](A){A}
\tkzLabelPoint[above](C){C}
\tkzLabelPoint[right](B){B}
\tkzLabelPoint[below](O){O}
\tkzLabelSegment(B,C){a}
\tkzLabelSegment[left](A,C){b}
\tkzLabelSegment(A,B){c}
\end{tikzpicture}
```

In the triangle ABC

$$\frac{a}{\sin A} = \frac{b}{\sin B} = \frac{c}{\sin C} \quad (1)$$

$$\hat{C} = \hat{D}$$

$$\frac{c}{2R} = \sin D = \sin C \quad (2)$$

Then

$$\frac{c}{\sin C} = 2R$$




## 47.14. Flower of Life

## Book IV, proposition XI \_Euclid's Elements\_

*Sacred geometry can be described as a belief system attributing a religious or cultural value to many of the fundamental forms of space and time. According to this belief system, the basic patterns of existence are perceived as sacred because in contemplating them one is contemplating the origin of all things. By studying the nature of these forms and their relationship to each other, one may seek to gain insight into the scientific, philosophical, psychological, aesthetic and mystical laws of the universe. The Flower of Life is considered to be a symbol of sacred geometry, said to contain ancient, religious value depicting the fundamental forms of space and time. In this sense, it is a visual expression of the connections life weaves through all mankind, believed by some to contain a type of Akashic Record of basic information of all living things.*

One of the beautiful arrangements of circles found at the Temple of Osiris at Abydos, Egypt (Rawles 1997).  
Weisstein, Eric W. "Flower of Life." From MathWorld—A Wolfram Web Resource.

<http://mathworld.wolfram.com/FlowerofLife.html>



```


\begin{tikzpicture}[scale=.75]
  \tkzSetUpLine[line width=2pt,color=teal!80!black]
  \tkzSetUpCompass[line width=2pt,color=teal!80!black]
  \tkzDefPoint(0,0){O}   \tkzDefPoint(2.25,0){A}
  \tkzDrawCircle(O,A)
  \foreach \i in {0,...,5}{
    \tkzDefPointBy[rotation= center O angle 30+60*\i](A)\tkzGetPoint{a\i}
    \tkzDefPointBy[rotation= center {a\i} angle 120](O)\tkzGetPoint{b\i}
    \tkzDefPointBy[rotation= center {a\i} angle 180](O)\tkzGetPoint{c\i}
    \tkzDefPointBy[rotation= center {c\i} angle 120](a\i)\tkzGetPoint{d\i}
    \tkzDefPointBy[rotation= center {c\i} angle 60](d\i)\tkzGetPoint{f\i}
    \tkzDefPointBy[rotation= center {d\i} angle 60](b\i)\tkzGetPoint{e\i}
    \tkzDefPointBy[rotation= center {f\i} angle 60](d\i)\tkzGetPoint{g\i}
    \tkzDefPointBy[rotation= center {d\i} angle 60](e\i)\tkzGetPoint{h\i}
    \tkzDefPointBy[rotation= center {e\i} angle 180](b\i)\tkzGetPoint{k\i}
    \tkzDrawCircle(a\i,O)
    \tkzDrawCircle(b\i,a\i)
    \tkzDrawCircle(c\i,a\i)
    \tkzDrawArc[rotate](f\i,d\i)(-120)
    \tkzDrawArc[rotate](e\i,d\i)(180)
    \tkzDrawArc[rotate](d\i,f\i)(180)
    \tkzDrawArc[rotate](g\i,f\i)(60)
    \tkzDrawArc[rotate](h\i,d\i)(60)
    \tkzDrawArc[rotate](k\i,e\i)(60)
  }
  \tkzClipCircle(O,f0)
\end{tikzpicture}

```

## 47.15. Pentagon in a circle

Book IV, proposition XI \_Euclid's Elements\_

*To inscribe an equilateral and equiangular pentagon in a given circle.*




```
\begin{tikzpicture}[scale=.75]
  \tkzDefPoint(0,0){O}
  \tkzDefPoint(5,0){A}
  \tkzDefPoint(0,5){B}
  \tkzDefPoint(-5,0){C}
  \tkzDefPoint(0,-5){D}
  \tkzDefMidPoint(A,O)
  \tkzInterLC(I,B)(I,A)
  \tkzInterCC(O,C)(B,E)
  \tkzInterCC(O,C)(B,F)
  \tkzGetPoint{I}
  \tkzGetPoints{F}{E}
  \tkzGetPoints{D3}{D2}
  \tkzGetPoints{D4}{D1}
  \tkzDrawArc[angles](B,E)(180,360)
  \tkzDrawArc[angles](B,F)(220,340)
  \tkzDrawLine[add=.5 and .5](B,I)
  \tkzDrawCircle(0,A)
  \tkzDefCircle[diameter](O,A)
  \tkzGetPoint{x}
  \tkzDrawCircle(x,A)
  \tkzDrawSegments(B,D C,A)
  \tkzDrawPolygon[new](D,D1,D2,D3,D4)
  \tkzDrawPoints(A,...,D,O)
  \tkzDrawPoints[new](E,F,I,D1,D2,D4,D3)
  \tkzLabelPoints[below left](A,...,D,O)
  \tkzLabelPoints[new,below right](I,E,F,D1,D2,D4,D3)
\end{tikzpicture}
```

## 47.16. Pentagon in a square

## Pentagon in a square

*To inscribe a pentagon in a given square.*



```

\begin{tikzpicture}[scale=.75]
  \tkzDefPoints{O/0/0,-5/-5/A,5/-5/B}
  \tkzDefSquare(A,B) \tkzGetPoints{C}{D}
  \tkzDefMidPoint(A,B) \tkzGetPoint{F}
  \tkzDefMidPoint(C,D) \tkzGetPoint{E}
  \tkzDefMidPoint(B,C) \tkzGetPoint{G}
  \tkzDefMidPoint(A,D) \tkzGetPoint{K}
  \tkzInterLC[near](C,D)(E,B) \tkzGetFirstPoint{T}
  \tkzDefMidPoint(D,T) \tkzGetPoint{I}
  \tkzInterCC[with nodes](O,D,I)(E,D,I) \tkzGetSecondPoint{H}
  \tkzInterLC(O,H)(O,E) \tkzGetSecondPoint{M}
  \tkzInterCC(O,E)(E,M) \tkzGetFirstPoint{Q}
  \tkzInterCC[with nodes](O,O,E)(Q,E,M) \tkzGetFirstPoint{P}
  \tkzInterCC[with nodes](O,O,E)(P,E,M) \tkzGetFirstPoint{N}
  \tkzCompass(O,H E,H)
  \tkzDrawArc(E,B)(T)
  \tkzDrawPolygons[purple](A,B,C,D M,E,Q,P,N)
  \tkzDrawCircle(O,E)
  \tkzDrawSegments(T,I O,H E,H E,F G,K)
  \tkzDrawPoints(T,M,Q,P,N,I)
  \tkzLabelPoints(A,B,O,N,P,Q,M,H)
  \tkzLabelPoints[above right](C,D,E,I,T)
\end{tikzpicture}


```

## 47.17. Hexagon Inscribed

## Hexagon Inscribed


*To inscribe a regular hexagon in a given equilateral triangle perfectly inside it (no borders).*

## 47.17.1. Hexagon Inscribed version 1



```
\begin{tikzpicture}[scale=.5]
\pgfmathsetmacro{\c}{6}
\tkzDefPoints{0/0/A,\c/0/B}
\tkzDefTriangle[equilateral](A,B)\tkzGetPoint{C}
\tkzDefTriangleCenter[centroid](A,B,C)
\tkzGetPoint{I}
\tkzDefPointBy[homothety=center A ratio 1./3](B)
\tkzGetPoint{c1}
\tkzInterLC(B,C)(I,c1)\tkzGetPoints{a1}{a2}
\tkzInterLC(A,C)(I,c1)\tkzGetPoints{b1}{b2}
\tkzInterLC(A,B)(I,c1)\tkzGetPoints{c1}{c2}
\tkzDrawPolygon(A,B,C)
\tkzDrawCircle[thin,orange](I,c1)
\tkzDrawPolygon[red,thick](a2,a1,b2,b1,c2,c1)
\end{tikzpicture}
```

## 47.17.2. Hexagon Inscribed version 2




```
\begin{tikzpicture}[scale=.5]
\pgfmathsetmacro{\c}{6}
\tkzDefPoints{0/0/A,\c/0/B}
\tkzDefTriangle[equilateral](A,B)\tkzGetPoint{C}
\tkzDefTriangleCenter[centroid](A,B,C)
\tkzGetPoint{I}
\tkzDefPointsBy[rotation= center I%
angle 60](A,B,C){a,b,c}
\tkzDrawPolygon[fill=teal!20,opacity=.5](A,B,C)
\tkzDrawPolygon[fill=purple!20,opacity=.5](a,b,c)
\end{tikzpicture}
```

## 47.18. Power of a point with respect to a circle

## Power of a point with respect to a circle

$$\overline{MA} \times \overline{MB} = MT^2 = MO^2 - OT^2$$



```


\begin{tikzpicture}
  \pgfmathsetmacro{\r}{2}%
  \pgfmathsetmacro{\x0}{6}%
  \pgfmathsetmacro{\xE}{\x0-\r}%
  \tkzDefPoints{\O/\O/M,\x0/\O/O,\xE/\O/E}
  \tkzDefCircle[diameter](M,O)
  \tkzGetPoint{I}
  \tkzInterCC(I,O)(O,E) \tkzGetPoints{T}{T'}
  \tkzDefShiftPoint[O](45:2){B}
  \tkzInterLC(M,B)(O,E) \tkzGetPoints{A}{B}
  \tkzDrawCircle(O,E)
  \tkzDrawSemiCircle[dashed](I,O)
  \tkzDrawLine(M,O)
  \tkzDrawLines(M,T O,T M,B)
  \tkzDrawPoints(A,B,T)
  \tkzLabelPoints[above](A,B,O,M,T)
\end{tikzpicture}

```

## 47.19. Radical axis of two non-concentric circles

## Radical axis of two non-concentric circles

From Wikipedia : *In geometry, the radical axis of two non-concentric circles is the set of points whose power with respect to the circles are equal. For this reason the radical axis is also called the power line or power bisector of the two circles. The notation radical axis was used by the French mathematician M. Chasles as axe radical.*




```
\begin{tikzpicture}
\tkzDefPoints{0/0/A,4/2/B,2/3/K}
\tkzDefCircle[R](A,1)\tkzGetPoint{a}
\tkzDefCircle[R](B,2)\tkzGetPoint{b}
\tkzDefCircle[R](K,3)\tkzGetPoint{k}
\tkzDrawCircles(A,a B,b)
\tkzDrawCircle[dashed,new](K,k)
\tkzInterCC(A,a)(K,k)\tkzGetPoints{a}{a'}
\tkzInterCC(B,b)(K,k)\tkzGetPoints{b}{b'}
\tkzDrawLines[new,add=2 and 2](a,a')
\tkzDrawLines[new,add=1 and 1](b,b')
\tkzInterLL(a,a')(b,b')\tkzGetPoint{X}
\tkzDefPointBy[projection= onto A--B](X)\tkzGetPoint{H}
\tkzDrawPoints(A,B,H,X,a,b,a',b')
\tkzDrawLine(A,B)
\tkzDrawLine[add= 1 and 2,new](X,H)
\tkzLabelPoints(A,B,H,X,a,b,a',b')
\end{tikzpicture}
```

## 47.20. External homothetic center

## External homothetic center

From Wikipedia: *Given two nonconcentric circles, draw radii parallel and in the same direction. Then the line joining the extremities of the radii passes through a fixed point on the line of centers which divides that line externally in the ratio of radii. This point is called the external homothetic center, or external center of similitude (Johnson 1929, pp. 19-20 and 41).*




```
\begin{tikzpicture}
\tkzDefPoints{O/Q/A,4/2/B,2/3/K}
\tkzDefCircle[R](A,1)\tkzGetPoint{a}
\tkzDefCircle[R](B,2)\tkzGetPoint{b}
\tkzDrawCircles(A,a B,b)
\tkzDrawLine(A,B)
\tkzDefShiftPoint[A](6Q:1){M}
\tkzDefShiftPoint[B](6Q:2){M'}
\tkzInterLL(A,B)(M,M') \tkzGetPoint{O}
\tkzDefLine[tangent from = O](B,M') \tkzGetPoints{X}{T'}
\tkzDefLine[tangent from = O](A,M) \tkzGetPoints{X}{T}
\tkzDrawPoints(A,B,O,T,T',M,M')
\tkzDrawLines[new](O,B O,T' O,M')
\tkzDrawSegments[new](A,M B,M')
\tkzLabelPoints(A,B,O,T,T',M,M')
\end{tikzpicture}
```



## 47.21. Tangent lines to two circles

## Tangent lines to two circles

For two circles, there are generally four distinct lines that are tangent to both if the two circles are outside each other. For two of these, the external tangent lines, the circles fall on the same side of the line; the external tangent lines intersect in the external homothetic center




```
\begin{tikzpicture}
  \pgfmathsetmacro{\r}{1}%
  \pgfmathsetmacro{\R}{2}%
  \pgfmathsetmacro{\rt}{\R-\r}%
  \tkzDefPoints{0/0/A,4/2/B,2/3/I}
  \tkzDefMidPoint(A,B) \tkzGetPoint{I}
  \tkzInterLC[R](A,B)(B,\rt) \tkzGetPoints{E}{F}
  \tkzInterCC(I,B)(B,F) \tkzGetPoints{a}{a'}
  \tkzInterLC[R](B,a)(B,\R) \tkzGetPoints{X'}{T'}
  \tkzDefLine[tangent at=T'](B) \tkzGetPoint{h}
  \tkzInterLL(T',h)(A,B) \tkzGetPoint{O}
  \tkzInterLC[R](O,T')(A,\r) \tkzGetPoints{T}{T}
  \tkzDefCircle[R](A,\r) \tkzGetPoint{a}
  \tkzDefCircle[R](B,\R) \tkzGetPoint{b}
  \tkzDefCircle[R](B,\rt) \tkzGetPoint{c}
  \tkzDrawCircles(A,a)
  \tkzDrawCircles[orange](B,b B,c)
  \tkzDrawCircle[orange,dashed](I,B)
  \tkzDrawPoints(O,A,B,a,a',E,F,T',T)
  \tkzDrawLines(O,B A,a B,T' A,T)
  \tkzDrawLines[add= 1 and 8](T',h)
  \tkzLabelPoints(O,A,B,a,a',E,F,T,T')
\end{tikzpicture}
```

## 47.22. Tangent lines to two circles with radical axis

## Tangent lines to two circles with radical axis

As soon as two circles are not concentric, we can construct their radical axis, the set of points of equal power with respect to the two circles. We know that the radical axis is a line orthogonal to the line of the centers. Note that if we specify  $P$  and  $Q$  as the points of contact of one of the common exterior tangents with the two circles and  $D$  and  $E$  as the points of the circles outside  $[AB]$ , then  $(DP)$  and  $(EQ)$  intersect on the radical axis of the two circles. We will show that this property is always true and that it allows us to construct common tangents, even when the circles have the same radius.



```


\begin{tikzpicture}
\tkzDefPoints{0/0/A,4/2/B,2/3/K}
\tkzDefCircle[R](A,1) \tkzGetPoint{a}
\tkzDefCircle[R](B,3) \tkzGetPoint{b}
\tkzInterCC[R](A,1)(K,3) \tkzGetPoints{a'}{a''}
\tkzInterCC[R](B,3)(K,3) \tkzGetPoints{b'}{b''}
\tkzInterLL(a,a')(b,b') \tkzGetPoint{X}
\tkzDefPointBy[projection= onto A--B](X) \tkzGetPoint{H}
\tkzGetPoint{C}
\tkzInterLC[R](A,B)(B,3) \tkzGetPoints{b1}{E}
\tkzInterLC[R](A,B)(A,1) \tkzGetPoints{D}{a2}
\tkzDefMidPoint(D,E) \tkzGetPoint{I}
\tkzDrawCircle[orange](I,D)
\tkzInterLC(X,H)(I,D) \tkzGetPoints{M}{M'}
\tkzInterLC(M,D)(A,D) \tkzGetPoints{P}{P'}
\tkzInterLC(M,E)(B,E) \tkzGetPoints{Q'}{Q}
\tkzInterLL(P,Q)(A,B) \tkzGetPoint{O}
\tkzDrawCircles(A,a B,b)
\tkzDrawSegments[orange](A,P I,M B,Q)
\tkzDrawPoints(A,B,D,E,M,I,O,P,Q,X,H)
\tkzDrawLines(O,E M,D M,E O,Q)
\tkzDrawLine[add= 3 and 4,orange](X,H)
\tkzLabelPoints(A,B,D,E,M,I,O,P,Q,X,H)
\end{tikzpicture}

```

## 47.23. Middle of a segment with a compass

## Tangent lines to two circles with radical axis

*This example involves determining the middle of a segment, using only a compass.*



```

\begin{tikzpicture}
\tkzDefPoint(0,0){A}
\tkzDefRandPointOn[circle= center A radius 4] \tkzGetPoint{B}
\tkzDefPointBy[rotation= center A angle 180](B) \tkzGetPoint{C}
\tkzInterCC(A,B)(B,A) \tkzGetPoints{I}{I'}
\tkzInterCC(A,I)(I,A) \tkzGetPoints{J}{J'}
\tkzInterCC(B,A)(C,B) \tkzGetPoints{D}{D'}
\tkzInterCC(D,B)(E,B) \tkzGetPoints{M}{M'}
\tkzSetUpArc[color=orange,style=solid,delta=10]
\tkzDrawArc(C,D)(E)
\tkzDrawArc(B,E)(D)
\tkzDrawCircle[color=teal,line width=.2pt](A,B)
\tkzDrawArc(D,B)(M)
\tkzDrawArc(E,M)(B)
\tkzCompass[color=orange,style=solid](B,I I,J J,C)
\tkzDrawPoints(A,B,C,D,E,M)
\tkzLabelPoints(A,B,M)
\end{tikzpicture}

```

## 47.24. Definition of a circle \_Apollonius\_


## Definition of a circle \_Apollonius\_

From Wikipedia : *Apollonius showed that a circle can be defined as the set of points in a plane that have a specified ratio of distances to two fixed points, known as foci. This Apollonian circle is the basis of the Apollonius pursuit problem. ... The solutions to this problem are sometimes called the circles of Apollonius.*

## Explanation

A circle is the set of points in a plane that are equidistant from a given point O. The distance  $r$  from the center is called the radius, and the point O is called the center. It is the simplest definition but it is not the only one. Apollonius of Perga gives another definition : The set of all points whose distances from two fixed points are in a constant ratio is a circle.

With tkz-euclide is easy to show you the last definition




```
\begin{tikzpicture}[scale=1.5]
  % Firstly we defined two fixed point.
  % The figure depends of these points and the ratio K
  \tkzDefPoint(0,0){A}
  \tkzDefPoint(4,0){B}
  % tkz-euclide.sty knows about the apollonius's circle
  % with K=2 we search some points like I such as IA=2 x IB
  \tkzDefCircle[apollonius,K=2](A,B) \tkzGetPoints{K1}{k}
  \tkzDefPointOnCircle[through= center K1 angle 30 point k]
  \tkzGetPoint{I}
  \tkzDefPointOnCircle[through= center K1 angle 280 point k]
  \tkzGetPoint{J}
  \tkzDrawSegments[new](A,I I,B A,J J,B)
  \tkzDrawCircle[color = teal,fill=teal!20,opacity=.4](K1,k)
  \tkzDrawPoints(A,B,K1,I,J)
  \tkzDrawSegment(A,B)
  \tkzLabelPoints[below,font=\scriptsize](A,B,K1,I,J)
\end{tikzpicture}
```

## 47.25. Application of Inversion : Pappus chain

## Pappus chain

From Wikipedia *In geometry, the Pappus chain is a ring of circles between two tangent circles investigated by Pappus of Alexandria in the 3rd century AD.*




```
\begin{tikzpicture}[ultra thin]
  \pgfmathsetmacro{\xB}{6}%
  \pgfmathsetmacro{\xC}{9}%
  \pgfmathsetmacro{\xD}{(\xC*\xC)/\xB}%
  \pgfmathsetmacro{\xJ}{(\xC+\xD)/2}%
  \pgfmathsetmacro{\r}{\xD-\xJ}%
  \pgfmathsetmacro{\nc}{16}%
  \tkzDefPoints{0/0/A,\xB/0/B,\xC/0/C,\xD/0/D}
  \tkzDefCircle[diameter](A,C) \tkzGetPoint{x}
  \tkzDrawCircle[fill=teal!30](x,C)
  \tkzDefCircle[diameter](A,B) \tkzGetPoint{y}
  \tkzDrawCircle[fill=teal!30](y,B)
  \foreach \i in {-\nc,...,0,...,\nc}
  {\tkzDefPoint(\xJ,2*\r*\i){J}
   \tkzDefPoint(\xJ,2*\r*\i-\r){H}
   \tkzDefCircleBy[inversion = center A through C](J,H)
   \tkzDrawCircle[fill=teal](tkzFirstPointResult,tkzSecondPointResult)}
\end{tikzpicture}
```

## 47.26. Book of lemmas proposition 1 Archimedes

## Book of lemmas proposition 1 Archimedes

*If two circles touch at A, and if [CD], [EF] be parallel diameters in them, A, C and E are aligned.*



```

\begin{tikzpicture}[scale=.75]
\tkzDefPoints{0/0/O_1,0/1/O_2,0/3/A}
\tkzDefPoint(15:3){F}
\tkzDefPointBy[symmetry=center O_1](F) \tkzGetPoint{E}
\tkzDefLine[parallel=through O_2](E,F) \tkzGetPoint{x}
\tkzInterLC(x,O_2)(O_2,A) \tkzGetPoints{D}{C}
\tkzDrawCircles(O_1,A O_2,A)
\tkzDrawSegments[orange](O_1,A E,F C,D)
\tkzDrawSegments[purple](A,E A,F)
\tkzDrawPoints(A,O_1,O_2,E,F,x,C,D)
\tkzLabelPoints(A,O_1,O_2,E,F,x,C,D)
\end{tikzpicture}

```

$(CD) \parallel (EF)$   $(AO_1)$  is secant to these two lines so  $\widehat{AO_2C} = \widehat{AO_1E}$ .

Since the triangles  $AO_2C$  and  $AO_1E$  are isosceles the angles at the base are equal  $\widehat{AC}O_2 = \widehat{AE}O_1 = \widehat{CA}O_2 = \widehat{EA}O_1$ . Thus A, C and E are aligned

## 47.27. Book of lemmas proposition 6 Archimedes

## Book of lemmas proposition 6 Archimedes


*Let AC, the diameter of a semicircle, be divided at B so that  $AC/AB = \phi$  or in any ratio. Describe semicircles within the first semicircle and on AB, BC as diameters, and suppose a circle drawn touching the all three semicircles. If GH be the diameter of this circle, to find relation between GH and AC.*

```

\begin{tikzpicture}
\tkzDefPoints{0/0/A,12/0/C}
\tkzDefGoldenRatio(A,C)
\tkzDefMidPoint(A,B)
\tkzDefMidPoint(A,B)
\tkzDefMidPoint(B,C)
\tkzDefExtSimilitudeCenter(O_1,A)(O_2,B)
\tkzDefIntSimilitudeCenter(O,A)(O_1,A)
\tkzDefIntSimilitudeCenter(O,C)(O_2,C)
\tkzInterCC(O_1,A)(M_2,C)
\tkzInterCC(O_2,C)(M_1,A)
\tkzInterCC(O,A)(M_0,B)
\tkzInterLL(O_1,E)(O_2,F)
\tkzDefCircle[ccircum](E,F,B)
\tkzInterLC(A,D)(O_1,A)
\tkzInterLC(C,D)(O_2,B)
\tkzInterLC[common=D](A,D)(O_3,D)
\tkzInterLC[common=D](C,D)(O_3,D)
\tkzInterLL(C,G)(B,K)
\tkzInterLL(A,H)(B,I)
\tkzInterLL(L,G)(A,C)
\tkzInterLL(M,H)(A,C)
\tkzDrawCircles[red,thin](O_3,F)
\tkzDrawCircles[new,thin](0_4,B)
\tkzDrawSemiCircles[teal](O,C O_1,B O_2,C)
\tkzDrawSemiCircles[green](M_2,C)
\tkzDrawSemiCircles[green,swap](M_1,A)
\tkzDrawSegment(A,C)
\tkzDrawSegments[new](O_1,O_3 O_2,O_3)
\tkzDrawSegments[new,very thin](B,H C,G A,H G,N H,P)
\tkzDrawSegments[new,very thin](B,D A,D C,D G,H I,B K,B B,G)
\tkzDrawPoints(A,B,C,M_1,M_2,E,O_3,F,D,0_4,O_1,O_2,I,K,G,H,L,P,N,M)
\tkzLabelPoints[font=\scriptsize](A,B,C,M_1,M_2,F,O_1,O_2,I,K,G,H,L,M,N)
\tkzLabelPoints[font=\scriptsize,right](E,O_3,D,0_4,P)
\end{tikzpicture}

```





Let GH be the diameter of the circle which is parallel to AC, and let the circle touch the semicircles on AC, AB, BC in D, E, F respectively.

Then, by Prop. 1 A,G and D are aligned, ainsi que D, H and C.

For a like reason A E and H are aligned, C F and G are aligned, as also are B E and G, B F and H.

Let (AD) meet the semicircle on [AC] at I, and let (BD) meet the semicircle on [BC] in K. Join CI, CK meeting AE, BF in L, M, and let GL, HM produced meet AB in N, P respectively.

Now, in the triangle AGB, the perpendiculars from A, C on the opposite sides meet in L. Therefore by the properties of triangles, (GN) is perpendicular to (AC). Similarly (HP) is perpendicular to (BC).

Again, since the angles at I, K, D are right, (CK) is parallel to (AD), and (CI) to (BD).

Therefore

$$\frac{AB}{BC} = \frac{AL}{LH} = \frac{AN}{NP} \quad \text{and} \quad \frac{BC}{AB} = \frac{CM}{MG} = \frac{PC}{NP}$$

hence

$$\frac{AN}{NP} = \frac{NP}{PC} \quad \text{so} \quad NP^2 = AN \times PC$$

Now suppose that B divides [AC] according to the divine proportion that is :

$$\phi = \frac{AB}{BC} = \frac{AC}{AB} \quad \text{then} \quad AN = \phi NP \text{ and } NP = \phi PC$$

We have

$$AC = AN + NP + PC \quad \text{either} \quad AB + BC = AN + NP + PC \quad \text{or} \quad (\phi + 1)BC = AN + NP + PC$$

we get

$$(\phi + 1)BC = \phi NP + NP + PC = (\phi + 1)NP + PC = \phi(\phi + 1)PC + PC = \phi^2 + \phi + 1)PC$$

as

$$\phi^2 = \phi + 1 \quad \text{then} \quad (\phi + 1)BC = 2(\phi + 1)PC \quad \text{i.e.} \quad BC = 2PC$$

That is, p is the middle of the segment BC.

Part of the proof from <https://www.cut-the-knot.org>

#### 47.28. "The" Circle of APOLLONIUS

The Apollonius circle of a triangle `_Apollonius_`


*The circle which touches all three excircles of a triangle and encompasses them is often known as "the" Apollonius circle (Kimberling 1998, p. 102)*

#### Explanation

The purpose of the first examples was to show the simplicity with which we could recreate these propositions. With TikZ you need to do calculations and use trigonometry while with `tkz-euclide` you only need to build simple objects

But don't forget that behind or far above `tkz-euclide` there is TikZ. I'm only creating an interface between TikZ and the user of my package.

The last example is very complex and it is to show you all that we can do with `tkz-euclide`.



```

\begin{tikzpicture}[scale=.6]
\tkzDefPoints{\Q/\Q/A,6/\Q/B,\Q.8/4/C}
\tkzDefTriangleCenter[euler](A,B,C) \tkzGetPoint{N}
\tkzDefTriangleCenter[circum](A,B,C) \tkzGetPoint{O}
\tkzDefTriangleCenter[lemoine](A,B,C) \tkzGetPoint{K}
\tkzDefTriangleCenter[ortho](A,B,C) \tkzGetPoint{H}
\tkzDefSpcTriangle[excentral,name=J](A,B,C){a,b,c}
\tkzDefSpcTriangle[centroid,name=M](A,B,C){a,b,c}
\tkzDefCircle[in](Ma,Mb,Mc) \tkzGetPoint{Sp} % Sp Spieker center
\tkzDefProjExcenter[name=J](A,B,C)(a,b,c){Y,Z,X}
\tkzDefLine[parallel=through Za](A,B) \tkzGetPoint{Xc}
\tkzInterLL(Za,Xc)(C,B) \tkzGetPoint{C'}
\tkzDefLine[parallel=through Zc](B,C) \tkzGetPoint{Ya}
\tkzInterLL(Zc,Ya)(A,B) \tkzGetPoint{A'}
\tkzDefPointBy[reflection= over Ja--Jc](C') \tkzGetPoint{Ab}
\tkzDefPointBy[reflection= over Ja--Jc](A') \tkzGetPoint{Cb}
\tkzInterLL(K,O)(N,Sp) \tkzGetPoint{Q}
\tkzInterLC(A,B)(Q,Cb) \tkzGetFirstPoint{Ba}
\tkzInterLC(A,C)(Q,Cb) \tkzGetPoints{Ac}{Ca}
\tkzInterLC(B,C')(Q,Cb) \tkzGetFirstPoint{Bc}
\tkzInterLC[next to=Ja](Ja,Q)(Q,Cb) \tkzGetFirstPoint{F'a}
\tkzInterLC[next to=Jc](Jc,Q)(Q,Cb) \tkzGetFirstPoint{F'c}
\tkzInterLC[next to=Jb](Jb,Q)(Q,Cb) \tkzGetFirstPoint{F'b}
\tkzInterLC[common=F'a](Sp,F'a)(Ja,F'a) \tkzGetFirstPoint{Fa}
\tkzInterLC[common=F'b](Sp,F'b)(Jb,F'b) \tkzGetFirstPoint{Fb}
\tkzInterLC[common=F'c](Sp,F'c)(Jc,F'c) \tkzGetFirstPoint{Fc}
\tkzInterLC(Mc,Sp)(Q,Cb) \tkzGetFirstPoint{A''}
\tkzDefCircle[euler](A,B,C) \tkzGetPoints{E}{e}
\tkzDefCircle[ex](C,A,B) \tkzGetPoints{Ea}{a}
\tkzDefCircle[ex](A,B,C) \tkzGetPoints{Eb}{b}
\tkzDefCircle[ex](B,C,A) \tkzGetPoints{Ec}{c}
% Calculations are done, now you can draw, mark and label
\tkzDrawCircles(Q,Cb E,e)%
\tkzDrawCircles(Eb,b Ea,a Ec,c)
\tkzDrawPolygon(A,B,C)
\tkzDrawSegments[dashed](A,A' C,C' A',Zc Za,C' B,Cb B,Ab A,Ca)
\tkzDrawSegments[dashed](C,Ac Ja,Xa Jb,Yb Jc,Zc)
\begin{scope}
\tkzClipCircle(Q,Cb) % We limit the drawing of the lines
\tkzDrawLine[add=5 and 12,orange](K,O)
\tkzDrawLine[add=12 and 28,red!50!black](N,Sp)
\end{scope}
\tkzDrawPoints(A,B,C,K,Ja,Jb,Jc,Q,N,O,Sp,Mc,Xa,Xb,Yb,Yc,Za,Zc)
\tkzDrawPoints(A',C',A'',Ab,Cb,Bc,Ca,Ac,Ba,Fa,Fb,Fc,F'a,F'b,F'c)
\tkzLabelPoints(Ja,Jb,Jc,Q,Xa,Xb,Za,Zc,Ab,Cb,Bc,Ca,Ac,Ba,F'b)
\tkzLabelPoints[above](O,K,F'a,Fa,A'')
\tkzLabelPoints[below](B,F'c,Yc,N,Sp,Fc,Mc)
\tkzLabelPoints[left](A',C',Fb)
\tkzLabelPoints[right](C)
\tkzLabelPoints[below right](A)
\tkzLabelPoints[above right](Yb)
\tkzDrawSegments(Fc,F'c Fb,F'b Fa,F'a)
\tkzDrawSegments[color=green!50!black](Mc,N Mc,A'' A'',Q)
\tkzDrawSegments[color=red,dashed](Ac,Ab Ca,Cb Ba,Bc Ja,Jc A',Cb C',Ab)
\tkzDrawSegments[color=red](Cb,Ab Bc,Ac Ba,Ca A',C')
\tkzMarkSegments[color=red,mark=|](Cb,Ab Bc,Ac Ba,Ca)
\tkzMarkRightAngles(Jc,Zc,A Ja,Xa,B Jb,Yb,C)
\tkzDrawSegments[green,dashed](A,F'a B,F'b C,F'c)
\end{tikzpicture}

```

Part X.

FAQ

## 48. FAQ

## 48.1. Most common errors

For the moment, I'm basing myself on my own, because having changed syntax several times, I've made a number of mistakes. This section is going to be expanded. With version 4.05 new problems may appear.

- The mistake I make most often is to forget to put an "s" in the macro used to draw more than one object: like `\tkzDrawSegment(s)` or `\tkzDrawCircle(s)` ok like in this example `\tkzDrawPoint(A,B)` when you need `\tkzDrawPoints(A,B);`
- Don't forget that since version 4 the unit is obligatorily the "cm" it is thus necessary to withdraw the unit like here `\tkzDrawCircle[R](0,3cm)` which becomes `\tkzDrawCircle[R](0,3)`. The traditional options of TikZ keep their units example below `right = 12pt` on the other hand one will write `size=1.2` to position an arc in `\tkzMarkAngle;`
- The following error still happens to me from time to time. A point that is created has its name in brackets while a point that is used either as an option or as a parameter has its name in braces.  
Example `\tkzGetPoint(A)` When defining an object, use braces and not brackets, so write: `\tkzGetPoint{A};`
- The changes in obtaining the points of intersection between lines and circles sometimes exchange the solutions, this leads either to a bad figure or to an error.
- `\tkzGetPoint{A}` in place of `\tkzGetFirstPoint{A}`. When a macro gives two points as results, either we retrieve these points using `\tkzGetPoints{A}{B}`, or we retrieve only one of the two points, using `\tkzGetFirstPoint{A}` or `\tkzGetSecondPoint{A}`. These two points can be used with the reference `tkzFirstPointResult` or `tkzSecondPointResult`. It is possible that a third point is given as `tkzPointResult;`
- Mixing options and arguments; all macros that use a circle need to know the radius of the circle. If the radius is given by a measure then the option includes a R.
- The angles are given in degrees, more rarely in radians.
- If an error occurs in a calculation when passing parameters, then it is better to make these calculations before calling the macro.
- Do not mix the syntax of `pgfmath` and `xfp`. I've often chosen `xfp` but if you prefer `pgfmath` then do your calculations before passing parameters.
- Error "dimension too large" : In some cases, this error occurs. One way to avoid it is to use the "veclen" option. When this option is used in a scope, the "veclen" function is replaced by a function dependent on "xfp". Do not use intersection macros in this scope. For example, an error occurs if you use the macro `\tkzDrawArc` with too small an angle. The error is produced by the `decoration` library when you want to place a mark on an arc. Even if the mark is absent, the error is still present.

## Index

- \add, 124
- \ang, 116
- \Ax, 182
- \Ay, 182
  
- \coordinate, 33
  
- \dAB, 180, 181
- \Delta, 169
- \draw (A)--(B);, 125
  
- \endpgfinterruptboundingbox, 154
- Environment
  - scope, 35, 191
  - tikzpicture, 191
  - tikzspicture, 191
  
- \foreach, 108
- \fpeval, 110
  
- \iftkzFlagCC, 111
- \iftkzFlagLC, 105
  
- \len, 181, 182
  
- Operating System
  - Windows, 17
  
- Packages
  - pgfmath, 247
  - tkz-elements, 16, 17
  - tkz-euclide, 147
  - xfp, 17, 33, 35, 180, 247
- \pgfinterruptboundingbox, 154
- \pgflinewidth, 122, 123
- \pgfmathsetmacro, 110
- \pgfresetboundingbox, 147
- \px, 182
- \py, 182
  
- \rAB, 40
- \rAp, 49
  
- standalone, 22
  
- TeX Distributions
  - MiKTeX, 17
  - TeXLive, 17
- TikZ Library
  - babel, 27
  - decoration, 247
- \tikzset, 190
- tkz-euclide: options
  - lua, 17
  - mini, 17
- \tkzAngleResult, 116, 118
- \tkzAutoLabelPoints, 167
- \tkzCalcLength, 180, 181

`\tkzCalcLength`: arguments  
      $(pt1, pt2)$ {name of macro}, 180  
`\tkzCalcLength`: options  
     cm, 181  
`\tkzCalcLength[local options]`( $\langle pt1, pt2 \rangle$ ), 180  
`\tkzCentroid`, 42  
`\tkzClip`, 27, 147, 148  
`\tkzClip`: options  
     space, 148  
`\tkzClipBB`, 149, 150  
`\tkzClipCircle[out]`, 155  
`\tkzClipCircle`, 95, 152  
`\tkzClipCircle`: arguments  
      $\langle A, B \rangle$ , 152  
`\tkzClipCircle`: options  
     out, 152  
`\tkzClipCircle[local options]`( $\langle A, B \rangle$ ), 152  
`\tkzClipPolygon[out]`, 151, 155  
`\tkzClipPolygon`, 151  
`\tkzClipPolygon`: arguments  
      $\langle pt1, pt2, pt3, \dots \rangle$ , 151  
`\tkzClipPolygon`: options  
     out, 151  
`\tkzClipPolygon[local options]`( $\langle points\ list \rangle$ ), 151  
`\tkzClipSector(O, A) (B)`, 153  
`\tkzClipSector[R] (O, 2) (30, 90)`, 153  
`\tkzClipSector[rotate] (O, A) (90)`, 153  
`\tkzClipSector`, 153  
`\tkzClipSector`: options  
     R, 153  
     rotate, 153  
     towards, 153  
`\tkzClipSector[local options]`( $\langle O, \dots \rangle$ )( $\langle \dots \rangle$ ), 153  
`\tkzClip[local options]`, 148  
`\tkzcmtopt`, 182  
`\tkzcmtopt`: arguments  
     (number){name of macro}, 182  
`\tkzcmtopt(number)`{[name of macro](#)}, 182  
`\tkzCompass`, 137, 174  
`\tkzCompass`: options  
     delta, 174  
     length, 174  
`\tkzCompasss`, 174, 175  
`\tkzCompasss`: options  
     delta, 174  
     length, 174  
`\tkzCompasss[local options]`( $\langle pt1, pt2\ pt3, pt4, \dots \rangle$ ), 174  
`\tkzCompass[local options]`( $\langle A, B \rangle$ ), 174  
`\tkzDefBarycentricPoint`, 41, 43  
`\tkzDefBarycentricPoint`: arguments  
      $(pt1 = \alpha_1, pt2 = \alpha_2, \dots)$ , 41  
`\tkzDefBarycentricPoint(pt1 =  \$\alpha\_1\$ , pt2 =  \$\alpha\_2\$ ,  \$\dots\$ )`, 41  
`\tkzDefCircle[radius] (A, B)`, 181  
`\tkzDefCircle`, 95  
`\tkzDefCircle`: arguments  
      $\langle pt1, pt2 \rangle$  or  $\langle pt1, pt2, pt3 \rangle$ , 95  
`\tkzDefCircle`: options  
     K, 95



- R, 95
- apollonius, 95
- circum, 95
- diameter, 95
- euler or nine, 95
- ex, 95
- in, 95
- orthogonal from, 95
- orthogonal through, 95
- spieker, 95
- \tkzDefCircleBy, 102
- \tkzDefCircleBy: arguments
  - pt1,pt2, 102
- \tkzDefCircleBy: options
  - homothety, 102
  - inversion, 102
  - projection , 102
  - reflection, 102
  - rotation , 102
  - symmetry , 102
  - translation, 102
- \tkzDefCircleBy[*(local options)*](*(pt1,pt2)*), 102
- \tkzDefCirclesBy, 102
- \tkzDefCircle[*(local options)*](*(A,B)*) or (*(A,B,C)*), 95
- \tkzDefEquipoints, 46
- \tkzDefEquipoints: arguments
  - (pt1,pt2), 46
- \tkzDefEquipoints: options
  - /compass/delta, 46
  - dist, 46
  - from=pt, 46
  - show, 46
- \tkzDefEquipoints[*(local options)*](*(pt1,pt2)*), 46
- \tkzDefExtSimilitudeCenter, 42
- \tkzDefGoldenRatio(A,C), 41
- \tkzDefGoldenRatio, 40, 41
- \tkzDefGoldenRatio: arguments
  - (pt1,pt2), 41
- \tkzDefGoldenRatio(*(pt1,pt2)*), 41
- \tkzDefGoldenRectangle, 92
- \tkzDefGoldenRectangle: arguments
  - (*(pt1,pt2)*), 92
- \tkzDefGoldenRectangle(*(point,point)*), 92
- \tkzDefGoldRectangle, 92
- \tkzDefHarmonic, 45
- \tkzDefHarmonic: options
  - both, 45
  - ext, 45
  - int, 45
- \tkzDefHarmonic[*(options)*](*(pt1,pt2,pt3)*) or (*(pt1,pt2,k)*), 45
- \tkzDefIntSimilitudeCenter, 42
- \tkzDefLine, 71
- \tkzDefLine: arguments
  - (*(pt1,pt2,pt3)*), 71
  - (*(pt1,pt2)*), 71
  - (*(pt1)*), 71
- \tkzDefLine: options
  - K, 72

- altitude, 72
- bisector out, 72
- bisector, 72
- euler, 72
- mediator, 72
- normed, 72
- orthogonal=through..., 72
- parallel=through..., 72
- perpendicular=through..., 72
- symmedian, 72
- tangent at, 72
- tangent from, 72
- \tkzDefLine[[⟨local options⟩](#)]([⟨pt1,pt2⟩](#)) or ([⟨pt1,pt2,pt3⟩](#)), 71
- \tkzDefMidArc, 46
- \tkzDefMidArc: arguments
  - pt1,pt2,pt3, 46
- \tkzDefMidArc([⟨pt1,pt2,pt3⟩](#)), 46
- \tkzDefMidPoint, 21, 40
- \tkzDefMidPoint: arguments
  - (pt1,pt2), 40
- \tkzDefMidPoint([⟨pt1,pt2⟩](#)), 40
- \tkzDefParallelogram, 92
- \tkzDefParallelogram: arguments
  - ([⟨pt1,pt2,pt3⟩](#)), 92
- \tkzDefParallelogram([⟨pt1,pt2,pt3⟩](#)), 92
- \tkzDefPoint, 33, 34, 40, 105, 116
- \tkzDefPoint: arguments
  - ( $\alpha$ :d), 34
  - (x,y), 34
  - {ref}, 34
- \tkzDefPoint: options
  - label, 34
  - shift, 34
- \tkzDefPointBy[rotation = ...], 116
- \tkzDefPointBy, 57
- \tkzDefPointBy: arguments
  - pt, 57
- \tkzDefPointBy: options
  - homothety, 57
  - inversion negative, 57
  - inversion, 57
  - projection , 57
  - reflection, 57
  - rotation in rad, 57
  - rotation with nodes, 57
  - rotation , 57
  - symmetry , 57
  - translation, 57
- \tkzDefPointBy[[⟨local options⟩](#)]([⟨pt⟩](#)), 57
- \tkzDefPointOnCircle, 49, 50
- \tkzDefPointOnCircle: options
  - R in rad, 49
  - R, 49
  - through in rad, 49
  - through, 49
- \tkzDefPointOnCircle[[⟨local options⟩](#)], 49
- \tkzDefPointOnLine, 48
- \tkzDefPointOnLine: arguments

pt1,pt2, 48  
 \tkzDefPointOnLine: options  
     pos=nb, 48  
 \tkzDefPointOnLine[(local options)]((A,B)), 48  
 \tkzDefPoints{0/0/0,2/2/A}, 37  
 \tkzDefPoints, 33, 37  
 \tkzDefPoints: arguments  
      $x_i/y_i/r_i$ , 37  
 \tkzDefPoints: options  
     shift, 37  
 \tkzDefPointsBy, 57, 65  
 \tkzDefPointsBy: arguments  
     ((list of points)){(list of pts)}, 65  
 \tkzDefPointsBy: options  
     homothety = center #1 ratio #2, 65  
     inversion = center #1 through #2, 65  
     inversion negative = center #1 through #2, 65  
     projection = onto #1--#2, 65  
     reflection = over #1--#2, 65  
     rotation = center #1 angle #2, 65  
     rotation in rad = center #1 angle #2, 65  
     rotation with nodes = center #1 from #2 to #3, 65  
     symmetry = center #1, 65  
     translation = from #1 to #2, 65  
 \tkzDefPointsBy[(local options)]((list of points)){(list of points)}, 65  
 \tkzDefPoints[(local options)]{(x<sub>1</sub>/y<sub>1</sub>/n<sub>1</sub>,x<sub>2</sub>/y<sub>2</sub>/r<sub>2</sub>, ...)}, 37  
 \tkzDefPointWith, 66  
 \tkzDefPointWith: arguments  
     (pt1,pt2), 66  
 \tkzDefPointWith: options  
     K, 66  
     colinear normed= at #1, 66  
     colinear= at #1, 66  
     linear normed, 66  
     linear, 66  
     orthogonal normed, 66  
     orthogonal, 66  
 \tkzDefPointWith((pt1,pt2)), 66  
 \tkzDefPoint[(local options)]((x,y)){(ref)} or ((a:d)){(ref)}, 34  
 \tkzDefProjExcenter[name=J] (A,B,C) (a,b,c) {Y,Z,X}, 99  
 \tkzDefProjExcenter, 99  
 \tkzDefProjExcenter: arguments  
     (pt1= $\alpha_1$ ,pt2= $\alpha_2$ ,...), 99  
 \tkzDefProjExcenter: options  
     name, 99  
 \tkzDefProjExcenter[(local options)]((A,B,C))((a,b,c)){(X,Y,Z)}, 99  
 \tkzDefRadicalAxis, 185  
 \tkzDefRadicalAxis: arguments  
     (pt1,pt2)(pt3,pt4), 185  
 \tkzDefRadicalAxis((pt1,pt2))((pt3,pt4)), 185  
 \tkzDefRandPointOn, 120  
 \tkzDefRandPointOn: options  
     circle =center pt1 radius dim, 120  
     circle through=center pt1 through pt2, 120  
     disk through=center pt1 through pt2, 120  
     line=pt1--pt2, 120  
     rectangle=pt1 and pt2, 120  
     segment= pt1--pt2, 120

---

```

\tkzDefRandPointOn[⟨local options⟩], 120
\tkzDefRectangle, 91
\tkzDefRectangle: arguments
    (⟨pt1,pt2⟩), 91
\tkzDefRectangle(⟨pt1,pt2⟩), 91
\tkzDefRegPolygon, 93
\tkzDefRegPolygon: arguments
    (⟨pt1,pt2⟩), 93
\tkzDefRegPolygon: options
    Options TikZ, 93
    center, 93
    name, 93
    sides, 93
    side, 93
\tkzDefRegPolygon[⟨local options⟩](⟨pt1,pt2⟩), 93
\tkzDefShiftPoint, 35, 36
\tkzDefShiftPoint: arguments
    (α:d), 36
    (x,y), 36
    {ref}, 36
\tkzDefShiftPoint: options
    [pt], 36
\tkzDefShiftPoint[⟨Point⟩](⟨x,y⟩){⟨ref⟩} or (⟨α:d⟩){⟨ref⟩}, 36
\tkzDefSimilitudeCenter, 42
\tkzDefSimilitudeCenter: arguments
    (⟨pt1,pt2⟩)(⟨pt3,pt4⟩), 42
\tkzDefSimilitudeCenter: options
    ext, 42
    int, 42
\tkzDefSimilitudeCenter[⟨options⟩](⟨O,A⟩)(⟨O',B⟩), 42
\tkzDefSpcTriangle[medial,name=M_](A,B,C){A,B,C}, 82
\tkzDefSpcTriangle[medial,name=M](A,B,C){_A,_B,_C}, 82
\tkzDefSpcTriangle[medial](A,B,C){a,b,c}, 82
\tkzDefSpcTriangle, 82
\tkzDefSpcTriangle: options
    centroid or medial, 82
    euler, 82
    ex or excentral, 82
    extouch, 82
    feuerbach, 82
    in or incentral, 82
    intouch or contact, 82
    name, 82
    orthic, 82
    symmedial, 82
    tangential, 82
    , 82
\tkzDefSpcTriangle[⟨local options⟩](⟨p1,p2,p3⟩){⟨r1,r2,r3⟩}, 82
\tkzDefSquare, 90, 91
\tkzDefSquare: arguments
    (⟨pt1,pt2⟩), 90
\tkzDefSquare(⟨pt1,pt2⟩), 90
\tkzDefTriangle, 77, 78
\tkzDefTriangle: options
    cheops, 78
    egyptian, 78
    equilateral, 78
    euclid, 78

```

- golden, 78
- gold, 78
- half, 78
- isosceles right, 78
- pythagoras, 78
- pythagore, 78
- school, 78
- sublime, 78
- swap, 78
- two angles= #1 and #2, 78
- \tkzDefTriangleCenter[ortho] (B,C,A), 51
- \tkzDefTriangleCenter, 51
- \tkzDefTriangleCenter: arguments
  - (pt1,pt2,pt3), 51
- \tkzDefTriangleCenter: options
  - centroid, 51
  - circum, 51
  - euler, 51
  - ex, 51
  - feuerbach, 51
  - gergonne, 51
  - grebe, 51
  - in, 51
  - lemoine, 51
  - median, 51
  - mittenpunkt, 51
  - nagel, 51
  - orthic, 51
  - ortho, 51
  - spieker, 51
  - symmedian, 51
- \tkzDefTriangleCenter[⟨local options⟩] (⟨A,B,C⟩), 51
- \tkzDefTriangle[⟨local options⟩] (⟨A,B⟩), 78
- \tkzDotProduct, 183
- \tkzDotProduct: arguments
  - (pt1,pt2,pt3), 183
- \tkzDotProduct(⟨pt1,pt2,pt3⟩), 183
- \tkzDrawArc[angles] (O,A) (0,90), 136
- \tkzDrawArc[delta=10] (O,A) (B), 136
- \tkzDrawArc[R with nodes] (O,2) (A,B), 136
- \tkzDrawArc[R] (O,2) (30,90), 136
- \tkzDrawArc[rotate,color=red] (O,A) (90), 136
- \tkzDrawArc, 116, 135, 136, 247
- \tkzDrawArc: options
  - R with nodes, 136
  - R, 136
  - angles, 136
  - delta, 136
  - reverse, 136
  - rotate, 136
  - towards, 136
- \tkzDrawArc[⟨local options⟩] (⟨O,...⟩) (⟨...⟩), 136
- \tkzDrawCircle(s), 247
- \tkzDrawCircle[R] (O,3), 247
- \tkzDrawCircle[R] (O,3cm), 247
- \tkzDrawCircle, 95, 130, 141
- \tkzDrawCircle: arguments
  - (⟨pt1,pt2⟩), 130

- \tkzDrawCircles, 131
- \tkzDrawCircles: arguments
  - (⟨pt1,pt2 pt3,pt4 ...⟩), 131
- \tkzDrawCircles: options
  - through, 131
- \tkzDrawCircles[⟨local options⟩](⟨A,B C,D ...⟩), 131
- \tkzDrawCircle[⟨local options⟩](⟨A,B⟩), 130
- \tkzDrawEllipse, 135
- \tkzDrawEllipse: arguments
  - (⟨C,a,b,An⟩), 135
- \tkzDrawEllipse[⟨local options⟩](⟨C,a,b,An⟩), 135
- \tkzDrawLine, 124
- \tkzDrawLine: options
  - TikZ options, 124
  - ..., 124
  - add, 124
- \tkzDrawLines, 124
- \tkzDrawLines[⟨local options⟩](⟨pt1,pt2 pt3,pt4 ...⟩), 124
- \tkzDrawLine[⟨local options⟩](⟨pt1,pt2⟩) , 124
- \tkzDrawPoint(A,B), 247
- \tkzDrawPoint, 122
- \tkzDrawPoint: arguments
  - name of point, 122
- \tkzDrawPoint: options
  - TikZ options, 122
  - color, 122
  - shape, 122
  - size, 122
- \tkzDrawPoints(A,B), 247
- \tkzDrawPoints(A,B,C), 123
- \tkzDrawPoints, 122, 123
- \tkzDrawPoints: arguments
  - points list, 123
- \tkzDrawPoints: options
  - color, 123
  - shape, 123
  - size, 123
- \tkzDrawPoints[⟨local options⟩](⟨liste⟩), 123
- \tkzDrawPoint[⟨local options⟩](⟨name⟩), 122
- \tkzDrawPolygon, 128
- \tkzDrawPolygon: arguments
  - (⟨pt1,pt2,pt3,...⟩), 128
- \tkzDrawPolygon: options
  - Options TikZ, 128
- \tkzDrawPolygon[⟨local options⟩](⟨points list⟩), 128
- \tkzDrawPolySeg, 129
- \tkzDrawPolySeg: arguments
  - (⟨pt1,pt2,pt3,...⟩), 129
- \tkzDrawPolySeg: options
  - Options TikZ, 129
- \tkzDrawPolySeg[⟨local options⟩](⟨points list⟩), 129
- \tkzDrawSector(O,A)(B), 139
- \tkzDrawSector[R with nodes](O,2)(A,B), 139
- \tkzDrawSector[R,color=teal](O,2)(30,90), 139
- \tkzDrawSector[rotate,color=red](O,A)(90), 139
- \tkzDrawSector, 139–141
- \tkzDrawSector: options
  - R with nodes, 139

- R, 139
- rotate, 139
- towards, 139
- \tkzDrawSector[*(local options)*](*(0,...)*)(*(...)*), 139
- \tkzDrawSegment(s), 247
- \tkzDrawSegment, 124, 125
- \tkzDrawSegment: arguments
  - (pt1,pt2), 125
- \tkzDrawSegment: options
  - TikZ options, 125
  - ..., 125
  - dim, 125
- \tkzDrawSegments, 127
- \tkzDrawSegments[*(local options)*](*(pt1,pt2 pt3,pt4 ...)*), 127
- \tkzDrawSegment[*(local options)*](*(pt1,pt2)*), 125
- \tkzDrawSemiCircle, 134
- \tkzDrawSemiCircle: arguments
  - (*(pt1,pt2)*), 134
- \tkzDrawSemiCircles, 134
- \tkzDrawSemiCircles: arguments
  - (*(pt1,pt2 pt3,pt4 ...)*), 134
- \tkzDrawSemiCircles[*(local options)*](*(A,B C,D ...)*), 134
- \tkzDrawSemiCircle[*(local options)*](*(0,A)*), 134
- \tkzDuplicateLen, 179
- \tkzDuplicateLength, 179
- \tkzDuplicateSegment, 179, 180
- \tkzDuplicateSegment: arguments
  - (pt1,pt2)(pt3,pt4){pt5}, 179
- \tkzDuplicateSegment(*(pt1,pt2)*)(*(pt3,pt4)*){*(pt5)*}, 179
- \tkzFillAngle, 145, 146, 202
- \tkzFillAngle: options
  - size, 146
- \tkzFillAngles, 146
- \tkzFillAngles[*(local options)*](*(A,0,B)*)(*(A',0',B')*)etc., 146
- \tkzFillAngle[*(local options)*](*(A,0,B)*), 146
- \tkzFillCircle, 95, 141
- \tkzFillCircle: options
  - R, 141
  - radius, 141
- \tkzFillCircle[*(local options)*](*(A,B)*), 141
- \tkzFillPolygon, 144
- \tkzFillPolygon: arguments
  - (*(pt1,pt2,...)*), 144
- \tkzFillPolygon[*(local options)*](*(points list)*), 144
- \tkzFillSector(0,A)(B), 145
- \tkzFillSector[R with nodes](0,2)(A,B), 145
- \tkzFillSector[R,color=blue](0,2)(30,90), 145
- \tkzFillSector[rotate,color=red](0,A)(90), 145
- \tkzFillSector, 140, 144, 145
- \tkzFillSector: options
  - R with nodes, 145
  - R, 145
  - rotate, 145
  - towards, 145
- \tkzFillSector[*(local options)*](*(0,...)*)(*(...)*), 145
- \tkzFindAngle, 116
- \tkzFindAngle: arguments
  - (pt1,pt2,pt3), 116

`\tkzFindAngle(<pt1,pt2,pt3>)`, 116  
`\tkzFindSlopeAngle`, 118, 119  
`\tkzFindSlopeAngle: arguments`  
     `(pt1,pt2)`, 118  
`\tkzFindSlopeAngle(<A,B>)`, 118  
`\tkzGetAngle`, 116–118  
`\tkzGetAngle: arguments`  
     name of macro, 116  
`\tkzGetAngle(<name of macro>)`, 116  
`\tkzGetFirstPoint{A}`, 247  
`\tkzGetFirstPoint{Jb}`, 98  
`\tkzGetFirstPoint{M}` , 39  
`\tkzGetFirstPoint`, 39, 90  
`\tkzGetFirstPoint: arguments`  
     `ref1`, 39  
`\tkzGetFirstPoint{<ref1>}`, 39  
`\tkzGetLength{dAB}`, 180, 181  
`\tkzGetLength`, 40, 95, 180, 181  
`\tkzGetLength: arguments`  
     name of a macro, 40  
`\tkzGetLength{<name of a macro>}`, 40  
`\tkzGetPoint(A)`, 247  
`\tkzGetPoint{A}`, 247  
`\tkzGetPoint{C}`, 66  
`\tkzGetPoint{M}` , 39  
`\tkzGetPoint{M}`, 57  
`\tkzGetPoint`, 21, 39–41, 51–53, 66, 71, 78, 92, 95, 96, 120  
`\tkzGetPoint: arguments`  
     `ref`, 39  
`\tkzGetPointCoord`, 182  
`\tkzGetPointCoord: arguments`  
     `(point){name of macro}`, 182  
`\tkzGetPointCoord(<A>){<name of macro>}`, 182  
`\tkzGetPoints{A}{B}`, 247  
`\tkzGetPoints{M,N}` , 39  
`\tkzGetPoints{O' }{M' }`, 102  
`\tkzGetPoints{z1}{z2}`, 101  
`\tkzGetPoints`, 39, 71, 90–92, 95, 102  
`\tkzGetPoints: arguments`  
     `{ref1,ref2}`, 39  
`\tkzGetPoints{<ref1>}{<ref2>}`, 39  
`\tkzGetPoint{<ref>}`, 39  
`\tkzGetRandPointOn`, 119  
`\tkzGetResult`, 183  
`\tkzGetSecondPoint{A}`, 247  
`\tkzGetSecondPoint{M}` , 40  
`\tkzGetSecondPoint{Tb}`, 98  
`\tkzGetSecondPoint`, 40, 90  
`\tkzGetSecondPoint: arguments`  
     `ref2`, 40  
`\tkzGetSecondPoint{<ref2>}`, 40  
`\tkzGetVectxy`, 71  
`\tkzGetVectxy: arguments`  
     `(point){name of macro}`, 71  
`\tkzGetVectxy(<A,B>){<text>}`, 71  
`\tkzInit`, 22, 27, 147, 148  
`\tkzInit: options`  
     `xmax`, 148



- xmin, 148
- xstep, 148
- ymax, 148
- ymin, 148
- ystep, 148
- \tkzInit[[\(local options\)](#)], 148
- \tkzInterCC, 39, 111
- \tkzInterCC: options
  - N, 111
  - R, 111
  - common=pt, 111
  - with nodes, 111
- \tkzInterCC[[\(options\)](#)]([\(O,A\)](#))([\(O',A'\)](#)) or ([\(O,r\)](#))([\(O',r'\)](#)) or ([\(O,A,B\)](#))([\(O',C,D\)](#)), 111
- \tkzInterLC, 105
- \tkzInterLC: options
  - N, 105
  - R, 105
  - common=pt, 105
  - near, 105
  - with nodes, 105
- \tkzInterLC[[\(options\)](#)]([\(A,B\)](#))([\(O,C\)](#)) or ([\(O,r\)](#)) or ([\(O,C,D\)](#)), 105
- \tkzInterLL, 105
- \tkzInterLL([\(A,B\)](#))([\(C,D\)](#)), 105
- \tkzIsLinear, 187, 188
- \tkzIsLinear: arguments
  - (pt1,pt2,pt3), 187
- \tkzIsLinear([\(pt1,pt2,pt3\)](#)), 187
- \tkzIsOrtho, 187, 188
- \tkzIsOrtho: arguments
  - (pt1,pt2,pt3), 187
- \tkzIsOrtho([\(pt1,pt2,pt3\)](#)), 187
- \tkzLabelAngle, 169
- \tkzLabelAngle: options
  - pos, 170
- \tkzLabelAngles, 171
- \tkzLabelAngles[[\(local options\)](#)]([\(A,O,B\)](#))([\(A',O',B'\)](#))etc., 171
- \tkzLabelAngle[[\(local options\)](#)]([\(A,O,B\)](#)), 169
- \tkzLabelArc(A,B){5}, 172
- \tkzLabelArc, 172
- \tkzLabelArc: arguments
  - (pt1,pt2,pt3), 172
  - label, 172
- \tkzLabelArc: options
  - pos, 172
- \tkzLabelArc[[\(local options\)](#)]([\(pt1,pt2,pt3\)](#)){[\(label\)](#)}, 172
- \tkzLabelCircle, 95, 171
- \tkzLabelCircle: options
  - tikz options, 171
- \tkzLabelCircle[[\(tikz options\)](#)]([\(O,A\)](#))([\(angle\)](#)){[\(label\)](#)}, 171
- \tkzLabelLine(A,B), 169
- \tkzLabelLine, 169
- \tkzLabelLine: arguments
  - label, 169
- \tkzLabelLine: options
  - pos, 169
- \tkzLabelLine[[\(local options\)](#)]([\(pt1,pt2\)](#)){[\(label\)](#)}, 169
- \tkzLabelPoint(A){\$A\_1\$}, 166
- \tkzLabelPoint(A,B,C), 167

- \tkzLabelPoint, 166
- \tkzLabelPoint: arguments
  - point, 166
- \tkzLabelPoint: options
  - TikZ options, 166
- \tkzLabelPoints(A,B,C), 166
- \tkzLabelPoints, 166, 167
- \tkzLabelPoints: arguments
  - list of points, 166, 167
- \tkzLabelPoints[[local options](#)]( $\langle A_1, A_2, \dots \rangle$ ), 166, 167
- \tkzLabelPoint[[local options](#)]( $\langle \text{point} \rangle$ ){ $\langle \text{label} \rangle$ }, 166
- \tkzLabelSegment(A,B){5}, 167
- \tkzLabelSegment, 167
- \tkzLabelSegment: arguments
  - (pt1,pt2), 167
  - label, 167
- \tkzLabelSegment: options
  - pos, 167
- \tkzLabelSegments, 169
- \tkzLabelSegments[[local options](#)]( $\langle \text{pt1}, \text{pt2} \text{ pt3}, \text{pt4} \dots \rangle$ ), 169
- \tkzLabelSegment[[local options](#)]( $\langle \text{pt1}, \text{pt2} \rangle$ ){ $\langle \text{label} \rangle$ }, 167
- \tkzMarkAngle, 159, 160, 202, 247
- \tkzMarkAngle: options
  - arc, 160
  - mark, 160
  - mkcolor, 160
  - mkpos, 160
  - mksize, 160
  - size, 160
- \tkzMarkAngles, 160
- \tkzMarkAngles[[local options](#)]( $\langle A, O, B \rangle$ )( $\langle A', O', B' \rangle$ )etc., 160
- \tkzMarkAngle[[local options](#)]( $\langle A, O, B \rangle$ ), 160
- \tkzMarkArc, 159
- \tkzMarkArc: options
  - color, 159
  - mark, 159
  - pos, 159
  - size, 159
- \tkzMarkArc[[local options](#)]( $\langle \text{pt1}, \text{pt2}, \text{pt3} \rangle$ ), 159
- \tkzMarkRightAngle, 161
- \tkzMarkRightAngle: options
  - german, 161
  - size, 161
- \tkzMarkRightAngles, 163
- \tkzMarkRightAngles[[local options](#)]( $\langle A, O, B \rangle$ )( $\langle A', O', B' \rangle$ )etc., 163
- \tkzMarkRightAngle[[local options](#)]( $\langle A, O, B \rangle$ ), 161
- \tkzMarkSegment, 158
- \tkzMarkSegment: options
  - color, 158
  - mark, 158
  - pos, 158
  - size, 158
- \tkzMarkSegments, 158
- \tkzMarkSegments[[local options](#)]( $\langle \text{pt1}, \text{pt2} \text{ pt3}, \text{pt4} \dots \rangle$ ), 158
- \tkzMarkSegment[[local options](#)]( $\langle \text{pt1}, \text{pt2} \rangle$ ), 158
- \tkzPermute, 89
- \tkzPermute: arguments
  - (pt1,pt2,pt3), 89

- \tkzPermute([⟨pt1,pt2,pt3⟩](#)), 89
- \tkzPicAngle, 163
- \tkzPicAngle: options
  - tikz option, 163
- \tkzPicAngle[[⟨tikz options⟩](#)]([⟨A,0,B⟩](#)), 163
- \tkzPicRightAngle, 163
- \tkzPicRightAngle: options
  - tikz option, 163
- \tkzPicRightAngle[[⟨tikz options⟩](#)]([⟨A,0,B⟩](#)), 163
- \tkzPowerCircle, 185
- \tkzPowerCircle: arguments
  - (pt1)(pt2,pt3), 185
- \tkzPowerCircle([⟨pt1⟩](#))([⟨pt2,pt3⟩](#)), 185
- \tkzProtractor, 178
- \tkzProtractor: options
  - lw, 178
  - return, 178
  - scale, 178
- \tkzProtractor[[⟨local options⟩](#)]([⟨O,A⟩](#)), 178
- \tkzpttocm, 181
- \tkzpttocm: arguments
  - (number){name of macro}, 181
- \tkzpttocm([⟨number⟩](#)){[⟨name of macro⟩](#)}, 181
- \tkzSetUpArc, 194
- \tkzSetUpArc: options
  - color, 194
  - line width, 194
  - style, 194
- \tkzSetUpArc[[⟨local options⟩](#)], 194
- \tkzSetUpColors, 190
- \tkzSetUpCompass, 195
- \tkzSetUpCompass: options
  - color, 195
  - delta, 195
  - line width, 195
  - style, 195
- \tkzSetUpCompass[[⟨local options⟩](#)], 195
- \tkzSetUpLabel, 195, 196
- \tkzSetUpLine, 123, 192
- \tkzSetUpLine: options
  - add, 192
  - color, 192
  - line width, 192
  - style, 192
- \tkzSetUpLine[[⟨local options⟩](#)], 192
- \tkzSetUpPoint, 190–192
- \tkzSetUpPoint: options
  - color, 190
  - fill, 190
  - shape, 190
  - size, 190
- \tkzSetUpPoint[[⟨local options⟩](#)], 190
- \tkzSetUpStyle, 196
- \tkzSetUpStyle[[⟨local options⟩](#)], 196
- \tkzShowBB, 149
- \tkzShowBB[[⟨local options⟩](#)], 149
- \tkzShowLine, 175, 176, 195
- \tkzShowLine: options

- K, 175
- bisector, 175
- gap, 175
- length, 175
- mediator, 175
- orthogonal, 175
- perpendicular, 175
- ratio, 175
- size, 175
- \tkzShowLine[*(local options)*](*(pt1,pt2)*) or (*(pt1,pt2,pt3)*), 175
- \tkzShowTransformation, 176, 177
- \tkzShowTransformation: options
  - K, 177
  - gap, 177
  - length, 177
  - projection=onto pt1--pt2, 177
  - ratio, 177
  - reflection= over pt1--pt2, 177
  - size, 177
  - symmetry=center pt, 177
  - translation=from pt1 to pt2, 177
- \tkzShowTransformation[*(local options)*](*(pt1,pt2)*) or (*(pt1,pt2,pt3)*), 176
- \tkzSwapPoints, 183
- \tkzSwapPoints: arguments
  - (pt1,pt2), 183
- \tkzSwapPoints(*(pt1,pt2)*), 183
- \tkzTestInterCC, 111
- \tkzTestInterCC(*(O,A)*)(*(O',B)*), 111
- \tkzTestInterLC, 105
- \tkzTestInterLC(*(O,A)*)(*(O',B)*), 105
- \useasboundingbox, 147
- \Vx, 71
- \Vy, 71
- \xstep, 148
- \ystep, 148